| Q.<br>No. | Topic | Question  | Option1                                     | Option2   | Option3   | Option4  | Correct Option No. |
|-----------|-------|---|---|---|---|--|--------------------|
| 1         | C#    | C# compiler compiles source code intocode.  | native                                      | byte  | IL  | script   | Option4            |
| 2         | C#    | There are primitive data types in .NET common type system                                     | 8   | 14  | 12  | 9  | Option2            |
| 3         | C#    | .NET Core runtime is available on   | only Windows platform                       | only Linux platform                                     | platform  | Windows, Linux<br>and macOS<br>platforms         | Option4            |
| 4         | C#    | C# code which includes a pointer type is compiled into  | safe managed code                           | unsafe managed code                                     | safe<br>unmanaged<br>code                             | unsafe<br>unmanaged code                         | Option2            |
| 5         | C#    | is a syntactically correct declaration of a C# method with optional parameters.               | void Combine(double first, double second=0) | void Combine(double<br>first, double<br>second=first+1) | void<br>Combine(doubl<br>e first=0,<br>double second) |  | Option1            |
| 6         | C#    | In a console type project with implicit usings enabled, the namespace must be explicitly used | System.IO                                   | System.Linq   | System.Thread ing                                     | System.Collections                               | Option4            |
| 7         | C#    | A static constructor of a type is declared with access modifier                               | public                                      | private   | no  | any  | Option3            |
| 8         | C#    | In C# class members are by default  | public                                      | private   | no  | any  | Option2            |
| 9         | C#    | An interface  | cannot be instantiated but can be extended  | cannot be extended<br>but can be<br>instantiated        | can be instantiated and can be extended               | cannot be<br>instantiated nor<br>can be extended | Option1            |
| 10        | C#    | 10: An interface cannot define  | a static field                              | a static method   | an instance<br>field                                  | an implemented instance method                   | Option3            |
| 11        | C#    | A struct type cannot contain the definition of a  | static field                                | static method   | parameterless constructor                             | virtual method                                   | Option4            |
| 12        | C#    | A parameter of a method declared with keyword accepts an uninitialized argument by reference. | ref   | out   | in  | this   | Option2            |
| 13        | C#    | is the correct order for constraints over type-parameter T in a generic declaration.          | T: struct, IComparable <t>, new()</t>       | T: struct, new(), IComparable <t></t>                   | T: IComparable< T>, new(), struct                     | T: new(), struct, IComparable <t></t>            | Option1            |

| Q.<br>No. | Topic | Question   | Option1  | Option2  | Option3              | Option4                      | Correct Option No. |
|-----------|-------|--|--|--|----------------------|------------------------------|--------------------|
| 14        | C#    | The complexity of searching for an item in System.Collections.Generic.SortedDictionary <k ,="" v=""> is</k>                          | O(n)   | O(log n)   | O(n2)                | O(nlogn)                     | Option2            |
| 15        | C#    | A delegate declaration is translated by the compiler into its equivalent type.   | pointer  | struct   | interface            | class                        | Option4            |
| 16        | C#    | Lambda expression can be assigned to a delegate defined as delegate bool InOrder(int m, int n);                                      | x => x < 0   | (x, y) => x - y  | (x, y) => x > y      | (x, y, z) => (x % y)<br>== z | Option3            |
| 17        | C#    | The using statement is equivalent to statement   | try-catch  | try-finally  | try-catch-finally    | throw                        | Option2            |
| 18        |       | In C# the throw statement can only be applied to an instance of a class which inherits from  | Sytem.Object   | System.ValueType   | System.Except ion    | System.Delegate              | Option3            |
| 19        | C#    | Under LINQ, query operator filters the elements of the sequence to which it is applied.  | Where  | Select   | OrderBy              | GroupBy                      | Option2            |
| 20        | C#    | In definition record struct Student(string name, float gpa); Student represents type   | an immutable reference                                 | an immutable value   | a mutable reference  | a mutable value              | Option4            |
| 21        | C#    | The expression Activator.CreateInstance() returns an instance of a type whose name is specified in the command line argument args[0] | args[0].GetType()                                      | Type.GetType(args[0] )   | GetType(args[<br>0]) | typeof(args[0])              | Option2            |
| 22        | C#    | A custom attribute defined with [AttributeUsage()] can be applied to both a property as well as a method of a class                  | AttributeTargets.Property  <br>AttributeTargets.Method | AttributeTargets.Prop<br>erty &<br>AttributeTargets.Meth<br>od | s.Property +         | AttributeTargets.Cl          | Option1            |

| Q.<br>No. | Topic | Question  | Option1                          | Option2                | Option3                                | Option4             | Correct Option No. |
|-----------|-------|---|----------------------------------|------------------------|--|---------------------|--------------------|
| 23        | C#    | A background thread of a process is terminated when its   | any other thread exits           | all other threads exit | all non-<br>background<br>threads exit | main thread exits   | Option3            |
| 24        | C#    | Monitor(target) enables a thread which has called Monitor.Wait(target) to resume execution.   | Enter                            | Exit                   | Pulse                                  | Notify              | Option3            |
| 25        | C#    | The ADO.NET data-provider for SQL server includes object for sequentially fetching rows resulting from execution of a query.                        | SqlConnection                    | SqlCommand             | SqlDataAdapte<br>r                     | SqlDataReader       | Option4            |
| 26        | C#    | The CommandText of a command object is set to sql SELECT COUNT(Id) FROM Students, this command is best executed using method of this command object | ExecuteScalar                    | ExecuteReader          | ExecuteNonQu<br>ery                    | ExecuteQuery        | Option1            |
| 27        | C#    | ASP.NET core uses by default as its web-server  | IIS                              | IIS-Express            | Kestrel                                | Apache              | Option3            |
| 28        | C#    | In ASP.NET request pipeline<br>middleware executes the handler selected for<br>the current request.   | Routing                          | Endpoint               | Authentication                         | Authorization       | Option2            |
| 29        | C#    | In default route mapping under ASP.NET MVC, the Print method of the PrinterController class is mapped to path                                       | /Printer                         | /Print                 | /Print/Printer                         | /Printer/Print      | Option4            |
| 30        | C#    | The View() method called from Print method of PrinterController renders page.   | ~/Views/Printer/Print.csht<br>ml | ~/Printer/Print.cshtml | ~/Print.cshtml                         | ~/Index.cshtml      | Option1            |
| 31        | C#    | In razor syntax the symbol is used to make a transition from HTML to C#   | @                                | \$                     | #                                      | %                   | Option1            |
| 32        | C#    | Under ASP.NET Core MVC, the model object handles  | presentation of data             | persistence of data    | passing of commands                    | parsing of commands | Option2            |
| 33        | C#    | By default the static page middleware serves static content from directory.   | ~/home                           | ~/pub                  | ~/wwwroot                              | ~/pages             | Option3            |
| 34        | C#    | In ASP.NET Core Web API, verb is handled to update the resource object.   | GET                              | PUT                    | POST                                   | DELETE              | Option2            |

| Q.<br>No. | Topic | Question  | Option1         | Option2      | Option3         | Option4       | Correct Option No. |
|-----------|-------|---|-----------------|--------------|-----------------|---------------|--------------------|
| 35        | C#    | A RESTful API action must return HTTP status code of to indicate server side exception.                                   | 200             | 300          | 400             | 500           | Option4            |
| 36        | C#    | The directive in a razor-page file turns it into an action without requiring a controller.                                | @code           | @page        | @mode           | @action       | Option2            |
| 37        | C#    | A service added to the service collection using method has shortest lifetime.   | AddSingleton    | AddScoped    | AddTransient    | AddPersistent | Option3            |
| 38        | C#    | A controller class decorated with attribute only supports routing through attributes.                                     | [ApiController] | [Controller] | [NonController] | [Route]       | Option1            |
| 39        | C#    | The is a dynamic property of controller used for transferring data from controller to the view.                           | TempData        | ViewData     | Session         | ViewBag       | Option4            |
| 40        | C#    | The column mapped to property of entity type Student is considered to be the primary key by Entity Framework conventions. | StudentId       | Student_Id   | StudentKey      | StudentNo     | Option1            |