

SearXNG Search API

Use the SearXNG API to integrate search results into your applications.

Base URL

`https://search.incraaxiautomation.in/api/search`

Authentication

All API requests require authentication using an API key. You can create API keys in the [Settings](#).

Header Authentication

`Authorization: Bearer YOUR_API_KEY`

Query Parameter

`/api/search?q=hello&apikey=YOUR_API_KEY`

Search Endpoint

Method	Endpoint	Description
GET	<code>/api/search</code>	Search for results
POST	<code>/api/search</code>	Search for results (form data)

Parameters

Parameter	Type	Required	Description
<code>q</code>	string	Yes	Search query

Parameter	Type	Required	Description
<code>apikey</code>	string	Yes	Your API key
<code>format</code>	string	No	Response format: json (default), csv, rss
<code>categories</code>	string	No	Comma-separated categories
<code>language</code>	string	No	Search language code
<code>safesearch</code>	integer	No	Safe search level: 0, 1, 2

Example Request

```
curl -H "Authorization: Bearer YOUR_API_KEY" \
  "https://search.incraaxiautomation.in/api/search?q=he
```

Example Response

```
{
  "query": "hello world",
  "results": [
    {
      "title": "Hello World - Example",
      "url": "https://example.com",
      "content": "Example content...",
      "engine": "google",
      "score": 1.0
    }
  ],
  "answers": [],
  "corrections": [],
  "suggestions": [],
  "unresponsive_engines": []
}
```

Response Fields

Field	Type	Description
-------	------	-------------

Field	Type	Description
<code>query</code>	string	The search query
<code>results</code>	array	Array of search results
<code>answers</code>	array	Instant answers
<code>corrections</code>	array	Search corrections
<code>suggestions</code>	array	Search suggestions
<code>unresponsive_engines</code>	array	Engines that failed to respond

Rate Limits

API requests are subject to the same rate limits as the web interface. Excessive usage may result in temporary blocking.

Security

- Keep your API keys secret and do not share them publicly.
- Revoke keys immediately if they are compromised.
- Use HTTPS in production to protect your API key in transit.

[Back to Settings](#)

Powered by **SearXNG** — 1.0.0 · [Source](#) · [Issues](#)

No tracking · No profiling · Your query stays private