MIT (Assignment – 4)

U20CS110
Krishna Pandey

(1). Write an assembly language program in 8085 to search a given number in an array of n numbers. If number is found, then store AA in memory location 4051 otherwise store BB in 4051.

```
;<Question-1>
JMP start
 start: LXI H, 2050H
        MOV B, M
        INX H
        MOV C, M
skip:  INX H
        MOV A, M
        CMP B
        JZ loop
        DCR C
        JNZ skip
        MVI A, BBH
        STA 4051H
        HLT
loop: MVI A, AAH
      STA 4051H
      HLT
```



Memory View

0x 4051

	0	1	2	3	4	5	6	7	8	9	A	B	C	D	E	F
400	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
401	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
402	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
403	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
404	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
405	00	AA	00	00	00	00	00	00	00	00	00	00	00	00	00	00
406	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
407	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
408	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
409	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40A	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40B	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40C	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40D	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40E	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
40F	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00

4026

Start Address at: 0x 3300

(2).Write an assembly language program to sort numbers in ascending order where six numbers are stored in consecutive memory locations starting from 2000H.

```
;<Question-2>
JMP START
START: LXI H, 2000H
          MVI D, 00H
      MOV C, M
      DCR C
      INX H
CHECK: MOV A, M
            INX H
        CMP M
        JC NEXTBYTE
        JZ NEXTBYTE
        MOV B, M
        MOV M, A
        DCX H
        MOV M, B
        INX H
        MVI D,01H
NEXTBYTE: DCR C
                JNZ CHECK
                MOV A, D
                CPI 01H
                JZ START
                HLT
```



(3).Write an assembly language program to take all numbers which are not 00H from array, and store them into different location. Numbers are stored at 3001 onwards, 3000 is holding the size of array, the results will be stored from 4000.

```
;<Question-3>
JMP START
START: LXI H,3000H
        MOV C,M
        LXI D,4000H

LOOP: INX H
        MOV A,M
    ORI 00H
        JZ SKIP
        STAX D
    INX D

SKIP: DCR C
        JNZ LOOP

HLT
```




Registers
A/PSW 0x 99 56
BC 0x 00 00
DE 0x 40 05
HL 0x 30 05
SP 0x FF FF
PC 0x 08 18
Flags
Z
S
P
C
AC
Load at 0x0800
main.asm
;<Question-3>
JMP START
START: LXI H,3000H
MOV C,M
LXI D,4000H
LOOP: INX H
MOV A,M
ORI 00H
JZ SKIP
STAX D
INX D
SKIP: DCR C
JNZ LOOP
HLT
Memory View
0x 4000
0 1 2 3 4 5 6 7 8 9 A B C D E F
400 0A 12 56 45 99 00 00 00 00 00 00 00 00 00 00
401 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
402 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
403 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
404 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
405 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
406 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
407 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
408 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
409 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40A 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40B 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40C 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40D 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40E 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
40F 00 00 00 00 00 00 00 00 00 00 00 00 00 00 00
Start Address at: 0x 3300

(4).Write an assembly language program to insert a new value in an array of data only if it is not present in the array. Assume suitable data and memory location.

```
;<Question-4>
JMP start

start: LXI H, 0000H
          MOV B, M
       INX H
       MOV C, M
skip:  INX H
          MOV A, M
       CMP B
       JZ loop
       DCR C
       JNZ skip
       MOV A, B
       STA 0007H
       HLT
loop:  HLT
```