

HeyReach API

Introduction

Welcome to the HeyReach API. Let's get started with a quick setup on how to use the API!

Finding your API key

The first step when using the HeyReach API is authenticating your requests with an API key.

The API key is used to authenticate the incoming requests and map them to your organization.

API keys never expire, however they can be deleted/deactivated.

Authentication

After you have your API key, you will need to provide it in every request that you make to the HeyReach API.

You will need to use add the `X-API-KEY` request header to every request and set your API key as the value.

Test your API key

Once you have your API key, you can check if it's working by sending the following request.

If everything is working properly, you should get a `200` HTTP status code.

Plain Text

```
curl --location 'https://api.heyreach.io/api/public/auth/CheckApiKey'; --header 'X-API-KEY'
```

Rate Limits

HeyReach allows a maximum of `300` requests per minute. All requests are attributed to the same limit.

Going above the limit will return a `429` HTTP status code and an error.

Enjoy building

Public Authentication

Check if your API token is set up properly

GET CheckApiKey

//api/public/auth/CheckApiKey

Check If your API key is working.

HEADERS

X-API-KEY

<YOUR_API_KEY>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Accept

text/plain

PublicCampaigns

Methods for working with HeyReach campaigns. Filter, pause resume and manage leads inside your campaigns.

POST GetAll

//api/public/campaign/GetAll

Get a paginated collection of all campaigns. Get up to 100 campaigns per request.

HEADERS

X-API-KEY

{{HR_API_KEY}}

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type

application/json

Accept

text/plain

Body raw (json)

```
json
```

```
{  
  "offset": 0,  
  "keyword": "mv campaign name",  
}
```

```
"statuses": ["DRAFT", "IN_PROGRESS", "PAUSED", "FINISHED", "CANCELED", "FAILED", "STARTING",  
"accountIds": [123, 2, 5],  
  
"limit": 10  
}
```

GET GetById

//api/public/campaign/GetById?campaignId=<long>

Get a Campaign by id

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Accept	text/plain

PARAMS

campaignId	<long> (Required)
-------------------	----------------------

POST Resume

//api/public/campaign/Resume?campaignId=<long>

Resumes the specified campaign.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Accept	text/plain

PARAMS

campaignId	<long>
(Required) The id of the campaign to be resumed	

POST Pause

//api/public/campaign/Pause?campaignId=<long>

Pauses the specified campaign.

HEADERS

X-API-KEY	<string>
API key header using this scheme. Example: "X-API-KEY: {API_KEY}"	
Accept	text/plain

PARAMS

campaignId	<long>
-------------------	--------

POST AddLeadsToCampaign

//api/public/campaign/AddLeadsToCampaign

Add leads to a campaign. Add up to 100 leads per request. If a LinkedIn account Id is specified in the AccountLeadPairs, that lead will be mapped to the account in the campaign.

The `name` field in the `customUserFields` array of the leads you are importing, must contain only alpha-numeric characters or underscores `_`. An error will be returned in the case the `name` field does not follow this format.

HEADERS

X-API-KEY	salama
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 235,
  "accountLeadPairs": [
    {
      "linkedInAccountId": 123,
      "lead": {
        "firstName": "John",
        "lastName": "Doe",
        "location": "USA",
        "summary": "SDR @ HeyReach",
        "companyName": "HeyReach",
        "position": "SDR",
        "about": "I like LinkedIn",
        "emailAddress": "john_doe@example.com",
        "customUserFields": [
          {
            "name": "favorite_color",
            "value": "blue"
          }
        ]
      }
    }
  ]
}
```

```
        "profileUrl": "https://www.linkedin.com/in/john-doe"
      }
    }
  ],
  "resumeFinishedCampaign": false,
  "resumePausedCampaign": true
}
```

POST AddLeadsToCampaignV2

//api/public/campaign/AddLeadsToCampaignV2

Add leads to a campaign. Add up to 100 leads per request. If a LinkedIn account Id is specified in the AccountLeadPairs, that lead will be mapped to the account in the campaign. Same as the **AddLeadsToCampaign** request, however this request returns counts for how many of the leads were added, how many were update and how many failed to be added.

The `name` field in the `customUserFields` array of the leads you are importing, must contain only alpha-numeric characters or underscores `_`. An error will be return in the case the `name` field does not follow this format.

HEADERS

X-API-KEY	salama
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 235,
  "accountLeadPairs": [
    {
      "linkedInAccountId": 123,
      "lead": {
        "firstName": "John",
        "lastName": "Doe",
        "location": "USA",
        "summary": "SDR @ HeyReach",
        "companyName": "HeyReach",
        "position": "SDR",
        "about": "I like LinkedIn",
        "emailAddress": "john.doe@example.com"
      }
    }
  ]
}
```

```
        "emailAddress": "john_doe@example.com",
        "customUserFields": [
            {
                "name": "favorite_color",
                "value": "blue"
            }
        ],
        "profileUrl": "https://www.linkedin.com/in/john-doe"
    }
},
{
    "resumeFinishedCampaign": false,
    "resumePausedCampaign": true
}
```

POST StopLeadInCampaign

//api/public/campaign/StopLeadInCampaign

Stops a lead in a campaign

Call this method if you want to stop the progression of a lead in a campaign.

Body Parameters

- **campaignId** (*integer*): The ID of the campaign.
- **leadMemberId**: The lead member Id. You can get the member Id from the field 'linkedin_id' in the method 'GetLeadsFromCampaign' or from 'GetLeadsFromList'
- **leadUrl**: the linked in URL for the lead

HEADERS

X-API-KEY	<string>
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 123,
  "leadMemberId": "123123123",
```

```
"leadUrl": "https://www.linkedin.com/in/john-doe"
}
```

POST GetLeadsFromCampaign

//api/public/campaign/GetLeadsFromCampaign

Gets the leads that are in a campaign.

This request corresponds to the "Lead Analytics" screen in the UI.

Remark: It shows only the "Pending" leads that are about to start executing actions in the campaign. There might be more "Pending" leads from the specified lead list, that the system will insert later for execution.

Body Parameters

- **campaignId** (*integer*): The ID of the campaign.
- **offset** (*integer*): The number of records to skip (for pagination).
- **limit** (*integer*): The maximum number of records to return.
- **timeFrom** (*string, ISO 8601*): The start of the time range for filtering.
- **timeTo** (*string, ISO 8601*): The end of the time range for filtering.
- **timeFilter** (*string*): Defines the time filter for fetching leads. Possible values:
 - **CreationTime** : Filters leads by their creation time.
 - **Everywhere** : No specific time filtering is applied. (*Default behavior if omitted*)
 - **LastActionTakenTime** : Filters leads that executed an action within the given time range
 - **FailedTime** : Filters leads that executed an action within the given time range
 - **LastActionTakenOrFailedTime** : Filters leads that executed an action OR failed within the given time range

Response:

LeadCampaignStatus

- Pending
- InSequence
- Finished
- Paused
- Failed

LeadConnectionStatus

- None
- ConnectionSent

- ConnectionAccepted

LeadMessageStatus

- None
- MessageSent
- MessageReply

LeadStatusMessage (string)

Usually null, but if the lead is in Failed status, this shows the reason why the lead failed.

HEADERS

X-API-KEY	<string>
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "campaignId": 1805
  , "offset": 0
  , "limit": 100
  , "timeFrom": "2024-10-06T17:34:00+02:00"
  , "timeTo": "2024-10-07T17:36:00+02:00"
  , "timeFilter": "CreationTime"
  //, "timeFilter": "Everywhere"
  //, "timeFilter": "LastActionTakenTime"
  //, "timeFilter": "FailedTime"
  //, "timeFilter": "LastActionTakenOrFailedTime"
}
```

POST GetCampaignsForLead

//api/public/campaign/GetCampaignsForLead

Gets Campaigns for a Lead

Retrieves the list of campaigns where the specified lead is.

Remark: The response will contain campaigns that match the provided lead information, such as email, LinkedIn ID, or profile URL.

Body Parameters

- **email** (*string, optional*): The email address of the lead.
- **linkedinId** (*string, optional*): The LinkedIn ID of the lead.
- **profileUrl** (*string, optional*): The LinkedIn profile URL of the lead.
 - for example: https://www.linkedin.com/in/john_doe/
- **offset** (*integer*): The number of records to skip (for pagination).
- **limit** (*integer*): The maximum number of records to return.

Response:

LeadStatus

- Pending
- InSequence
- Finished
- Paused
- Failed
- Excluded
- PendingOrExcludedToBeCalculated

CampaignStatus

- DRAFT
- IN_PROGRESS
- PAUSED
- FINISHED
- CANCELED
- FAILED
- STARTING

HEADERS

X-API-KEY	<string>
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "email": "string",
  "linkedinId": "string",
  "profileUrl": "string",
  "offset": 0,
  "limit": 100
}
```

POST StartCampaign

//api/public/campaign/StartCampaign?campaignId=<long>

Activates a campaign that was created via Create.

Call this after **Create** (and after any **UpdateSequence** / **UpdateSchedule** / **UpdateAccounts** configuration) to start running the campaign. The campaign must have a valid sequence and at least one connected LinkedIn sender account.

Query Parameters

- **campaignId** (*long, required*): The ID of the campaign to activate.

Errors

- **400**: Campaign is in an invalid status, the schedule is invalid, or the lead list / accounts are not usable.
- **404**: Campaign does not exist.

HEADERS

X-API-KEY

{{HR_API_KEY}}

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Accept

text/plain

PARAMS

campaignId

<long>

(Required) The id of the campaign to activate.

POST UpdateSettings

//api/public/campaign/UpdateSettings

Updates the general settings of a campaign: name, lead list, and exclusion options.

Allowed statuses: DRAFT, SCHEDULED, PAUSED. Returns 400 for any other status (e.g. IN_PROGRESS, FINISHED). If the campaign was SCHEDULED, it reverts to DRAFT.

Important: this is a full replacement of the settings below - every exclusion field you omit from the body will be reset to its default (`false` for booleans, `null` for `excludeListId`). Always send the complete set of exclusion settings you want, not a partial diff.

Body Parameters

- **campaignId** (*long, required*): The campaign to update.
- **name** (*string, required*): New campaign name. 1-50 characters.
- **linkedInUserId** (*long, required*): Replacement lead list ID. Must be of type USER_LIST. Cannot be changed once the campaign has been started at least once.
- **excludeContactedFromOtherCampaigns** (*bool, optional*): Default `false` .
- **excludeHasOtherAccConversations** (*bool, optional*): Default `false` .
- **excludeContactedFromSenderInOtherCampaign** (*bool, optional*): Default `false` .
- **excludeListId** (*long, optional*): Must not equal `linkedInUserId` .

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 12345,
  "name": "Renamed Campaign",
  "linkedInUserId": 123456,
  "excludeContactedFromOtherCampaigns": false,
```

```
"excludeHasOtherAccConversations": false,
"excludeContactedFromSenderInOtherCampaign": false,

"excludeListId": null
}
```

POST UpdateSchedule

//api/public/campaign/UpdateSchedule

Replaces the schedule of a campaign.

Defines when the campaign runs each day, which days it is active, the timezone, and optional start/end dates.

Allowed statuses: DRAFT, SCHEDULED, PAUSED. Returns 400 for any other status (e.g. IN_PROGRESS, FINISHED). For SCHEDULED campaigns the campaign reverts to DRAFT. Once a campaign has been started at least once, `startDate` cannot be changed.

Body Parameters

- **campaignId** (*long, required*): The campaign to update.
- **schedule** (*CampaignScheduleApiDto, required*): The new schedule configuration.

CampaignScheduleApiDto fields

- **dailyStartTime** (*TimeSpan, required*): Start of the daily active window, format `"HH:mm:ss"` (e.g. `"09:00:00"`). Must be before `dailyEndTime`. Maximum is 24 hours - see note below.
- **dailyEndTime** (*TimeSpan, required*): End of the daily active window, format `"HH:mm:ss"` (e.g. `"17:00:00"`). Must be after `dailyStartTime`. Maximum is 24 hours - see note below.
- **timeZoneId** (*string, required*): IANA timezone identifier (e.g. `"America/New_York"`, `"Europe/London"`). Default `"Etc/GMT"`.
- **enabledMonday** (*bool, optional*): Default `true`.
- **enabledTuesday** (*bool, optional*): Default `true`.
- **enabledWednesday** (*bool, optional*): Default `true`.
- **enabledThursday** (*bool, optional*): Default `true`.
- **enabledFriday** (*bool, optional*): Default `true`.
- **enabledSaturday** (*bool, optional*): Default `false`.
- **enabledSunday** (*bool, optional*): Default `false`.
- **startDate** (*date, optional*): ISO date, e.g. `"2025-06-01"`. If `null` or in the past, the campaign starts immediately when activated. Cannot be modified after the campaign has been started.
- **endDate** (*date, optional*): ISO date. Campaign stops automatically on this date. Must be after `startDate` if both are set.

At least one `enabled*` day must be `true`.

Note on the 24-hour boundary: the maximum is 24 hours and is sent as `"24:00:00"` (interpreted as end-of-day in the

campaign's `timeZoneId`). Some client libraries (e.g. Python's `datetime.strptime` with `%H:%M:%S`) reject hours outside 0-23. If yours does, send `"23:59:59"` instead.

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 12345,
  "schedule": {
    "dailyStartTime": "09:00:00",
    "dailyEndTime": "17:00:00",
    "timeZoneId": "Etc/GMT",
    "enabledMonday": true,
    "enabledTuesday": true,
    "enabledWednesday": true,
    "enabledThursday": true,
    "enabledFriday": true,
    "enabledSaturday": false,
    "enabledSunday": false,
    "startDate": null,
    "endDate": null
  }
}
```

POST UpdateAccounts

//api/public/campaign/UpdateAccounts

Replaces the entire list of LinkedIn sender accounts assigned to a campaign.

This is a **full replacement**, not a merge. Any account not in the new list will be removed. On a PAUSED campaign, leads assigned to a removed account will be stopped and cannot be resumed.

Allowed statuses: DRAFT, SCHEDULED, PAUSED. Returns 400 for any other status (e.g. IN_PROGRESS, FINISHED). For SCHEDULED campaigns the campaign reverts to DRAFT.

Body Parameters

- **campaignId** (*long, required*): The campaign to update.
- **linkedInAccountIds** (*int[], required*): Full replacement list of sender account IDs. 1-100 items. All accounts must exist and have valid auth.

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignId": 12345,
  "linkedInAccountIds": [
    11111,
    22222
  ]
}
```

POST Create

//api/public/campaign/Create

Creates a campaign in DRAFT status.

After the campaign is fully configured, call **StartCampaign** (`POST /api/public/campaign/StartCampaign?campaignId=`) to activate it.

Important: a campaign cannot be activated without a sequence. The example body below includes a sample `schedule` and `sequence` ; if you omit `sequence` from your own call, you must add one via **UpdateSequence** before **StartCampaign** will succeed.

Body Parameters

- **name** (*string, required*): The campaign name. 1-50 characters.

name (string, required): The campaign name. 1-50 characters.

- **linkedinUserId** (*long, required*): ID of the lead list. Must exist and be of type USER_LIST.
- **linkedinAccountIds** (*int[], required*): Sender LinkedIn account IDs. 1-100 items. All accounts must exist and have valid auth.
- **excludeContactedFromOtherCampaigns** (*bool, optional*): Skip leads already in any other campaign. Default `false`.
- **excludeHasOtherAccConversations** (*bool, optional*): Skip leads that already have conversations with other sender accounts. Default `false`.
- **excludeContactedFromSenderInOtherCampaign** (*bool, optional*): Skip leads the sender accounts have already contacted in other campaigns. Default `false`.
- **excludeListId** (*long, optional*): A separate list of leads to always exclude. Must not equal `linkedinUserId`.
- **schedule** (*CampaignScheduleApiDto, optional*): When the campaign runs. See **UpdateSchedule** for the object shape. If omitted, defaults to Mon-Fri 09:00-17:00 UTC.
- **sequence** (*PublicSequenceNodeDto, optional*): The automation workflow. The START node is implicit - do not include it. See **UpdateSequence** for the object shape and the `actionDelay` rules. Note: every node that follows an action step (including `END` nodes) must have `actionDelay` of at least 3 hours - use `actionDelay: 3` with `actionDelayUnit: "HOUR"`; an omitted or `0` delay is rejected with `Node at: ... has invalid delay: 00:00:00`. If this parameter is omitted, add it via **UpdateSequence** before starting.

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "name": "My New Campaign",
  "linkedinUserId": 123456,
  "linkedinAccountIds": [
    11111,
    22222
  ],
  "schedule": {
    "dailyStartTime": "09:00:00",
    "dailyEndTime": "17:00:00",
    "timeZoneId": "Europe/London",
    "enabledMonday": true,
    "enabledTuesday": true,
    "enabledWednesday": true,
```



```

    "enabledThursday": true,
    "enabledFriday": true,
    "enabledSaturday": false,

    "enabledSunday": false,
    "startDate": null,
    "endDate": null
  },
  "sequence": {
    "nodeType": "CONNECTION_REQUEST",
    "actionDelay": 0,
    "actionDelayUnit": "DAY",
    "payload": {
      "messages": [
        "Hi {FIRST_NAME}, I'd love to connect!"
      ],
      "fallbackMessage": "Hi there, I'd love to connect!",
      "toBeWithdrawnAfterDays": 30
    },
    "conditionalNode": {
      "nodeType": "MESSAGE",
      "actionDelay": 2,
      "actionDelayUnit": "DAY",
      "payload": {
        "messages": [
          "Thanks for connecting, {FIRST_NAME}!"
        ],
        "fallbackMessage": "Thanks for connecting!"
      },
      "unconditionalNode": {
        "nodeType": "END",
        "actionDelay": 3,
        "actionDelayUnit": "HOUR"
      }
    },
    "unconditionalNode": {
      "nodeType": "VIEW_PROFILE",
      "actionDelay": 1,
      "actionDelayUnit": "DAY",
      "unconditionalNode": {
        "nodeType": "END",
        "actionDelay": 3,
        "actionDelayUnit": "HOUR"
      }
    }
  }
}

```

POST UpdateSequence

//api/public/campaign/UpdateSequence

Creates or fully replaces the sequence (workflow) of a campaign.

The START node is implicit; the root of the request must be your first action node. Every path through the tree must terminate with an **END** node.

Allowed statuses: DRAFT, SCHEDULED, PAUSED. Returns 400 for any other status (e.g. IN_PROGRESS, FINISHED). For PAUSED campaigns a safe update is performed - existing lead states are preserved and leads are remapped to compatible positions in the new sequence. For SCHEDULED campaigns the campaign reverts to DRAFT.

Body Parameters

- **campaignId** (*long, required*): The campaign to update.
- **sequence** (*PublicSequenceNodeDto, required*): Root node of the workflow tree.

PublicSequenceNodeDto fields

- **nodeType** (*string, required*): One of `CONNECTION_REQUEST`, `MESSAGE`, `INMAIL`, `VIEW_PROFILE`, `FOLLOW`, `LIKE_POST`, `FIND_EMAIL`, `CHECK_IS_CONNECTION`, `CHECK_IS_OPEN_PROFILE`, `SEND_LEAD_TO_INSTANTLY`, `SEND_LEAD_TO_SMARTLEAD`, `SEND_LEAD_TO_BISON`, `END`.
- **unconditionalNode** (*PublicSequenceNodeDto, required for non-END nodes*): The next node to follow unconditionally, or when a branching condition is `false`.
- **conditionalNode** (*PublicSequenceNodeDto, required for branching nodes*): The next node to follow when the branching condition is `true`. Branching nodes are `CONNECTION_REQUEST`, `CHECK_IS_CONNECTION`, `CHECK_IS_OPEN_PROFILE`, `FIND_EMAIL`. All other non-END nodes must NOT set this field.
- **actionDelay** (*int, optional*): How long to wait before executing this node, paired with `actionDelayUnit`. Range 0-100. **Recommended default for non-root nodes:** `actionDelay: 3` with `actionDelayUnit: "HOUR"` - that is the minimum the server accepts when the parent is in the list below. The resulting delay (`actionDelay` x `actionDelayUnit`) must be at least 3 hours and not more than 500 days if the parent is in the list - this applies to every node type, including `END`. Parents that require the minimum on their **unconditional** child: `CONNECTION_REQUEST`, `MESSAGE`, `INMAIL`, `VIEW_PROFILE`, `FOLLOW`, `LIKE_POST`. Parents that require the minimum on their **conditional** child: `CONNECTION_REQUEST`. The root node has no parent and may use `0`.
- **actionDelayUnit** (*string, optional*): Unit for `actionDelay`. `HOUR` or `DAY`.
- **payload** (*object, conditional*): **Schema is node-specific** - the shape of `payload` depends on `nodeType`, it is NOT a shared object. Required for action nodes that take configuration: `CONNECTION_REQUEST`, `MESSAGE`, `INMAIL`, `LIKE_POST`, `SEND_LEAD_TO_INSTANTLY`, `SEND_LEAD_TO_SMARTLEAD`, `SEND_LEAD_TO_BISON`. Not used for action-only nodes: `VIEW_PROFILE`, `FOLLOW`, `FIND_EMAIL`, `CHECK_IS_CONNECTION`, `CHECK_IS_OPEN_PROFILE`, `END`. Refer to the API documentation for the exact schema per node type.
- **externalReference** (*string, optional*): Your own tracking ID for this step, returned via API and webhooks. Max 100 characters.

HEADERS

X-API-KEY `{{HR_API_KEY}}`

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type `application/json`

Accept `text/plain`

json

```
{
  "campaignId": 12345,
  "sequence": {
    "nodeType": "CONNECTION_REQUEST",
    "actionDelay": 0,
    "actionDelayUnit": "DAY",
    "payload": {
      "messages": [
        "Hi {FIRST_NAME}, I'd love to connect!"
      ],
      "fallbackMessage": "Hi there, I'd love to connect!",
      "toBeWithdrawnAfterDays": 30
    },
    "conditionalNode": {
      "nodeType": "MESSAGE",
      "actionDelay": 2,
      "actionDelayUnit": "DAY",
      "payload": {
        "messages": [
          "Thanks for connecting, {FIRST_NAME}!"
        ],
        "fallbackMessage": "Thanks for connecting!"
      },
      "unconditionalNode": {
        "nodeType": "END",
        "actionDelay": 3,
        "actionDelayUnit": "HOUR"
      }
    },
    "unconditionalNode": {
      "nodeType": "END",
      "actionDelay": 3,
      "actionDelayUnit": "HOUR"
    }
  }
}
```

GET GetCampaignSequence

//api/public/campaign/GetCampaignSequence?campaignId=<long>

Retrieves the current sequence (workflow) of a campaign as a **PublicSequenceNodeDto**.

The returned object is directly compatible with the `sequence` field in **Create** and **UpdateSequence** - you can use it as-is without modification. Returns an empty 200 response if the campaign has no sequence.

Query Parameters

- campaignId** (*long, required*): The campaign whose sequence to retrieve.

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Accept	text/plain

PARAMS

campaignId	<long>
	(Required) The campaign whose sequence to retrieve

POST CreateCampaignFromTemplate

//api/public/campaign/CreateCampaignFromTemplate

Creates a new campaign by cloning the sequence and schedule of an existing campaign (the template).

The new campaign is created in DRAFT status. The sequence (workflow) and schedule are copied from the template campaign identified by `campaignIdForTemplate` ; you supply the new name, lead list, sender accounts and exclude options. After creation, call **StartCampaign** (`POST /api/public/campaign/StartCampaign?campaignId=<id>`) to activate it.

Body Parameters

- campaignIdForTemplate** (*long, required*): ID of the existing campaign to use as the template. Its sequence and schedule are copied to the new campaign.
- name** (*string, required*): The new campaign name. 1-50 characters.
- linkedInUserListId** (*long, required*): ID of the lead list for the new campaign. Must exist and be of type USER_LIST.
- linkedInAccountIdsForCampaign** (*long[], required*): Sender LinkedIn account IDs. 1-100 items. All accounts must exist and have valid auth.
- excludeContactedFromOtherCampaigns** (*bool, required*): Skip leads already in any other campaign.
- excludeHasOtherAccConversations** (*bool, required*): Skip leads that already have conversations with other sender accounts.

- **excludeContactedFromSenderInOtherCampaign** (*bool, required*): Skip leads the sender accounts have already contacted in other campaigns.
- **excludeListId** (*long, optional*): A separate list of leads to always exclude. Must not equal `linkedInUserId`.

HEADERS

X-API-KEY	{{HR_API_KEY}}
	API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "campaignIdForTemplate": 12345,
  "name": "My Campaign From Template",
  "linkedInUserId": 123456,
  "excludeContactedFromOtherCampaigns": false,
  "excludeHasOtherAccConversations": false,
  "excludeContactedFromSenderInOtherCampaign": false,
  "linkedInAccountIdsForCampaign": [
    11111,
    22222
  ],
  "excludeListId": null
}
```

PublicInbox

Methods for working with the HeyReach Inbox. Get and filter conversations and send messages from any of your accounts.

POST GetConversationsV2

//api/public/inbox/GetConversationsV2

Get a paginated collection of LinkedIn conversations. Get up to 100 lists per request

Get a paginated collection of LinkedIn conversations. Get up to 100 hits per request.

Body Parameters

- **filters**
 - **linkedinAccountIds** (int[]): The ids of the LinkedIn senders
 - **campaignIds** (int[])
 - **searchString** (string, optional)
 - **leadLinkedInId** (string, optional) - The LinkedIn ID of the lead. You can find this ID as "linkedin_id" in the response of many of our endpoints, for example in the '/api/public/lead/GetLead' endpoint.
 - **leadProfileUrl** (string, optional) - The linkedin URL of the lead
 - **searchString** (string, optional)
 - **tags** - case-insensitive list of lead's tags. Only the conversations of the leads that have at least one of the tags will be exported.
 - **seen** (boolean, optional)

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "filters": {
    "linkedinAccountIds": [],
    "campaignIds": [],
    "searchString": "",
    "leadLinkedInId": "",
    "leadProfileUrl": "https://www.linkedin.com/in/john_doe/",
    "tags": [
      "Lead tag1",
      "Lead Tag2"
    ],
    "seen": null
  },
  "offset": 0,
  "limit": 10
}
```

GET GetChatroom

//api/public/inbox/GetChatroom/:accountId/:conversationId

Get a LinkedIn conversation with its messages by Id.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Accept	text/plain

PATH VARIABLES

accountId	<integer> (Required)
conversationId	<string> (Required)

POST SendMessage

//api/public/inbox/SendMessage

Send a message to a LinkedIn conversation.

Parameters:

- **linkedinAccountId** - The id of your LinkedIn sender

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "message": "Hi there",
  "subject": "Hi there",
  "conversationId": "2-ODM0YmIzNzgtOGEyOS00ZTYzLWExYTItNmM0MWNhMjNlNGZjXzAxMw==",
  "linkedInAccountId": 123
}
```

POST SetSeenStatus

//api/public/inbox/SetSeenStatus

Mark a given conversation as seen or unseen based on the seen parameter.

HEADERS

X-API-KEY	Public API Key
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "conversationId": "string",
  "linkedInAccountId": 1320,
  "seen": true
}
```

PublicLinkedInAccount

Methods for working with LinkedIn accounts in HeyReach. Filter accounts. Soon to add more methods.

POST GetAll

//api/public/li_account/GetAll

Get a paginated collection of all LinkedIn accounts. Get up to 100 accounts per request.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "offset": 0,
  "keyword": "My account name",
  "limit": 10
}
```

GET GetById

//api/public/li_account/GetById?accountId=<integer>

Get a LinkedIn account by id

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Accept	text/plain

PARAMS

accountId

<integer>

(Required) Id of the account to be returned

PublicList

Methods for working with HeyReach lists. Get leads and companies from lists. And add leads to a list.

GET GetById

//api/public/list/GetById?listId=<integer>

Get a lead or company list by Id

HEADERS

X-API-KEY

<string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Accept

text/plain

PARAMS

listId

<integer>

(Required) The Id of the list to be retrieved

POST GetAll

//api/public/list/GetAll

Get a paginated collection of all company and lead lists. Get up to 100 lists per request.

HEADERS

X-API-KEY

<string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type application/json

Accept text/plain

Body raw (json)

json

```
{
  "offset": 0,
  "keyword": "my list name",
  "listType": "USER_LIST",
  "campaignIds": [123,125],
  "limit": 10
}
```

POST GetLeadsFromList

//api/public/list/GetLeadsFromList

Get a paginated collection of leads from a lead list. Get up to 1000 leads per request.

- **listId**: The id of the lead list.
- **keyword (optional)**: A search term to filter leads by name or other relevant fields.
- **leadProfileUrl (optional)**: the linkedIn profile url of the lead, for example '<https://www.linkedin.com/in/john-doe/>'
- **leadLinkedInId (string, optional)**: The LinkedIn ID of the lead. You can find this ID as "linkedin_id" in the response of many of our endpoints, for example in the '/api/public/lead/GetLead' endpoint.
- **createdFrom (string, ISO 8601)**: Specifies the start date and time for filtering leads based on their creation timestamp. Only leads created on or after this date will be included. Can be omitted.
- **createdTo (string, ISO 8601)**: Specifies the end date and time for filtering leads based on their creation timestamp. Only leads created before or at this date will be included. Can be omitted.

HEADERS

X-API-KEY <string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type application/json

Accept text/plain

Body raw (json)

```
json

{
  "listId": 123,
  "offset": 0,
  "keyword": "",
  "leadProfileUrl": "https://www.linkedin.com/in/john-doe/",
  "leadLinkedInId": "121313fsdf234",
  "limit": 10,
  "createdFrom": "2024-10-06T17:34:00+02:00",
  "createdTo": "2024-10-07T17:34:00+02:00"
}
```

DELETE DeleteLeadsFromList

//api/public/list/DeleteLeadsFromList

Deletes the specified leads from a lead list.

Params:

- **listId** (*integer*): The ID of the list.
- **leadMemberIds** : Array of the LinkedIn IDs of the leads to be deleted. In our API responses, this *MemberId* can also be named as 'linkedin_id'.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json
```

```
{
  "listId": 3672,

  "leadMemberIds": ["1111", "222"]
}
```

DELETE DeleteLeadsFromListByProfileUrl

//api/public/list/DeleteLeadsFromListByProfileUrl

Deletes the specified leads from a lead list by LinkedIn profile url.

Params:

- **listId** (*integer*): The ID of the list.
- **profileUrls**: Array of LinkedIn urls of the leads to be deleted.

NOTE: this endpoint will return OK(200) even if the leads are not found in the list.

If leads are not found in the list, they will be returned in the response, in the field 'notFoundInList' which will consist only the 'username', not the whole url. (see the example response)

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "listId": 3672,
  "profileUrls": [
    "https://www.linkedin.com/in/john-doe/",
    "https://www.linkedin.com/in/jane-doe/"
  ]
}
```

POST GetCompaniesFromList

//api/public/list/GetCompaniesFromList

Get a paginated collection of companies from a company list. Get up to 1000 companies per request.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "listId": 123,
  "offset": 0,
  "keyword": "HeyReach",
  "limit": 10
}
```

POST AddLeadsToList

//api/public/list/AddLeadsToList

Add leads to a lead list. Add up to 100 leads per request.

The `name` field in the `customUserFields` array of the leads you are importing, must contain only alpha-numeric characters or underscores `_`. An error will be return in the case the `name` field does not follow this format.

Be aware that adding leads to a list is not the same as addig them to a campaign. If the campaign is in a finished state or has already used all the leads in it, then leads added to the list will not be started in the campaign. If you want to add the leads to a specific campaign, then use the `AddLeadsToCampaign` or `AddLeadsToCampaignV2` methods.

HEADERS

X-API-KEY

<string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type

application/json

Accept

text/plain

Body raw (json)

json

```
{
  "leads": [
    {
      "firstName": "John",
      "lastName": "Doe",
      "location": "USA",
      "summary": "SDR @ HeyReach",
      "companyName": "HeyReach",
      "position": "SDR",
      "about": "I like LinkedIn",
      "emailAddress": "john_doe@example.com",
      "customUserFields": [
        {
          "name": "favorite_color",
          "value": "blue"
        }
      ],
      "profileUrl": "https://www.linkedin.com/in/john-doe"
    }
  ],
  "listId": 123
}
```

POST AddLeadsToListV2

//api/public/list/AddLeadsToListV2

Add leads to a lead list. Add up to 100 leads per request. Same as the **AddLeadsToList** request, however this request returns counts for how many of the leads were added, how many were update and how many failed to be added.

The `name` field in the `customUserFields` array of the leads you are importing, must contain only alpha-numeric characters or underscores `_`. An error will be return in the case the `name` field does not follow this format.

Be aware that adding leads to a list is not the same as adding them to a campaign. If the campaign is in a finished state or has already used all the leads in it, then leads added to the list will not be started in the campaign. If you want to add the leads to a specific campaign, then use the `AddLeadsToCampaign` or `AddLeadsToCampaignV2` methods.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "leads": [
    {
      "firstName": "John",
      "lastName": "Doe",
      "location": "USA",
      "summary": "SDR @ HeyReach",
      "companyName": "HeyReach",
      "position": "SDR",
      "about": "I like LinkedIn",
      "emailAddress": "john_doe@example.com",
      "customUserFields": [
        {
          "name": "favorite_color",
          "value": "blue"
        }
      ],
      "profileUrl": "https://www.linkedin.com/in/john-doe"
    }
  ],
  "listId": 123
}
```

POST GetListsForLead

//api/public/list/GetListsForLead

Gets Lists for a Lead

This endpoint retrieves the lists associated with a specific lead.

Remark: The response will include lead lists that match the provided lead details such as email, LinkedIn ID, or profile URL.

Body Parameters

- **email** (*string, optional*): The email address of the lead.
- **linkedinId** (*string, optional*): The LinkedIn ID of the lead.
- **profileUrl** (*string, optional*): The LinkedIn profile URL of the lead. For example: https://www.linkedin.com/in/john_doe/
- **offset** (*integer*): The number of records to skip (for pagination).
- **limit** (*integer*): The maximum number of records to return.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "email": "john_doe@example.com",
  "linkedinId": "121313fsdf234",
  "profileUrl": "https://www.linkedin.com/in/john_doe/",
  "offset": 0,
  "limit": 100
}
```

POST CreateEmptyList

//api/public/list/CreateEmptyList

Create an empty lead or company list. You pass the list name and the list type (**USER_LIST** or **COMPANY_LIST**). If the type value is left empty, a Lead list will be created by default.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
------------------	---

API key header using this scheme. Example: X-API-KEY: {API_KEY}

Content-Type application/json

Accept text/plain

Body raw (json)

json

```
{
  "name": "<string>",
  "type": "<COMPANY_LIST|USER_LIST>"
}
```

PublicStats

POST Get Overall Stats

//api/public/stats/GetOverallStats

Gets the overall stats for the specified filters.

- **Method:** POST
 - **Content-Type:** application/json
-

Request Body

- **accountIds:** Array of Ids of the LinkedIn senders. If empty - all the senders will be included.
- **campaignIds:** Array of the Ids of the campaigns to be included. If empty - all the campaigns will be included.
- **startDate:**
- **endDate:**

```
{
"accountIds": [1234],
"campaignIds": [],
"startDate": "2024-12-17T00:00:00.000Z",
"endDate": "2024-12-19T23:59:59.999Z"
}
```

HEADERS

X-API-KEY	<string>
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "accountIds": [1234],
  "campaignIds": [],
  "startDate": "2024-12-17T00:00:00.000Z",
  "endDate": "2024-12-19T23:59:59.999Z"
}
```

POST GetOverallStatsByCampaign

//api/public/stats/GetOverallStatsByCampaign

Gets the overall stats broken down per campaign for the specified filters.

Same filters as **GetOverallStats**, but the response is grouped by campaign: both `byDayStats` and `overallStats` return a list of per-campaign stat objects (each carrying `campaignId`, `campaignName` and `isCampaignDeleted`) instead of a single aggregated object.

- **Method:** POST
- **Content-Type:** application/json

Request Body

- **accountIds:** Array of Ids of the LinkedIn senders. If empty - all the senders will be included.
- **campaignIds:** Array of the Ids of the campaigns to be included. If empty - all the campaigns will be included.
- **startDate:**
- **endDate:**

```
{
  "accountIds": [1234],
  "campaignIds": [],
  "startDate": "2024-12-17T00:00:00.000Z",
  "endDate": "2024-12-19T23:59:59.999Z"
}
```

```
"startDate": "2024-12-17T00:00:00.000Z",
"endDate": "2024-12-19T23:59:59.999Z"
}
```

HEADERS

X-API-KEY	<string>
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "accountIds": [1234],
  "campaignIds": [],
  "startDate": "2024-12-17T00:00:00.000Z",
  "endDate": "2024-12-19T23:59:59.999Z"
}
```

PublicLead

POST GetLead

//api/public/lead/GetLead

Gets Lead Details

This endpoint retrieves the details of a specific lead based on their LinkedIn profile URL.

Remark: The response will provide detailed information about the lead that matches the specified profile URL.

Body Parameters

- profileUrl** (*string*): The LinkedIn profile URL of the lead. This parameter is required.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{  
  "profileUrl": "https://www.linkedin.com/in/john_doe/"  
}
```

POST AddTags

//api/public/lead/AddTags

Add Tags to Lead

Adds tags to the lead. Existing tags will not be changed.

- **leadProfileUrl (optional)**: the linkedIn profile url of the lead, for example '<https://www.linkedin.com/in/john-doe/>'
- **leadLinkedInId (string, optional)**: The LinkedIn ID of the lead. You can find this ID as "linkedin_id" in the response of many of our endpoints, for example in the '/api/public/lead/GetLead' endpoint.
- **tags (string array)**: The tags to be added to the lead.
- **createTagIfNotExisting (boolean)**: If `true`, creates tags that don't exist. if `false` and there is a tag that does not exist, "Bad Request" will be returned.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "leadProfileUrl": "https://www.linkedin.com/in/john_doe/",
  "leadLinkedInId": "",
  "tags": [
    "tag1",
    "tag2"
  ],
  "createTagIfNotExisting": false
}
```

POST GetTags

//api/public/lead/GetTags

Get Tags for a Lead

Gets the tags for a lead. The tags are alphabetically sorted.

- **profileUrl**: the linkedIn profile url of the lead, for example '<https://www.linkedin.com/in/john-doe/>'

HEADERS

X-API-KEY

<string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type

application/json

Accept

text/plain

Body raw (json)

json

```
{
  "profileUrl": "https://www.linkedin.com/in/john_doe/"
}
```

POST ReplaceTags

Replaces Tags to Lead

Removes the existing tags and replaces with the new tags.

- **leadProfileUrl (optional)**: the linkedIn profile url of the lead, for example '<https://www.linkedin.com/in/john-doe/>'
- **leadLinkedInId (string, optional)**: The LinkedIn ID of the lead. You can find this ID as "linkedin_id" in the response of many of our endpoints, for example in the '/api/public/lead/GetLead' endpoint.
- **tags (string array)**: The tags to be added to the lead.
- **createTagIfNotExisting (boolean)**: If `true`, creates tags that don't exist. if `false` and there is a tag that does not exist, "Bad Request" will be returned.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "leadProfileUrl": "https://www.linkedin.com/in/john_doe/",
  "leadLinkedInId": "",
  "tags": [
    "tag1",
    "tag2"
  ],
  "createTagIfNotExisting": false
}
```

LeadTags

POST CreateTags

Create one or multiple tags for your workspace. You can assign these tags to leads. Available colors: Blue, Green, Purple, Pink, Red, Cyan, Yellow, Orange.

HEADERS

X-API-KEY	Public API Key
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "tags": [
    {
      "displayName": "string",
      "color": "Blue|Green|Purple|Pink|Red|Cyan|Yellow|Orange"
    }
  ]
}
```

PublicWebhooks

POST Create Webhook

//api/public/webhooks/CreateWebhook

Create Webhook

Endpoint

POST //api/public/webhooks/CreateWebhook

Description

This API creates a new webhook that listens to specified events, optionally filtered by campaign IDs.

Request Body Example

```
json

{
  "webhookName": "string",
  "webhookUrl": "string",
  "eventType": "CONNECTION_REQUEST_SENT" | "CONNECTION_REQUEST_ACCEPTED" | "MESSAGE_SENT" |
              "MESSAGE_REPLY_RECEIVED" | "INMAIL_SENT" | "INMAIL_REPLY_RECEIVED" | "FOLLOW_SENT" |
              "LIKED_POST" | "VIEWED_PROFILE" | "CAMPAIGN_COMPLETED" | "LEAD_TAG_UPDATED" |
              "EVERY_MESSAGE_REPLY_RECEIVED"
  "campaignIds": []
}
```

Request Parameters

- webhookName** (string): The name of the webhook.
- webhookUrl** (string): The URL to which the webhook will send POST requests.
- eventType** (string): The type of event that triggers the webhook. It must be one of the following values:
 - CONNECTION_REQUEST_SENT
 - CONNECTION_REQUEST_ACCEPTED
 - MESSAGE_SENT
 - MESSAGE_REPLY_RECEIVED (only the first reply)
 - INMAIL_SENT
 - INMAIL_REPLY_RECEIVED (only the first reply)
 - EVERY_MESSAGE_REPLY_RECEIVED (including repliies for both messages and inmails)
 - FOLLOW_SENT
 - LIKED_POST
 - VIEWED_PROFILE
 - CAMPAIGN_COMPLETED
 - LEAD_TAG_UPDATED
- campaignIds** (array): A list of campaign IDs. If this array is empty, the webhook will listen for the specified **eventType** across all campaigns. If specific campaign IDs are provided, the webhook will listen only to those campaigns.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body: raw (json)

```
json

{
  "webhookName": "string",
  "webhookUrl": "string",
  "eventType": "CONNECTION_REQUEST_SENT" | "CONNECTION_REQUEST_ACCEPTED" | "MESSAGE_SENT" |
    "MESSAGE_REPLY_RECEIVED" | "INMAIL_SENT" | "INMAIL_REPLY_RECEIVED" | "FOLLOW_S
    "LIKED_POST" | "VIEWED_PROFILE" | "CAMPAIGN_COMPLETED" | "LEAD_TAG_UPDATED" |
    "EVERY_MESSAGE_REPLY_RECEIVED"
  "campaignIds": []
}
```

GET Get Webhook By Id

//api/public/webhooks/GetWebhookById?webhookId=123&includeCustomHeaders=false

Get Webhook By Id

Description
Get a webhook by Id.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

PARAMS

webhookId	123
includeCustomHeaders	false

POST GetAllWebhooks

//api/public/webhooks/GetAllWebhooks

//api/public/webhooks/GetAllWebhooks

Get All Webhooks

Description

Get all webhooks.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "offset": 0,
  "limit": 100,
  "includeCustomHeaders": false
}
```

PATCH Update Webhook

//api/public/webhooks/UpdateWebhook?webhookId=1234

Update Webhook

Endpoint

PATCH //api/public/webhooks/UpdateWebhook?webhookId=1234

Description

This API updates an existing webhook by modifying its configuration, such as name, URL, event type, associated campaigns, and status.

Query Parameters

- **webhookId** (`string`): The unique identifier of the webhook to update. This must be provided as a query parameter.

Request Body Example

json

```
{
  "webhookName": "string",
  "webhookUrl": "string",
  "eventType": "CONNECTION_REQUEST_SENT",
  "campaignIds": [],
  "isActive": true
}
```

Request Parameters

- **webhookName** (`string`): The name of the webhook. If NULL or omitted, the original name will be kept.
- **webhookUrl** (`string`): The URL to which the webhook will send POST requests. If NULL or omitted, the original url will be kept
- **eventType** (`string`): The type of event that triggers the webhook. If null or omitted, the original will be kept. It must be one of the following values:
 - `CONNECTION_REQUEST_SENT`
 - `CONNECTION_REQUEST_ACCEPTED`
 - `MESSAGE_SENT`
 - `MESSAGE_REPLY_RECEIVED`
 - `INMAIL_SENT`
 - `INMAIL_REPLY_RECEIVED`
 - `FOLLOW_SENT`
 - `LIKED_POST`
 - `VIEWED_PROFILE`
 - `CAMPAIGN_COMPLETED`
 - `LEAD_TAG_UPDATED`
- **campaignIds** (`array`): A list of campaign IDs.
If null or omitted, the original array will be kept.
If this array is empty, the webhook will listen for the specified `eventType` across all campaigns. If specific campaign IDs are provided, the webhook will listen only to those campaigns.
- **isActive** (`boolean` | `null`): Determines whether the webhook should be active. If `true`, the webhook is enabled; if `false`, it is disabled. If `null`, the activation status remains unchanged.

HEADERS

X-API-KEY

<string>

API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type	application/json
Accept	text/plain

PARAMS

webhookId1234

Body raw (json)

```
json

{
  "webhookName": "string" | null,
  "webhookUrl": "string" | null,
  "eventType": "CONNECTION_REQUEST_SENT" | "CONNECTION_REQUEST_ACCEPTED" | "MESSAGE_SENT" | "MESSAGE_RECEIVED" | "MESSAGE_READ",
  "campaignIds": [] | null
  "isActive": true | null
}
```

DELETE Delete Webhook

//api/public/webhooks/DeleteWebhook?webhookId=1234

Delete Webhook

Endpoint
Delete //api/public/webhooks/DeleteWebhook?webhookId=1234

Description
This API deletes an existing webhook.

Query Parameters

- webhookId (string): The unique identifier of the webhook to delete. This must be provided as a query parameter.

HEADERS

X-API-KEY <string>
API key header using this scheme. Example: "X-API-KEY: {API_KEY}"

Content-Type application/json

Accept text/plain

PARAMS

webhookId 1234

PublicMyNetwork

POST GetMyNetworkForSender

//api/public/MyNetwork/GetMyNetworkForSender

GetMyNetworkForSender

Endpoint

POST / api/public/MyNetwork/GetMyNetworkForSender

Description

Gets paginated list of the network for the specified sender

Request Body Example

```
json
{
  "pageNumber": 0,
  "pageSize": 100,
  "senderId": 1234
}
```

StartFragment

Request Parameters

- `senderId` (number): The id of the sender account for which to retrieve the network

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "pageNumber": 0,
  "pageSize": 100,
  "senderId": 1234
}
```

POST IsConnection

//api/public/MyNetwork/IsConnection

IsConnection

Endpoint

POST / api/public/MyNetwork/IsConnection

Description

Gets a value indicating if the lead is a connection to the sender

Request Body Example

json

```
{
  "senderAccountId": 0,
  "leadProfileUrl": "string",
  "leadLinkedInId": "string"
}
```

```
}
```

StartFragment

Request Parameters

- **senderId** (number): The id of the sender account for which to check.
 - **leadProfileUrl** (optional): The linkedIn url lead.
 - **leadLinkedInId** (optional): The linkedIn id of the lead.
- Either **leadProfileUrl** or **leadLinkedInId** should be specified in the request, if both are specified there will be an error.

HEADERS

X-API-KEY	<string> API key header using this scheme. Example: "X-API-KEY: {API_KEY}"
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "senderAccountId": 0,
  "leadProfileUrl": "string",
  "leadLinkedInId": "string"
}
```

Organization

Organization Management API

This HeyReach API allows you to manage workspaces, users, permissions and other API/Integration Keys in your organization. This API has the highest access privileges so access is only available for organization Admins.

Finding your Organization API key

Authentication is done same as the regular HeyReach API, using the **X-API-KEY** Header. The only difference is that these methods require the Organization API Key which can be found in your **Organization settings**.

The API key is used to authenticate the incoming requests and map them to your organization. These API keys never expire, however they can be deleted/deactivated/rolled-over.

Rate Limits

The Organization API has a separate rate limit of `300` requests per minute. This limit is separate from the regular API.

Going above the limit will return a `429` HTTP status code and an error.

Workspace API Keys

GET GetWorkspaceApiKeys

`//api/public/management/organizations/api-keys/workspaces/:workspaceId`

Get Public API, Make, Zapier, N8N and other relevant integration keys for a given workspace.

HEADERS

X-API-KEY	Workspace API Key
-----------	-------------------

Accept	text/plain
--------	------------

PATH VARIABLES

workspaceId	5421
-------------	------

POST CreateWorkspaceApiKeys

`//api/public/management/organizations/api-keys/workspaces/:workspaceId`

Generate new API/Integration (Make, Zapier, N8N etc...) keys in a given workspace. Available API key types: **PUBLIC, N8N, MAKE, ZAPIER, MCP**

HEADERS

X-API-KEY	workspace API Key
Content-Type	application/json
Accept	text/plain

PATH VARIABLES

workspaceId	5421
-------------	------

Body raw (json)

```
json

{
  "apiKeyType": "PUBLIC | N8N | MAKE | ZAPIER | MCP"
}
```

Workspaces

GET GetAllWorkspaces

//api/public/management/organizations/workspaces?Offset=9109&Limit=66

List all workspaces in your organization.

HEADERS

X-API-KEY	Workspace API Key
Accept	text/plain

PARAMS

Offset	9109
Limit	66

POST CreateWorkspace

//api/public/management/organizations/workspaces

Create new workspace in your organization

HEADERS

X-API-KEY	Workspace API Key
Content-Type	application/json
Accept	text/plain

Body raw (json)

```
json

{
  "workspaceName": "string",
  "seatsLimit": null
}
```

PATCH UpdateWorkspace

//api/public/management/organizations/workspaces/:workspaceId

Update a given workspace in your organization.

HEADERS

X-API-KEY	Workspace API Key
Content-Type	application/json
Accept	text/plain

PATH VARIABLES

Body raw (json)

json

```
{
  "workspaceName": "string",
  "seatsLimit": {
    "value": 9730
  }
}
```

Workspace Users

POST GetAllUsers

//api/public/management/organizations/users

Get all existing and invited users in your organization. Filter by role and invitation status.

HEADERS

X-API-KEY	Workspace API Key
------------------	-------------------

Content-Type	application/json
---------------------	------------------

Accept	text/plain
---------------	------------

Body raw (json)

json

```
{
  "offset": 895,
  "role": "Admin",
  "invitationStatus": [
    "Accepted",
    "Pending"
  ]
}
```

```
    "limit": 38
  }
```

POST InviteAdmins

//api/public/management/organizations/users/invite/admins

Invite one or multiple users as admins in your organization. The invitation emails will not be sent, only an invitation URL is generated. You can send this URL to the relevant user in order to register them to HeyReach.

HEADERS

X-API-KEY Workspace API Key

Content-Type application/json

Accept text/plain

Body raw (json)

json

```
{
  "inviterEmail": "tLAFGLB@fSaRWLZVXcdVaLk1wbvnAC.bnc",
  "emails": [
    "string",
    "string"
  ]
}
```

POST InviteMembers

//api/public/management/organizations/users/invite/members

Invite one or multiple users in your organization. Specify the relevant permissions for each invited user. The invitation emails will not be sent, only an invitation URL is generated. You can send this URL to the relevant user in order to register them to HeyReach.

HEADERS

X-API-KEY	Workspace API Key
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "inviterEmail": "pQswPC@kZCGIUB0EKCZxNQjhScp.jef",
  "workspaceIds": [
    8731,
    1166
  ],
  "permissions": {
    "viewLinkedInSenders": false,
    "manageLinkedInSendersSettings": false,
    "viewLeadLists": false,
    "importEditManageLeadLists": false,
    "viewMyNetwork": false,
    "viewCampaigns": false,
    "editManageCampaigns": false,
    "viewLinkedInSenderInboxes": false,
    "replyFromLinkedInSenderInboxes": false,
    "viewIntegrations": false,
    "manageIntegrations": false,
    "exportDataToCRMs": false,
    "viewNotifications": false,
    "manageNotifications": false
  },
  "emails": [
    "string",
    "string"
  ]
}
```

POST InviteManagers

//api/public/management/organizations/users/invite/managers

Invite one or multiple users as managers in your organization. Manager users are special kind of users that exist outside your organization and are invited to specific workspaces. These users will not be part of you organization and only have access to the specified workspaces. These users are automatically added to your workspace and don't need to register.

HEADERS

X-API-KEY	Workspace API Key
Content-Type	application/json
Accept	text/plain

Body raw (json)

json

```
{
  "inviterEmail": "nzLa4CYTiLt@yXST.ltrp",
  "emails": [
    "string",
    "string"
  ],
  "workspaceIds": [
    6519,
    3651
  ]
}
```

GET GetUserById

//api/public/management/organizations/users/:userId

Get information about a given user.

HEADERS

X-API-KEY	Workspace API Key
Accept	text/plain

PATH VARIABLES

userId	5421
--------	------

POST **GetWorkspaceUsers**

//api/public/management/organizations/users/workspaces/:workspaceId

Get all users in a given workspace along with their role and permissions.

HEADERS

X-API-KEY	Workspace API Key
Content-Type	application/json
Accept	text/plain

PATH VARIABLES

workspaceId	5421
--------------------	------

Body raw (json)

```
json

{
  "offset": 895,
  "role": "Admin",
  "invitationStatus": [
    "Accepted",
    "Pending"
  ],
  "limit": 38
}
```