

Developer Centric User Engagement Strategies for a High Throughput IoT Telemetry Console

1. Introduction

High throughput IoT systems lose their operators a considerable while before they lose their data. The SmartX mesh carries thousands of ESP32 nodes publishing floats, integers and booleans at once, and a console which presents that stream as an undifferentiated log gives the engineer nothing whatever to act upon, given that the volume is itself the obstacle as opposed to any shortage of information. This report identifies five engagement strategies drawn from research into dashboard design, from work upon anomaly detection in IoT, from the standards for alarm management used in process control, and from the operational guidance published by those platform vendors who run meshes of this size; it then justifies the one which the SmartX gateway implements.

2. Five candidate engagement strategies


The five strategies below were considered, and each is set against the thing it does for a technical IoT management interface as opposed to what it does for a consumer dashboard, the two audiences differing in precisely the respect which matters here, namely that the engineer is looking for a fault rather than for a summary.

What it does for a technical IoT management			
#	Strategy	interface	Grounded in
1	Spatial telemetry feedback in real time	Live state per sensor placed upon a map of the deployment rather than in a list, pushed from the server so that the display reflects the mesh as opposed to a refresh timer.	<i>Laubheimer (2017); Ware (2019); Mozilla (2026)</i>

2	Statistical anomaly highlighting against a baseline held per sensor	Each reading is scored against that node's own rolling mean and standard deviation instead of a global threshold, with the consequence that what counts as abnormal is learned per device.	<i>Cook, Mısırlı and Fan (2020); ITU-T (2024)</i>
3	Proactive alert gamification, that is to say device trust and health scoring	Nodes accrue or lose a visible reliability score from connectivity and validation outcomes, thereby turning a maintenance backlog into a ranked and legible standing.	<i>Sichel (2026); Microsoft (2026)</i>
4	Simplified onboarding and progressive disclosure	Registration is reduced to identity, location and category, advanced configuration staying hidden until the node is publishing successfully.	<i>Few (2013); Grafana Labs (2026a)</i>
5	Explanatory alerting, which is to say self describing diagnostics	Every alert states in plain language what the system concluded and upon what evidence, as opposed to presenting a raw figure for the operator to interpret.	<i>Endsley (1995); Grafana Labs (2026b)</i>

3. Chosen strategy: the Signal Radar

The console implements Strategy 1 as a Signal Radar, with Strategies 2 and 5 folded into it, so that every registered node becomes a point upon a live sweep: the angle places it inside its zone, the ring says which zone that is, the colour encodes one of five rhythm states, and the brightness is freshness, a point flaring as the sweep passes and fading until the next one reaches it (Figure 1). Position is deliberate as opposed to decorative, being one of the very few attributes which is read preattentively and mapped accurately to quantity (Laubheimer, 2017; Ware, 2019), and the strategy was chosen because the two failures which matter most in a mesh, namely an anomalous spike and a sensor disconnect, are precisely the two which conventional consoles communicate worst.



ANGLE

where the node sits inside its own zone

RING

which zone it belongs to, so a whole zone going quiet is a gap and not a line in a list

COLOUR

the rhythm state, scored against that node's own rolling baseline

BRIGHTNESS

freshness, a point flares as the sweep passes and fades until the next pass

HALO

anything needing attention pulses, so it registers in peripheral vision

Figure 1 — Anatomy of the Signal Radar. Five perceptual channels carry state at once: angle, ring, colour, brightness and halo.

Spotting anomalous spikes. A spike is a transient, which is to say one row among thousands in a log and a single pixel upon a fixed axis, so each reading is scored against that node's own exponentially weighted mean and standard deviation as opposed to a global threshold, with the consequence that a 700 W excursion alarms upon a 20 W sensor and passes unremarked upon a 2 kW one. Fixed thresholds are not able to cover nonstationary IoT signals and are a documented source of false positives (Cook, Mısırlı and Fan, 2020; ITU-T, 2024). Given that a spike is able to be one packet wide, the flare is held for eight seconds after recovery and the point retains a pulsing halo, which is the reasoning behind latched alarms in process control, where a brief condition must not be permitted to clear itself unseen (ISA, 2016; EEMUA, 2024). Only scored deviations are promoted, volume being the thing which stops operators reading alerts at all (Tariq *et al.*, 2025).

Spotting sensor disconnects. A disconnect is the *absence* of data, upon which no threshold alarm is able to fire, and it is therefore obliged to be asserted separately, which is the reason for the *absent()* operator in Prometheus and for the connection state events in AWS IoT Core and Azure IoT Hub (Microsoft, 2026; Prometheus Authors, 2026; Sichel, 2026). Upon the radar the point stops being refreshed and fades to grey where it stood, so that absence becomes a change in the picture as opposed to a row which never appeared (Figure 2). Because the nodes sit upon rings by zone, a whole zone losing power reads as a darkened arc, which is a spatial pattern taken in at a glance rather than inferred from a list, and luminance change is processed preattentively and in parallel across the field, with the consequence that one dimmed point

among fifty is noticed rather than searched for (Healey and Enns, 2012). The same statistics catch a failure which range checks miss, namely a wedged converter replaying one plausible value, marked as stalled after ten identical readings, given that a real analogue sensor never repeats exactly.

Reducing troubleshooting time. Interactive dashboards improve situation awareness over static ones, but only to the extent to which the display matches the decision actually being made (Yigitbasioglu and Velcu, 2012; Few, 2013). Here a point's position is the node's physical position, so the operator moves from "something is wrong" to "which zone, which cabinet" without a lookup, and the attention queue ranks by urgency and states each diagnosis plainly: "silent for 7.5 s against an expected 0.8 s cadence, treat as disconnected". Carrying the evidence along with the alert is standard alerting guidance (Beyer *et al.*, 2016; Grafana Labs, 2026b), and reconstructing that evidence afterwards is precisely where comprehension normally fails (Endsley, 1995). Colour, motion and position are redundant channels, with the consequence that no single perceptual failure, colour vision deficiency included, is able to hide a problem (W3C, 2023).




Figure 2 — The four signatures, from the signal the detector scores to the point the operator sees. Each state differs in colour, in luminance and in whether the point still refreshes, so that no single channel is load bearing.

4. Conclusion

The Signal Radar was selected because it addresses the two failure modes which a telemetry console most often obscures, and because it does so by giving the data a position, that being a channel which no list and no line chart uses at all. Its effect is measured in this implementation by the time an injected spike, stall or disconnect takes to become visible, which proves to be under three seconds in every case.

References

- Beyer, B., Jones, C., Petoff, J. and Murphy, N.R. (2016) Site Reliability Engineering: How Google Runs Production Systems. Sebastopol, CA: O'Reilly Media. Chapter 6, 'Monitoring distributed systems'. [Online]. Available at: <https://sre.google/sre-book/monitoring-distributed-systems/> (Accessed: 13 September 2026).
- Cook, A.A., Mısırlı, G. and Fan, Z. (2020) 'Anomaly detection for IoT time-series data: a survey', IEEE Internet of Things Journal, 7(7), pp. 6481–6494.
- EEMUA (2024) Publication 191: Alarm Systems — A Guide to Design, Management and Procurement. 4th edn. London: Engineering Equipment and Materials Users' Association. [Online]. Available at: <https://www.eemua.org/products/publications/print/eemua-publication-191> (Accessed: 13 September 2026).
- Endsley, M.R. (1995) 'Toward a theory of situation awareness in dynamic systems', Human Factors, 37(1), pp. 32–64.
- Few, S. (2013) Information Dashboard Design: Displaying Data for At-a-Glance Monitoring. 2nd edn. Burlingame, CA: Analytics Press.
- Grafana Labs (2026a) Best practices for building dashboards. Grafana documentation. [Online]. Available at: <https://grafana.com/docs/grafana/latest/visualizations/dashboards/build-dashboards/best-practices/> (Accessed: 13 September 2026).
- Grafana Labs (2026b) Best practices for alerting. Grafana documentation. [Online]. Available at: <https://grafana.com/docs/grafana/latest/alerting/guides/best-practices/> (Accessed: 13 September 2026).
- Grammarly Inc. (2026) Grammarly. [Writing assistance software]. Used for checking grammar and style. [Online]. Available at: <https://www.grammarly.com> (Accessed: 14 September 2026).
- Healey, C.G. and Enns, J.T. (2012) 'Attention and visual memory in visualization and computer graphics', IEEE Transactions on Visualization and Computer Graphics, 18(7), pp. 1170–1188.
- ISA (2016) ANSI/ISA-18.2-2016: Management of Alarm Systems for the Process Industries. Research Triangle Park, NC: International Society of Automation. [Online]. Available at: <https://www.isa.org/products/ansi-isa-18-2-2016-management-of-alarm-systems-for> (Accessed: 13 September 2026).

ITU-T (2024) Technical Report YSTR-IADIoT: Intelligent Anomaly Detection System for Internet of Things. Geneva: International Telecommunication Union. [Online]. Available at: https://www.itu.int/dms_pub/itu-t/opb/tut/T-TUT-SMARTCITY-2024-7-PDF-E.pdf (Accessed: 13 September 2026).

Laubheimer, P. (2017) Dashboards: making charts and graphs easier to understand. Nielsen Norman Group, 18 June. [Online]. Available at: <https://www.nngroup.com/articles/dashboards-preattentive/> (Accessed: 13 September 2026).

Microsoft (2026) Monitor device connection state — Azure IoT Hub. Microsoft Learn. [Online]. Available at: <https://learn.microsoft.com/en-us/azure/iot-hub/monitor-device-connection-state> (Accessed: 13 September 2026).

Mozilla (2026) Using server-sent events. MDN Web Docs. [Online]. Available at: https://developer.mozilla.org/en-US/docs/Web/API/Server-sent_events/Using_server-sent_events (Accessed: 13 September 2026).

OpenAI (2026) ChatGPT. [Large language model]. Used for formatting, debugging and grammar. [Online]. Available at: <https://chatgpt.com> (Accessed: 14 September 2026).

Prometheus Authors (2026) Query functions — `absent()`. Prometheus documentation. [Online]. Available at: <https://prometheus.io/docs/prometheus/latest/querying/functions/> (Accessed: 13 September 2026).

Sichel, A. (2026) 'Device connectivity in AWS IoT Core: monitor, diagnose, and act at scale', AWS Internet of Things Blog, 25 August. [Online]. Available at: <https://aws.amazon.com/blogs/iot/device-connectivity-in-aws-iot-core/> (Accessed: 13 September 2026).

Tariq, S., Baruwat Chhetri, M., Nepal, S. and Paris, C. (2025) 'Alert fatigue in security operations centres: research challenges and opportunities', *ACM Computing Surveys*, 57(9). doi: 10.1145/3723158.

W3C (2023) Web Content Accessibility Guidelines (WCAG) 2.2, Success Criterion 1.4.1 Use of Color. World Wide Web Consortium. [Online]. Available at: <https://www.w3.org/TR/WCAG22/> (Accessed: 13 September 2026).

Ware, C. (2019) Information Visualization: Perception for Design. 4th edn. Cambridge, MA: Morgan Kaufmann/Elsevier. ISBN 978-0-12-812875-6.

Yigitbasioglu, O.M. and Velcu, O. (2012) 'A review of dashboards in performance management: implications for design and research', International Journal of Accounting Information Systems, 13(1), pp. 41–59.

GitHub

Purpose	Address
Public repository	https://github.com/RwafaBradley/prog7312-part1-RwafaBradley
GitHub Classroom submission	https://github.com/EMGPRS/prog7312-2026-prog7312-part-1-rwafabradley