AA200_PS4_Problem2_with_P3

March 7, 2026

1 AA200 Problem Set 4 — Problem 2

1.1 Viscous Flow Over NACA 2410 Airfoil

1.1.1 Hess-Smith Panel Method + Thwaites/Head BL + Michel's Transition

Re_c = 5×10 , = 1°, N = 160 panels

The Hess-Smith implementation is a **direct Python translation** of previous MATLAB code (`naca4.m`, `panel_geometry.m`, `infl_coeff.m`, `veldis.m`, `aero_coeff.m`).

Two-step procedure (no inviscid-viscous coupling): 1. Hess-Smith → $V_e(s)$, dV_e/ds on upper and lower surfaces 2. Thwaites (laminar) → Michel transition → Head's method (turbulent) → C_d via Squire-Young

[17]:
```
import numpy as np
import matplotlib.pyplot as plt
from scipy.integrate import solve_ivp
from scipy.interpolate import interp1d

plt.rcParams.update({'figure.dpi': 120, 'font.size': 12,
                     'lines.linewidth': 2, 'axes.grid': True, 'grid.alpha': 0.
 ↪35})
```

1.2 1. NACA 4-digit Geometry — `naca4.m` (Python translation)

[18]:
```
def naca4(naca4_digits, npanel):
    """
    Building a NACA profile
    """
    n1 = naca4_digits % 10
    n2 = (naca4_digits % 100) // 10
    n3 = (naca4_digits % 1000) // 100
    n4 = (naca4_digits % 10000) // 1000
    m = n4 / 100.0;  p = n3 / 10.0;  t = (n2*10 + n1) / 100.0

    if npanel % 2 != 0: raise ValueError('Even number of panels required')
    nside = npanel // 2 + 1
```

```
    an = 1.5;  anp = an + 1.0

    xx = np.zeros(nside);  yt = np.zeros(nside);  yc = np.zeros(nside)
    for i in range(nside):
        f = i / (nside - 1)
        xx[i] = 1 - anp*f*(1-f)**an - (1-f)**anp
        yt[i] = (0.29690*np.sqrt(xx[i]) - 0.12600*xx[i] - 0.35160*xx[i]**2
                 + 0.28430*xx[i]**3 - 0.10150*xx[i]**4) * t / 0.20
        yc[i] = (m/p**2*(2*p*xx[i] - xx[i]**2) if xx[i] < p
                 else m/(1-p)**2*((1-2*p) + 2*p*xx[i] - xx[i]**2))

    x = np.zeros(npanel + 1);  y = np.zeros(npanel + 1)
    for i in range(nside):
        x[nside+i-1] = xx[i];  x[nside-i-1] = xx[i]
        y[nside+i-1] = yc[i] + yt[i];  y[nside-i-1] = yc[i] - yt[i]
    return x, y


N_panels = 160
x_foil, y_foil = naca4(2410, N_panels)

fig, ax = plt.subplots(figsize=(10, 3))
ax.plot(x_foil, y_foil, 'b.-', ms=3)
ax.set_aspect('equal');  ax.set_xlabel('x/c');  ax.set_ylabel('y/c')
ax.set_title(f'NACA 2410 - {N_panels} panels ')
plt.tight_layout();  plt.show()
print(f'Nodes: {len(x_foil)},  Panels: {N_panels}')
```




```
Nodes: 161,  Panels: 160
```

1.3 2. Hess-Smith Panel Method

Direct Python translation of `panel_geometry.m`, `infl_coeff.m`, `veldis.m`, `aero_coeff.m`.

Formulation: - N panels, each with uniform source strength q_i - Single global vortex γ (constant, enforces Kutta condition) - $(N+1)\times(N+1)$ linear system: N flow-tangency + 1 Kutta - Influence coefficients use $\ln(r_{i,j+1}/r_{i,j})$ and $\beta_{ij} = \text{atan2}(...)$

[19]:
```
def panel_geometry(x, y, npanel):
    """Translation of panel_geometry.m"""
    l = np.zeros(npanel);  st = np.zeros(npanel);  ct = np.zeros(npanel)
    xbar = np.zeros(npanel);  ybar = np.zeros(npanel)
    for i in range(npanel):
        l[i]    = np.sqrt((x[i+1]-x[i])**2 + (y[i+1]-y[i])**2)
        st[i]   = (y[i+1]-y[i]) / l[i]
        ct[i]   = (x[i+1]-x[i]) / l[i]
        xbar[i] = 0.5*(x[i+1]+x[i])
        ybar[i] = 0.5*(y[i+1]+y[i])
    return l, st, ct, xbar, ybar


def infl_coeff(x, y, xbar, ybar, st, ct, npanel):
    """Translation of infl_coeff.m - builds (N+1)x(N+1) influence matrix"""
    p2 = 1.0/(2*np.pi)
    ainfl = np.zeros((npanel+1, npanel+1))
    cosdt = np.zeros((npanel, npanel));  sindt = np.zeros((npanel, npanel))
    lns   = np.zeros((npanel, npanel));  betas = np.zeros((npanel, npanel))

    for i in range(npanel):
        for j in range(npanel):
            cosdt[i,j] = ct[i]*ct[j] + st[i]*st[j]
            sindt[i,j] = st[i]*ct[j] - st[j]*ct[i]
            if i == j:
                lns[i,j] = 0.0;  betas[i,j] = np.pi
            else:
                r1 = np.sqrt((xbar[i]-x[j  ])**2 + (ybar[i]-y[j  ])**2)
                r2 = np.sqrt((xbar[i]-x[j+1])**2 + (ybar[i]-y[j+1])**2)
                lns[i,j]   = np.log(r2 / r1)
                betas[i,j] = np.arctan2(
                    (ybar[i]-y[j+1])*(xbar[i]-x[j]) -␣
↪(xbar[i]-x[j+1])*(ybar[i]-y[j]),
                    (xbar[i]-x[j+1])*(xbar[i]-x[j]) +␣
↪(ybar[i]-y[j+1])*(ybar[i]-y[j]))

    for i in range(npanel):
        for j in range(npanel):
            ainfl[i,j] = p2*(sindt[i,j]*lns[i,j] + cosdt[i,j]*betas[i,j])
        ainfl[i, npanel] = p2*np.sum(cosdt[i,:]*lns[i,:] - sindt[i,:]*betas[i,:
↪])

    # Kutta condition: panels 0 (lower TE) and npanel-1 (upper TE)
    for j in range(npanel):
        s = sum(sindt[k,j]*betas[k,j] - cosdt[k,j]*lns[k,j] for k in [0,␣
↪npanel-1])
        ainfl[npanel, j] = p2 * s
```

```
    ainfl[npanel, npanel] = p2 * sum(
        np.sum(sindt[k,:]*lns[k,:] + cosdt[k,:]*betas[k,:]) for k in [0,␣
 ↪npanel-1])

    return ainfl, cosdt, sindt, lns, betas


def veldis(qg, cosdt, sindt, lns, betas, st, ct, al, npanel):
    """Translation of veldis.m - tangential velocity at each panel midpoint"""
    p2 = 1.0/(2*np.pi);  vt = np.zeros(npanel);  gamma = qg[npanel]
    for i in range(npanel):
        vt[i] = ct[i]*np.cos(al) + st[i]*np.sin(al)
        for j in range(npanel):
            vt[i] += p2*qg[j]   * (sindt[i,j]*betas[i,j] - cosdt[i,j]*lns[i,j])
            vt[i] += p2*gamma   * (sindt[i,j]*lns[i,j]   +␣
 ↪cosdt[i,j]*betas[i,j])
    return vt


def aero_coeff(x, y, cp, al, npanel):
    """Translation of aero_coeff.m - cl, cd, cm about c/4"""
    cl = cd = cm = 0.0
    for i in range(npanel):
        dx = x[i+1]-x[i];  dy = y[i+1]-y[i]
        xa = 0.5*(x[i+1]+x[i]) - 0.25;  ya = 0.5*(y[i+1]+y[i])
        dcl = -cp[i]*dx;  dcd = cp[i]*dy
        cl += dcl;  cd += dcd;  cm += dcd*ya - dcl*xa
    dcl = cl*np.cos(al) - cd*np.sin(al)
    cd  = cl*np.sin(al) + cd*np.cos(al)
    return dcl, cd, cm


def hess_smith(naca4_digits, alpha_deg, npanel):
    """Full Hess-Smith solver - Python translation of hess_smith.m"""
    x, y = naca4(naca4_digits, npanel)
    l, st, ct, xbar, ybar = panel_geometry(x, y, npanel)
    ainfl, cosdt, sindt, lns, betas = infl_coeff(x, y, xbar, ybar, st, ct,␣
 ↪npanel)

    al = np.radians(alpha_deg)
    b  = np.zeros(npanel + 1)
    for i in range(npanel):
        b[i] = st[i]*np.cos(al) - np.sin(al)*ct[i]
    b[npanel] = -(ct[0]*np.cos(al)      + st[0]*np.sin(al)
                + ct[npanel-1]*np.cos(al) + st[npanel-1]*np.sin(al))

    qg = np.linalg.solve(ainfl, b)
```

```
    vt = veldis(qg, cosdt, sindt, lns, betas, st, ct, al, npanel)
    cp = 1.0 - vt**2
    cl, cd, cm = aero_coeff(x, y, cp, al, npanel)
    return cl, cd, cm, x, y, cp, xbar, ybar, vt, l, st, ct
```

[20]:
```
# ---- Run Hess-Smith ----
alpha_deg = 1.0
Re_c      = 5e6

cl, cd, cm, x, y, cp, xbar, ybar, vt, l, st, ct = hess_smith(2410, alpha_deg,␣
 ↪N_panels)

print(f'cl = {cl:.4f}   cd = {cd:.6f}   cm = {cm:.5f}')
print(f'(XFOIL ref at alpha=1°: cl   0.63 for NACA 2410)')

nside = N_panels // 2
fig, ax = plt.subplots(figsize=(9, 5))
ax.plot(xbar[:nside][::-1], cp[:nside][::-1], 'r-', label='Lower surface')
ax.plot(xbar[nside:],       cp[nside:],        'b-', label='Upper surface')
ax.invert_yaxis()
ax.set_xlabel('x/c');  ax.set_ylabel('Cp')
ax.set_title(f'NACA 2410 - Cp (Hess-Smith),  ={alpha_deg}°, Re={Re_c:.0e}')
ax.legend();  plt.tight_layout();  plt.show()
```

```
cl = 0.3460   cd = 0.000123   cm = -0.05127
(XFOIL ref at alpha=1°: cl   0.63 for NACA 2410)
```



1.4 3. Surface Splitting: Upper / Lower from Stagnation

The stagnation point is identified as the panel with minimum $|V_t|$ near the LE.
The BL is marched from stagnation toward the TE on each surface.
Arclength s is measured along the surface from the stagnation point.

[21]:
```
# Panel lengths
l_all = np.sqrt(np.diff(x)**2 + np.diff(y)**2)

# Find stagnation panel (min |Vt| near LE)
nside = N_panels // 2
stag  = np.argmin(np.abs(vt[nside-5:nside+5])) + nside - 5
print(f'Stagnation panel: {stag},  xbar = {xbar[stag]:.5f},  Vt = {vt[stag]:.
 ↪4f}')

# Upper: stag → N-1  (Vt > 0, LE → upper TE)
# Lower: stag-1 → 0 reversed  (|Vt|, LE → lower TE)
up_idx = np.arange(stag, N_panels)
lo_idx = np.arange(stag-1, -1, -1)

def build_surface(idx):
    """Compute arclength, |Ve|, dVe/ds, xbar for a surface given panel indices.
 ↪"""
    Ve_s = np.abs(vt[idx])
    s    = np.zeros(len(idx))
    s[0] = l_all[idx[0]] / 2.0
    for k in range(1, len(idx)):
        s[k] = s[k-1] + 0.5*(l_all[idx[k-1]] + l_all[idx[k]])
    dVe = np.gradient(Ve_s, s)
    return s, Ve_s, dVe, xbar[idx]

s_up, Ve_up, dVe_up, xc_up = build_surface(up_idx)
s_lo, Ve_lo, dVe_lo, xc_lo = build_surface(lo_idx)

print(f'Upper: {len(s_up)} panels,  s_max = {s_up[-1]:.4f},  Ve(LE) = {Ve_up[0]:
 ↪.4f}')
print(f'Lower: {len(s_lo)} panels,  s_max = {s_lo[-1]:.4f},  Ve(LE) = {Ve_lo[0]:
 ↪.4f}')

fig, axes = plt.subplots(1, 2, figsize=(12, 4))
axes[0].plot(s_up, Ve_up, 'b-', label='Upper');  axes[0].plot(s_lo, Ve_lo,␣
 ↪'r-', label='Lower')
axes[0].set_xlabel('s');  axes[0].set_ylabel('Ve/Vω');  axes[0].set_title('Edge␣
 ↪Velocity');  axes[0].legend()
axes[1].plot(s_up, dVe_up, 'b-', label='Upper');  axes[1].plot(s_lo, dVe_lo,␣
 ↪'r-', label='Lower')
```

```
axes[1].set_xlabel('s');  axes[1].set_ylabel('dVe/ds');  axes[1].
 ↪set_title('Velocity Gradient');  axes[1].legend()
plt.tight_layout();  plt.show()
```

```
Stagnation panel: 79,  xbar = 0.00015,  Vt = 0.0856
Upper: 81 panels,  s_max = 1.0215,  Ve(LE) = 0.0856
Lower: 79 panels,  s_max = 1.0060,  Ve(LE) = 0.1971
```



1.5 4. Boundary Layer Solver

Michel's transition criterion:

$$\text{Transition when: } Re_\theta > 1.174\left(1+\frac{22400}{Re_s}\right)Re_s^{0.46}$$

[22]:
```
# ---- Thwaites correlations ----
def thwaites_lH(lam):
    if lam >= 0.0:
        return 0.22 + 1.57*lam - 1.8*lam**2, 2.61 - 3.75*lam + 5.24*lam**2
    else:
        return 0.22 + 1.402*lam + 0.018*lam/(lam + 0.107), 2.088 + 0.0731/(lam␣
 ↪+ 0.14)

# ---- Head's closure functions ----
def H_from_H1(H1):
    if H1 <= 3.3:   return 3.0
    elif H1 < 5.3:  return 0.6778 + 1.1536*(H1 - 3.3)**(-0.326)
    else:           return 1.1    + 0.86  *(H1 - 3.3)**(-0.777)

def H1_from_H(H):
    return (3.3 + 0.8234*(H - 1.1)**(-1.287) if H <= 1.6
            else 3.3 + 1.5501*(H - 0.6778)**(-3.064))
```

```python
def cf_ludwieg_tillman(Re_th, H):
    return 0.246 * 10**(-0.678*H) * max(Re_th, 10.0)**(-0.268)

# ---- Michel's criterion ----
def michel_check(Re_th, Re_s):
    return Re_th >= 1.174 * (1.0 + 22400.0/max(Re_s, 1.0)) * Re_s**0.46


def solve_bl(s_arr, Ve_arr, dVe_arr, Re_c, H0_turb=1.35):
    """
    Full BL solver: Thwaites (laminar) + Michel transition + Head (turbulent).
    Initial condition at stagnation: theta_0 = sqrt(0.075*nu / dVe/ds|_0) ␣
↪[Moran eq. 7-44]
    """
    N2  = len(s_arr)
    nu  = 1.0 / Re_c
    Vf  = interp1d(s_arr, Ve_arr,  fill_value='extrapolate')
    dVf = interp1d(s_arr, dVe_arr, fill_value='extrapolate')

    theta = np.zeros(N2);  dstar = np.zeros(N2)
    H_a   = np.zeros(N2);  cf_a  = np.zeros(N2)
    i_trans = N2;  s_trans = np.inf

    # --- Stagnation-point IC ---
    dVe0     = max(abs(dVe_arr[0]), 5e-3)
    theta[0] = np.sqrt(0.075 * nu / dVe0)
    lam0     = np.clip(theta[0]**2/nu * dVe_arr[0], -0.0842, 0.1)
    l0, H0a  = thwaites_lH(lam0)
    cf_a[0]  = 2*l0 / max(Ve_arr[0]*theta[0]/nu, 1e-10)
    H_a[0]   = H0a;  dstar[0] = H0a * theta[0]

    # --- Thwaites integration ---
    t2V6 = theta[0]**2 * Ve_arr[0]**6
    for i in range(1, N2):
        ds_i  = s_arr[i] - s_arr[i-1]
        t2V6 += 0.45*nu * 0.5*(Ve_arr[i]**5 + Ve_arr[i-1]**5) * ds_i
        theta[i] = np.sqrt(max(t2V6 / Ve_arr[i]**6, 0.0))

        lam = np.clip(theta[i]**2/nu * dVe_arr[i], -0.0842, 0.1)
        li, Hi = thwaites_lH(lam)
        Re_th  = Ve_arr[i]*theta[i] / nu
        Re_s   = Ve_arr[i]*s_arr[i] / nu
        cf_a[i] = 2*li / max(Re_th, 1e-10)
        H_a[i]  = Hi;  dstar[i] = Hi * theta[i]

        if michel_check(Re_th, Re_s):
            i_trans = i;  s_trans = s_arr[i];  break
```

```
    if i_trans == N2:  # fully laminar
        return dict(theta=theta, dstar=dstar, H=H_a, cf=cf_a,
                    s_trans=s_trans, i_trans=i_trans)

    # --- Head's method (turbulent) ---
    theta_tr = theta[i_trans]
    H1_0     = H1_from_H(H0_turb)

    def heads_rhs(sv, Y):
        th, H1 = Y
        Ve_v   = float(Vf(sv));  dVe_v = float(dVf(sv))
        H_v    = H_from_H1(H1)
        cf_v   = cf_ludwieg_tillman(Ve_v*th/nu, H_v)
        dth    = cf_v/2.0 - (H_v + 2.0)*th/Ve_v * dVe_v
        F      = 0.0306 * (max(H1, 3.01) - 3.0)**(-0.6169)
        dH1    = F - H1*dth/th - H1*dVe_v/Ve_v
        return [dth, dH1]

    sol = solve_ivp(heads_rhs, (s_arr[i_trans], s_arr[-1]),
                    [theta_tr, H1_0], method='RK45',
                    t_eval=s_arr[i_trans:], rtol=1e-6, atol=1e-9)

    for k, i in enumerate(range(i_trans, N2)):
        if k >= len(sol.y[0]): break
        H_v       = H_from_H1(sol.y[1][k])
        theta[i]  = sol.y[0][k]
        dstar[i]  = H_v * theta[i]
        H_a[i]    = H_v
        cf_a[i]   = cf_ludwieg_tillman(Ve_arr[i]*theta[i]/nu, H_v)

    return dict(theta=theta, dstar=dstar, H=H_a, cf=cf_a,
                s_trans=s_trans, i_trans=i_trans)
```

1.6 5. Results: BL Solver on Upper and Lower Surfaces

[23]:
```
bl_up = solve_bl(s_up, Ve_up, dVe_up, Re_c)
bl_lo = solve_bl(s_lo, Ve_lo, dVe_lo, Re_c)

print('=== UPPER SURFACE ===')
print(f'  Transition: s = {bl_up["s_trans"]:.4f},  '
      f'x/c   {xc_up[min(bl_up["i_trans"], len(xc_up)-1)]:.4f}')

print('\n=== LOWER SURFACE ===')
print(f'  Transition: s = {bl_lo["s_trans"]:.4f},  '
```

```
      f'x/c   {xc_lo[min(bl_lo["i_trans"], len(xc_lo)-1)]:.4f}')
```

```
=== UPPER SURFACE ===
  Transition: s = 0.3437,  x/c   0.3247

=== LOWER SURFACE ===
  Transition: s = 0.2708,  x/c   0.2637
```

[24]:
```
fig, axes = plt.subplots(2, 2, figsize=(14, 10))
fig.suptitle("NACA 2410 - Boundary Layer Properties\n"
             " =1°, Re_c=5×10 , N=160 panels, Michel's transition", fontsize=14)

def mark_transition(ax, bl, color, label):
    if bl['i_trans'] < 500:
        ax.axvline(bl['s_trans'], color=color, ls=':', lw=1.5, label=f'{label}␣
 ↪transition')

# theta
ax = axes[0, 0]
ax.plot(s_up, bl_up['theta'], 'b-', label='Upper')
ax.plot(s_lo, bl_lo['theta'], 'r-', label='Lower')
mark_transition(ax, bl_up, 'b', 'Upper');  mark_transition(ax, bl_lo, 'r',␣
 ↪'Lower')
ax.set_xlabel('s (arclength from stagnation)');  ax.set_ylabel(' /c')
ax.set_title('Momentum Thickness  ');  ax.legend(fontsize=9)

# delta*
ax = axes[0, 1]
ax.plot(s_up, bl_up['dstar'], 'b-', label='Upper')
ax.plot(s_lo, bl_lo['dstar'], 'r-', label='Lower')
mark_transition(ax, bl_up, 'b', 'Upper');  mark_transition(ax, bl_lo, 'r',␣
 ↪'Lower')
ax.set_xlabel('s');  ax.set_ylabel(' */c')
ax.set_title('Displacement Thickness  *');  ax.legend(fontsize=9)

# H
ax = axes[1, 0]
ax.plot(s_up, bl_up['H'], 'b-', label='Upper')
ax.plot(s_lo, bl_lo['H'], 'r-', label='Lower')
mark_transition(ax, bl_up, 'b', 'Upper');  mark_transition(ax, bl_lo, 'r',␣
 ↪'Lower')
ax.axhline(2.4, ls='--', color='orange', alpha=0.7, label='Turb. sep. H=2.4')
ax.set_xlabel('s');  ax.set_ylabel('H =  */ ')
ax.set_title('Shape Factor H');  ax.legend(fontsize=9);  ax.set_ylim([1.0, 6.0])

# cf
ax = axes[1, 1]
```

```
ax.plot(s_up, bl_up['cf'], 'b-', label='Upper')
ax.plot(s_lo, bl_lo['cf'], 'r-', label='Lower')
mark_transition(ax, bl_up, 'b', 'Upper');  mark_transition(ax, bl_lo, 'r',␣
 ↪'Lower')
ax.set_xlabel('s');  ax.set_ylabel('cf')
ax.set_title('Local Skin Friction cf');  ax.legend(fontsize=9)

plt.tight_layout();  plt.show()
```



1.7 6. Drag Coefficient

Squire-Young formula (momentum deficit at TE, avoiding sharp-TE $V_e \to 0$ singularity by averaging V_e over the last 15% of arclength):

$$C_d = 2\,\theta_{TE}\left(\frac{\bar{V}_{e,TE}}{V_\infty}\right)^{(H_{TE}+5)/2}$$

Also reported: **direct friction drag** $C_{d,f} = \int c_f\,ds$ (upper + lower).

[10]:
```python
def squire_young(theta, H, Ve, s):
    """Squire-Young with TE velocity averaged over last 15% of arclength."""
    mask   = s > 0.85*s[-1]
    Ve_TE  = np.mean(Ve[mask])
    H_TE   = H[mask][-1]
    th_TE  = theta[mask][-1]
    return 2.0 * th_TE * Ve_TE**((H_TE + 5.0)/2.0)

Cd_up  = squire_young(bl_up['theta'], bl_up['H'], Ve_up, s_up)
Cd_lo  = squire_young(bl_lo['theta'], bl_lo['H'], Ve_lo, s_lo)
Cd_SY  = Cd_up + Cd_lo

Cdf_up = np.trapz(bl_up['cf'], s_up)
Cdf_lo = np.trapz(bl_lo['cf'], s_lo)
Cdf    = Cdf_up + Cdf_lo

print('=== AERODYNAMIC COEFFICIENTS ===')
print(f'  cl              = {cl:.4f}')
print(f'  cm (c/4)        = {cm:.5f}')
print(f'  Cd (Squire-Young) = {Cd_SY:.6f}   (upper={Cd_up:.6f}, lower={Cd_lo:.
 ↪6f})')
print(f'  Cd (friction  )   = {Cdf:.6f}   (upper={Cdf_up:.6f}, lower={Cdf_lo:.
 ↪6f})')
print(f'  cl/Cd (S-Y)     = {cl/Cd_SY:.1f}')
print(f'\n  Transition x/c:')
print(f'    Upper: {xc_up[min(bl_up["i_trans"], len(xc_up)-1)]:.4f} ␣
 ↪(s={bl_up["s_trans"]:.4f})')
print(f'    Lower: {xc_lo[min(bl_lo["i_trans"], len(xc_lo)-1)]:.4f} ␣
 ↪(s={bl_lo["s_trans"]:.4f})')
```

```
=== AERODYNAMIC COEFFICIENTS ===
  cl              = 0.3460
  cm (c/4)        = -0.05127
  Cd (Squire-Young) = 0.006198   (upper=0.004519, lower=0.001679)
  Cd (friction  )   = 0.002219   (upper=0.001154, lower=0.001065)
  cl/Cd (S-Y)     = 55.8

  Transition x/c:
    Upper: 0.3247  (s=0.3437)
    Lower: 0.2637  (s=0.2708)
```

1.8 7. Discussion

1.8.1 Difficulties at Leading and Trailing Edges

Leading Edge:
The panel method uses a discrete stagnation panel rather than an exact stagnation point, so V_e near

the LE is not exactly zero but rather a small positive value (~0.09 for the stagnation-adjacent panel at =1°). This causes the Thwaites stagnation-point IC $\theta_0 = \sqrt{0.075\nu/\dot{V}_0}$ to depend sensitively on the local velocity gradient, which itself is computed from finite differences over coarse panels near the LE. The fix applied here is to clamp $|dV_e/ds|_0 \geq 5 \times 10^{-3}$ and to start the BL at the stagnation panel rather than at $s = 0$ exactly.

Trailing Edge:
At the sharp TE, $V_e \to 0$ from both sides (Kutta condition). This makes the direct Squire-Young formula $C_d = 2\theta_{TE}\, V_{e,TE}^{(H+5)/2}$ collapse to zero. The fix is to use the average V_e over the last 15% of arclength, which gives a physically representative TE velocity. Alternatively, one could integrate $c_f\, ds$ directly (no such singularity).

1.8.2 What Moran's Code Does at Transition

1. Thwaites' method is used up to the point where Michel's criterion is satisfied (eq. 7-66).
2. At transition, the program stops and asks the user to input H (since H changes radically through transition and neither laminar nor turbulent correlations are valid in the transition zone).
3. The momentum thickness θ from Thwaites is carried over continuously (no jump).
4. H_1 is initialized from the user-supplied H via the inverse closure relation, then Head's method is integrated forward.
5. Moran notes that the solution quickly forgets the initial H guess — any value in the range 1.3–1.4 is acceptable, as the turbulent BL converges to the correct downstream state within a short distance.

In our implementation, we use $H_0 = 1.35$ at transition, consistent with Moran's recommended range.

2 Problem 3 — Inviscid-Viscous Coupling

The idea is that the BL displaces the outer flow by $\delta^*(s)$. We account for this by displacing the airfoil surface outwar (normal to each panel) by δ^*, creating a *effective* thickened geometry. We then re-run Hess-Smith on this new geometry to get an updated V_e, and iterate until δ^* converges

Algorithm (underrelaxed fixed-point iteration): 1. Run Hess-Smith on **original** NACA 2410 $\to V_e^{(0)}(s)$ 2. Run BL solver $\to \delta^{*(0)}(s)$ on upper + lower surfaces 3. Displace airfoil nodes outward by $\omega \cdot \delta^*(s)$ (underrelaxation $\omega = 0.5$) 4. Re-run Hess-Smith on displaced geometry $\to V_e^{(1)}(s)$ 5. Repeat until $\|\delta^{*(k+1)} - \delta^{*(k)}\|_\infty < \varepsilon$

After convergence: compute Δc_l (viscous reduction) and C_d (including pressure drag from Squire-Young).

2.1 3.1 XFOIL Reference Run

[ ]:
```
import subprocess, tempfile, os, re
import numpy as np
import matplotlib.pyplot as plt
```

```python
XFOIL_PATH = os.path.expanduser('~/Downloads/XFOIL-MACOSX-15.2/xfoil')

def run_xfoil(naca_digits, alpha_deg, Re, n_panels=160, n_iter=100,
              xfoil_path=XFOIL_PATH):
    """
    Run XFOIL in batch mode for a NACA airfoil.
    Returns:
      polar : dict with keys cl, cd, cdp, cm, xtr_top, xtr_bot
      cp_data : dict with 'x', 'cp_upper', 'cp_lower' arrays
    """
    with tempfile.TemporaryDirectory() as tmpdir:
        polar_file = os.path.join(tmpdir, 'polar.txt')
        cp_file    = os.path.join(tmpdir, 'cp.txt')

        # Build XFOIL input script
        cmds = '\n'.join([
            f'NACA {naca_digits}',
            f'PANE',              # re-panel with n_panels
            f'PPAR',
            f'N {n_panels}',
            '',
            '',
            'OPER',
            f'VISC {Re:.0e}',
            f'ITER {n_iter}',
            f'ALFA {alpha_deg}',
            f'CPWR {cp_file}',   # write Cp
            'PACC',
            f'{polar_file}',
            '',
            f'ALFA {alpha_deg}', # re-run to get polar entry
            'PACC',
            '',
            'QUIT\n',
        ])

        result = subprocess.run(
            [xfoil_path],
            input=cmds, capture_output=True, text=True, timeout=60
        )

        # --- Parse polar file ---
        polar = {}
        if os.path.exists(polar_file):
            with open(polar_file) as pf:
                lines = pf.readlines()
            for line in lines:
```

```
                nums = re.findall(r'[-+]?\d*\.\d+(?:[eE][-+]?\d+)?|[-+]?\d+',␣
↪line)
                if len(nums) >= 7:
                    try:
                        vals = [float(v) for v in nums]
                        if abs(vals[0] - alpha_deg) < 0.05:
                            polar = dict(alpha=vals[0], cl=vals[1], cd=vals[2],
                                         cdp=vals[3], cm=vals[4],
                                         xtr_top=vals[5], xtr_bot=vals[6])
                            break
                    except: pass

        # --- Parse Cp file ---
        cp_data = {}
        if os.path.exists(cp_file):
            raw = np.loadtxt(cp_file, skiprows=3, usecols=(0,1,2),
                             comments='#')
            if raw.ndim == 2 and raw.shape[1] >= 2:
                x_all  = raw[:, 0]
                cp_all = raw[:, 1]
                # XFOIL Cp file: upper surface first (x decreasing), then lower␣
↪(x increasing)
                split = np.argmin(x_all) + 1  # LE is at min(x)
                cp_data = dict(
                    x_up  = x_all[:split],
                    cp_up = cp_all[:split],
                    x_lo  = x_all[split:],
                    cp_lo = cp_all[split:]
                )

        return polar, cp_data, result.stdout


# ---- Run XFOIL ----
print('Running XFOIL...')
xf_polar, xf_cp, xf_log = run_xfoil(2410, 1.0, 5e6, n_panels=160)

if xf_polar:
    print(f'XFOIL polar at  =1°:')
    print(f'  cl  = {xf_polar["cl"]:.4f}')
    print(f'  cd  = {xf_polar["cd"]:.6f}')
    print(f'  cm  = {xf_polar["cm"]:.5f}')
    print(f'  xtr_top = {xf_polar["xtr_top"]:.4f}  (transition x/c upper)')
    print(f'  xtr_bot = {xf_polar["xtr_bot"]:.4f}  (transition x/c lower)')
else:
    print('XFOIL polar not parsed - check XFOIL_PATH or inspect xf_log below.')
    print('You can hardcode reference values in the comparison cells.')
```

```
    print(xf_log[:500])
```

```
Running XFOIL… (may take ~5 s)
```

```
---------------------------------------------------------------------------
OSError                                   Traceback (most recent call last)
Cell In[11], line 86
     84 # ---- Run XFOIL ----
     85 print('Running XFOIL… (may take ~5 s)')
---> 86 xf_polar, xf_cp, xf_log = run_xfoil(2410, 1.0, 5e6, n_panels=160)
     88 if xf_polar:
     89     print(f'XFOIL polar at  =1°:')

Cell In[11], line 42, in run_xfoil(naca_digits, alpha_deg, Re, n_panels, n_iter␣
↪xfoil_path)
     20 # Build XFOIL input script
     21 cmds = '\n'.join([
     22     f'NACA {naca_digits}',
     23     f'PANE',              # re-panel with n_panels
   (…)
     39     'QUIT\n',
     40 ])
---> 42 result = subprocess.run(
     43     [xfoil_path],
     44     input=cmds, capture_output=True, text=True, timeout=60
     45 )
     47 # --- Parse polar file ---
     48 polar = {}

File ~/anaconda3/envs/inf554/lib/python3.11/subprocess.py:548, in run(input,␣
↪capture_output, timeout, check, *popenargs, **kwargs)
    545     kwargs['stdout'] = PIPE
    546     kwargs['stderr'] = PIPE
--> 548 with Popen(*popenargs, **kwargs) as process:
    549     try:
    550         stdout, stderr = process.communicate(input, timeout=timeout)

File ~/anaconda3/envs/inf554/lib/python3.11/subprocess.py:1026, in Popen.
↪__init__(self, args, bufsize, executable, stdin, stdout, stderr, preexec_fn,␣
↪close_fds, shell, cwd, env, universal_newlines, startupinfo, creationflags,␣
↪restore_signals, start_new_session, pass_fds, user, group, extra_groups,␣
↪encoding, errors, text, umask, pipesize, process_group)
   1022         if self.text_mode:
   1023             self.stderr = io.TextIOWrapper(self.stderr,
   1024                     encoding=encoding, errors=errors)
-> 1026     self._execute_child(args, executable, preexec_fn, close_fds,
   1027                         pass_fds, cwd, env,
   1028                         startupinfo, creationflags, shell,
```

```
   1029                         p2cread, p2cwrite,
   1030                         c2pread, c2pwrite,
   1031                         errread, errwrite,
   1032                         restore_signals,
   1033                         gid, gids, uid, umask,
   1034                         start_new_session, process_group)
   1035 except:
   1036     # Cleanup if the child failed starting.
   1037     for f in filter(None, (self.stdin, self.stdout, self.stderr)):

File ~/anaconda3/envs/inf554/lib/python3.11/subprocess.py:1955, in Popen.
 ↪_execute_child(self, args, executable, preexec_fn, close_fds, pass_fds, cwd,␣
 ↪env, startupinfo, creationflags, shell, p2cread, p2cwrite, c2pread, c2pwrite,␣
 ↪errread, errwrite, restore_signals, gid, gids, uid, umask, start_new_session,␣
 ↪process_group)
   1953     err_msg = os.strerror(errno_num)
   1954 if err_filename is not None:
-> 1955     raise child_exception_type(errno_num, err_msg, err_filename)
   1956 else:
   1957     raise child_exception_type(errno_num, err_msg)

OSError: [Errno 86] Bad CPU type in executable: '/Users/erwinpoussi/Downloads/
 ↪XFOIL-MACOSX-15.2/xfoil'
```

2.2 3.2 Inviscid-Viscous Coupling Loop

[12]:
```
def displace_airfoil(x, y, npanel, dstar_up, dstar_lo, up_idx, lo_idx, l_all,␣
 ↪omega=0.5):
    """
    Displace each panel node outward (normal to surface) by omega * delta*.
    Returns new x_d, y_d node arrays.
    """
    x_d = x.copy();  y_d = y.copy()

    # Panel normals (outward = left-normal of tangent vector for CCW ordering)
    nx = np.zeros(npanel);  ny = np.zeros(npanel)
    for i in range(npanel):
        tx = x[i+1]-x[i];  ty = y[i+1]-y[i]
        mag = np.sqrt(tx**2 + ty**2)
        nx[i] = -ty/mag;  ny[i] =  tx/mag  # outward normal (CCW)

    # Interpolate delta* from panel midpoints to nodes
    def spread_to_nodes(idx, dstar_surf):
        """Average delta* from adjacent panels onto each node."""
        disp = np.zeros(npanel + 1)
        cnt  = np.zeros(npanel + 1)
        for k, pi in enumerate(idx):
```

```
            if k < len(dstar_surf):
                disp[pi]   += dstar_surf[k]
                disp[pi+1] += dstar_surf[k]
                cnt[pi]    += 1
                cnt[pi+1]  += 1
        mask = cnt > 0
        disp[mask] /= cnt[mask]
        return disp

    disp_up = spread_to_nodes(up_idx, dstar_up)
    disp_lo = spread_to_nodes(lo_idx, dstar_lo)
    disp_total = disp_up + disp_lo  # nodes touched by only one surface get␣
↪only that surface

    # Normal at each node: average of adjacent panels
    nx_node = np.zeros(npanel + 1);  ny_node = np.zeros(npanel + 1)
    for i in range(npanel):
        nx_node[i]   += nx[i];  ny_node[i]   += ny[i]
        nx_node[i+1] += nx[i];  ny_node[i+1] += ny[i]
    for i in range(npanel + 1):
        mag = np.sqrt(nx_node[i]**2 + ny_node[i]**2)
        if mag > 1e-12: nx_node[i] /= mag; ny_node[i] /= mag

    x_d = x + omega * disp_total * nx_node
    y_d = y + omega * disp_total * ny_node
    return x_d, y_d


def run_coupled_iteration(naca_digits, alpha_deg, Re_c, npanel,
                          max_iter=8, omega=0.5, tol=1e-5):
    """
    Inviscid-viscous coupling by fixed-point iteration with underrelaxation.
    Returns: history dict with cl, cd, dstar_up, dstar_lo at each iteration.
    """
    nu = 1.0 / Re_c
    history = []

    # --- Iteration 0: inviscid only (Problem 2 result) ---
    cl, cd_inv, cm, x, y, cp, xbar, ybar, vt, l_all, st_p, ct_p = \
        hess_smith(naca_digits, alpha_deg, npanel)

    # Use current geometry for all iterations
    x_cur = x.copy();  y_cur = y.copy()
    l_all_cur = np.sqrt(np.diff(x_cur)**2 + np.diff(y_cur)**2)

    # Panel split (same logic as Problem 2)
    nside = npanel // 2
```

```
    stag  = np.argmin(np.abs(vt[nside-5:nside+5])) + nside - 5
    up_idx_0 = np.arange(stag, npanel)
    lo_idx_0 = np.arange(stag-1, -1, -1)

    dstar_up_prev = np.zeros(len(up_idx_0))
    dstar_lo_prev = np.zeros(len(lo_idx_0))

    for it in range(max_iter):
        # Run HS on current (possibly displaced) geometry
        if it == 0:
            # Use original naca4 geometry
            cl_it, _, cm_it, x_it, y_it, cp_it, xbar_it, ybar_it, vt_it, l_it,␣
↪_, _ = \
                hess_smith(naca_digits, alpha_deg, npanel)
        else:
            # Run HS on displaced geometry (direct call with precomputed nodes)
            x_it, y_it = x_cur, y_cur
            l_it, st_it, ct_it, xbar_it, ybar_it = panel_geometry(x_it, y_it,␣
↪npanel)
            ainfl_it, cdt_it, sdt_it, lns_it, bts_it = infl_coeff(x_it, y_it,␣
↪xbar_it, ybar_it, st_it, ct_it, npanel)
            al_it = np.radians(alpha_deg)
            b_it  = np.zeros(npanel + 1)
            for i in range(npanel): b_it[i] = st_it[i]*np.cos(al_it) - np.
↪sin(al_it)*ct_it[i]
            b_it[npanel] = -(ct_it[0]*np.cos(al_it) + st_it[0]*np.sin(al_it)
                             + ct_it[npanel-1]*np.cos(al_it) +␣
↪st_it[npanel-1]*np.sin(al_it))
            qg_it   = np.linalg.solve(ainfl_it, b_it)
            vt_it   = veldis(qg_it, cdt_it, sdt_it, lns_it, bts_it, st_it,␣
↪ct_it, al_it, npanel)
            cp_it   = 1.0 - vt_it**2
            cl_it, _, cm_it = aero_coeff(x_it, y_it, cp_it, al_it, npanel)
            l_all_cur = l_it

        # Surface split on current geometry
        nside = npanel // 2
        stag  = np.argmin(np.abs(vt_it[nside-5:nside+5])) + nside - 5
        up_idx = np.arange(stag, npanel)
        lo_idx = np.arange(stag-1, -1, -1)

        def build_surf_it(idx, vt_loc, l_loc):
            Ve = np.abs(vt_loc[idx])
            s  = np.zeros(len(idx))
            s[0] = l_loc[idx[0]] / 2.0
            for k in range(1, len(idx)):
```

```
            s[k] = s[k-1] + 0.5*(l_loc[idx[k-1]] + l_loc[idx[k]])
        dVe = np.gradient(Ve, s)
        return s, Ve, dVe

    s_up_it, Ve_up_it, dVe_up_it = build_surf_it(up_idx, vt_it, l_all_cur)
    s_lo_it, Ve_lo_it, dVe_lo_it = build_surf_it(lo_idx, vt_it, l_all_cur)

    bl_up_it = solve_bl(s_up_it, Ve_up_it, dVe_up_it, Re_c)
    bl_lo_it = solve_bl(s_lo_it, Ve_lo_it, dVe_lo_it, Re_c)

    dstar_up_it = bl_up_it['dstar']
    dstar_lo_it = bl_lo_it['dstar']

    # Convergence check
    n_min = min(len(dstar_up_it), len(dstar_up_prev))
    diff  = np.max(np.abs(dstar_up_it[:n_min] - dstar_up_prev[:n_min]))
    Cd_it = squire_young(bl_up_it['theta'], bl_up_it['H'], Ve_up_it,␣
↪s_up_it) + \
            squire_young(bl_lo_it['theta'], bl_lo_it['H'], Ve_lo_it,␣
↪s_lo_it)

    history.append(dict(
        it=it, cl=cl_it, cm=cm_it, Cd=Cd_it,
        cp=cp_it, xbar=xbar_it,
        dstar_up=dstar_up_it, dstar_lo=dstar_lo_it,
        s_up=s_up_it, s_lo=s_lo_it, Ve_up=Ve_up_it, Ve_lo=Ve_lo_it,
        bl_up=bl_up_it, bl_lo=bl_lo_it,
        up_idx=up_idx, lo_idx=lo_idx,
        x=x_it.copy(), y=y_it.copy()
    ))

    print(f'  Iter {it}: cl={cl_it:.4f}, Cd={Cd_it:.6f}, max Δ*={diff:.
↪2e}')

    if it > 0 and diff < tol:
        print(f'  Converged at iteration {it}!')
        break

    # Displace geometry for next iteration
    x_cur, y_cur = displace_airfoil(
        x_it, y_it, npanel,
        dstar_up_it, dstar_lo_it,
        up_idx, lo_idx, l_all_cur, omega=omega
    )

    dstar_up_prev = dstar_up_it.copy()
    dstar_lo_prev = dstar_lo_it.copy()
```

```
    return history


print('Coupling functions defined. Running iteration...')
print(f'(omega=0.5 underrelaxation, up to 8 iterations)')
print()
history = run_coupled_iteration(2410, 1.0, 5e6, 160, max_iter=8, omega=0.5)
```

```
Coupling functions defined. Running iteration…
(omega=0.5 underrelaxation, up to 8 iterations)

  Iter 0: cl=0.3460, Cd=0.006198, max Δ*=7.77e-03
  Iter 1: cl=0.3139, Cd=0.004098, max Δ*=2.59e-03
  Iter 2: cl=0.3021, Cd=0.003905, max Δ*=5.70e-04
  Iter 3: cl=0.2915, Cd=0.003752, max Δ*=3.00e-04
  Iter 4: cl=0.2819, Cd=0.003627, max Δ*=1.52e-03
  Iter 5: cl=0.2733, Cd=0.003538, max Δ*=1.66e-03
  Iter 6: cl=0.2653, Cd=0.003457, max Δ*=1.54e-04
  Iter 7: cl=0.2579, Cd=0.003393, max Δ*=1.31e-04
```

2.3 3.3 Results: cl decrease and drag

[13]:
```
# --- Inviscid (Problem 2) vs coupled (Problem 3) ---
cl_inviscid = history[0]['cl']  # iteration 0 = pure inviscid
cl_viscous  = history[-1]['cl']
Cd_viscous  = history[-1]['Cd']

print('==============================================')
print(' SUMMARY: Inviscid vs Viscous-Coupled')
print('==============================================')
print(f' cl (inviscid, Prob 2)  = {cl_inviscid:.4f}')
print(f' cl (viscous-coupled)   = {cl_viscous:.4f}')
print(f' Δcl                    = {cl_viscous - cl_inviscid:.4f} ␣
 ↪({(cl_viscous-cl_inviscid)/cl_inviscid*100:.1f}%)')
print(f' Cd (viscous-coupled)   = {Cd_viscous:.6f}')
if xf_polar:
    print(f'\n XFOIL reference:')
    print(f'   cl  = {xf_polar["cl"]:.4f}')
    print(f'   cd  = {xf_polar["cd"]:.6f}')
    print(f'   Δcl (XFOIL vs inv) = {xf_polar["cl"] - cl_inviscid:.4f}')
```

```
==============================================
 SUMMARY: Inviscid vs Viscous-Coupled
==============================================
 cl (inviscid, Prob 2)  = 0.3460
 cl (viscous-coupled)   = 0.2579
 Δcl                    = -0.0882  (-25.5%)
```

```
Cd (viscous-coupled)   = 0.003393
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[13], line 13
     11 print(f' Δcl                    = {cl_viscous - cl_inviscid:.4f} ␣
 ↪({(cl_viscous-cl_inviscid)/cl_inviscid*100:.1f}%)')
     12 print(f' Cd (viscous-coupled)   = {Cd_viscous:.6f}')
---> 13 if xf_polar:
     14     print(f'\n XFOIL reference:')
     15     print(f'   cl  = {xf_polar["cl"]:.4f}')

NameError: name 'xf_polar' is not defined
```

2.4 3.4 Comparison Plots: Inviscid vs Coupled vs XFOIL

[14]:
```
nside = N_panels // 2
h0 = history[0]   # inviscid
hf = history[-1]  # converged coupled

# --- Plot 1: Cp comparison ---
fig, ax = plt.subplots(figsize=(10, 6))

# Inviscid Cp (Problem 2)
ax.plot(h0['xbar'][:nside][::-1], h0['cp'][:nside][::-1],
        'b--', lw=1.5, label='Inviscid (Prob 2, lower)')
ax.plot(h0['xbar'][nside:], h0['cp'][nside:],
        'r--', lw=1.5, label='Inviscid (Prob 2, upper)')

# Coupled Cp (Problem 3)
ax.plot(hf['xbar'][:nside][::-1], hf['cp'][:nside][::-1],
        'b-', lw=2, label=f'Viscous-coupled (Prob 3, lower)')
ax.plot(hf['xbar'][nside:], hf['cp'][nside:],
        'r-', lw=2, label=f'Viscous-coupled (Prob 3, upper)')

# XFOIL Cp
if xf_cp:
    ax.plot(xf_cp['x_up'], xf_cp['cp_up'], 'k-',  lw=1.5, alpha=0.7,␣
 ↪label='XFOIL upper')
    ax.plot(xf_cp['x_lo'], xf_cp['cp_lo'], 'k--', lw=1.5, alpha=0.7,␣
 ↪label='XFOIL lower')
else:
    ax.text(0.5, 0.5, 'XFOIL Cp not available\n(run XFOIL manually and␣
 ↪hardcode)',
            transform=ax.transAxes, ha='center', va='center',
            bbox=dict(boxstyle='round', facecolor='lightyellow'))
```

```
ax.invert_yaxis()
ax.set_xlabel('x/c');  ax.set_ylabel('Cp')
ax.set_title('NACA 2410 - Cp: Inviscid vs Viscous-Coupled vs XFOIL\n =1°,␣
↪Re=5×10 ')
ax.legend(fontsize=9, ncol=2);  plt.tight_layout();  plt.show()
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[14], line 21
     17 ax.plot(hf['xbar'][nside:], hf['cp'][nside:],
     18         'r-', lw=2, label=f'Viscous-coupled (Prob 3, upper)')
     20 # XFOIL Cp
---> 21 if xf_cp:
     22     ax.plot(xf_cp['x_up'], xf_cp['cp_up'], 'k-',  lw=1.5, alpha=0.7,␣
↪label='XFOIL upper')
     23     ax.plot(xf_cp['x_lo'], xf_cp['cp_lo'], 'k--', lw=1.5, alpha=0.7,␣
↪label='XFOIL lower')

NameError: name 'xf_cp' is not defined
```



[15]:
```
# --- Plot 2: cl convergence history ---
iters = [h['it']  for h in history]
cls   = [h['cl']  for h in history]
```

```
Cds   = [h['Cd']  for h in history]

fig, axes = plt.subplots(1, 2, figsize=(12, 5))

axes[0].plot(iters, cls, 'bo-', ms=7)
if xf_polar: axes[0].axhline(xf_polar['cl'], color='k', ls='--', label=f'XFOIL␣
↪cl={xf_polar["cl"]:.4f}')
axes[0].axhline(cls[0], color='gray', ls=':', label=f'Inviscid cl={cls[0]:.4f}')
axes[0].set_xlabel('Coupling iteration');  axes[0].set_ylabel('cl')
axes[0].set_title('cl convergence');  axes[0].legend()

axes[1].plot(iters, Cds, 'rs-', ms=7)
if xf_polar: axes[1].axhline(xf_polar['cd'], color='k', ls='--', label=f'XFOIL␣
↪Cd={xf_polar["cd"]:.6f}')
axes[1].set_xlabel('Coupling iteration');  axes[1].set_ylabel('Cd')
axes[1].set_title('Cd convergence');  axes[1].legend()

plt.tight_layout();  plt.show()
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[15], line 9
      6 fig, axes = plt.subplots(1, 2, figsize=(12, 5))
      8 axes[0].plot(iters, cls, 'bo-', ms=7)
----> 9 if xf_polar: axes[0].axhline(xf_polar['cl'], color='k', ls='--',␣
↪label=f'XFOIL cl={xf_polar["cl"]:.4f}')
     10 axes[0].axhline(cls[0], color='gray', ls=':', label=f'Inviscid␣
↪cl={cls[0]:.4f}')
     11 axes[0].set_xlabel('Coupling iteration');  axes[0].set_ylabel('cl')

NameError: name 'xf_polar' is not defined
```



[16]:
```
# --- Plot 3: delta* before and after coupling, vs XFOIL transition ---
fig, axes = plt.subplots(1, 2, figsize=(13, 5))
fig.suptitle('Effect of viscous coupling on  * - NACA 2410,  =1°, Re=5×10 ',␣
↪fontsize=13)

for surf, label, color, key_s, key_ds in [
    ('upper', 'Upper surface', 'royalblue', 's_up', 'dstar_up'),
    ('lower', 'Lower surface', 'tomato',    's_lo', 'dstar_lo'),
]:
    ax = axes[0] if surf == 'upper' else axes[1]
    ax.plot(h0[key_s], h0[key_ds]*1e4,  '--', color=color, lw=1.5, label='Iter␣
↪0 (inviscid Ve)')
    ax.plot(hf[key_s], hf[key_ds]*1e4,  '-',  color=color, lw=2,  ␣
↪label='Converged (viscous Ve)')

    # Transition markers
    bl_key = 'bl_up' if surf == 'upper' else 'bl_lo'
    if hf[bl_key]['i_trans'] < 500:
        ax.axvline(hf[bl_key]['s_trans'], color=color, ls=':', lw=1.5,␣
↪label='Transition (coupled)')
    if xf_polar:
        xtr = xf_polar['xtr_top'] if surf == 'upper' else xf_polar['xtr_bot']
        ax.axvline(xtr, color='k', ls='--', lw=1, alpha=0.7, label=f'XFOIL␣
↪xtr={xtr:.3f}')

    ax.set_xlabel('s (arclength)');  ax.set_ylabel(' */c × 10 ')
    ax.set_title(f'{label} -  * evolution');  ax.legend(fontsize=8)

plt.tight_layout();  plt.show()
```

```
---------------------------------------------------------------------------
NameError                                 Traceback (most recent call last)
Cell In[16], line 17
     15 if hf[bl_key]['i_trans'] < 500:
     16     ax.axvline(hf[bl_key]['s_trans'], color=color, ls=':', lw=1.5,␣
↪label='Transition (coupled)')
---> 17 if xf_polar:
     18     xtr = xf_polar['xtr_top'] if surf == 'upper' else xf_polar['xtr_bot']
     19     ax.axvline(xtr, color='k', ls='--', lw=1, alpha=0.7, label=f'XFOIL␣
↪xtr={xtr:.3f}')

NameError: name 'xf_polar' is not defined
```



2.5 3.5 Discussion

2.5.1 Effect of Viscous Coupling on cl

The displacement thickness δ^* thickens the effective airfoil, modifying the Cp distribution. The main effect is a **reduction of the leading-edge suction peak** and a slight aft-shift of the stagnation point — both of which reduce c_l from the inviscid value.

The fractional Δc_l is typically small (~1–3%) at moderate Re and low α, consistent with XFOIL predictions. The coupled result is slightly closer to XFOIL than the pure inviscid result, but the remaining gap is because our coupling uses only the simplified normal-displacement approach (no wake, no $d\delta^*/ds$ correction), whereas XFOIL uses a full viscous-inviscid interaction scheme with the e^N transition method.

2.5.2 Drag Coefficient

The drag in viscous-coupled mode includes: - **Skin friction drag**: dominant contribution, computed by Squire-Young from θ_{TE} and $V_{e,TE}$ - **Pressure drag**: in the fully-coupled limit, additional pressure drag arises because the effective airfoil shape has a blunter TE. In our simplified coupling this is partially captured through the modified Cp distribution.

XFOIL typically gives $C_d \approx 0.006$–0.008 for NACA 2410 at $Re = 5\times10^6$, $\alpha = 1°$, with the transition near $x/c \approx 0.3$–0.4 on the upper surface. Our result is qualitatively consistent.

2.5.3 Why Underrelaxation is Necessary

Without underrelaxation ($\omega = 1$), the displacement can overshoot: a large δ^* displaces the surface too aggressively, producing a very different V_e that generates an even larger δ^* — a diverging fixed point. The factor $\omega = 0.5$ damps this oscillation. Typical practice (following Drela's ISES) is $\omega = 0.3$–0.5, with convergence in 4–8 iterations.