

IBM Resilient



Incident Response Platform Integrations

LDAP Search Function V1.0.0

Release Date: June 2018

Resilient Functions simplify development of integrations by wrapping each activity into an individual workflow component. These components can be easily installed, then used and combined in Resilient workflows. The Resilient platform sends data to the function component that performs an activity then returns the results to the workflow. The results can be acted upon by scripts, rules, and workflow decision points to dynamically orchestrate the security incident response activities.

This guide describes the LDAP Search Function.

Overview

The Lightweight Directory Access Protocol or LDAP is an open, vendor-neutral, industry standard application protocol for accessing and maintaining distributed directory information services over an IP network. It is used to connect to, search, and modify internet directories.

The LDAP search integration with the IBM Resilient platform allows an LDAP search to be initiated from the Resilient platform to an external LDAP server. The returned results can be used to make customized updates to the Resilient platform such as updating incidents, artifacts, data tables and so on.

There is one function supplied in the Resilient function package for LDAP search. The function runs a query against an LDAP server. There are example workflows in the customizations section of the package which demonstrate usage of the Resilient Investigate Functions to update data tables.

The remainder of this document describes the included function, how to configure example custom workflows, and any additional customization options.

Installation

Before installing, verify that your environment meets the following prerequisites:

- The Resilient platform must be 30 or later.
- You must have Resilient account to use for the integrations. This can be any account that has the permission to view and modify administrator and customization settings, and read and update incidents. You must know the account username and password.
- You must have access to the command line of the Resilient appliance, which hosts the Resilient platform; or to a separate integration server where you will deploy and run the functions code. If you are using a separate integration server, you must install Python version 2.7.10 or later, or version 3.6 or later, and “pip”. (The Resilient appliance is preconfigured with a suitable version of Python.)

LDAP server configuration

Access to the LDAP server is based on user and password. The user is in the form of a cn or common name.

The LDAP search Function currently supports the following possible authentication types for connection to an LDAP server:

```
ANONYMOUS
SIMPLE
NTLM
```

The LDAP Search function defaults to ANONYMOUS login if there are no credentials provided.

Install the Python components

The functions package contains Python components that are called by the Resilient platform to execute the functions during your workflows. These components run in the `resilient-circuits` integration framework.

The package also includes Resilient customizations that will be imported into the platform later.

Complete the following steps to install the Python components:

1. Ensure that the environment is up to date, as follows:

```
sudo pip install --upgrade pip
sudo pip install --upgrade setuptools
sudo pip install --upgrade resilient-circuits
```

2. Run the following command to install the package:

```
sudo pip install --upgrade fn_ldap_search-1.0.0.tar.gz
```

Configure the Python components

The `resilient-circuits` components run as an unprivileged user, typically named `integration`. If you do not already have an `integration` user configured on your appliance, create it now.

Complete the following to configure and run the integration:

1. Using `sudo`, switch to the `integration` user, as follows:

```
sudo su - integration
```

2. Use one of the following commands to create or update the `resilient-circuits` configuration file. Use `-c` for new environments or `-u` for existing environments:

```
resilient-circuits config -c
```

or

```
resilient-circuits config -u
```

3. Edit the `resilient-circuits` configuration file, as follows:

- a. In the `[resilient]` section, ensure that you provide all the information required to connect to the Resilient platform.
- b. In the `[fn_ldap_search]` section, edit the settings as follows: (Note: The default credentials are for an on-line test server.)

```
# LDAP server ip or fully qualified hostname
server=ldap.forumsys.com
port=389
# The domain setting must be set to a valid Windows domain if using NTLM
authentication.
#domain=WORKGROUP
user=cn=read-only-admin,dc=example,dc=com
password=password
auth=SIMPLE
use_ssl=False
```

- c. For an Active Directory, the following are both valid configuration settings formats.

```
# Active Directory example 1.
server=adserver
port=389
user=mydomain\myuser
password=mypass
auth=SIMPLE
use_ssl=False
connect_timeout=10

# Active Directory example 2.
server=adserver
port=389
domain=mydomain
user=myuser
password=mypass
auth=NTLM
use_ssl=False
connect_timeout=10
```

Deploy customizations to the Resilient platform

The package contains function definitions that you can use in workflows, and includes example workflows and rules that show how to use these functions.

Complete the following steps to deploy customizations:

1. Use the following command to deploy these customizations to the Resilient platform:

```
resilient-circuits customize
```

2. Respond to the prompts to deploy functions, message destinations, workflows and rules.

Run the integration framework

To test the integration package before running it in a production environment, you must run the integration manually, using the following command:

```
resilient-circuits run
```

The `resilient-circuits` command starts, loads its components, and continues to run until interrupted. If it stops immediately with an error message, check your configuration values and retry.

Configure resilient-circuits for restart

For normal operation, `resilient-circuits` must run continuously. The recommended way to do this is to configure it to automatically run at startup. On a Red Hat appliance, you can do this using a `systemd` unit file such as the one below. You might need to change the paths to your working directory and `app.config`.

1. The unit file must be named `resilient_circuits.service`. To create the file, enter the following command:

```
sudo vi /etc/systemd/system/resilient_circuits.service
```

2. Add the following contents to the file and change as necessary:

```
[Unit]
Description=Resilient-Circuits Service
After=resilient.service
Requires=resilient.service

[Service]
Type=simple
User=integration
WorkingDirectory=/home/integration
ExecStart=/usr/local/bin/resilient-circuits run
Restart=always
TimeoutSec=10
Environment=APP_CONFIG_FILE=/home/integration/.resilient/app.config
Environment=APP_LOCK_FILE=/home/integration/.resilient/resilient_circuits.lock

[Install]
WantedBy=multi-user.target
```

3. Ensure that the service unit file has the correct permissions:

```
sudo chmod 664 /etc/systemd/system/resilient_circuits.service
```

4. Use the `systemctl` command to manually start, stop, restart and return status on the service:

```
sudo systemctl resilient_circuits [start|stop|restart|status]
```

You can view log files for `systemd` and the `resilient-circuits` service using the `journalctl` command:

```
sudo journalctl -u resilient_circuits --since "2 hours ago"
```

Function Description

Once the function package deploys the function, ldap_search, you can view it in the Resilient platform Functions tab, as shown below. The package also includes an example workflow, rule and data table that show how the function can be used. You can copy and modify these items for your own needs.

Customization Settings

Layouts	Rules	Scripts	Workflows	Functions	Message Destinations	Phases & Tasks	Incident Types
---------	-------	---------	-----------	------------------	----------------------	----------------	----------------

Functions / ldap_search

Name *	ldap_search
API Name * ⓘ	ldap_search
Message Destination *	ldap ▾
Description	Resilient Function to do a search or query against an LDAP server.

Inputs

ldap_search_base	×
ldap_search_filter	×
ldap_search_attributes	×
ldap_param	×

This function takes the following input fields. Refer to LDAP documentation on the use of LDAP search arguments.

- ldap_search_base
- ldap_search_filter
- ldap_search_attributes
- ldap_param

Workflow

The **Example: LDAP Search – Person** workflow is available in the Workflows tab, as shown below. The rule Object Type is Artifact.

Customization Settings

Layouts Rules Scripts **Workflows** Functions Message Destinations Phases & Tasks Incident Types Breach Artifacts

Workflows / Example: LDAP Search - Person

Cancel Save & Close Save

Name * Example: LDAP Search - Person

API Name * wf_ldap_search

Description Example workflow which runs a person query against an LDAP server.

Creator Resilient Sysadmin

Last Modified 05/16/2018 12:20

Last Modified By Resilient Sysadmin

Associated Rules Example: LDAP Search - Person

Input	Pre-Process Script	Output	Post-Process Script
Input Parameter	Value		
ldap_search_base	dc=example,dc=com		
ldap_search_filter	(&(objectClass=person)(uid=%param%))		
ldap_search_attributes	uid,cn,sn,mail,telephoneNumber		
ldap_param	domain.com		

The package includes predefined parameter values. Users should change these values to match their environment either in the Input tab or the Pre-Process Script as shown in the following figure.

Customization Settings

Layouts Rules Scripts **Workflows** Functions Message Destinations Phases & Tasks Incident Types Breach Artifacts

Workflows / Example: LDAP Search - Person

Cancel Save & Close Save

Name * Example: LDAP Search - Person

API Name * wf_ldap_search

Description Example workflow which runs a person query against an LDAP server.

Creator Resilient Sysadmin

Last Modified 05/16/2018 12:20

Last Modified By Resilient Sysadmin

Associated Rules Example: LDAP Search - Person

Input	Pre-Process Script	Output	Post-Process Script
Language: Python Theme light Mode Default Tab Size 2 - Font + Font	<pre>1 ## LDAP Search Workflow - pre-processing script ## 2 inputs.ldap_search_base = "dc=example,dc=com" 3 inputs.ldap_search_filter = "&(objectClass=person)(uid=%param%)" 4 inputs.ldap_search_attributes = "uid,cn,sn,mail,telephoneNumber" 5 inputs.ldap_param = artifact.value</pre>		

Rule

You can view the example rule in the Rules tab. The rule is a Menu Item rule that is selectable in the Actions button when viewing the Artifacts tab of an incident. When selected, the rule calls the provided workflow.

Customization Settings

Order	Rule Name	Process Type	Object Type	Conditions
-	Example: LDAP Search - Person	Menu Item	Artifact	

Resilient Platform Configuration

To display query results, users need to manually add the “LDAP Query results” data table to the Artifacts tab.

1. Navigate to the Customization Settings and select the Layouts tab.
2. Select Artifacts.
3. Drag the “LDAP Query results” data table to your Artifacts tab.
4. Click Save.

Customization Settings

Incident: Artifacts

Save

Fields ⓘ Add Field

Search...

Address ⓘ

Assessed Liability ⓘ

City ⓘ

Country ⓘ

Created By ⓘ

Criminal Activity ⓘ

Data Compromised ⓘ

Data Encrypted ⓘ

Data Format ⓘ

Data Tables ⓘ Add Table

LDAP Query results ⓘ

To run an LDAP search query:

1. Go to the Artifacts tab of an incident.
2. Click the **Actions** icon for an artifact.
3. Select **Example: LDAP Search – Person**.

This executes the corresponding workflow against that particular artifact. In the following example, the corresponding data table is updated, where the artifact values are User Accounts.

Phase Respond

Severity Low

Date Created 05/16/2018

Date Occurr... —

Date Discov... 05/16/2018

Data Compr... Unknown

Incident Type —

People

Created By Resilient Sysadmin

Owner Resilient Sysadmin

Members There are no members.

Related Incidents

No related incidents.

Attachments

There are no attachments.

Newsfeed

Resilient Sysadmin created the artifact gauss 2 minutes ago

Resilient Sysadmin created the artifact pasteur

Tasks Details Breach Notes Members News Feed Attachments Stats Timeline Artifacts

Artifacts

Edit

Add Artifact Table Graph

Search...

Artifact Type: All Date Created: All Has Attachment: All

Show 25 entries

Type	Value	Created	Relate?	Actions
User Account	boyle	05/16/2018	As specified in artifact type settings	Example: LDAP Search - Person
User Account	newton	05/16/2018	As specified in artifact type settings	
User Account	gauss	05/16/2018	As specified in artifact type settings	
User Account	einstein	05/16/2018	As specified in artifact type settings	
User Account	pasteur	05/16/2018	As specified in artifact type settings	

LDAP Query results

Search... Print Export

UID	Fullname	Surname	Email address	Telephone Number
There is no data for this table				

Showing 0 to 0 of 0 entries

Users can update the LDAP Query results data table with an entry for each user name by running the LDAP search action.

Phase Respond

Severity Low

Date Created 05/16/2018

Date Occurr... —

Date Discov... 05/16/2018

Data Compr... Unknown

Incident Type —

People

Created By Resilient Sysadmin

Owner Resilient Sysadmin

Members There are no members.

Related Incidents

No related incidents.

Attachments

There are no attachments.

Newsfeed

Resilient Sysadmin added a row to the Data Table LDAP Query results a moment ago

Resilient Sysadmin added a row to the Data Table LDAP Query results a moment ago

Resilient Sysadmin added a row to the Data Table LDAP Query results a moment ago

Resilient Sysadmin added a row to the Data Table LDAP Query results a moment ago

Resilient Sysadmin added a row to the Data Table LDAP Query results a moment ago

Tasks Details Breach Notes Members News Feed Attachments Stats Timeline Artifacts

Artifacts

Edit

Add Artifact Table Graph

Search...

Artifact Type: All Date Created: All Has Attachment: All

Show 25 entries

Type	Value	Created	Relate?	Actions
User Account	newton	05/16/2018	As specified in artifact type settings	
User Account	boyle	05/16/2018	As specified in artifact type settings	
User Account	pasteur	05/16/2018	As specified in artifact type settings	
User Account	gauss	05/16/2018	As specified in artifact type settings	
User Account	einstein	05/16/2018	As specified in artifact type settings	

LDAP Query results

Search... Print Export

UID	Fullname	Surname	Email address	Telephone Number
einstein	Albert Einstein	Einstein	einstein@ldap.forumsys.com	314-159-2653
pasteur	Louis Pasteur	Pasteur	pasteur@ldap.forumsys.com	602-214-4978
boyle	Robert Boyle	Boyle	boyle@ldap.forumsys.com	999-867-5309
newton	Isaac Newton	Newton	newton@ldap.forumsys.com	N/A
gauss	Carl Friedrich Gauss	Gauss	gauss@ldap.forumsys.com	N/A

Displaying 1 - 5 of 5

Troubleshooting

There are several ways to verify the successful operation of a function.

- Resilient Action Status

When viewing an incident, use the Actions menu to view Action Status. By default, pending and errors are displayed. Modify the filter for actions to also show Completed actions. Clicking on an action displays additional information on the progress made or what error occurred.

- Resilient Scripting Log

A separate log file is available to review scripting errors. This is useful when issues occur in the pre-processing or post-processing scripts. The default location for this log file is:
`/var/log/resilient-scripting/resilient-scripting.log`.

- Resilient Logs

By default, Resilient logs are retained at `/usr/share/co3/logs`. The `client.log` may contain additional information regarding the execution of functions.

- Resilient-Circuits

The log is controlled in the `.resilient/app.config` file under the section `[resilient]` and the property `logdir`. The default file name is `app.log`. Each function will create progress information. Failures will show up as errors and may contain python trace statements.

Support

For additional support, contact support@resilientsystems.com.

Including relevant information from the log files will help us resolve your issue.