This page is a full-page electronic schematic diagram and cannot be faithfully represented as text. The primary readable labels and title block content are transcribed below.

Connectors (top):
- J7 — PM254-2-04-W-8.5
- J8 — PM254-2-04-W-8.5
- GND

USB protection resistors (top): R9, R10, R11, R12, R13, R14, R15, R16 — 34R

ESD diodes: IP4220CZ6.125 (D4B, D4A, D4D, D4C, D3B, D3A, D3D, D3C, D2C, D2B, D1A, D1C, D1B, D2A, D2D, D4E, D3E, D2E, D1E, D5E, D5A, D5B, D5C, D5D)

Power:
- +5V
- C15 1u, C16 100n, C17 100n
- LED2 / LED1 — TC5050RGBF08-3CJH-AF53A
- R17–R22 1k
- Q1–Q6 — S8050_C20069125
- R23–R28 47k

Microcontrollers:
- U1B STM32G431KBU3
- U1A STM32G431KBU3

Regulator:
- U2 XC6206P332MR
- C1 4.7u, C2 1u, C3 100n, C4 4.7u, C5 1u, C6 100n
- C7 1u, C8 100n, C9 1u, C10 100n, C12 100n, C11 1u
- FB1 FerriteBead
- +3V3 / 3V3A

USB:
- USB1 — micro USBFemale
- USB_P / USB_N (USB_Data)
- UART RX / UART TX
- R1, R2, R3, R4 — 100
- R5, R6, R7, R8 — 100 (SWDIO / SWCLK)

UART XCVR — Conn_01x03_Socket (J1, J2) — marked X

Op-amps:
- U5A, U5B, U5C, U5D, U5E — MCP6024T-I/ST
- R29, R30 — 47k
- R36, R37 — 51
- C20 68n 1206, C21 68n 1206
- C22 100p, C23 100p
- R33 51 1206, R32 51 1206
- C25 100n, C26 100n
- R34 51, R35 51
- R38 10M, R39 10M
- C19 100n, C18 1u
- C24 100n

SMA Connectors:
- J4, J3, J5, J6 — SMA-KWE_C7498154

Decoupling: C13, C14, C31 100n, C27, C28, C29, C30 100n

Engineer: Ryan Brandt
Ryan.Brandt.Tech@gmail.com
BrandtTech

Sheet: /
File: TwinDAQ_v1.kicad_sch
Title: TwinDAQv1
Size: A3 Date: 2025-11-17 Rev: v1
KiCad E.D.A. 9.0.0 Id: 1/1