



# **LDAP client services**

## **System Manager Classic**

NetApp  
December 09, 2021

# Table of Contents

- LDAP client services ..... 1
  - Add an LDAP client configuration ..... 1
  - Deleting an LDAP client configuration ..... 1
  - Editing an LDAP client configuration ..... 2
  - LDAP Client window ..... 2

# LDAP client services

You can use System Manager to add, edit, and delete LDAP client configurations.



## Add an LDAP client configuration

You can use System Manager to add an LDAP client configuration at the cluster level or the storage virtual machine (SVM) level if you want to use LDAP services. You must first set up an LDAP client to use LDAP services.

### About this task

At the SVM level, you can add an LDAP client only for a selected SVM.

### Steps

1. Add an LDAP client configuration by using one of the following methods:
  - Cluster level: click  > **LDAP**.
  - SVM level: click **SVM** > **SVM Settings** > **LDAP Client**.
2. Click **Add**.
3. Type the name of the LDAP client.
4. Add either the Active Directory domain or the LDAP server.
5. Click  (advanced options), select the **Schema**, and click **Apply**.
6. Specify the **Base DN** and **TCP Port**.
7. Click **Binding**, and then specify the authentication details.
8. Click **Save and Close**.
9. Verify that the LDAP client that you added is displayed.

### Related information

[LDAP](#)


## Deleting an LDAP client configuration

You can use System Manager to delete an LDAP client configuration at the cluster level or the storage virtual machine (SVM) level.

### About this task

At the SVM level, you can delete an LDAP client only for a selected SVM.

### Steps

1. To delete an LDAP client configuration:
  - Cluster level: Click  > **LDAP**.
  - SVM level: Click **SVM** > **SVM Settings** > **LDAP Client**.
2. Select the LDAP client that you want to delete, and then click **Delete**.
3. Select the confirmation check box, and then click **Delete**.

4. Verify that the LDAP client that you deleted is no longer displayed.

## Related information

### LDAP


## Editing an LDAP client configuration

You can use System Manager to edit an LDAP client configuration at the cluster level or the storage virtual machine (SVM) level.

### About this task

At the SVM level, you can edit an LDAP client only for a selected SVM.

### Steps

1. To edit an LDAP client configuration:
  - Cluster level: Click  > **LDAP**.
  - SVM level: Click **SVM** > **SVM Settings** > **LDAP Client**.
2. Select the LDAP client that you want to modify, and then click **Edit**.
3. In the **Edit LDAP Client** dialog box, edit the LDAP client configuration as required.
4. Click **Save and Close**.
5. Verify that the changes that you made to the LDAP client configuration are displayed.

## Related information

### LDAP

## LDAP Client window

You can use the LDAP Client window to create LDAP clients for user authentication, file access authorization, user search, and mapping services between NFS and CIFS at the storage virtual machine (SVM) level.

## Command buttons

- **Add**

Opens the Create LDAP Client dialog box, which enables you to create and configure LDAP clients.

- **Edit**

Opens the Edit LDAP Client dialog box, which enables you to edit LDAP client configurations. You can also edit active LDAP clients.

- **Delete**

Opens the Delete LDAP Client(s) dialog box, which enables you to delete LDAP client configurations. You can also delete an active LDAP client.

- **Refresh**

Updates the information in the window.

## **LDAP client list**

Displays (in tabular format) details about LDAP clients.

- **LDAP Client Configuration**

Displays the name of the LDAP client configuration that you specified.

- **Storage Virtual Machine**

Displays the name of the SVM for each LDAP client configuration.

- **Schema**

Displays the schema for each LDAP client.

- **Minimum Bind Level**

Displays the minimum bind level for each LDAP client.

- **Active Directory Domain**

Displays the Active Directory domain for each LDAP client configuration.

- **LDAP Servers**

Displays the LDAP server for each LDAP client configuration.

- **Preferred Active Directory Servers**

Displays the preferred Active Directory server for each LDAP client configuration.

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.