



Volume restore workflow

System Manager Classic

NetApp

December 09, 2021


This PDF was generated from https://docs.netapp.com/us-en/ontap-sm-classic/volume-restore-snapvault/task_identifying_snapvault_backup_destination_volume.html on December 09, 2021. Always check docs.netapp.com for the latest.

Table of Contents

- Volume restore workflow 1
 - Identify the SnapVault backup destination volume..... 2
 - Restore data from a SnapVault backup 3
 - Verify the restore operation 5
 - Where to find additional information..... 5

Volume restore workflow

When your source volume is unavailable or data is corrupted, you can perform a restore from a SnapVault backup. Restoring a volume from a SnapVault backup involves selecting the SnapVault destination volume, restoring either to a new volume or existing volume, and verifying the restore operation.



Identify the SnapVault backup destination volume

You must identify the SnapVault backup destination volume from which you want to

restore data when the data in the source volume is corrupted or lost.

About this task

You must perform this task from the **source** cluster.

Steps

1. Enter the URL `https://IP-address-of-cluster-management-LIF` in a web browser and log in to System Manager using your cluster administrator credential.
2. Navigate to the **Volumes** window.
3. Identify the destination volume in the SnapVault relationship and the name of the SVM that contains the volume:
 - ONTAP 9.3 or later: Double-click the volume to view the details, and then click **PROTECTION**.
 - ONTAP 9.2 or earlier: Click the **Data Protection** tab at the bottom of the Volumes window.

Restore data from a SnapVault backup

After selecting the SnapVault backup destination volume, you must perform the restore operation either to a new volume to test the backed-up data or to an existing volume to restore the lost or corrupted data.

About this task

You must perform this task from the **destination** cluster.

Steps

1. Depending on the System Manager version that you are running, perform one of the following steps:
 - ONTAP 9.4 or earlier: Click **Protection > Relationships**.
 - Starting with ONTAP 9.5: Click **Protection > Volume Relationships**.
2. Select the SVM that contains the SnapVault backup destination volume, and then click **Operations > Restore**.
3. In the **Restore** dialog box, restore the data to the original source volume or a new volume:

If you want to restore to...	Then...
The original source volume	Select Source volume .

If you want to restore to...	Then...
A new volume	<ol style="list-style-type: none"> Select Other volume. Select the peered cluster and the peered SVM for the volume. Select a peered SVM from the list. If the SVM is not peered, create the SVM peer relationship: <ol style="list-style-type: none"> Select the SVM. Click Authenticate. Enter the cluster administrator's credentials of the peered cluster, and then click Create. Select New Volume. If you want to change the default name, displayed in the format <code>destination_SVM_name_destination_volume_name_restore</code>, specify a new name and select the containing aggregate for the volume. Select the Enable dedupe check box.

Restore to

☐ Source volume
☒ Other volume

Cluster:

Storage Virtual Machine:

Volume: ☒ New Volume ☐ Select Volume

Volume name:
Aggregate:

☒ Enable dedupe
517.22 GB available (of 520.28 GB)

- Select either the latest Snapshot copy or select a specific Snapshot copy that you want to restore.
- Select the **OK to restore the volume from the Snapshot copy** check box.
- Select the **Enable Network Compression** check box to compress the data that is being transferred during the restore operation.
- Click **Restore**.

During the restore process, the volume being restored is changed to read-only. After the restore operation finishes, the temporary relationship is removed and the restored volume is changed to read/write.

The image shows a 'Configuration' dialog box with the following elements:

- Configuration** (Title bar)
- Radio button selection:
 - ☒ Latest Snapshot copy: "daily.2014-09-11_0010" 09/11/2014 00:10:00
 - ☐ Select Snapshot copy: [Text field] [Browse...]
- Checkboxes:
 - ☒ OK to restore the volume from the Snapshot copy
 - ☒ Enable Network Compression
- Buttons at the bottom right: [Restore] [Cancel]

8. Click **OK** in the message box.

Verify the restore operation

After performing the restore operation from the SnapVault backup destination volume, you must verify the status of the restore operation on the source cluster.

About this task

You must perform this task from the **source** cluster.

Steps

1. Navigate to the **Volumes** window.
2. Select the source volume in the volumes list and perform one of the following actions, depending on your ONTAP version:
 - Starting with ONTAP 9.3: Double-click the source volume to view the details, and then click **PROTECTION** to identify the destination volume in the SnapMirror relationship and the name of the SVM that contains the volume.
 - ONTAP 9.2 or earlier: Click the **Data Protection** bottom tab to identify the destination volume in the SnapMirror relationship and the name of the SVM that contains the volume. The Type field displays `Restore` temporarily. After the restore operation is completed, the field displays `Vault`.

You should troubleshoot any issues in the SnapVault relationships. The troubleshooting procedures for SnapMirror relationships are also applicable to SnapVault relationships.

[NetApp Technical Report 4015: SnapMirror Configuration and Best Practices for ONTAP 9.1, 9.2](#)

Where to find additional information

Additional information is available to help you to manage the SnapVault backup relationships and to use other methods of data protection to protect the availability of your data resources.

- [Volume disaster recovery preparation](#)

Describes how to quickly configure a destination volume on a different ONTAP cluster in preparation for disaster recovery.

- [Volume disaster recovery](#)

Describes how to quickly activate a destination volume from a different ONTAP cluster after a disaster, as well as how to restore the SnapMirror relationship to its original state by reactivating the source volume after its recovery.

- [Data protection](#)

Describes how to prevent data loss using Snapshot copies and SnapMirror replication to a remote system

- [Data protection using tape backup](#)

Describes how to back up and recover data using tape backup and recovery features in clusters, using NDMP and dump technologies.

- [ONTAP concepts](#)

Describes conceptual information about ONTAP clusters in preparation for disaster recovery.

Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system- without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.