src/gui.py Page 1

```
Ryan Kennedy, Gabriel Waldner
Cmdr. Schenk
Cloud Computing
7th Period
May 5, 2025
import tkinter as tk
from tkinter import ttk
from tkinter import messagebox
from user_record import UserRecord
from task_record import TaskRecord
from database import Database
from gui_states import GUIStates
from register_user import RegisterUser
from login_user import LoginUser
from user_info import UserInfo
from task_browser import TaskBrowser
class GUI():
    def __init__(self):
        # tkinter init
        self.root = tk.Tk()
        self.root.geometry("800x800")
        # db init
        self.db = Database()
        # where you can create a new user
        self.register_user = RegisterUser(self.root, self.db)
        # where you can login to the user
        self.login_user = LoginUser(self.root, self.db)
        # where you can update/delete your user
        self.user_info = UserInfo(self.root, self.db)
        # where you can view/CRUD on the logged in user's tasks
        self.task_browser = TaskBrowser(self.root, self.db)
        # a map that stores the functions to show the different states so that a butto
n in one state can change to another state
        show_map = {
            GUIStates.REGISTER_USER : self.register_user.show,
            GUIStates.LOGIN_USER : self.login_user.show,
GUIStates.USER_INFO : self.user_info.show,
            GUIStates.TASK_BROWSER : self.task_browser.show
        self.register_user.assign_show_map(show_map)
        self.login_user.assign_show_map(show_map)
        self.user_info.assign_show_map(show_map)
        self.task_browser.assign_show_map(show_map)
        # this is the actual init because now inside the states the self.show_map is v
alid
        self.register_user.init_resources()
        self.login_user.init_resources()
        self.user_info.init_resources()
        self.task_browser.init_resources()
    def ___del___(self):
        self.db.close()
    def run(self):
```

src/gui.py Page 2

self.login\_user.show()
self.root.mainloop()