# Arch Linux on the Raspberry Pi

Ryan Matlock, Magzor Corp.

2014/05/05

## Abstract

Arch is a Linux distribution built around "The Arch Way,"[1] a philosophy of simplicity, code-correctness, user-centricity, openness, and freedom. Simplicity lends itself to a minimalist approach, which in turn leads to lower system resource overhead—exactly what one wants in an embedded system. Code-correctness means that the software is clean, correct, and simple, which implies a greater degree of comprehensibility and predictability, albeit sometimes accompanied with a steeper learning curve. User-centricity, not to be confused with user-friendliness, manifests itself as giving the user complete control over their system. Openness and freedom allow for greater control of the system; as Arch Linux's founder, Judd Vinet said, "[Arch Linux] is what *you* make it."

# Contents

---

[1] https://wiki.archlinux.org/index.php/The_Arch_Way

# 1  Overview

This guide aims to show the reader how to

1. install Arch Linux for Raspberry Pi onto a blank SD card,

2. expand the root partition to fill the disk,

3. add a new user,

4. modify user groups and grant superuser privileges,

5. establish wireless connectivity,

6. enable SSH access,

7. install GNU Compiler Collection (GCC),

8. install Python 3,

9. install WiringPi library,

10. install pigpio library,

11. install RPi.GPIO library,

12. install GNU Emacs 24+,

13. set up Emacs,

14. . . .

15. ??? install watchdog dæmon – reboots Pi on failure [http://pi.gadgetoid.com/article/who-watches-the-watcher](http://pi.gadgetoid.com/article/who-watches-the-watcher)

16. ??? install Lynx (text-based web browser)

# 2  Configuring Arch: The Hard Way

## 2.1  Installation

Download the Arch Linux disk image from [http://archlinuxarm.org/platforms/armv6/raspberry-pi](http://archlinuxarm.org/platforms/armv6/raspberry-pi) and follow the instructions. (Note: for Mac OS X[2], the

---

[2]The `bash` terminal is assumed to be used, so user input lines are started with `$`. Later, the `tty` prompt of Arch will start user input lines with `#`.

process is a little different[3]:

1. Plug in your SD card and run

```
$ diskutil list
```

to find the /dev/diskN node (e.g. disk3, which is the sdX in the linked instructions) on which it's located.

2. Unmount the drive by running

```
$ diskutil unmountDisk /dev/diskN
```

which will print

```
Unmount of all volumes on diskN was successful
```

if successful.

3. Write the Arch image by running

```
$ dd bs=1m if=/path/to/ArchLinuxARM*-rpi.img of
  ↪ =/dev/rdiskN
```

as root[4].

tested on identical Class 4, 4 GB SD cards:

```
matlocksmacbook:~ matlock$ sudo dd bs=1m if=~/
  ↪ Downloads/ArchLinuxARM-2014.04-rpi.img of=/
  ↪ dev/disk4
1870+0 records in
1870+0 records out
1960837120 bytes transferred in 452.680379 secs
  ↪ (4331615 bytes/sec)
```

```
matlocksmacbook:~ matlock$ sudo dd bs=1m if=~/
  ↪ Downloads/ArchLinuxARM-2014.04-rpi.img of=/
  ↪ dev/rdisk4
Password:
1870+0 records in
```

---

[3]source: http://www.embeddedarm.com/support/faqs.php?item=10

[4]Some guides recommend using of=/dev/diskN instead of of=/dev/diskN for increased security as rdiskN is the raw path, while diskN is a buffered device. (source: http://elinux.org/RPi_Easy_SD_Card_Setup#Flashing_the_SD_card_using_Mac_OS~X)

```
1870+0 records out
1960837120 bytes transferred in 394.117681 secs
    ↪ (4975258 bytes/sec)
```

## 2.2   Expanding the Root Partition

When you first boot up the Pi with a fresh Arch Linux installation, you will
eventually be greeted with something like

```
Arch Linux 3.10.35 -1 - ARCH (tty1)


alarmpi login:
```

for which the username and password are simply `root`.

1. Begin[5] by logging in as `root`.

2. Run

   ```
   # fdisk /dev/mmcblk0
   ```

   then enter `p` to display the partition table, which looks something like
   the following[6]:

   ```
   Disk /dev/mmcblk0: 3.7 GiB, 3965190144 bytes, 7744512
       ↪ sectors
   Units: sectors of 1 * 512 = 512 bytes
   Sector size (logical/physical): 512 bytes / 512 bytes
   I/O size (minimum/optimal): 512 bytes / 512 bytes
   Disklabel type: dos
   Disk identifier: 0x417ee54b


   Device          Boot    Start       End   Blocks Id System
   /dev/mmcblk0p1           2048    186367    92160   c W95 FAT32
       ↪  (LBA)
   /dev/mmcblkp2          186368   3667967  1740800   5 Extended
   /dev/mmcblkp5          188416   3667967  1739776  83 Linux
   ```

   The first partition is the boot partition. The second is an extended
   partition used to overcome the 4 primary partition limit. The third

---

[5]source: http://jan.alphadev.net/post/53594241659/growing-the-rpi-root-partition

[6]This example was performed on a 4 GB class 4 SanDisk SDHC card. With the exception of the `Disk` and `Disk identifier` entries, all the numbers are in agreement with those posted on the previously referenced Jan's Stuff "Growing the RPi root partition" blog entry (but that concerned a 32 GB disk, and the identifier is presumably unique).

partition—that is, partition 5—is contained within partition 2, and holds only 849.5 MiB[7], which is only a fraction of the disk's available space.

3. Now we must delete partition 2 by entering `d`, which will produce

```
Command (m for help): d
Partition number (1,2,5, default 5):
```

Enter 2, so we have

```
Partition number (1,2,5, default 5): 2

Partition 2 has been deleted.
```

If you enter `p`, you'll see that partition 5 is also gone because it was contained within partition 2.

4. We will now recreate the extended partition. Enter `n`, so we have

```
Command (m for help): n

Partition type:
  p   primary (1 primary, 0 extended, 3 free)
  e   extended
Select (default p):
```

enter `e`,

```
Select (default p): e
Partition number (2-4, default 2):
```

enter 2,

```
Partition number (2-4, default 2): 2
First sector (186368-7744511, default 186368):
```

press ⟨RETURN⟩ (or manually enter the number, make a mistake, and *ruin everything*),

```
Last sector, +sectors or +size{K,M,G,T,P}
    ↪ (186368-7744511, default 7744511):
```

---

[7]Note the distinction between MiB (1 mebibyte = $1024 \cdot 1024$ bytes) and MB (1 megabyte = $10^6$ bytes). I've tried to be consistent in this document, but mistakes have a way of creeping in, and it's ultimately not terribly important.

press ⟨RETURN⟩, which results in

```
Created a new partition 2 of type 'Extended' and
   ↪  a size of 3.6 GiB.
```

The extended partition has now been created, but this time it occupies the disk space not taken up by the boot partition.

5. The root partition will now be recreated following a similar process. For the sake of brevity, I won't detail each step but instead show it done all at once.

   Note: it is *absolutely critical* that the first block of the old and new partition match. The data within the old partition is still there; all we're doing is resizing the partition while keeping its data intact. Changing the starting block can (and almost assuredly will) render useless the data we want to preserve.

```
Command (m for help): n

Partition type:
   p   primary (1 primary, 1 extended, 2 free)
   l   logical (numbered from 5)
Select (default p): l

Adding logical partition 5
First sector (188416-7744511, default 188416):
```

⟨RETURN⟩

```
Last sector, +sectors or +size{K,M,G,T,P}
   ↪  (188416-7744511, default 7744511):
```

⟨RETURN⟩

```
Created a new partition 5 of type 'Linux' and of
   ↪  size 3.6 GiB.
```

Success!

6. Well, not so fast. We haven't actually written any of our changes yet, and we also want to make sure that we got the first block of our root partition right (see the note in step 5).

   To do that, enter p, and you should see the following:

```
Disk /dev/mmcblk0: 3.7 GiB, 3965190144 bytes, 7744512
   ↪ sectors
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disklabel type: dos
Disk identifier: 0x417ee54b

Device          Boot    Start       End   Blocks   Id System
/dev/mmcblk0p1           2048    186367    92160    c W95
   ↪ FAT32 (LBA)
/dev/mmcblk0p2         186368   7744511  3779072    5 Extended
/dev/mmcblk0p5         186416   7744511  3778048   83 Linux
```

Looks like everything checks out, so enter `w` to write the changes, which
will give the following message (and should not cause you to worry):

```
The partition table has been altered.
Calling ioctl() to re-read partition table.
Re-reading the partition table failed.: Device
   ↪ or resource busy

The kernel still uses the old table. The new
   ↪ table will be used at the next reboot or
   ↪ after you run partprobe(8) or kpartx(8).
```

7. Reboot the system:

```
# reboot
```

8. When the system restarts, log back in as `root`.

9. (optional) We will use `resize2fs` to actually resize the partitions, but
   first, let's run `df` and see what our filesystem looks like currently (dis-
   played in an abbreviated form):

```
# df
Filesystem        1K-blocks    Used  Available Use% Mounted on
/dev/root           1679632  441176    1135084  28% /
...
/dev/mmcblk0p1        91962   25328      66634  28% /boot
...
```

10. Now it's time to use `resize2fs`:

```
# resize2fs /dev/mmcblk0p5
resize2fs 1.42.9 (28-Dec-2013)
Filesystem at /dev/mmcblk0p5 is mounted on /; on
  ↪ -line resizing requited
old_desc_blocks = 1, new_desc_blocks = 1
The filesystem on /dev/mmcblk0p5 is now 944512
  ↪ blocks long.
```

11. (optional) Finally, we'll run a quick check with `df` to see how our filesystem looks now:

```
# df
Filesystem       1K-blocks    Used Available Use% Mounted on
/dev/root          3688608 442024   3065496  13% /
...
/dev/mmcblk0p1       91962   25328     66634  28% /boot
...
```

Now only 13% of the root partition is being used instead of 28%, which is a quick and easy sanity check.

## 2.3   Adding a User

It's generally considered unsafe to log in as root[8], so we will add a user[9]. To see what users currently exist, run

```
# cat /etc/passwd
```

which lists users in the format

```
account : password : UID : GID : GECOS : directory : shell
```

where `UID` is the user ID, `GID` is the primary group ID, `GECOS` is an optional field usually containing the full user name, `directory` is the path of `$HOME`, and `shell` is the user's command interpreter, which defaults to `/bin/sh`.

Adding a user is straightforward, and uses the following syntax:

---

[8]see http://www.slackbook.org/html/shell.html and http://lmgtfy.com/?q=why+shouldn%27t+you+log+in+as+root
[9]source: https://wiki.archlinux.org/index.php/users_and_groups

```
# useradd -m -g <initial group> -G <additional
↪ groups> -s <login shell> <username>
```

We'll worry about groups in the next section, so for now enter something like

```
# useradd -m -s /bin/bash matlock
```

although I generally suggest you pick a different username unless you're a relative or an Andy Griffith fan.

To change the password, enter

```
# passwd <username>
```

which in my case is set to **********. To force a user to change this password on their first login, run

```
chage -d 0 <username>
```

(Yes, that's right, it's chage, not change—remember that *chage* deals with password *age*, not password change.)

The GECOS field is edited by issuing the command

```
# chfn <username>
```

but doing so is not especially important.

If you're ever curious as to what user you are, it's a simple as

```
# whoami
```

which may be among the least arcane Linux commands.

To switch between users,

```
# logout
```

## 2.4   User Groups and sudo