

CSC230

Outline

2

- Memory Management

Dynamic memory in C

3

void * malloc(int num_bytes)

- Function defined in `stdlib.h`
- Allocates `num_bytes` of bytes and return a pointer to the allocated block of memory

free(void* ptr)

- Function defined in `stdlib.h`
- Return the memory pointed by `ptr`. The memory will be re-used by subsequent `malloc` calls

```
#include<stdio.h>
#include<stdlib.h>

int main()
{
    int *ptr;

    ptr = (int *)malloc(sizeof(int));

    *ptr = 25;
    free(ptr);
    return 0;
}
```

Both gcc and g++
can compile this
code

Dynamic memory in C++

4

new

- Allocates memory from heap
- Returns a **pointer** to the memory
 - `double *ptr = new double;`
 - `int *array = new int[24];`

delete


- Returns the memory to heap
- followed by the pointer to the data that you want to deallocate
 - `delete ptr;`
 - `delete [] ptr; // ptr is a pointer to an array`

Dynamic memory allocation

5

```
#include <iostream>
using namespace std;

int main(int argc, char *argv[]){
    int count;
    cin >> count;
    int *salary=new int[count];
    delete [] salary;
    return 0;
}
```



new allocates:
salary[0]
salary[1]
salary[2]
salary[3]
salary[4]

What to fill?

6

- `int*`
- `double*`
- `char*`
- `char**`
- `color*`




- `_____ ptr = new int;`
- `_____ ptr = new double;`
- `_____ ptr = new char[10];`
- `_____ ptr = new char*[10];`
- `_____ ptr = new color;`

Dynamic allocation

7

Dynamic Allocation

- Stored in heap
 - Pointer accesses it
- Exists until user 'delete' it
 - If it is not deleted, the data exists in heap even pointer dies



```
int area(int, int);
```

```
int main()  
{  
    int wid = 5, len = 4,  
        a; a = area(wid, len);  
}
```

```
int area(int w, int l)  
{  
    int* ans = new int;  
    *ans = w * l;  
    return *ans;  
}
```

Dynamic allocation

8


Dynamic Allocation

- Stored in heap
 - Pointer accesses it
- Exists until user 'delete' it
 - If it is not deleted, the data exists in heap even pointer dies

Stack Area of RAM



Heap Area of RAM



```
int area(int, int);
```

```
int main()  
{  
    int wid = 5, len = 4,  
        a; a = area(wid, len);  
}
```

```
int area(int w, int l)  
{  
    int* ans = new int;  
    *ans = w * l;  
    return *ans;  
}
```


Memory Leak
No pointer to it. Memory
space is wasted.

Dynamic allocation

9

Dynamic Allocation

- Stored in heap
 - Pointer accesses it
- Exists until user 'delete' it
 - If it is not deleted, the data exists in heap even pointer dies



```
int area(int, int);
```

```
int main()  
{  
    int wid = 5, len = 4,  
        a; a = area(wid, len);  
}
```

```
int area(int w, int l)  
{  
    int* ans = new int;  
    ans = &l;  
    return *ans;  
}
```




Dynamic allocation

10

Dynamic Allocation

- Stored in heap
 - Pointer accesses it
- Exists until user 'delete' it
 - If it is not deleted, the data exists in heap even pointer dies



```
int area(int, int);
```

```
int main()  
{  
    int wid = 5, len = 4,  
        a; a = area(wid, len);  
}
```

```
int area(int w, int l)  
{  
    int* ans = new int;  
    ans = &l;  
    return *ans;  
}
```

Memory Leak
No pointer to it.
Memory space is
wasted.

Object assignment

11

Assigning one struct or class object to another will cause an element by element copy of the source data.

```
#include<iostream>
using namespace std;
enum {CS, MATH, BIO};
struct student {
    char name[80];
    int id;
    int major;
};
int main(int argc, char *argv[])
{
    student s1;
    strncpy(s1.name, "Bill", 80);
    s1.id = 5;
    s1.major = CS;
    student s2 = s1;
    return 0;
}
```

s1	s2
Bill	Bill
5	5
CS	CS

Objects in C++

- **Objects** can be created as **local variables** just like any basic data types in C++.

C++:

```
ComplexType num1;
```

Java: Nothing equivalent – Objects cannot be in **stack**.

Objects in **Heap**



C++:

```
ComplexType *num1 = new ComplexType(...);
```

Java:

```
ComplexType num1 = new ComplexType(...);
```

Arrays



- Basic data types and classes are treated the same way in C++, unlike Java.

C++: `ComplexType colors[5];`

Java: *nothing equivalent.*