

Ch11練習

鄭安翔

ansel_cheng@hotmail.com

練習一

1. 修改 EmployeePractice 專案
2. 宣告 RegularStaff 介面 (正職員工)
 - ❑ 宣告 String[] 屬性 gifts
 - ❑ 宣告 getLuckDraw() : String 類別方法
 - ❑ 宣告 calcPerMultiplier() : double 預設方法
 - ❑ 宣告 getBonus() : double 抽象方法
3. 修改 Engineer 類別，實作 RegularStaff 介面
 - ❑ 實作 getBonus() 方法，傳回 salary * calcPerMultiplier()
4. 修改 Manager, 類別，實作 RegularStaff 介面
 - ❑ 宣告 baseBonus 類別屬性，數值為100,000
 - ❑ 實作 getBonus() 方法，傳回 baseBonus * calcPerMultiplier()

練習一

5. 修改 Director 類別


- ❑ 宣告 `baseBonus` 類別屬性，數值為500,000
- ❑ 實作 `getBonus()` 方法，傳回 `baseBonus * calcPerMultiplier()`

6. 修改 EmployeeTest 類別

- ❑ 列印所有正職員工的 `bonus` 及尾牙摸彩結果

7. 測試執行

練習一



RegularStaff 介面

```
RegularStaff.java ×
1 package com.example.domain;
2
3 import java.util.Random;
4
5 public interface RegularStaff {
6     String[] gifts = {"汽車", "機票", "電視", "住宿券", "Buffet餐券", "1000元禮券", "銘謝惠顧"};
7
8     public static String getLuckyDraw() {
9         int idx = new Random().nextInt(gifts.length);
10        return gifts[idx];
11    }
12
13    public default double calcPerMultiplier() {
14        return (int) (Math.random()*5+1)*0.5;
15    }
16
17    double getBonus();
18 }
19
```

Engineer 類別

```
Engineer.java ×
package com.example.domain;

public class Engineer extends Employee implements RegularStaff{
    private String[] skills;
    private int skillCount;

    public Engineer(String name, String ssn, double salary) {

    }

    public void addSkill(String skill) {
        if(skillCount<5)
            skills[skillCount++] = skill;
        else
            System.out.println("最多註冊五種技能,新增失敗!");
    }

    @Override
    public double getPay() {
        return this.getSalary() + skillCount*3000;
    }

    @Override
    public double getBonus() {
        return getSalary()*calcPerMultiplier();
    }

    @Override
    public String toString() {
        StringBuilder sb = new StringBuilder(super.toString());
        if(skillCount>0) {
            sb.append("技能:");
            for(int i=0; i<skillCount; i++)
                sb.append(" "+skills[i]);
            sb.append("\n");
        }
        return sb.toString();
    }
}
```

Manager 類別

```
Manager.java X
1 package com.example.domain;
2
3 import java.util.ArrayList;
4
5 public class Manager extends Employee implements RegularStaff {
6     private String deptName;
7     protected ArrayList employees;
8     private double baseBonus = 100000;
9
10    public Manager(String name, String ssn, double salary, String deptName) {
11
12    }
13
14    @Override
15    public double getPay() {
16        return this.getSalary() + employees.size() * 2000;
17    }
18
19    @Override
20    public double getBonus() {
21        return baseBonus * calcPerMultiplier();
22    }
23
24    public String getDeptName() {
25
26    }
27
28    public boolean addEmployee(Employee emp) {
29
30    }
31
32    public boolean removeEmployee(Employee emp) {
33
34    }
35
36    public String getStaffDetails() {
37
38    }
39
40    public String toString() {
41
42    }
43 }
```

Director 類別

```
Director.java ×
1 package com.example.domain;
2
3 public class Director extends Manager {
4     private double budget;
5     private double baseBonus = 500000;
6
7     public Director(String name, String ssn, double salary, String deptName, double budget) {
8         super(name, ssn, salary, deptName);
9         this.budget = budget;
10    }
11
12    @Override
13    public double getPay() {
14        return this.getSalary()+employees.size()*10000;
15    }
16
17    @Override
18    public double getBonus() {
19        return baseBonus*calcPerMultiplier();
20    }
21
22    public double getBudget() {
23        return budget;
24    }
25
26    @Override
27    public String toString() {
28        return super.toString() +
29            "管理預算: " + formatter.format(budget) + "\n";
30    }
31
32 }
33
```


EmployeeTest 類別

```
1 package com.example;
2
3 import com.example.domain.*;
4
5 public class EmployeeTest {
6
7     public static void main(String[] args) {
8         Employee[] emps = new Employee[5];
9         emps[0] = new Admin("Sean", "A123456789", 50000, 180);
10        emps[1] = new Admin("Amy", "B210987654", 70000, 120);
11        emps[2] = new Engineer("David", "C109876543", 80000);
12        emps[3] = new Manager("Louis", "D124680135", 100000, "TW Sales");
13        emps[4] = new Director("Nicole", "R202468135", 120000, "Global Sales", 1000000);
14
15        System.out.println("David 學會了Java, Android");
16        if(emps[2] instanceof Engineer) {
17            Engineer eng = (Engineer) emps[2];
18            eng.addSkill("Java");
19            eng.addSkill("Android");
20        }
21
22        System.out.println("部門分配.....");
23        if(emps[3] instanceof Manager) {
24            Manager m1 = (Manager) emps[3];
25            m1.addEmployee(emps[0]);
26            m1.addEmployee(emps[1]);
27            m1.addEmployee(emps[2]);
28        }
29
30        ((Manager) emps[4]).addEmployee(emps[3]);
31
32        for(int i=0; i<emps.length; i++) {
33            System.out.print(emps[i]);
34            System.out.println("本日薪資"+emps[i].getPay()+"元");
35            if(emps[i] instanceof RegularStaff) {
36                System.out.println("年終獎金"+((RegularStaff) emps[i]).getBonus()+"元");
37                System.out.println("尾牙摸彩得到"+RegularStaff.getLuckyDraw());
38            }
39        }
40    }
41 }
42
```

測試

```
Console ×
<terminated> EmployeeTest [Java Application]
David 學會了Java, Android
部門分配.....
=====員工資料=====
編號: 101
姓名: Sean
SSN: A123456789
薪水: $50,000.00元
本月薪資56250.0元
=====員工資料=====
編號: 102
姓名: Amy
SSN: B210987654
薪水: $70,000.00元
本月薪資52500.0元
=====員工資料=====
編號: 103
姓名: David
SSN: C109876543
薪水: $80,000.00元
技能: Java Android
本月薪資86000.0元
年終獎金80000.0元
尾牙摸彩得到住宿券
```

```
=====員工資料=====
編號: 104
姓名: Louis
SSN: D124680135
薪水: $100,000.00元
管理部門: TW Sales
Louis管理員工: Sean(101) Amy(102) David(103)
本月薪資106000.0元
年終獎金200000.0元
尾牙摸彩得到機票
=====員工資料=====
編號: 105
姓名: Nicole
SSN: R202468135
薪水: $120,000.00元
管理部門: Global Sales
Nicole管理員工: Louis(104)
管理預算: $1,000,000.00
本月薪資130000.0元
年終獎金1000000.0元
尾牙摸彩得到1000元禮券
```


練習二 實作 DAO 模式

1. 開啟 EmployeeDAO 專案
2. 測試、執行
 - ❑ 日期格式: Jul 9, 2013
 - ❑ EmployeeID: 0~9
3. 檢視Employee.java原始碼
 - ❑ `private static Employee[] employeeArray = new Employee[10];`
 - ❑ `save()/delete()/findById(int id)/getAllEmployees()` 方法
4. 建立com.example.dao.EmployeeDAO介面
 - ❑ `public void add(Employee emp);`
 - ❑ `public void update(Employee emp);`
 - ❑ `public void delete(int id);`
 - ❑ `public Employee findById(int id);`
 - ❑ `public Employee[] getAllEmployees();`

練習二 實作 DAO 模式

5. 建立`com.example.dao.EmployeeDAOMemoryImpl`類別
 - ❑ 實作`EmployeeDAO`介面
 - ❑ 將`Employee`類別中`employeeArray`陣列及操控陣列的方法改由`EmployeeDAO`介面的方法實作
 - ❑ 目前`EmployeeDAOMemoryImpl`中`add()`與`update()`邏輯相同
6. 建立`com.example.dao.EmployeeDAOFactory`類別
 - ❑ 提供 `EmployeeDAO createEmployeeDAO()` 工廠方法, 傳回`EmployeeDAOMemoryImpl`物件
7. 修改`EmployeeTestInteractive`類別
 - ❑ 建構`EmployeeDAOFactory`類別
 - ❑ 使用`EmployeeDAOFactory`類別取得`EmployeeDAO`物件
 - ❑ 修改`executeMenu(BufferedReader in)`, 加入`EmployeeDAO`傳入參數, 成為`executeMenu(BufferedReader in, EmployeeDAO dao)`
 - ❑ 原`emp`物件呼叫`save()/delete()/findById()/getAllEmployees()`方法, 以`dao`物件`add()/update()/delete()/findById()/getAllEmployees()`取代
8. 測試、執行

練習 實作 DAO 模式



EmployeeMemoryDAO 測試、執行

Console X

<terminated> EmployeeTestInteractive [Java Application] C:\Program Files\Java\jdk-17.0.4\

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

C

Enter int value for employee id:

1

Enter value for employee first name :

Sean

Enter value for employee last name :

Cheng

Enter value for employee birth date (MMM d, yyyy) :

Mar 21, 1974

Enter float value for employee salary :

75000.00

Successfully added Employee Record: 1

Created Employee ID: 1

Employee Name: Sean Cheng

Birth Date: 3月 21, 1974

Salary: \$75,000.00

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

R

Enter int value for employee id:

1

Employee ID: 1

Employee Name: Sean Cheng

Birth Date: 3月 21, 1974

Salary: \$75,000.00

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

U

Enter int value for employee id:

1

Modify the fields of Employee record: 1. Press return to accept current value.

Enter value for employee first name [Sean] :

Enter value for employee last name [Cheng] :

Enter value for employee birth date (MMM d, yyyy) [Mar 21, 1974] :

Enter float value for employee salary [\$75,000.00] :

80000

Successfully updated Employee Record: 1

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

L

Employee ID: 1

Employee Name: Sean Cheng

Birth Date: 3月 21, 1974

Salary: \$80,000.00

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

D

Enter int value for employee id:

1

Deleted Employee 1

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

Q




檢視employee.java原始碼

Employee.java

```
1 package com.example.model;
2
3 import java.text.NumberFormat;
4
5
6
7
8
9 public class Employee {
10
11     private int id;
12     private String firstName;
13     private String lastName;
14     private Date birthDate;
15     private float salary;
16     // not thread-safe
17     private static Employee[] employeeArray = new Employee[10];
18
19 public Employee() {}
20
21
22 public Employee(int id, String firstName, String last
23
24
25
26
27
28
29
30 public int getId() {}
31
32
33
34 public String getFirstName() {}
35
36
37
38 public String getLastName() {}
39
40
41
42 public Date getBirthDate() {}
43
44
45
46 public float getSalary() {}
47
48
49
50
51 public String toString() {}
```

```
57
58 // Save our Employee record
59 public void save() {
60     employeeArray[id] = this;
61 }
62
63 // Delete our employee record
64 public void delete() {
65     employeeArray[id] = null;
66 }
67
68 // Find an Employee record using this ID
69 public static Employee findById(int id) {
70     return employeeArray[id];
71 }
72
73 // Return an array of all of the Employee records
74 // We are using a collection List object to store the results
75 // This makes it easier to just add to the collection
76 public static Employee[] getAllEmployees() {
77     List<Employee> emps = new ArrayList<>();
78     // Iterate through the memory array and find Employee objects
79     for (Employee e : employeeArray) {
80         if (e != null) {
81             emps.add(e);
82         }
83     }
84     return emps.toArray(new Employee[0]);
85 }
86
87 }
```

新增com.example.dao.EmployeeDAO



```
EmployeeDAO.java ×
1 package com.example.dao;
2
3 import com.example.model.Employee;
4
5 public interface EmployeeDAO {
6     public void add(Employee emp);
7
8     public void update(Employee emp);
9
10    public void delete(int id);
11
12    public Employee findById(int id);
13
14    public Employee[] getAllEmployees();
15
16 }
17
```



新增 EmployeeDAOMemoryImpl

EmployeeDAOMemoryImpl.java ×

```
1 package com.example.dao;
2
3 import java.util.ArrayList;
4 import java.util.List;
5 import com.example.model.Employee;
6
7 public class EmployeeDAOMemoryImpl implements EmployeeDAO {
8     private Employee[] employeeArray = new Employee[10];
9
10    @Override
11    public void add(Employee emp) {
12        employeeArray[emp.getId()] = emp;
13    }
14
15    @Override
16    public void update(Employee emp) {
17        employeeArray[emp.getId()] = emp;
18    }
19
20    @Override
21    public void delete(int id) {
22        employeeArray[id] = null;
23    }
24
25    @Override
26    public Employee findById(int id) {
27        return employeeArray[id];
28    }
29
```

```
29
30    @Override
31    public Employee[] getAllEmployees() {
32        List<Employee> emps = new ArrayList<>();
33        // Iterate through the memory array and find Employee objects
34        for (Employee e : employeeArray) {
35            if (e != null) {
36                emps.add(e);
37            }
38        }
39        return emps.toArray(new Employee[0]);
40    }
41
42 }
43
```


新增 EmployeeDAOFactory



```
EmployeeDAOFactory.java ×
1 package com.example.dao;
2
3 public class EmployeeDAOFactory {
4
5     public EmployeeDAO createEmployeeDAO() {
6         return new EmployeeDAOMemoryImpl();
7     }
8
9 }
10
```

修改 EmployeeTestInteractive


```
9 public class EmployeeTestInteractive {
10
11     public static void main(String[] args) throws Exception {
12         //TODO create factory
13         //TODO create dao
14
15         boolean timeToQuit = false;
16         BufferedReader in = new BufferedReader(new InputStreamReader(System.in));
17         do {
18             timeToQuit = executeMenu(in);
19         } while (!timeToQuit);
20     }
21 }
```



```
9 public class EmployeeTestInteractive {
10
11     public static void main(String[] args) throws Exception {
12         EmployeeDAOFactory factory = new EmployeeDAOFactory();
13         EmployeeDAO dao = factory.createEmployeeDAO();
14
15         boolean timeToQuit = false;
16
17         BufferedReader in = new BufferedReader(new InputStreamReader(System.in));
18         do {
19             timeToQuit = executeMenu(in, dao);
20         } while (!timeToQuit);
21     }
22 }
```

修改 EmployeeTestInteractive


```
22 public static boolean executeMenu(BufferedReader in) throws IOException {  
23     Employee emp;  
24     String action;  
25     int id;  
26  
27     System.out.println("\n\n[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit: ");  
28     action = in.readLine();  
29     if ((action.length() == 0) || action.toUpperCase().charAt(0) == 'Q') {  
30         return true;  
31     }  
32 }
```



```
23 public static boolean executeMenu(BufferedReader in, EmployeeDAO dao) throws IOException {  
24     Employee emp;  
25     String action;  
26     int id;  
27  
28     System.out.println("\n\n[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit: ");  
29     action = in.readLine();  
30     if ((action.length() == 0) || action.toUpperCase().charAt(0) == 'Q') {  
31         return true;  
32     }  
33 }
```

修改 EmployeeTestInteractive


```
33     switch (action.toUpperCase().charAt(0)) {  
34         // Create a new employee record  
35         case 'C':  
36             emp = inputEmployee(in);  
37             emp.save();  
38             System.out.println("Successfully added Employee Record: " + emp.getId());  
39             System.out.println("\n\nCreated " + emp);  
40             break;  
41     }
```



```
34     switch (action.toUpperCase().charAt(0)) {  
35         // Create a new employee record  
36         case 'C':  
37             emp = inputEmployee(in);  
38             //emp.save();  
39             dao.add(emp);  
40             System.out.println("Successfully added Employee Record: " + emp.getId());  
41             System.out.println("\n\nCreated " + emp);  
42             break;  
    }
```

修改 EmployeeTestInteractive


```
42 // Display an employee record
43 case 'R':
44     System.out.println("Enter int value for employee id: ");
45     id = Integer.valueOf(in.readLine().trim());
46
47     // Find this Employee record
48     emp = Employee.findById(id);
49     if (emp != null) {
50         System.out.println(emp + "\n");
51     } else {
52         System.out.println("\n\nEmployee " + id + " not found");
53         break;
54     }
55
56     break;
```



```
44 // Display an employee record
45 case 'R':
46     System.out.println("Enter int value for employee id: ");
47     id = Integer.valueOf(in.readLine().trim());
48
49     // Find this Employee record
50     emp = dao.findById(id);
51     if (emp != null) {
52         System.out.println(emp + "\n");
53     } else {
54         System.out.println("\n\nEmployee " + id + " not found");
55         break;
56     }
57
58     break;
```

修改 EmployeeTestInteractive


```
58      // Update an existing employee record
59      case 'U':
60          System.out.println("Enter int value for employee id: ");
61          id = Integer.valueOf(in.readLine().trim());
62          // Find this Employee record
63          emp = null;
64          emp = Employee.findById(id);
65          if (emp == null) {
66              System.out.println("\n\nEmployee " + id + " not found");
67              break;
68          }
69          // Go through the record to allow changes
70
71          emp = inputEmployee(in, emp);
72          emp.save();
73          System.out.println("Successfully updated Employee Record: " + emp.getId());
74          break;
```



```
60      // Update an existing employee record
61      case 'U':
62          System.out.println("Enter int value for employee id: ");
63          id = Integer.valueOf(in.readLine().trim());
64          // Find this Employee record
65          emp = null;
66          emp = dao.findById(id);
67          if (emp == null) {
68              System.out.println("\n\nEmployee " + id + " not found");
69              break;
70          }
71          // Go through the record to allow changes
72
73          emp = inputEmployee(in, emp);
74          dao.update(emp);
75          System.out.println("Successfully updated Employee Record: " + emp.getId());
76          break;
```

修改 EmployeeTestInteractive


```
76 // Delete an employee record
77 case 'D':
78     System.out.println("Enter int value for employee id: ");
79     id = Integer.valueOf(in.readLine().trim());
80
81     // Find this Employee record
82     emp = null;
83     emp = Employee.findById(id);
84     if (emp == null) {
85         System.out.println("\n\nEmployee " + id + " not found");
86         break;
87     }
88     emp.delete();
89     System.out.println("Deleted Employee " + id);
90     break;
```



```
78 // Delete an employee record
79 case 'D':
80     System.out.println("Enter int value for employee id: ");
81     id = Integer.valueOf(in.readLine().trim());
82
83     // Find this Employee record
84     emp = null;
85     emp = dao.findById(id);
86     if (emp == null) {
87         System.out.println("\n\nEmployee " + id + " not found");
88         break;
89     }
90     dao.delete(id);
91     System.out.println("Deleted Employee " + id);
92     break;
```




修改 EmployeeTestInteractive

```
92         // Display a list (Read the records) of Employees
93         case 'L':
94             Employee[] allEmps = Employee.getAllEmployees();
95             for (Employee employee : allEmps) {
96                 System.out.println(employee + "\n");
97             }
98             break;
99     }
100
101     return false;
102 }
```



```
94         // Display a list (Read the records) of Employees
95         case 'L':
96             Employee[] allEmps = dao.getAllEmployees();
97             for (Employee employee : allEmps) {
98                 System.out.println(employee + "\n");
99             }
100             break;
101     }
102
103     return false;
104 }
```

測試、執行

Console  
<terminated> EmployeeTestInteractive [Java Application] C:\Program Files\

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

C

Enter int value for employee id:

2

Enter value for employee first name :

David

Enter value for employee last name :

Wang

Enter value for employee birth date (MMM d, yyyy) :

Dec 25, 1980

Enter float value for employee salary :

45000.00

Successfully added Employee Record: 2

Created Employee ID: 2

Employee Name: David Wang

Birth Date: 12月 25, 1980

Salary: \$45,000.00

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

R

Enter int value for employee id:

2

Employee ID: 2

Employee Name: David Wang

Birth Date: 12月 25, 1980

Salary: \$45,000.00

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

U

Enter int value for employee id:

2

Modify the fields of Employee record: 2. Press return to accept current value.

Enter value for employee first name [David] :

Enter value for employee last name [Wang] :

Enter value for employee birth date (MMM d, yyyy) [Dec 25, 1980] :

Enter float value for employee salary [\$45,000.00] :

50000.00

Successfully updated Employee Record: 2

[C]reate | [R]ead | [U]pdate | [D]elete | [L]ist | [Q]uit:

L

Employee ID: 2

Employee Name: David Wang

Birth Date: 12月 25, 1980

Salary: \$50,000.00