bakery-example.com

Passive security audit by Loïc Tellier · 2026-10-17 · overall grade = weakest area

High exposure: priority fixes are needed.

Overall	Website	Certificate & TLS	Email	Domain & DNS
F	**F**	**B**	**C**	**C-**
weakest area	15/100 · Mozilla HTTP Observatory scoring	70/100 · this project's scale (RFC 8996, 9325, certificate validity)	55/100 · this project's scale (RFC 7208, 7489, 6376, 8461)	45/100 · this project's scale (RFC 4033, 8659, 9083, 9162)

1 critical · 13 to improve · 7 compliant · 11 info

Priority actions

1. **Forgotten subdomains (CT logs)** (Critical)
   Delete these DNS records now, or recreate the resource at the provider before someone else does.
2. **Content-Security-Policy** (To improve)
   Define a CSP suited to the site, starting in "Report-Only" mode.
3. **Accepted TLS versions** (To improve)
   Disable TLS 1.0 and 1.1 and only allow TLS 1.2 and 1.3 (current browsers no longer use the old versions).
4. **HTTP to HTTPS redirect** (To improve)
   Set up a permanent (301) redirect from HTTP to HTTPS.
5. **HSTS** (To improve)
   Add "Strict-Transport-Security: max-age=31536000; includeSubDomains".
6. **Clickjacking protection** (To improve)
   Add "X-Frame-Options: SAMEORIGIN" or "frame-ancestors 'self'" in the CSP.
7. **SPF (authorized senders)** (To improve)
   Move to "~all", then "-all" once your senders are listed.
8. **DMARC (anti-spoofing policy)** (To improve)
   After a few weeks of report analysis, move to "quarantine", then "reject".
9. **DNSSEC** (To improve)
   Enable DNSSEC at your DNS host, then publish the DS record at your registrar (often a single option in their interface).
10. **HTTPS certificate** (To improve)
    Check that automatic renewal is in place.
11. **MTA-STS (encrypted email delivery)** (To improve)
    Publish an MTA-STS policy (in "testing" mode first), or enable it in your email service.
12. **CAA (allowed certificate authorities)** (To improve)
    Publish a CAA record naming the authority you use, e.g. 0 issue "letsencrypt.org".
13. **Transfer lock** (To improve)
    Turn on the transfer lock (often called "registrar lock") at your registrar.
14. **Software version disclosure** (To improve)
    Hide version numbers in the server configuration.

Website security

To improve — **Content-Security-Policy** — -25 pts

Missing: no limit on which scripts the page can load (protection against XSS injection).

> Define a CSP suited to the site, starting in "Report-Only" mode.

On Apache:

```
Header always set Content-Security-Policy-Report-Only "default-src 'self'; object-src 'none'; frame-ancestors 'self'"
```

Source: W3C Content Security Policy Level 3 — See also: ANSSI website guide PA-009 v2.0 (2021), R14, R15, R16

To improve — **HTTP to HTTPS redirect** — -20 pts

The site is still reachable over unencrypted HTTP, without a redirect.

> Set up a permanent (301) redirect from HTTP to HTTPS.

On Apache (.htaccess):

```
RewriteEngine On
RewriteCond %{HTTPS} off
RewriteRule ^ https://%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
```

Source: MDN TLS guide: HTTP redirection — See also: ANSSI website guide PA-009 v2.0 (2021), R1 · CNIL personal data security guide (2024): securing websites

To improve — **HSTS** — -20 pts

Missing: the browser is not required to use HTTPS on later visits.

> Add "Strict-Transport-Security: max-age=31536000; includeSubDomains".

On Apache:

```
Header always set Strict-Transport-Security "max-age=31536000; includeSubDomains"
```

Source: RFC 6797 (HTTP Strict Transport Security) — See also: ANSSI website guide PA-009 v2.0 (2021), R2

To improve — **Clickjacking protection** — -20 pts

The site can be displayed inside a frame on another site (clickjacking risk).

> Add "X-Frame-Options: SAMEORIGIN" or "frame-ancestors 'self'" in the CSP.

On Apache:

```
Header always set X-Frame-Options "SAMEORIGIN"
```

Source: RFC 7034 (X-Frame-Options) — See also: ANSSI website guide PA-009 v2.0 (2021), R17, R18

To improve — **Software version disclosure** — not scored

The server announces its versions (Server: Apache/2.4.41 (Ubuntu); X-Powered-By: PHP/7.4.3), which helps an attacker target known vulnerabilities.

> Hide version numbers in the server configuration.

On Apache (main configuration; for PHP, expose_php = Off in php.ini):

```
ServerTokens Prod
ServerSignature Off
```

Source: OWASP Secure Headers Project

Info — **Cookies** — 0 pts

No cookies set on the home page.

Source: RFC 6265 (HTTP cookies) and MDN cookie guide — See also: ANSSI website guide PA-009 v2.0 (2021), §5.5.3 · CNIL personal data security guide (2024): securing websites

Info	**Referrer-Policy** Missing: browsers apply their default policy (strict-origin-when-cross-origin in recent versions). > Add "Referrer-Policy: strict-origin-when-cross-origin" (worth bonus points). **On Apache:** `Header always set Referrer-Policy "strict-origin-when-cross-origin"` Source: W3C Referrer Policy — See also: ANSSI website guide PA-009 v2.0 (2021), §5.4	0 pts
Info	**Subresource Integrity** No scripts on the home page. Source: W3C Subresource Integrity — See also: ANSSI website guide PA-009 v2.0 (2021), R11, R12	0 pts
Info	**Cross-Origin-Resource-Policy** Not set (optional; earns bonus points when set). Source: MDN: Cross-Origin-Resource-Policy	0 pts
Info	**Cross-Origin-Opener-Policy** Not set (optional; earns bonus points when set). Source: MDN: Cross-Origin-Opener-Policy	0 pts
Info	**Cross-Origin-Embedder-Policy** Not set (optional; earns bonus points when set). Source: MDN: Cross-Origin-Embedder-Policy	0 pts
Info	**Permissions-Policy** Missing: no restriction on access to browser features (camera, microphone, geolocation). > Add for example "Permissions-Policy: camera=(), microphone=(), geolocation=()". **On Apache:** `Header always set Permissions-Policy "camera=(), microphone=(), geolocation=()"` Source: W3C Permissions Policy	not scored
Info	**security.txt (vulnerability reporting)** No security.txt file: someone who finds a vulnerability on the site does not know whom to warn. > Publish /.well-known/security.txt with at least a Contact and an Expires field (for example generated on securitytxt.org). Source: RFC 9116 (security.txt)	not scored
Compliant	**X-Content-Type-Options** Present (nosniff). Source: WHATWG Fetch: X-Content-Type-Options — See also: ANSSI website guide PA-009 v2.0 (2021), R6	0 pts

Certificate & TLS

To improve	**Accepted TLS versions** The server still accepts old versions (TLS 1.0, TLS 1.1), deprecated since 2021: an attacker who can force an old version weakens the encryption. Accepted: TLS 1.0, TLS 1.1, TLS 1.2, TLS 1.3. > Disable TLS 1.0 and 1.1 and only allow TLS 1.2 and 1.3 (current browsers no longer use the old versions). **On Apache:** `SSLProtocol -all +TLSv1.2 +TLSv1.3` Source: RFC 8996 (deprecating TLS 1.0 and 1.1) — See also: ANSSI TLS guide v1.2 (2020), R3, R4 · ANSSI website guide PA-009 v2.0 (2021), R1 · CNIL personal data security guide (2024): securing websites	-20 pts
To improve	**HTTPS certificate** The certificate expires in 20 days (2026-11-07). > Check that automatic renewal is in place. Source: MDN TLS guide — See also: ANSSI TLS guide v1.2 (2020), R8 · CNIL personal data security guide (2024): securing websites	-10 pts
Compliant	**TLS protocol version** Connection negotiated with TLSv1.3. Source: RFC 8996 (deprecating TLS 1.0 and 1.1) — See also: ANSSI TLS guide v1.2 (2020), R3, R4 · ANSSI website guide PA-009 v2.0 (2021), R1 · CNIL personal data security guide (2024): securing websites	0 pts
Compliant	**Weak cipher suites** No broken cipher suite accepted (RC4, 3DES, export, no encryption or no authentication). Source: RFC 9325 (recommendations for the secure use of TLS)	0 pts
Compliant	**Forward secrecy** Every accepted key exchange has forward secrecy: a stolen private key would not decrypt recorded traffic. Source: RFC 9325 (recommendations for the secure use of TLS)	0 pts
Compliant	**Certificate key** Key strong enough (RSA 2048 bits). Source: RFC 9325 (recommendations for the secure use of TLS)	0 pts

Email protection

To improve	**SPF (authorized senders)** The SPF record ends with "?all" (neutral): it provides almost no protection. > Move to "~all", then "-all" once your senders are listed. **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 7208 (SPF) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), R44	-20 pts
To improve	**DMARC (anti-spoofing policy)** "none" policy: DMARC monitors but blocks nothing. > After a few weeks of report analysis, move to "quarantine", then "reject". **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 7489 (DMARC) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), R48+	-20 pts
To improve	**MTA-STS (encrypted email delivery)** Not set: other mail servers may deliver your incoming email without encryption if an attacker tampers with the connection. > Publish an MTA-STS policy (in "testing" mode first), or enable it in your email service. **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 8461 (SMTP MTA Strict Transport Security) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), §5.3	-5 pts
Info	**DMARC: reports** No report address (rua): you cannot see who sends email on your behalf. > Add "rua=mailto:..." to receive aggregate reports. **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 7489 (DMARC) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), R48+	0 pts
Info	**DKIM (email signing)** No DKIM key found among the common selectors tested (16). This is not necessarily a problem: the selector may have another name. > Check in your email service (Google Workspace, Microsoft 365...) that DKIM signing is enabled. Source: RFC 6376 (DKIM) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), R46+	not scored
Info	**TLS reporting (TLS-RPT)** Not set: you are not told when other servers fail to deliver your mail securely. > Publish a _smtp._tls TXT record, e.g. "v=TLSRPTv1; rua=mailto:tls-reports@your-domain". **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 8460 (SMTP TLS Reporting) — See also: ANSSI Internet gateway guide PA-066 v3.0 (2020), §5.3	not scored
Compliant	**Mail servers (MX)** 2 server(s): mx1.hosting-example.com, mx2.hosting-example.com Source: RFC 7505 (null MX for domains that receive no email)	0 pts

Domain & DNS

Critical	**Forgotten subdomains (CT logs)** 4 subdomain(s) found in Certificate Transparency logs (crt.sh), 3 still in use. These subdomains point to a resource that no longer exists at a provider where anyone can create it again, and then publish content on your domain (subdomain takeover): old-shop.bakery-example.com bakery-shop-2019.azurewebsites.net (Azure App Service). > Delete these DNS records now, or recreate the resource at the provider before someone else does. Source: RFC 9162 (Certificate Transparency) — See also: ANSSI website guide PA-009 v2.0 (2021), R3	-30 pts
To improve	**DNSSEC** Not enabled for bakery-example.com: DNS answers are not signed, so a resolver cannot detect forged answers (redirecting visitors or emails to another server). > Enable DNSSEC at your DNS host, then publish the DS record at your registrar (often a single option in their interface). **On OVHcloud:** turn on DNSSEC in the settings of the DNS zone. Source: RFC 4033 (DNS Security Introduction and Requirements) — See also: ANSSI domain name guide BP-038 v1.3 (2017), R4+ · ANSSI Internet gateway guide PA-066 v3.0 (2020), R50+	-15 pts
To improve	**CAA (allowed certificate authorities)** No CAA record: any certificate authority may issue a certificate for this domain. > Publish a CAA record naming the authority you use, e.g. 0 issue "letsencrypt.org". **On OVHcloud:** add or edit the record in the DNS zone of the domain. Source: RFC 8659 (DNS Certification Authority Authorization)	-5 pts
To improve	**Transfer lock** The domain is not locked against transfers: with a stolen access to your registrar account, it is easier to move it elsewhere. > Turn on the transfer lock (often called "registrar lock") at your registrar. Source: RFC 5731 (domain status, including transfer prohibited) — See also: ANSSI domain name guide BP-038 v1.3 (2017), R1, R3+	-5 pts
Compliant	**Domain expiry date** The domain bakery-example.com is registered until 2027-05-05 (199 days). Registrar: Example Registrar. Source: RFC 9083 (RDAP, registration data of domain names) — See also: ANSSI domain name guide BP-038 v1.3 (2017), §4.10	0 pts

Method. Passive audit carried out by Loïc Tellier using public information only: DNS records, the certificate presented by the server and the home page. No intrusion testing was performed. Grades. The website grade follows the Mozilla HTTP Observatory scoring (penalties and bonuses per header). The certificate, email and DNS grades use this project's own scale, based on the standards cited under each item. The overall grade is the lowest of the four. Limits. This audit does not cover the site's applications, workstations or user accounts. It gives an overview of the exposure visible from the Internet on the date shown. The ANSSI recommendations cited show what each check relates to; meeting them fully also depends on settings that cannot be seen from outside, so this report is not a certificate of compliance.