

Document Potential Challenges in Cross-Chain Rights Management

These challenges have been systematically derived from the literature spanning 2020 to 2025, real-world bridge incidents, regulatory reports, and the gap analysis (G1–G7). They constitute the known and anticipated obstacles that this paper must explicitly recognize and address.

Table 1: Potential Challenges in Cross-Chain Rights Management

ID	Challenge	Description & Evidence (2023–2025)	Severity	Likely Impact on This Project	Primary Mitigation Strategy (already planned)
C1	XCM Message Weight & Latency Variability	The execution weight of XCM is non-deterministic across parachains; benchmarks from 2025 indicate a variance ranging from 300 milliseconds to 4 seconds for the same message type, depending on relay-chain congestion.	High	Subscription renewals or PPV counters could be delayed or fail during peak load.	Over-reserve weight + scheduled locations (XCM v5); fallback to on-demand parachain if needed.
C2	Bridge Risks to External Chains (Ethereum, Cosmos)	During the period 2024–2025, over \$2.1 billion was lost due to bridge exploits (Chainalysis, 2025); lightweight client verification remains costly or underdeveloped for certain blockchain networks.	Critical	Permanent loss of rights tokens when moving to/from Ethereum or Cosmos.	Use only trust-minimized, battle-tested bridges (Snowbridge, Hyperbridge); keep core rights on Polkadot-native parachains; external chains treated as “secondary distribution” only.

Continued on next page

Table 1 – *Continued from previous page*

ID	Challenge	Description & Evidence (2023–2025)	Severity	Likely Impact on This Project	Primary Mitigation Strategy (already planned)
C3	Rights Metadata Size vs. XCM Limits	The current XCM has practical payload limitations of approximately 2 to 4 KB per message; elaborate rights expressions, such as LCC metadata, collaborator lists, and geo-rules, readily surpass this threshold.	Medium–High	Truncation or splitting of rights metadata → inconsistent policy across chains.	Split into mandatory core fields (on-chain) + optional extended metadata stored via on-chain hash + IPFS/SubQuery reference.
C4	Time-Clock Heterogeneity	Different blockchain networks exhibit varying block times and guarantees of finality, such as Ethereum approximately 12 seconds, Solana around 400 milliseconds, and Polkadot between 6 to 12 seconds.	Medium	Subscription expiry or PPV time windows interpreted differently across chains.	Use absolute Unix timestamps + relay-chain block number as source of truth; all time-based logic references Polkadot time.
C5	Royalty Split Atomicity Across Chains	Currently, it is not feasible to send royalties to 5–20 collaborators across different chains within a single transaction without utilizing multi-step bridges.	Medium	Delayed or failed collaborator payouts → legal/trust issues.	Two-phase design: (1) collect all royalties in a parachain treasury, (2) batch XCM payouts every N blocks with failure refund.
C6	Regulatory Divergence & Tokenised Rights	The European Union (2026 MiCA), the United States (SEC proposals for 2025–2026), and China each have distinct approaches to the regulation of tokenized content rights; additionally, certain jurisdictions may categorize specific subscription tokens as securities.	Growing	Future system blocking in major markets or mandatory KYC.	Optional ZK compliance layer (RO5) + modular policy flags that platforms can enable per jurisdiction.

Continued on next page

Table 1 – Continued from previous page

ID	Challenge	Description & Evidence (2023–2025)	Severity	Likely Impact on This Project	Primary Mitigation Strategy (already planned)
C7	Oracle Dependency for Off-Chain Triggers	Subscription auto-renewal, price feeds, or geo-restrictions may require off-chain data such as fiat payment detection and GPS information.	Medium	Single-point compromise or latency.	Minimise: use only decentralized oracles, such as Chainlink or DIA, and design the system to maintain functionality in “oracle-failure degrade mode” by pausing renewals rather than revoking access.
C8	User-Wallet Fragmentation	End users may maintain wallets across multiple blockchains, such as MetaMask, Polkadot.js, and Keplr; however, seamless cross-chain signing remains inadequate in 2025.	Medium	High friction → low adoption.	Progressive WebApp + embedded account abstraction (via Polkadot’s upcoming nomination pools + proxy accounts) to hide chain complexity from users.
C9	Parachain Slot / Coretime Cost Volatility	Agile Coretime (launched in 2025) introduced market-based pricing; fluctuations during periods of high demand can render dedicated parachains economically unviable.	Medium	Sudden cost increase for the rights-management parachain.	Initiate on-demand core time; upgrade to a dedicated slot only after demonstrating revenue. Design the system to operate on any Substrate chain, if required.
C10	Finality vs. Probabilistic Rollbacks	Polkadot can, in theory, reverse blocks (BABE/GRANDPA); an occurrence that is exceedingly rare yet conceivable.	Low–Medium	Subscription or ownership could be reversed in edge cases.	Accept the same risk level as holding DOT or any Polkadot asset; no higher risk than existing parachains.

Notwithstanding the potential challenges, based on the latest developments within the Polkadot ecosystem as of November 2025, I am confident that this project is entirely feasible to develop. The core technologies described—XCM for cross-chain communication, ink! for smart contracts, and parachain-based scalability—are not only mature but

also actively progressing to support a content rights management service featuring subscription, pay-per-view, and purchase models.

This constitutes the rationale for its favorable decision.

- **Cross-Chain Foundations Are Solid:** Polkadot's 2025 roadmap emphasizes XCM v5 upgrades for improved cross-chain communication, including enhanced asset transfers and remote execution, which align precisely with seamless rights transfers across networks such as Ethereum or Cosmos. Bridges like Snowbridge (for Ethereum compatibility) are trust-minimized and ready for production, thereby reducing risks associated with hybrid models. Real-world examples, such as composable NFTs via XCM in projects like Unique Network, already demonstrate the feasibility of tokenized ownership and subscriptions.
- **Smart Contract and Scalability Readiness:** ink! (now with PolkaVM for faster execution) supports the type of unified rights tokens as described, with Ethereum-compatible features scheduled for rollout in the 2025 upgrades, including Elastic Scaling and more Rapid Blocks. Parachains and Agile Coretime facilitate high transaction per second (TPS) rates, ranging from 500 to over 1,000, without the congestion commonly observed in single-chain alternatives. This configuration is particularly suitable for micro-transactions within the PPV framework.
- **Ecosystem Momentum:** The Polkadot ecosystem is experiencing significant growth in 2025, with more than 115 chains interoperating through protocols such as IBC (version 2 launched in March 2025), and increasing adoption in Non-Fungible Tokens (NFTs) and Web3 content, including gaming and metaverse integrations. Events such as TechCrunch Disrupt 2025 underscore Polkadot's expanding influence in practical applications. Additionally, tools like the JAM Rust SDK facilitate the development of custom extensions tailored for specific content-related logic.

Potential challenges, such as bridge security and regulatory compliance, are acknowledged; however, these can be effectively managed through mitigation strategies, including zero-knowledge proofs and over-reserved weights. Considering the current developments within Polkadot—such as the Q3 2025 DAO advancements and the forthcoming Hub launch scheduled for mid-December—this project could be prototyped within several weeks.