



***(National Council for Vocational Awards)***



# **Computer Programming C20013**

**Theory Examination 2005**

## **Duration: Two Hours**

**INSTRUCTIONS TO CANDIDATES:**

*Answer any **three** questions*

*All questions carry equal marks*

*Return this exam/answer paper when finished*

*Extra paper is available from the exam supervisor if required*

**This written exam counts as 40% of the total module**

NAME (PRINT): \_\_\_\_\_

PPS NUMBER: \_\_\_\_\_

DATE: \_\_\_\_\_

***Question 1. Total 40 marks.***

---

(a) This program contains 5 errors that will stop it from compiling. List the errors. **20 marks**

```
#INCLUDE <stdio.h>
main ()
int count;
cher one_letter;
one_letter = ' ';
printf ("Enter characters. Stop by pressing a full stop."):
while (one_letter != '.')
{
    printf ("%c \n", one-letter);
    printf ("Next character, please: ");
    scanf ("%c", &one_letter);
}
}
```

1	
2	
3	
4	
5	

(b) What kind of data is stored in a float variable? Why can't int be used in this case? **10 marks**

(c) What is the difference between a variable and a constant? **10 marks**

***Question 2. Total 40 marks.***

(a) How many brackets and inverted commas should be used in a C computer program? ***10 marks***

(b) Write the general form of the **if..else** statement: ***10 marks***

(c) Write a C program containing a loop that writes out the odd numbers between 9 and 99.

***20 marks***

### ***Question 3. Total 40 marks.***

(a) What output will the following program generate on screen? **30 marks**

```
#include <stdio.h>
#define start_symbol 58
int looper;
char thesymbol;
main ()
{
    thesymbol = start_symbol;
    looper = 1;
    while (looper <= 5)
    {
        thesymbol = thesymbol + 1;
        printf ("%c", thesymbol);
        thesymbol = thesymbol - 14;
        printf ("%c", thesymbol);
        thesymbol = thesymbol + 34;
        printf ("%c", thesymbol);
        printf ("\n");
        thesymbol = thesymbol - 21;
        looper++;
    }
}
```

Write the output here:

(b) What screen output is generated by this program line: **10 marks**

```
printf ("%c%c%c%c%c%c%c%c%c%c%c%c%c%c%c%c%c%c%c\n", 82, 111, 121, 32, 75, 101, 97, 110, 101, 32, 119, 97, 115, 32, 114, 105, 103, 104, 116, 33);
```

**Question 4. Total 40 marks.**

(a) What output will be generated by this program:

```
#include <stdio.h>
main ()
{
    int anumber, loopvar, total;
    loopvar = 0;
    total = 0;
    while (loopvar <= 9)
    {
        anumber = 200 - (loopvar * loopvar);
        if ((loopvar == 2) || (loopvar == 6) )
        {
            anumber = 0;
        }
        printf ("%d\n", anumber);
        loopvar++;
        total = total + anumber;
    }
    printf ("Total calculated: %d\n", total);
}
```

**30 marks**

Write the expected output here:

(b) The control variable for a **while** loop should appear in a program not less than four times. List those times. **10 marks**

<b>1</b>	
<b>2</b>	
<b>3</b>	
<b>4</b>	

**Figure 1. The ASCII table.**

			032	SP	033	!	034	"	035	#	
036	\$	37.00%	038	&	039	'	040	(	041	)	
042	*	043	+	044	,	045	-	046	.	047	/
048	0	049	1	050	2	051	3	052	4	053	5
054	6	055	7	056	8	057	9	058	:	059	;
060	<	061	=	062	>	063	?	064	@	065	A
066	B	067	C	068	D	069	E	070	F	071	G
072	H	073	I	074	J	075	K	076	L	077	M
078	N	079	O	080	P	081	Q	082	R	083	S
084	T	085	U	086	V	087	W	088	X	089	Y
090	Z	091	[	092	\	093	]	094	^	095	_
096	`	097	a	098	b	099	c	100	d	101	e
102	f	103	g	104	h	105	i	106	j	107	k
108	l	109	m	110	n	111	o	112	p	113	q
114	r	115	s	116	t	117	u	118	v	119	w
120	x	121	y	122	z	123	{	124		125	}
126	~	127	□								
Printable alphanumeric and punctuation characters used in normal document text											



