

## NAME

CPANPLUS::Shell::Default

## SYNOPSIS

```
### loading the shell:
$ cpanp                # run 'cpanp' from the command line
$ perl -MCPANPLUS -eshell  # load the shell from the command line

use CPANPLUS::Shell qw[Default];      # load this shell via the API
                                       # always done via

CPANPLUS::Shell

my $ui = CPANPLUS::Shell->new;
$ui->shell;                            # run the shell
$ui->dispatch_on_input( input => 'x');  # update the source using the
                                       # dispatch method

### when in the shell:
### Note that all commands can also take options.
### Look at their underlying CPANPLUS::Backend methods to see
### what options those are.
cpanp> h                # show help messages
cpanp> ?                # show help messages

cpanp> m Acme           # find acme modules, allows regexes
cpanp> a KANE           # find modules by kane, allows regexes
cpanp> f Acme::Foo      # get a list of all releases of Acme::Foo

cpanp> i Acme::Foo      # install Acme::Foo
cpanp> i Acme-Foo-1.3   # install version 1.3 of Acme::Foo
cpanp> i <URI>          # install from URI, like ftp://foo.com/X.tgz
cpanp> i 1 3..5         # install search results 1, 3, 4 and 5
cpanp> i *              # install all search results
cpanp> a KANE; i *;     # find modules by kane, install all results
cpanp> t Acme::Foo      # test Acme::Foo, without installing it
cpanp> u Acme::Foo      # uninstall Acme::Foo
cpanp> d Acme::Foo      # download Acme::Foo
cpanp> z Acme::Foo      # download & extract Acme::Foo, then open a
                        # shell in the extraction directory

cpanp> c Acme::Foo      # get a list of test results for Acme::Foo
cpanp> l Acme::Foo      # view details about the Acme::Foo package
cpanp> r Acme::Foo      # view Acme::Foo's README file
cpanp> o                # get a list of all installed modules that
                        # are out of date
cpanp> o 1..3           # list uptodateness from a previous search

cpanp> s conf           # show config settings
cpanp> s conf md5 1     # enable md5 checks
cpanp> s program        # show program settings
cpanp> s edit           # edit config file
cpanp> s reconfigure    # go through initial configuration again
cpanp> s selfupdate     # update your CPANPLUS install
```

```
cpanp> s save                # save config to disk
cpanp> s mirrors             # show currently selected mirrors

cpanp> ! [PERL CODE]        # execute the following perl code

cpanp> b                    # create an autobundle for this computers
                           # perl installation
cpanp> x                    # reload index files (purges cache)
cpanp> x --update_source    # reload index files, get fresh source files
cpanp> p [FILE]             # print error stack (to a file)
cpanp> v                    # show the banner
cpanp> w                    # show last search results again

cpanp> q                    # quit the shell

cpanp> /plugins              # list avialable plugins
cpanp> /? PLUGIN            # list help test of <PLUGIN>

### common options:
cpanp> i ... --skiptest    # skip tests
cpanp> i ... --force      # force all operations
cpanp> i ... --verbose    # run in verbose mode
```

## DESCRIPTION

This module provides the default user interface to CPANPLUS. You can start it via the `cpanp` binary, or as detailed in the *SYNOPSIS*.

## BUG REPORTS

Please report bugs or other issues to <bug-cpanplus@rt.cpan.org>.

## AUTHOR

This module by Jos Boumans <kane@cpan.org>.

## COPYRIGHT

The CPAN++ interface (of which this module is a part of) is copyright (c) 2001 - 2007, Jos Boumans <kane@cpan.org>. All rights reserved.

This library is free software; you may redistribute and/or modify it under the same terms as Perl itself.

## SEE ALSO

*CPANPLUS::Shell::Classic*, *CPANPLUS::Shell*, *cpanp*