

Aggregations with pandas and numpy

About the Data

In this notebook, we will be working with 2 data sets:

- Facebook's stock price throughout 2018 (obtained using the `stock_analysis` package).
- daily weather data for NYC from the [National Centers for Environmental Information \(NCEI\) API](#).

Note: The NCEI is part of the National Oceanic and Atmospheric Administration (NOAA) and, as you can see from the URL for the API, this resource was created when the NCEI was called the NCDC. Should the URL for this resource change in the future, you can search for the NCEI weather API to find the updated one.

Background on the weather data

Data meanings:

- `AWND` : average wind speed
- `PRCP` : precipitation in millimeters
- `SNOW` : snowfall in millimeters
- `SNWD` : snow depth in millimeters
- `TMAX` : maximum daily temperature in Celsius
- `TMIN` : minimum daily temperature in Celsius

Setup

```
In [1]: import numpy as np
import pandas as pd

weather = pd.read_csv('data/weather_by_station.csv', index_col='date', parse_dates=True)
weather.head()
```

Out [1]:

	datatype	station	value	station_name
	date			
2018-01-01	PRCP	GHCND:US1CTFR0039	0.0	STAMFORD 4.2 S, CT US
2018-01-01	PRCP	GHCND:US1NJBG0015	0.0	NORTH ARLINGTON 0.7 WNW, NJ US
2018-01-01	SNOW	GHCND:US1NJBG0015	0.0	NORTH ARLINGTON 0.7 WNW, NJ US
2018-01-01	PRCP	GHCND:US1NJBG0017	0.0	GLEN ROCK 0.7 SSE, NJ US
2018-01-01	SNOW	GHCND:US1NJBG0017	0.0	GLEN ROCK 0.7 SSE, NJ US

```
In [2]: fb = pd.read_csv('data/fb_2018.csv', index_col='date', parse_dates=True).assign(
        trading_volume=lambda x: pd.cut(x.volume, bins=3, labels=['low', 'med', 'high']))
        fb.head()
```

Out [2]:

	open	high	low	close	volume	trading_volume
	date					
2018-01-02	177.68	181.58	177.5500	181.42	18151903	low
2018-01-03	181.88	184.78	181.3300	184.67	16886563	low
2018-01-04	184.90	186.21	184.0996	184.33	13880896	low
2018-01-05	185.59	186.90	184.9300	186.85	13574535	low
2018-01-08	187.20	188.90	186.3300	188.28	17994726	low

Before we dive into any calculations, let's make sure pandas won't put things in scientific notation. We will modify how floats are formatted for displaying. The format we will apply is `.2f` , which will provide the float with 2 digits after the decimal point:

```
In [3]: pd.set_option('display.float_format', lambda x: '%.2f' % x)
```

Summarizing DataFrames

We learned about `agg()` in the **dataframe operations notebook** when we learned about window calculations; however, we can call this on the dataframe directly to aggregate its contents into a single series:

```
In [4]: fb.agg({
        'open': np.mean,
        'high': np.max,
        'low': np.min,
        'close': np.mean,
        'volume': np.sum
    })
```

```
Out[4]: open          171.45
        high          218.62
        low           123.02
        close         171.51
        volume    6949682394.00
        dtype: float64
```

We can use this to find the total snowfall and precipitation recorded in Central Park in 2018:

```
In [5]: weather.query(
        'station == "GHCND:USW00094728"')
        .pivot(columns='datatype', values='value')[['SNOW', 'PRCP']].sum()
```

```
Out[5]: datatype
        SNOW    1007.00
        PRCP    1665.30
        dtype: float64
```

This is equivalent to passing 'sum' to agg() :

```
In [6]: weather.query(
        'station == "GHCND:USW00094728"')
        .pivot(columns='datatype', values='value')[['SNOW', 'PRCP']].agg('sum')
```

```
Out[6]: datatype
        SNOW    1007.00
        PRCP    1665.30
        dtype: float64
```

Note that we aren't limited to providing a single aggregation per column. We can pass a list, and we will get a dataframe back instead of a series. nan values are placed where we don't have a calculation result to display:

```
In [7]: fb.agg({
        'open': 'mean',
        'high': ['min', 'max'],
        'low': ['min', 'max'],
```

```
'close': 'mean'  
})
```

```
Out[7]:
```

	open	high	low	close
max	nan	218.62	214.27	nan
mean	171.45	nan	nan	171.51
min	nan	129.74	123.02	nan

Using `groupby()`

Often we won't want to aggregate on the entire dataframe, but on groups within it. For this purpose, we can run `groupby()` before the aggregation. If we group by the `trading_volume` column, we will get a row for each of the values it takes on:

```
In [8]: fb.groupby('trading_volume').mean()
```

```
Out[8]:
```

	open	high	low	close	volume
trading_volume					
low	171.36	173.46	169.31	171.43	24547207.71
med	175.82	179.42	172.11	175.14	79072559.12
high	167.73	170.48	161.57	168.16	141924023.33

After we run the `groupby()`, we can still select columns for aggregation:

```
In [9]: fb.groupby('trading_volume')['close'].agg(['min', 'max', 'mean'])
```

```
Out[9]:
```

	min	max	mean
trading_volume			
low	124.06	214.67	171.43
med	152.22	217.50	175.14
high	160.06	176.26	168.16

We can still provide a dictionary specifying the aggregations to perform, but passing a list for a column will result in a hierarchical index for the columns:

```
In [10]: fb_agg = fb.groupby('trading_volume').agg({
    'open': 'mean',
    'high': ['min', 'max'],
    'low': ['min', 'max'],
    'close': 'mean'
})
fb_agg
```

Out[10]:

	open	high		low		close
	mean	min	max	min	max	mean
trading_volume						
low	171.36	129.74	216.20	123.02	212.60	171.43
med	175.82	162.85	218.62	150.75	214.27	175.14
high	167.73	161.10	180.13	149.02	173.75	168.16

The hierarchical index in the columns looks like this:

```
In [11]: fb_agg.columns
```

Out[11]: MultiIndex(levels=[['open', 'high', 'low', 'close'], ['max', 'mean', 'min']], labels=[[0, 1, 1, 2, 2, 3], [1, 2, 0, 2, 0, 1]])

Using a list comprehension, we can join the levels (in a tuple) with an `_` at each iteration:

```
In [12]: fb_agg.columns = ['_'.join(col_agg) for col_agg in fb_agg.columns]
fb_agg.head()
```

Out[12]:

	open_mean	high_min	high_max	low_min	low_max	close_mean
trading_volume						
low	171.36	129.74	216.20	123.02	212.60	171.43
med	175.82	162.85	218.62	150.75	214.27	175.14
high	167.73	161.10	180.13	149.02	173.75	168.16

We can group on datetimes despite them being in the index if we use a `Grouper` :

```
In [13]: weather['2018-10'].query('datatype == "PRCP"').groupby(
         pd.Grouper(freq='D')
         ).mean().head()
```

Out[13]:

	value
date	
2018-10-01	0.01
2018-10-02	2.23
2018-10-03	19.69
2018-10-04	0.32
2018-10-05	0.96

This `Grouper` can be one of many group by values. Here, we find the quarterly total precipitation per station:

```
In [14]: weather.query('datatype == "PRCP"').groupby(
         ['station_name', pd.Grouper(freq='Q')]
         ).sum().unstack().sample(5, random_state=1)
```

Out[14]:

	value			
date	2018-03-31	2018-06-30	2018-09-30	2018-12-31
station_name				
WANTAGH 1.1 NNE, NY US	279.90	216.80	472.50	277.20
STATEN ISLAND 1.4 SE, NY US	379.40	295.30	438.80	409.90
SYOSSET 2.0 SSW, NY US	323.50	263.30	355.50	459.90
STAMFORD 4.2 S, CT US	338.00	272.10	424.70	390.00
WAYNE TWP 0.8 SSW, NJ US	246.20	295.30	620.90	422.00

Note that we can use `filter()` to exclude some groups from aggregation. Here, we only keep groups with 'NY' in the group's `name` attribute, which is the station ID in this case:

```
In [15]: weather.groupby('station').filter( # station IDs with NY in them
        lambda x: 'NY' in x.name
    ).query('datatype == "SNOW"]').groupby('station_name').sum().squeeze() # aggregate and make a series (squeeze)
```

```
Out[15]: station_name
ALBERTSON 0.2 SSE, NY US      1087.00
AMITYVILLE 0.1 WSW, NY US    434.00
AMITYVILLE 0.6 NNE, NY US   1072.00
ARMONK 0.3 SE, NY US         1504.00
BROOKLYN 3.1 NW, NY US       305.00
CENTERPORT 0.9 SW, NY US     799.00
ELMSFORD 0.8 SSW, NY US      863.00
FLORAL PARK 0.4 W, NY US     1015.00
HICKSVILLE 1.3 ENE, NY US    716.00
JACKSON HEIGHTS 0.3 WSW, NY US 107.00
LOCUST VALLEY 0.3 E, NY US     0.00
LYNBROOK 0.3 NW, NY US       325.00
MASSAPEQUA 0.9 SSW, NY US     41.00
MIDDLE VILLAGE 0.5 SW, NY US  1249.00
NEW HYDE PARK 1.6 NE, NY US    0.00
NEW YORK 8.8 N, NY US         0.00
NORTH WANTAGH 0.4 WSW, NY US  471.00
PLAINEDGE 0.4 WSW, NY US      610.00
PLAINVIEW 0.4 ENE, NY US     1360.00
SADDLE ROCK 3.4 WSW, NY US    707.00
STATEN ISLAND 1.4 SE, NY US   936.00
STATEN ISLAND 4.5 SSE, NY US   89.00
SYOSSET 2.0 SSW, NY US       1039.00
VALLEY STREAM 0.6 SE, NY US   898.00
WANTAGH 0.3 ESE, NY US       1280.00
WANTAGH 1.1 NNE, NY US        940.00
WEST NYACK 1.3 WSW, NY US    1371.00
Name: value, dtype: float64
```

Let's see which months have the most precipitation. First, we need to group by day and average the precipitation across the stations. Then we can group by month and sum the resulting precipitation. We use `nlargest()` to give the 5 months with the most precipitation:

```
In [16]: weather.query('datatype == "PRCP"]').groupby(
        pd.Grouper(freq='D')
    ).mean().groupby(pd.Grouper(freq='M')).sum().value.nlargest()
```

```
Out[16]: date
2018-11-30    210.59
2018-09-30    193.09
2018-08-31    192.45
2018-07-31    160.98
2018-02-28    158.11
Name: value, dtype: float64
```

Perhaps the previous result was surprising. The saying goes "April showers bring May flowers"; yet April wasn't in the top 5 (neither was May for that matter). Snow will count towards precipitation, but that doesn't explain why summer months are higher than April. Let's look for days that accounted for a large percentage of the precipitation in a given month.

In order to do so, we need to calculate the average daily precipitation across stations and then find the total per month. This will be the denominator. However, in order to divide the daily values by the total for their month, we will need a Series of equal dimensions. This means we will need to use `transform()` :

```
In [17]: weather.query('datatype == "PRCP"').rename(
          dict(value='prcp'), axis=1
        ).groupby(pd.Grouper(freq='D')).mean().groupby(
          pd.Grouper(freq='M')
        ).transform(np.sum)['2018-01-28':'2018-02-03']
```

Out[17]:

	prcp
date	
2018-01-28	69.31
2018-01-29	69.31
2018-01-30	69.31
2018-01-31	69.31
2018-02-01	158.11
2018-02-02	158.11
2018-02-03	158.11

Notice how we have the same value repeated for each day in the month it belongs to. This will allow us to calculate the percentage of the monthly precipitation that occurred each day and then pull out the largest values:

```
In [18]: weather\
          .query('datatype == "PRCP"')\
```



```

.rename(dict(value='prcp'), axis=1)\
.groupby(pd.Grouper(freq='D')).mean()\
.assign(
    total_prcp_in_month=lambda x: x.groupby(
        pd.Grouper(freq='M')
    ).transform(np.sum),
    pct_monthly_prcp=lambda x: x.prcp.div(
        x.total_prcp_in_month
    )
).nlargest(5, 'pct_monthly_prcp')

```

Out[18]:

	prcp	total_prcp_in_month	pct_monthly_prcp
date			
2018-10-12	34.77	105.63	0.33
2018-01-13	21.66	69.31	0.31
2018-03-02	38.77	137.46	0.28
2018-04-16	39.34	140.57	0.28
2018-04-17	37.30	140.57	0.27

`transform()` can be used on dataframes as well. We can use it to easily standardize the data:

In [19]:

```

fb[['open', 'high', 'low', 'close']].transform(
    lambda x: (x - x.mean()).div(x.std())
).head()

```

Out[19]:

	open	high	low	close
date				
2018-01-02	0.32	0.41	0.41	0.50
2018-01-03	0.53	0.57	0.60	0.66
2018-01-04	0.68	0.65	0.74	0.64
2018-01-05	0.72	0.68	0.78	0.77
2018-01-08	0.80	0.79	0.85	0.84

Pivot tables and crosstabs

We saw pivots in before; however, we weren't able to provide any aggregations. With `pivot_table()` , we get the mean by default as the `aggfunc` . In its simplest form, we provide a column to place along the columns:

```
In [20]: fb.pivot_table(columns='trading_volume')
```

Out[20]:

trading_volume	low	med	high
close	171.43	175.14	168.16
high	173.46	179.42	170.48
low	169.31	172.11	161.57
open	171.36	175.82	167.73
volume	24547207.71	79072559.12	141924023.33

By placing the trading volume in the index, we get the aggregation from the first example in the group by section above:

```
In [21]: fb.pivot_table(index='trading_volume')
```

Out[21]:

	close	high	low	open	volume
trading_volume					
low	171.43	173.46	169.31	171.36	24547207.71
med	175.14	179.42	172.11	175.82	79072559.12
high	168.16	170.48	161.57	167.73	141924023.33

With `pivot()` , we also weren't able to handle multi-level indices or indices with repeated values. For this reason we haven't been able to put the weather data in the wide format. The `pivot_table()` method solves this issue:

```
In [22]: weather.reset_index().pivot_table(  
    index=['date', 'station', 'station_name'],  
    columns='datatype',  
    values='value',  
    aggfunc='median'  
).reset_index().tail()
```

Out [22]:

	datatype	date	station	station_name	AWND	DAPR	MDPR	PGTM	PRCP	SNOW	SNWD	...	WSF5	WT01	WT02	WT03	WT04	WT05	WT06	WT08	WT
	28740	2018-12-31	GHCND:USW00054787	FARMINGDALE REPUBLIC AIRPORT, NY US	5.00	nan	nan	2052.00	28.70	nan	nan	...	15.70	nan	nan	nan	nan	nan	nan	nan	r
	28741	2018-12-31	GHCND:USW00094728	NY CITY CENTRAL PARK, NY US	nan	nan	nan	nan	25.90	0.00	0.00	...	nan	1.00	nan	nan	nan	nan	nan	nan	r
	28742	2018-12-31	GHCND:USW00094741	TETERBORO AIRPORT, NJ US	1.70	nan	nan	1954.00	29.20	nan	nan	...	8.90	nan	nan	nan	nan	nan	nan	nan	r
	28743	2018-12-31	GHCND:USW00094745	WESTCHESTER CO AIRPORT, NY US	2.70	nan	nan	2212.00	24.40	nan	nan	...	11.20	nan	nan	nan	nan	nan	nan	nan	r
	28744	2018-12-31	GHCND:USW00094789	JFK INTERNATIONAL AIRPORT, NY US	4.10	nan	nan	nan	31.20	0.00	0.00	...	12.50	1.00	1.00	nan	nan	nan	nan	nan	r

5 rows × 30 columns

We can use the `pd.crosstab()` function to create a frequency table. For example, if we want to see how many low-, medium-, and high-volume trading days Facebook stock had each month, we can use `crosstab`:

In [23]:

```
pd.crosstab(  
    index=fb.trading_volume,  
    columns=fb.index.month,  
    colnames=['month'] # name the columns index  
)
```

Out [23]:

	month	1	2	3	4	5	6	7	8	9	10	11	12
trading_volume													
	low	20	19	15	20	22	21	18	23	19	23	21	19
	med	1	0	4	1	0	0	2	0	0	0	0	0
	high	0	0	2	0	0	0	1	0	0	0	0	0

We can normalize with the row or column totals with the `normalize` parameter. This shows percentage of the total:

```
In [24]: pd.crosstab(
    index=fb.trading_volume,
    columns=fb.index.month,
    colnames=[ 'month' ],
    normalize='columns'
)
```

Out[24]:

	month	1	2	3	4	5	6	7	8	9	10	11	12
trading_volume													
low	0.95	1.00	0.71	0.95	1.00	1.00	0.86	1.00	1.00	1.00	1.00	1.00	1.00
med	0.05	0.00	0.19	0.05	0.00	0.00	0.10	0.00	0.00	0.00	0.00	0.00	0.00
high	0.00	0.00	0.10	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.00	0.00

If we want to perform a calculation other than counting the frequency, we can pass the column to run the calculation on to `values` and the function to use to `aggfunc` :

```
In [25]: pd.crosstab(
    index=fb.trading_volume,
    columns=fb.index.month,
    colnames=[ 'month' ],
    values=fb.close,
    aggfunc=np.mean
)
```

Out[25]:

	month	1	2	3	4	5	6	7	8	9	10	11	12
trading_volume													
low	185.24	180.27	177.07	163.29	182.93	195.27	201.92	177.49	164.38	154.19	141.64	137.16	
med	179.37	nan	164.76	174.16	nan	nan	194.28	nan	nan	nan	nan	nan	nan
high	nan	nan	164.11	nan	nan	nan	176.26	nan	nan	nan	nan	nan	nan

We can also get row and column subtotals with the `margins` parameter. Let's count the number of times each station recorded snow per month and include the subtotals:

```
In [26]: snow_data = weather.query('datatype == "SNOW"')
pd.crosstab(
    index=snow_data.station_name,
    columns=snow_data.index.month,
    colnames=[ 'month' ],
```

```
values=snow_data.value,  
aggfunc=lambda x: (x > 0).sum(),  
margins=True, # show row and column subtotals  
margins_name='total observations of snow' # name the subtotals  
)
```

Out [26] :

	month	1	2	3	4	5	6	7	8	9	10	11	12	total observations of snow
	station_name													
	ALBERTSON 0.2 SSE, NY US	3.00	1.00	3.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	9.00
	AMITYVILLE 0.1 WSW, NY US	1.00	0.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	3.00
	AMITYVILLE 0.6 NNE, NY US	3.00	1.00	3.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	8.00
	ARMONK 0.3 SE, NY US	6.00	4.00	6.00	3.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	3.00	23.00
	BLOOMINGDALE 0.7 SSE, NJ US	2.00	1.00	3.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	8.00
	BOONTON 0.6 NW, NJ US	4.00	2.00	2.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	11.00
	BOONTON 0.7 WSW, NJ US	nan	nan	nan	0.00	nan	nan	0.00	0.00	nan	0.00	nan	nan	0.00
	BOONTON 1 SE, NJ US	3.00	2.00	3.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	9.00
	BROOKLYN 3.1 NW, NY US	2.00	0.00	2.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	5.00
	CANOE BROOK, NJ US	2.00	nan	2.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	6.00
	CARTERET 0.6 WSW, NJ US	1.00	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	1.00
	CEDAR GROVE TWP 0.4 W, NJ US	4.00	2.00	5.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	2.00	2.00	17.00
	CENTERPORT 0.9 SW, NY US	2.00	1.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	8.00
	CENTERPORT, NY US	5.00	3.00	6.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	17.00
	CHATHAM 0.6 NW, NJ US	3.00	1.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	9.00
	CHATHAM TWP 1.1 NNW, NJ US	nan	nan	nan	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	nan	0.00
	CHATHAM TWP 2.0 NNW, NJ US	nan	nan	nan	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	nan	0.00
	COLTS NECK TWP 2.4 NW, NJ US	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00
	CRANFORD TWP 1.1 NNW, NJ US	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	EAST BRUNSWICK TWP 3.3 NNE, NJ US	nan	1.00	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	1.00
	EATONTOWN 1.2 NE, NJ US	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00
	EDISON TWP 1.9 N, NJ US	nan	nan	nan	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	ELMSFORD 0.8 SSW, NY US	3.00	3.00	2.00	nan	nan	nan	nan	nan	nan	nan	nan	nan	8.00
	FLORAL PARK 0.4 W, NY US	3.00	1.00	3.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	8.00
	FLORHAM PARK 0.2 WNW, NJ US	6.00	2.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	14.00

month	1	2	3	4	5	6	7	8	9	10	11	12	total observations of snow
station_name													
GLEN ROCK 0.4 WNW, NJ US	nan	nan	nan	nan	nan	nan	nan	0.00	0.00	0.00	nan	nan	0.00
GLEN ROCK 0.7 SSE, NJ US	6.00	2.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	15.00
HARRISON 0.3 N, NJ US	4.00	2.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	13.00
HARRISON, NJ US	4.00	2.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	13.00
HAWTHORNE 0.4 S, NJ US	4.00	2.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	2.00	0.00	14.00
...
PARSIPPANY TROY HILLS TWP 1.5, NJ US	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	1.00	1.00	2.00
PLAINEDGE 0.4 WSW, NY US	1.00	nan	1.00	1.00	nan	nan	nan	nan	nan	nan	nan	nan	3.00
PLAINVIEW 0.4 ENE, NY US	3.00	1.00	5.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	10.00
PUTNAM LAKE, CT US	nan	nan	nan	nan	nan	nan	nan	nan	0.00	0.00	0.00	nan	0.00
RED BANK 0.6 ENE, NJ US	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	0.00	0.00	0.00
RINGWOOD 3.0 SSE, NJ US	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	1.00
RIVER EDGE 0.4 NNE, NJ US	0.00	0.00	0.00	0.00	0.00	0.00	0.00	nan	nan	0.00	0.00	0.00	0.00
SADDLE ROCK 3.4 WSW, NY US	3.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	nan	7.00
SOUTH PLAINFIELD 0.7 NNE, NJ US	nan	nan	1.00	nan	nan	nan	nan	nan	nan	nan	nan	nan	1.00
SPRINGFIELD TWP 0.7 NNE, NJ US	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
STAMFORD 4.2 S, CT US	1.00	1.00	1.00	1.00	nan	nan	nan	nan	nan	nan	nan	0.00	4.00
STATEN ISLAND 1.4 SE, NY US	4.00	2.00	5.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	14.00
STATEN ISLAND 4.5 SSE, NY US	0.00	1.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	2.00
SYOSSET 2.0 SSW, NY US	2.00	1.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	9.00
SYOSSET, NY US	3.00	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	6.00
TENAFLY 1.3 W, NJ US	1.00	2.00	7.00	2.00	0.00	0.00	nan	0.00	0.00	0.00	2.00	1.00	15.00
TENAFLY 1.6 NW, NJ US	nan	1.00	nan	nan	nan	nan	nan	nan	nan	nan	nan	nan	1.00
TETERBORO AIRPORT, NJ US	nan	3.00	4.00	1.00	nan	nan	nan	nan	nan	nan	1.00	nan	9.00
VALLEY STREAM 0.6 SE, NY US	2.00	2.00	4.00	1.00	0.00	0.00	0.00	nan	nan	nan	nan	nan	9.00

month	1	2	3	4	5	6	7	8	9	10	11	12	total observations of snow
station_name													
WANAQUE RAYMOND DAM, NJ US	1.00	1.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	8.00
WANTAGH 0.3 ESE, NY US	3.00	1.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	11.00
WANTAGH 1.1 NNE, NY US	2.00	1.00	4.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	nan	9.00
WAYNE TWP 0.8 SSW, NJ US	nan	1.00	2.00	1.00	nan	nan	nan	nan	nan	nan	1.00	nan	5.00
WEST CALDWELL TWP 1.3 NE, NJ US	0.00	3.00	4.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	10.00
WEST NYACK 1.3 WSW, NY US	3.00	1.00	5.00	1.00	nan	nan	nan	nan	nan	nan	1.00	nan	11.00
WESTFIELD 0.6 NE, NJ US	3.00	0.00	4.00	1.00	0.00	nan	0.00	0.00	0.00	nan	1.00	nan	9.00
WOODBIDGE TWP 1.1 ESE, NJ US	4.00	1.00	3.00	2.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	11.00
WOODBIDGE TWP 1.1 NNE, NJ US	2.00	1.00	3.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	1.00	0.00	7.00
WOODBIDGE TWP 3.0 NNW, NJ US	nan	0.00	0.00	nan	nan	0.00	nan	nan	nan	0.00	0.00	nan	0.00
total observations of snow	190.00	97.00	237.00	81.00	0.00	0.00	0.00	0.00	0.00	0.00	49.00	13.00	667.00

99 rows × 13 columns