(1) File occurrences

#	repo	path	sha	location
1	A	.claude/skills/pdf/SKILL.md	a1	canonical
2	B	skills/pdf/SKILL.md	a1	skills-dir
3	C	.claude/skills/pdf/SKILL.md	a1	canonical
4	D	.claude/skills/lint/SKILL.md	b2	canonical
5	D	.codex/skills/lint/SKILL.md	b2	skills-dir
6	E	docs/deploy/SKILL.md	c3	other

location: canonical = .claude/skills/<name>/; skills-dir = any other skills/<name>/ folder; other = everything else.

(2) Group by file_sha

sha	files	repos	label
a1	3	3	cross-repo
b2	2	1	within-repo
c3	1	1	single

files = occurrences of the content
repos = distinct repositories

cross-repo: repos ≥ 2
within-repo: files ≥ 2, repos = 1
single: files = 1

(3) RQ1 metrics

Reuse shares
duplicated = (3 + 2) / 6 = 83%
cross-repo = 3 / 6 = 50%
within-repo only = 2 / 6 = 33%

Reuse distribution
repos per content: 1, 1, 3
Gini of repos per content
top-k share of cross-repo files

Location comparisons
% cross-repo: canonical 2/3,
skills-dir 1/2, other 0/1
chi-square test, odds ratios

Robustness
repeat without short contents
and forked repositories