AIVS: Anonymous Identification Verification System

Based on Ring Signatures with Isolated Smart Card Hardware

Dinh Anh Khoa Nguyen - 245849840 - nguy9840@mylaurier.ca
Jiangtao Wang - 245823800 - Wang2370@mylaurier.ca
Leila Chen - 245850620 - chen5062@mylaurier.ca
Yuyang Wu - 245817310 - wuxx7310@mylaurier.ca

April 2026

Abstract

This report outlines the engineering implementation of a privacy-preserving messaging platform that decouples message integrity from identity revelation. Leveraging Yubikey hardware PRF and nested Ring Signatures, the system allows users to send undeniable, tamper-proof messages anonymously, with the exclusive capability to retroactively prove authorship. The project adopts an Agile methodology, utilizing React/TypeScript for the frontend and Node.js for the backend.

Contents

1 Introduction **3**
1.1 Motivation and Problem Statement . . . 3
1.2 Project Objectives . . . 3
1.3 Scope and Limitations . . . 3

2 Background and Related Work **3**
2.1 Ring Signatures — Theory and Prior Work . . . 3
2.2 Hardware Security Tokens and WebAuthn PRF . . . 4
2.3 Gap Analysis . . . 4

3 System Design **5**
3.1 Architecture Overview . . . 5
3.2 Security Model and Threat Model . . . 5
3.3 Cryptographic Construction . . . 5
3.4 Component Diagram . . . 5
3.5 Data Flow Diagram . . . 6
3.6 Database Schema . . . 6

4 Implementation **8**
4.1 Technology Stack . . . 8
4.2 Cryptography Module . . . 8
4.3 YubiKey Integration via WebAuthn PRF . . . 9
4.4 Backend API . . . 10
4.5 Frontend UI . . . 11
4.6 End-to-End Flow: Alice → Bob → Reveal . . . 12

5 Evaluation **13**
5.1 Functional Testing . . . 13
5.2 Security Analysis . . . 15
5.3 Performance Analysis . . . 16
5.4 Limitations and Edge Cases . . . 17

6 Conclusion and Future Work **17**
6.1 Summary of Achievements . . . 17
6.2 Future Directions . . . 19

1 Introduction

1.1 Motivation and Problem Statement

In current cryptographic systems, users typically face a binary choice:

1. **Signed Messages:** Authenticity is guaranteed, but privacy is compromised immediately (e.g., PGP).
2. **Anonymous Messages:** Privacy is maintained, but credibility is low, and the author cannot later claim credit or reputation for the content (e.g., Tor-based drops).

There is a lack of infrastructure that supports *conditional anonymity*. Where a user can speak freely now and prove they spoke later, without relying on a trusted third party.

1.2 Project Objectives

- **Objective A:** Anonymous message dispatching where the sender is mathematically hidden among a set of 7 decoys (1-of-8 Ring Signature).
- **Objective B:** Integrity verification by the recipient without identity knowledge.
- **Objective C:** A "Challenge-Response" flow where the sender can prove authorship by unlocking a cryptographic proof using their physical Yubikey.

1.3 Scope and Limitations

AIVS is a research prototype that is used to demonstrate the combination of cryptography with a two-party messaging system to present conditional anonymity. The system consists of anonymous message, verification, and authorship proof via a hardware based Yubikey. All important operations are performed on the client browser side, while the backend server serves as a relay and a storage service, without knowing the identity of users. As a prototype, there are several limitations in the current implementation:

- **Anonymity Set Size:** The ring of public keys is fixed at 1-of-8 (one real public key and seven generated decoy ones). This is sufficient for a prototype, but is not suitable for larger schemes, which provide stronger anonymity guaranties and are more appropriate for production systems.
- **Hardware Dependency:** The system specifically requires a physical hardware device named Yubikey with PRF extension support. Environments with different hardware cannot participate in the process.
- **Prototype Scope:** The implementation is not designed for production use. Such factors as: Scalability, multi-device support and account recovery are not in scope.

2 Background and Related Work

2.1 Ring Signatures — Theory and Prior Work

Rivest, Shamir, and Tauman have introduced Ring signatures which can provide a mechanism for anonymous authentication by leveraging a predefined set of public keys. This mechanism relies on

a signature being generated by a signer on behalf of a group and can be verified to confirm that one of the group members signed the message without revealing the exact signer. Differing from group signature schemes, a trusted setup phase, a group manager, or a revocation mechanism are not required for ring signatures. So, by selecting a set of public keys, the ring can be independently constructed by the signer. This makes the scheme particularly suitable for decentralized settings. Linkable Ring Signature (LRS) is an important extension of this concept. In LRS schemes, each signature includes a linking tag which is often known as a key image. This tag is generated based on the signer's secret key and the public key. The purpose of this tag is to link different signatures produced by the same signer and to keep the signer's identity secret. Because of this feature, this schema is widely used in cryptocurrency systems, as it can prevent double spending and preserve anonymity. In this project, this LRS is used in a different context which is establishing a verifiable relationship between two signatures generated from the same one-time key. As a result of this mechanism, a controlled disclosure workflow is generated and this workflow can demonstrate authorship by revealing additional information and preserve anonymity by default.

2.2 Hardware Security Tokens and WebAuthn PRF

Secret keys management is also an important aspect in the context of security of cryptographic systems. In many browser-based applications, key material is handled in software, but this may enhance the risk of cross-site scripting (XSS) and cause a compromised execution environment. The FIDO2/WebAuthn standard introduces a model to allow cryptographic operations to be performed by external authenticators, such as hardware security tokens. In this model, the host application cannot directly access the private keys which are generated and stored within the authenticator. A recent extension to WebAuthn is the PRF (Pseudo-Random Function) extension. In this extension, by giving an input, an output would be generated based on a credential-bound secret and it is accessible to the application. The authenticator can return the PRF output while keeping the underlying secret. As a result, applications can derive high-entropy values tied to the authenticator. In this project, PRF outputs are used as part of the key derivation process for one-time signing keys. And they also are used for deriving symmetric keys used in proof encryption. This design creates a connection between critical cryptographic operations and the possession of a hardware authenticator, so that the reliance on software-managed long-term secrets in the browser environment can be significantly reduced.

2.3 Gap Analysis

There are several limitations which cannot be simultaneously addressed in current solutions according to existing systems and research approaches. First, a trade-off between identity and privacy. Traditional PKI-based systems like PGP or S/MIME provide strong authenticity and non-repudiation, however, a connection of signatures and long-term identities is created. Conversely, anonymous communication systems provide strong privacy but sacrifice verifiable authorship. Second, the integration ring signatures and linkable ring signatures with browser-based security mechanisms. Their strong anonymity properties make them widely used in specialized environments such as cryptocurrency systems or native applications, but it is difficult to integrate them into standardized browser-based security mechanisms, such as WebAuthn. Third, the limitation of standard ring signature constructions. Although standard ring signature constructions can ensure signer anonymity, they do not inherently support identity disclosure, as they do not provide a built-in approach for a signer to later prove authorship. To address these gaps, the AIVS system combines hardware-assisted key derivation with a two-layer ring signature construction. The goal is to enable

anonymous message authentication in a browser environment, while supporting a controlled and verifiable authorship disclosure process when required.

3 System Design

3.1 Architecture Overview

The system follows a **Thick Client, Thin Server** architecture. The server acts purely as a bulletin board and relay, possessing zero knowledge of user identities or private keys, and is explicitly excluded from the trusted computing base.

3.2 Security Model and Threat Model

- **Key Derivation:** The OTK is derived with the participation of the Yubikey, ensuring it cannot be predicted or extracted.
- **Anonymity Set:** 1 real signer + 7 random decoys = 8 total keys. Probability of guessing the signer is 1/8 per message (statistically negligible for identification).
- **Forward Secrecy:** Compromise of the Yubikey allows decryption of past Proofs but does not reveal the identity of past messages *unless* the attacker actively performs the decryption and linking.

3.3 Cryptographic Construction

1. **Setup:** Generate One-Time Key (OTK) via Yubikey. Generate 7 Fake Keys ($FK_{1...7}$).
2. **Inner Layer (The Proof):**

$$Sig_{inner} = RingSign(Message, \{OTK, FK_{1...7}\})$$

$$Key_{proof} = KDF(PRF_{Yubikey}(Hash(OTK)))$$

$$Proof = Encrypt_{AES-GCM}(Sig_{inner}, Key_{proof})$$


   where the hash of the OTK is used as a salt to bind the proof key to the one-time signing key.


3. **Outer Layer (The Transmission):**

$$Sig_{outer} = RingSign(Message||Hash(Sig_{inner}), \{OTK, FK_{1...7}\})$$

4. **Verification:** Upon decryption, the Linkable Tag of Sig_{inner} must equal the Linkable Tag of Sig_{outer}.

3.4 Component Diagram





3.5 Data Flow Diagram

1. **Registration:** None required for the messaging protocol itself (stateless). Optional username registration maps public handles to WebAuthn Credential IDs for routing.
2. **Signing:** All cryptographic operations occur in the browser memory. The Yubikey is accessed via `navigator.credentials.get({prf: ... })`.

3.6 Database Schema

The database is implemented in PostgreSQL and consists of five tables. The server stores only public key in binary data type and metadata for message routing and username verification.

Credentials

Stores WebAuthn registration data for each user handle.

- `id` — UUID, primary key.
- `handle` — VARCHAR(255), username.
- `credential_id` — TEXT, unique WebAuthn credential identifier.
- `public_key` — BYTEA, public key.
- `sign_count` — INTEGER, count login time used with the hardware, default 0.
- `transports` — TEXT, nullable.
- `created_at` / `updated_at` — TIMESTAMP.

Challenges

Stores timeout WebAuthn challenges issued during registration and authentication process. Each challenge is used and deleted after verification.

- `id` — UUID, primary key.
- `handle` — VARCHAR(255), username.

- `challenge` — TEXT, base64url-encoded.
- `challenge_type` — VARCHAR(50), either `registration` or `login`.
- `expires_at` — TIMESTAMP, 10 minutes for registration, 5 minutes for login.
- `created_at` — TIMESTAMP.

Sessions

Manages session tokens created after a successful WebAuthn login and its time-alive is 24 hours.

- `id` — UUID, primary key.
- `handle` — VARCHAR(255).
- `session_token` — TEXT.
- `expires_at` — TIMESTAMP, 24-hour TTL.
- `created_at` / `updated_at` — TIMESTAMP.

Message_packs

Stores the JSON-serialized message payload. Ownership can be transferred between handles, with the timestamp updated on each transfer.

- `id` — UUID, primary key.
- `content` — TEXT, JSON-serialized payload.
- `memo` — TEXT, description.
- `credential_id` — TEXT.
- `owner` — VARCHAR(255), current owner handle.
- `created_at` — TIMESTAMP, updated on transfer.

Validation_requests

Implements an identity confirmation workflow between 2 users around a message pack

- `id` — UUID, primary key.
- `message_pack_id` — UUID, foreign key referencing `message_packs(id)` ON DELETE CASCADE.
- `requester` — VARCHAR(255).
- `responder` — VARCHAR(255).
- `status` — VARCHAR(20), CHECK constraint enforced.
- `response_payload` — TEXT, nullable, responder evidence.
- `created_at` / `updated_at` — TIMESTAMP.

4 Implementation

4.1 Technology Stack

- **Frontend:** React, TypeScript.
- **Cryptography (Client):** WebAuthn API (PRF extension), Elliptic Curve Library (e.g., `elliptic` or WASM-based Rust bindings) for Ring Signatures.
- **Backend:** Node.js (Express/NestJS).
- **Database:** PostgreSQL (Stores only blobs: Message, Public Keys Ring, Signature, Encrypted Proof).

4.2 Cryptography Module

This module implements the core cryptographic operations. The core functions of this module are implements of a LRS based on Ristretto255 and Ed25519 curves. We can divided the module into four main components: core cryptographic implementation, key management, serialization tools and utility Functions.

Core Cryptographic Implementation The core functionality of the part revolves around LRS, which allows a user to sign a message anonymously on behalf of a group (ring) while providing a way to ”link” signatures if the same member signs multiple times.

- **Data Structures**: It defines `LRSSignature` and `LRSSignatureRaw` interfaces to store signature components: `c0` (initial hash), `r` (responses), `I` (linkability tag/key image), and `ring` (public keys).
- **Signature Generation**:
  - `generateLRS`: Generates a signature given a message, a set of public keys, the signer's index, and the signer's private key.
  - `generateLRSWithoutFakeKeys`: A helper that automatically generates random “fake” keys to fill the ring, simplifying the signing process for a single user.
- **Verification**:
  - `verifyLRS`: Validates the signature by reconstructing the hash chain across the ring and checking if it matches the provided `c0`.

Key Management This part provides methods for managing cryptographic keys using the Ristretto255 curve:

- `generateKeyPair`: Creates a public/private key pair, optionally from a provided seed for deterministic generation.
- `validatePublicKey`: Verifies that a specific public key corresponds to a given private key.

Serialization Tools To facilitate data transmission and storage, the part includes utilities to convert signature objects to and from byte formats.

- `LRSToBytes`: Serializes an `LRSSignature` object into a `Uint8Array`.
- `bytesToLRS / bytesToRawLRS`: Deserializes a byte array back into a structured signature object.

Utility Functions

- **Hashing**: Includes `sha256` for standard data hashing, `hashToScalar` for curve-specific scalar generation, and `H_p` (Hash-to-Curve) for mapping data to a point on the Ristretto255 curve.
- **Data Conversion**: Exports standard utilities like `hexToBytes` and `bytesToHex` for handling hexadecimal strings.
- **Comparison**: `uint8ArrayEquals` for comparing two byte arrays for equality.

Conclusion In conclusion, the cryptography module is designed to be efficient and secure, ensuring that all operations are performed locally on the client side with the assistance of the Yubikey, while the server remains a passive relay that handles only opaque data blobs.

4.3 YubiKey Integration via WebAuthn PRF

This component handles the interaction with the YubiKey hardware token using the WebAuthn API, specifically leveraging the PRF extension to derive one-time keys for signing and encryption. This is the main component that ensures the security of the key material by keeping it within the hardware boundary. For its implementation, it can be divided into two different parts:

WebAuthn and Hardware Key Derivation The system utilizes the **WebAuthn PRF (Pseudo-Random Function) extension** to securely derive cryptographic keys from the user's hardware authenticator (e.g., TouchID, FaceID, or YubiKey) rather than storing private keys in plain text.

- `getCredential`: Triggers the `navigator.credentials.get` API with PRF extensions enabled to fetch hardware-backed credentials.
- `generateKeyWithPRF`: Uses the derived key from the hardware as a seed to generate deterministic Ristretto255 asymmetric key pairs.

Cryptographic MessagePack Processing This is the core privacy logic that implements Linkable Ring Signatures (LRS) to ensure anonymity and verifiability.

- `getMessagePack`: Orchestrates the creation of a secure message pack. It combines the payload with a timestamp/nonce, generates an *internal* LRS, encrypts it via AES-GCM, and wraps it in an *external* LRS.
- `ValidateMessagePack`: Checks metadata versioning and verifies the external ring signature to ensure message integrity.
- `getProofForReceiver`: Enables the receiver to attempt decryption of the AES-GCM ciphertext using their own derived keys to verify the sender.

4.4 Backend API

The backend API is implemented as a Noje.js RESTful API consisted of 4 services: WebAuthn service, Message pack service, Validation request service and an authentication middleware. The middleware is used to validate session tokens between API calls of message pack service and validation request services.

WebAuthn Service

Handles YubiKey credential registration and generates session token for authentication.

- `POST /register/challenge` — Create a registration challenge for a new credential.
- `POST /register/publickey` — Final step of the registration process by storing the authenticator public key.
- `POST /auth/challenge` — Create an authentication challenge for login.
- `POST /auth/session` — Verify the challenge along with the response and generate a session token.
- `GET /session` — Returns the current authenticated session (auth required, use to test the authentication).

Message Pack Service

Handles creation, retrieval, and ownership transfer of message packs.

- `POST /message` — Create a new message pack.
- `GET /message/by_id/:id` — Retrieve a message pack by UUID.
- `GET /message/list/by_username/:username` — List all message packs owned by a given handle.
- `PUT /message/by_id/:id/owner` — Transfer ownership of a message pack to another handle.

Validation Request Service

Manages the challenge-response flow between 2 users for authorship verification.

- `POST /validation-requests` — Create a new validation request for a message pack.
- `GET /validation-requests/sent` — List validation requests created by the current user.
- `GET /validation-requests/received` — List validation requests assigned to the current user.
- `PUT /:id/respond` — User submits the decrypted signature as evidence.
- `PUT /:id/result` — User finalizes the validation request after verifying the evidence.

Authentication Middleware

- **Auth middleware** — Validates the session token on each protected API request.

4.5 Frontend UI

The frontend project is structured as a Single-Page Application (SPA). The overall architecture can be summarized as: **Single-Page Entry + Authentication Gateway + Signing Workbench + Data Request Utility Layer**. In terms of implementation style, it follows a React functional layered architecture, with the core business logic centered around WebAuthn authentication and cryptographic signing workflows.

Application Entry Layer

- `index.html`: Provides the `root` container and loads `/src/main.tsx`.
- `src/main.tsx`: Creates the React Root, injects `StrictMode`, and mounts the application.

Application Shell Layer

- `src/App.tsx`: The application shell component; currently lightweight, primarily responsible for rendering the login wrapper component.
- `src/App.css`: Global base styles (root container and heading styles).

Authentication and Session Layer

- `src/login.tsx`: The primary business entry point, responsible for fetching registration/login challenges, invoking WebAuthn, managing session tokens, and switching the UI post-login.
- Supports Message Pack file imports, serving as the bridge between the authentication domain and the business domain.

Business Feature Layer (Signing and Verification)

- `src/Sign.tsx`: An aggregation layer for the signing workbench, using a collapse panel to organize features:
  - Create new signed messages
  - Message Pack list
  - Received/Sent verification request lists
- `src/Message.tsx`: List details and operations layer, responsible for:
  - Message Pack detail display and local validation
  - File export
  - Ownership transfer
  - Sending identity confirmation requests
  - Request verification/rejection workflows

Domain and Infrastructure Layer

- `src/utils.ts`: The core utility layer, handling API communication, cryptographic process encapsulation, authentication header assembly, and type definitions.
- This file also provides Message Pack construction and validation logic, serving as a critical dependency for upper-layer components.

Reserved Layer

- `src/constants.ts`: Currently empty; can serve as a unified entry point for constants in the future.
- `src/assets/`: Currently stores static resources (e.g., `react.svg`).

Rendering Flow This application rendered in this flow:
`index.html` → `main.tsx` → `App.tsx` → `login.tsx` → `Sign.tsx` → `Message.tsx`

State Flow The project relies primarily on React local state (`useState` or `useEffect` or `useCallback`); no global state management library is introduced. Session state is persisted via `sessionStorage`, and user state is restored via session APIs after a refresh.

Data Flow UI components call functions in `src/utils.ts`, and the utility layer performs unified access to the backend `/api`. In the development environment, Vite proxies and forwards requests to local backend services.

Dependency Boundaries

- UI and Interaction: React + Ant Design
- Shared Types and Cryptography: `@repo/shared`
- Build and Development: Vite + TypeScript + ESLint

Strengths

- Clear Layering: Distinct boundaries between page orchestration and infrastructure capabilities.
- Comprehensive Typing: Request/response types are centrally defined in the utility layer.
- Complete Business Loop: Covers core processes including login, signing, requesting, verification, and import/export.

4.6 End-to-End Flow: Alice → Bob → Reveal

The system involves three primary roles: the Sender, the Recipient, and a Backend Server, with a YubiKey hardware token participating in cryptographic operations. Both the Sender and the Recipient interact with the system through a web browser, while the backend server functions solely as a message relay and storage service.

All cryptographic operations are performed locally on the client side with the assistance of the YubiKey. The server does not generate, store, or process private keys, and only handles opaque data blobs, including messages, signatures, and encrypted proofs. The YubiKey is used to provide hardware-bound PRF outputs that participate in one-time key derivation and proof encryption, without exposing secret material to the browser or operating system.

The system does not maintain a global signing key registry. Each message is associated with a freshly derived one-time key, and no signing keys are reused across messages.

During message transmission, the Sender composes a message using a browser-based client with a connected YubiKey. A one-time key is derived with the participation of the YubiKey and used,

together with a fixed set of randomly generated decoy keys, to construct a ring signature over the message. To support future authorship verification, an additional inner ring signature is generated and encrypted as a proof using a symmetric key derived from the YubiKey PRF output. An outer ring signature is then computed over the message concatenated with the hash of the encrypted proof. The message, outer signature, and encrypted proof are transmitted to the Recipient via the backend server.

Upon receipt, the Recipient verifies the outer ring signature to confirm message integrity and authenticity, while the Sender's identity remains hidden within the anonymity set. The encrypted proof is not required for this initial verification.

If identity verification is later requested, the Recipient sends the original message, signature, and encrypted proof to the claimed Sender. Using the same YubiKey, the Sender derives the corresponding decryption key and decrypts the proof to reveal the inner ring signature. The decrypted signature is returned to the Recipient, who verifies its validity and linkability against the original message and signature to confirm authorship.

5 Evaluation

5.1 Functional Testing

Functional testing was conducted to evaluate whether the prototype correctly supports the intended end-to-end workflow, including authentication, anonymous message creation, message-pack management, and authorship confirmation. The purpose of this evaluation was not to assess user interface quality in isolation, but to verify that the frontend, backend, and client-side cryptographic components operate consistently as an integrated system.

The first group of tests focused on the WebAuthn-based login flow. A user was able to initiate registration or authentication challenges from the browser, complete credential operations with the hardware token, and obtain a valid session for subsequent requests. After successful login, the client correctly restored the authenticated state and exposed the corresponding user functions, indicating that challenge handling, session issuance, and session recovery were functioning as expected.




Figure 1: Authenticated user interface after successful login and session establishment.

The second group of tests examined anonymous message-pack generation and storage. After authentication, the client successfully derived a one-time key with the participation of the YubiKey PRF, generated the corresponding ring-signature-based message pack locally, and submitted the serialized result to the backend. The stored message pack could then be retrieved and displayed in the message list, confirming that local cryptographic generation, backend persistence, and frontend rendering were correctly connected.




Figure 2: Stored message pack displayed in the list with management actions.

Additional tests covered message-pack management and the authorship confirmation workflow. A user could export a stored message pack, transfer its ownership to another user, and observe the updated ownership state after refreshing the list. Furthermore, a recipient could initiate a validation request, the claimed sender could respond with a proof derived from the original credential, and the requester could obtain a final validation status. These results indicate that the prototype already supports the complete functional loop from anonymous message creation to later identity revelation.




Figure 3: Received validation request shown in the pending state before proof handling.




Figure 4: Sent validation request shown after the responder has returned a proof.

5.2 Security Analysis

The security properties of the system are primarily derived from the combination of client-side cryptographic execution, hardware-assisted key derivation, and the two-layer ring-signature construction. Instead of directly signing messages with a long-term identity key, the prototype derives a one-time key with the participation of the YubiKey through the WebAuthn PRF extension. As a result, message authenticity can be established without creating a direct and persistent link between signed content and the user's long-term identity.

With respect to anonymity, the outer ring signature allows a verifier to confirm that a valid member of the ring signed the message, while preventing direct identification of the actual sender. Because each message uses a freshly derived one-time key together with a set of decoy public keys, signatures are not naturally tied to a stable signing identity across messages. This design reduces the risk of straightforward cross-message linkage and supports the system's goal of anonymous transmission by default.

The system also provides controlled identity revelation through the encrypted proof mechanism. In addition to the outer signature, the sender generates an inner ring signature and encrypts it

with a symmetric key derived from a YubiKey-bound PRF output. Only a party with access to the original hardware credential can derive the correct decryption key and recover the proof. This enables the claimed sender to later demonstrate authorship without requiring the server or any third party to act as an identity escrow authority.

From a key-management perspective, the backend does not store private signing material and does not perform the cryptographic operations required to generate or reveal proofs. Its role is limited to challenge management, session handling, message-pack storage, and request coordination. This design reduces the server's position in the trusted computing base and avoids concentrating sensitive signing material in a single backend component.

Overall, the prototype demonstrates a credible balance between anonymity and revealability: recipients can verify message validity without immediately learning the sender's identity, while the legitimate sender retains the exclusive ability to prove authorship later through the original hardware credential. At the same time, the present version should be understood as a research prototype, where the main security contribution lies in validating the feasibility of the mechanism rather than delivering a production-ready assurance level.

5.3 Performance Analysis

Functional testing and backend API timing observations were conducted through the online test environment at `https://cp683.ryonanamizu.com/`. The system was accessed through a web browser, and browser developer tools were used to inspect request timing for representative backend endpoints. Cryptographic performance measurements, by contrast, were collected through a separate local benchmark that focused on client-side ring-signature generation, verification, message-pack construction, and proof revelation.

Metric	Mean (ms)	Min (ms)	Max (ms)
LRS generation	39.34	37.19	45.96
LRS verification	38.81	37.12	44.11
Approx. message pack generation	77.71	75.15	85.28
Approx. proof revelation	0.96	0.39	2.68

Table 1: Local benchmark results for the default configuration with ring size 8.

To evaluate the prototype under its default anonymity-set size, a local benchmark was conducted with `ring size = 8`. The benchmark focused on client-side cryptographic operations, and each metric was measured over 20 runs with mean, minimum, and maximum values recorded.

The results show that LRS generation required an average of 39.34 ms, while LRS verification required an average of 38.81 ms. The two operations therefore have comparable costs and both remain within a few tens of milliseconds.

The approximate message-pack generation process required an average of 77.71 ms, with observed values ranging from 75.15 ms to 85.28 ms. As expected, this stage is more expensive than a single signature operation because it combines multiple cryptographic steps, but it still remained below 100 ms in the local setup.

By contrast, approximate proof revelation required only 0.96 ms on average. In this simplified benchmark setting, proof decryption itself was therefore not the dominant cost. These measurements, however, do not include real browser-based WebAuthn or YubiKey PRF interaction.

Overall, the results for `ring size = 8` indicate that the main performance cost lies in local ring-signature computation and full message-pack construction rather than in proof revelation. For the

current prototype, the default 1-of-8 configuration provides a reasonable balance between privacy and usability.

As a supplementary observation, several backend API latencies were also inspected through the browser developer tools. Under the local deployment setup, `POST /message`, `GET /message/list/by\_username/:username`, and `POST /validation-requests` required approximately 66.57 ms, 53.44 ms, and 47.61 ms, respectively. These values remained within the same general range as, or below, the local message-pack generation cost, which further suggests that the current prototype is more constrained by client-side cryptographic processing than by server-side storage or routing.

5.4 Limitations and Edge Cases

Although the prototype demonstrates the engineering feasibility of anonymous messaging, public verification, and later authorship revelation, several limitations and edge cases remain and should be considered when interpreting the evaluation results.

First, the current system is still a research prototype, and its server-side WebAuthn logic has not yet reached production-level completeness. The frontend supports browser-based registration and authentication flows, and the backend manages challenges, sessions, and credentials, but attestation verification during registration and assertion verification during login are not yet fully implemented. The evaluation therefore demonstrates workflow feasibility rather than deployment-ready authentication assurance.

Second, the system depends strongly on hardware support. The current design assumes a YubiKey, or another authenticator, that supports the WebAuthn PRF extension. If the browser, operating system, or hardware token does not provide this capability, one-time key derivation and proof decryption cannot proceed as intended.

Third, the anonymity-set size is fixed in the current implementation. The default configuration uses a 1-of-8 ring, consisting of one real public key and seven decoy keys. This is sufficient for prototype validation, but both anonymity strength and computational cost are directly influenced by the ring size.

Finally, the core cryptographic workflow is executed in the browser, so correctness and security still depend in part on the integrity of the client environment. Loss of the original hardware token also removes the ability to reveal authorship later, interrupted validation requests are handled mainly through application-level status updates, and metadata such as timestamps, request relationships, and ownership transfers may still introduce correlation risks.

Taken together, these limitations clarify the present scope of the project. The main contribution of the current prototype is to validate the feasibility of the mechanism itself. Future work may extend this foundation with production-grade WebAuthn verification, more flexible ring-size selection, stronger recovery handling, and improved metadata protection.

6 Conclusion and Future Work

6.1 Summary of Achievements

The objectives achieved by the project so far can be summarized into the following six levels:

1. **Established a Comprehensive Full-stack Monorepo Architecture**
    - Organized a three-tier structure (frontend, backend, and shared libraries) using pnpm workspaces.

- Unified use of TypeScript across both frontend and backend, with reusable shared types and utility functions.
- Supported parallel development and unified builds (root directory scripts have been configured).

2. **Implemented the Main WebAuthn-based Authentication Workflow**
   - Backend provides endpoints for registration challenges, registration completion, login challenges, login completion, and session queries.
   - Frontend completed the implementation of registration and login flows using the browser's WebAuthn API.
   - Implemented subsequent interface authentication via session tokens (Header or Bearer).
   - Supported session persistence and recovery (session can be retrieved after page refresh).
3. **Implemented the Business Closed-loop for Message Packs as Transferable Assets**
   - Supported the creation of Message Packs (Content + Memo + CredentialId).
   - Supported querying by ID and by username lists.
   - Supported ownership transfer (change of owner).
   - Data models and indexes are persisted in the database, providing basic retrieval performance.
4. **Implemented Identity Validation Request Workflows**
   - Supported initiating requests (requester → responder).
   - Supported querying "Requests I Sent" and "Requests I Received."
   - Responders can execute respond/refuse actions;
   - Requesters can write final results: Passed/Failed/Error.
   - Backend implemented state machine constraints and protection against illegal state transitions.
5. **Implemented Cryptographic Message Signing and Verification (Shared Library + Frontend)**
   - Implemented signing, serialization, and verification based on ristretto255 / linkable ring signature (LRS).
   - Used PRF for key derivation combined with AES-GCM for encapsulating internal proofs.
   - Frontend supports generating Message Packs, verifying signatures, importing/exporting Message Packs, and triggering the verification process.
6. **Implemented a Deployable and Runnable Local Environment**
   - Orchestrated PostgreSQL, API, and Nginx using docker-compose.
   - Nginx supports HTTP-to-HTTPS redirection and reverse proxying for /api.
   - init.sql includes core table structures and indexes for initialization capabilities.
   - API integrates Swagger documentation (/docs) and healthz/readyz monitoring endpoints.

6.2 Future Directions

We would contribute to the project in the future by implementing the following features:

1. **UI Enhancements and User Experience Improvements**
   - Implement a more intuitive and visually appealing user interface for message composition and verification.
   - Add real-time notifications for incoming messages and verification requests.
   - Provide better error handling and user feedback during cryptographic operations.
2. **Bug catching and Fixing**
   - Conduct thorough testing to identify and fix any bugs or edge cases that may arise during usage.
   - Implement additional unit and integration tests to ensure the robustness of the system.
3. **Performance Optimization**
   - Optimize cryptographic operations to reduce latency, especially for larger messages or higher volumes of messages.
   - Explore caching strategies for frequently used keys or signatures to improve performance.

References

[1] Shen Noether, Ring Signature Confidential Transactions for Monero, Cryptology ePrint Archive, Paper 2015/1098, 2015. Available at `https://eprint.iacr.org/2015/1098`

[2] Tim Cappalli, Michael B. Jones, Akshay Kumar, Emil Lundberg, and Matthew Miller, Web Authentication: An API for accessing Public Key Credentials - Level 3, W3C Candidate Recommendation Snapshot, January 2026. Available at `https://www.w3.org/TR/webauthn-3/`