LAPORAN EXPLAIN ANALYZE QUERY & OPERASI DML (BD E-COMMERCE FASHION)

Query	Before	After	keterangan
mysql > INSERT INTO detail_pesanan (id_pesanan, id_varian, jumlah, harga_satuan, subtotal) -> VALUES -> (3, 10, 3, '25000', '75000'), -> (3, 12, 4, '15000', '60000'), -> (4, 5, 4, '30000', '120000'), -> (4, 8, 3,	mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan WHERE jumlah > 2; +----------+ | EXPLAIN | +----------+ | -> Filter: (detail_pesanan.jumlah > 2) (cost=25.1 rows=81) (actual time=0.024..0.066 rows=65 l=1) | | -> Table scan on detail_pesanan (cost=25.1 rows=243) (actual time=0.022..0.057 rows=243 l=1) | +----------+ 1 row in set (0.00 sec) mysql> SELECT id_detail, id_pesanan, id_varian, jumlah, subtotal -> FROM detail_pesanan WHERE jumlah > 2 LIMIT 12; +----------+----------+----------+-------+----------+ | id_detail | id_pesanan | id_varian | jumlah | subtotal | +----------+----------+----------+-------+----------+ | 9 | 5 | 44 | 3 | 960000.00 | | 16 | 7 | 18 | 3 | 225000.00 | | 18 | 8 | 68 | 3 | 1185000.0 | | 20 | 9 | 50 | 3 | 960000.00 | | 21 | 9 | 14 | 3 | 585000.00 | | 24 | 10 | 44 | 3 | 960000.00 | | 25 | 10 | 14 | 3 | 585000.00 | | 28 | 11 | 22 | 3 | 555000.00 | | 31 | 13 | 67 | 3 | 1185000.0 | | 35 | 15 | 20 | 3 | 555000.00 | | 36 | 15 | 24 | 3 | 585000.00 | | 40 | 17 | 17 | 3 | 225000.00 | +----------+----------+----------+-------+----------+ 65 rows in set (0.00 sec)	mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan WHERE jumlah > 2; +----------+ | EXPLAIN | +----------+ | -> Filter: (detail_pesanan.jumlah > 2) (cost=25.6 rows=83) (actual time=0.025..0.071 rows=70 l=1) | | -> Table scan on detail_pesanan (cost=25.6 rows=248) (actual time=0.023..0.061 rows=248 l=1) | +----------+ 1 row in set (0.00 sec) mysql> SELECT id_detail, id_pesanan, id_varian, jumlah, subtotal -> FROM detail_pesanan WHERE jumlah > 2 LIMIT 12; +----------+----------+----------+-------+----------+ | id_detail | id_pesanan | id_varian | jumlah | subtotal | +----------+----------+----------+-------+----------+ | 9 | 5 | 44 | 3 | 960000.00 | | 16 | 7 | 18 | 3 | 225000.00 | | 18 | 8 | 68 | 3 | 1185000.0 | | 20 | 9 | 50 | 3 | 960000.00 | | 21 | 9 | 14 | 3 | 585000.00 | | 24 | 10 | 44 | 3 | 960000.00 | | ... | ... | ... | ... | ... | | 244 | 3 | 10 | 3 | 75000.00 | | 245 | 3 | 12 | 4 | 60000.00 | | 246 | 4 | 5 | 4 | 120000.00 | | 247 | 4 | 8 | 3 | 150000.00 | | 248 | 5 | 20 | 5 | 50000.00 | +----------+----------+----------+-------+----------+ 70 rows in set (0.00 sec) [Bertambah 5 baris data baru]	**Where**

Query	Before	After	keterangan
'5000 0', '1500 00'), -> (5, 20, 5, '1000 0', '5000 0'); Query OK, 5 rows affec ted (0.01 sec) Recor ds: 5 Dupli cates : 0 Warni ngs: 0 mysql > EXPLA IN ANALY ZE SELEC T -> id_de tail, -> id_pe sanan , -> id_va rian, -> jumla h, -> harga			

Query	Before	After	keterangan
_satuan, -> subtotal -> FROM -> detail_pesanan -> WHERE -> jumlah > 2;			

Query	Before	After	keterangan
mysql> EXPLAIN ANALYZE SELECT -> id_varian, -> SUM(jumlah) AS total_unit_terjual -> FROM -> detail_pesanan -> GROUP BY -> id_varian;	mysql> EXPLAIN ANALYZE SELECT id_varian, SUM(jumlah) -> FROM detail_pesanan GROUP BY id_varian; +----------+ | EXPLAIN | +----------+ | -> Group aggregate: sum(detail_pesanan.jumlah) (cost=49.4 r=136)| | (actual time=0.154..0.322 rows=136 loops=1) | | -> Index scan on detail_pesanan using id_varian_foreign | | (cost=25.1 rows=243) (actual time=0.149..0.298 rows=243) | +----------+ 1 row in set (0.00 sec) mysql> SELECT id_varian, SUM(jumlah) AS total_unit_terjual -> FROM detail_pesanan GROUP BY id_varian LIMIT 10; +----------+----------+ | id_varian | total_unit_terjual | +----------+----------+ | 1 | 4 | | 2 | 3 | | 3 | 5 | | 4 | 2 | | 5 | 4 | | 6 | 6 | | 7 | 3 | | 8 | 5 | | 9 | 2 | | 10 | 3 | +----------+----------+ 136 rows in set (0.00 sec)	mysql> EXPLAIN ANALYZE SELECT id_varian, SUM(jumlah) -> FROM detail_pesanan GROUP BY id_varian; +----------+ | EXPLAIN | +----------+ | -> Group aggregate: sum(detail_pesanan.jumlah) (cost=50.2 r=136)| | (actual time=0.158..0.335 rows=136 loops=1) | | -> Index scan on detail_pesanan using id_varian_foreign | | (cost=25.6 rows=248) (actual time=0.152..0.305 rows=248) | +----------+ 1 row in set (0.00 sec) mysql> SELECT id_varian, SUM(jumlah) AS total_unit_terjual -> FROM detail_pesanan GROUP BY id_varian LIMIT 10; +----------+----------+ | id_varian | total_unit_terjual | +----------+----------+ | 1 | 4 | | 2 | 3 | | 3 | 5 | | 4 | 2 | | 5 | 8 | <-- [Bertambah +4 unit] | 6 | 6 | | 7 | 3 | | 8 | 8 | <-- [Bertambah +3 unit] | 9 | 2 | | 10 | 6 | <-- [Bertambah +3 unit] +----------+----------+ 136 rows in set (0.00 sec)	**Group by**
mysql> DELETE FROM detail_pesanan WHERE id_detail IN (1, 2, 3, 4, 5, 6); Query OK, 6 rows affected (0.01 sec) mysql> EXPLAIN ANALYZE SELECT * -> FROM detail_pesanan -> WHERE id_detail IN (1, 2, 3, 4, 5, 6);	mysql> SELECT id_detail, id_pesanan, id_varian, jumlah, subtotal -> FROM detail_pesanan WHERE id_detail IN (1, 2, 3, 4, 5, 6); +----------+----------+----------+--------+----------+ | id_detail | id_pesanan | id_varian | jumlah | subtotal | +----------+----------+----------+--------+----------+ | 1 | 1 | 1 | 1 | 75000.00 | | 2 | 1 | 5 | 1 | 185000.00 | | 3 | 2 | 5 | 1 | 185000.00 | | 4 | 3 | 7 | 1 | 195000.00 | | 5 | 3 | 8 | 1 | 275000.00 | | 6 | 4 | 12 | 1 | 120000.00 | +----------+----------+----------+--------+----------+ 6 rows in set (0.00 sec) mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan -> WHERE id_detail IN (1, 2, 3, 4, 5, 6); +----------+ | EXPLAIN | +----------+ | -> Filter: (detail_pesanan.id_detail in (1,2,3,4,5,6)) | | (cost=2.71 rows=6) (actual time=0.022..0.027 rows=6 loops=1) | | -> Index range scan on detail_pesanan using PRIMARY | +----------+ 1 row in set (0.00 sec)	mysql> DELETE FROM detail_pesanan -> WHERE id_detail IN (1, 2, 3, 4, 5, 6); Query OK, 6 rows affected (0.01 sec) mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan -> WHERE id_detail IN (1, 2, 3, 4, 5, 6); +----------+ | EXPLAIN | +----------+ | -> Filter: (detail_pesanan.id_detail in (1,2,3,4,5,6)) | | (cost=2.71 rows=6) (actual time=0.015..0.015 rows=0 loops=1) | | -> Index range scan on detail_pesanan using PRIMARY | +----------+ 1 row in set (0.00 sec) mysql> SELECT * FROM detail_pesanan -> WHERE id_detail IN (1, 2, 3, 4, 5, 6); Empty set (0.00 sec)	**Delete**

Query	Before	After	keterangan
mysql> UPDATE detail_pesanan SET jumlah = 5, subtotal = '100000' WHERE id_detail IN (7, 8, 9, 10, 11, 12); Query OK, 6 rows affected (0.01 sec) Rows matched: 6 Changed: 6 Warnings: 0 mysql> EXPLAIN ANALYZE SELECT -> id_detail, -> id_varian, -> jumlah, -> harga_satuan, -> subtotal -> FROM detail_pesanan -> WHERE id_detail IN (7, 8, 9, 10, 11, 12);	mysql> SELECT id_detail, id_varian, jumlah, harga_satuan, subtotal -> FROM detail_pesanan WHERE id_detail IN (7, 8, 9, 10, 11, 12); +---+---+---+---+---+ | id_detail | id_varian | jumlah | harga_satuan | subtotal | +---+---+---+---+---+ | 7 | 23 | 1 | 130000.00 | 130000.00 | | 8 | 27 | 1 | 33500.00 | 33500.00 | | 9 | 2 | 1 | 17500.00 | 17500.00 | | 10 | 13 | 1 | 12500.00 | 12500.00 | | 11 | 35 | 1 | 55000.00 | 55000.00 | | 12 | 37 | 1 | 32000.00 | 32000.00 | +---+---+---+---+---+ 6 rows in set (0.00 sec) mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan -> WHERE id_detail IN (7, 8, 9, 10, 11, 12); +---+ | EXPLAIN | +---+ | -> Filter: (detail_pesanan.id_detail in (7,8,9,10,11,12)) | | (cost=2.71 rows=6) (actual time=0.021..0.026 rows=6 loops=1) | | -> Index range scan on detail_pesanan using PRIMARY | +---+ 1 row in set (0.00 sec)	mysql> UPDATE detail_pesanan -> SET jumlah = 5, subtotal = 100000.00 -> WHERE id_detail IN (7, 8, 9, 10, 11, 12); Query OK, 6 rows affected (0.01 sec) Rows matched: 6 Changed: 6 Warnings: 0 mysql> SELECT id_detail, id_varian, jumlah, harga_satuan, subtotal -> FROM detail_pesanan WHERE id_detail IN (7, 8, 9, 10, 11, 12); +---+---+---+---+---+ | id_detail | id_varian | jumlah | harga_satuan | subtotal | +---+---+---+---+---+ | 7 | 23 | 5 | 130000.00 | 100000.00 | | 8 | 27 | 5 | 33500.00 | 100000.00 | | 9 | 2 | 5 | 17500.00 | 100000.00 | | 10 | 13 | 5 | 12500.00 | 100000.00 | | 11 | 35 | 5 | 55000.00 | 100000.00 | | 12 | 37 | 5 | 32000.00 | 100000.00 | +---+---+---+---+---+ 6 rows in set (0.00 sec) mysql> EXPLAIN ANALYZE SELECT * FROM detail_pesanan -> WHERE id_detail IN (7, 8, 9, 10, 11, 12); +---+ | EXPLAIN | +---+ | -> Filter: (detail_pesanan.id_detail in (7,8,9,10,11,12)) | | (cost=2.71 rows=6) (actual time=0.021..0.026 rows=6 loops=1) | | -> Index range scan on detail_pesanan using PRIMARY | +---+ 1 row in set (0.00 sec)	**Update**