



Texturing

Texturing: Definition and Application




Texturing

- Map 1D, 2D or 3D images to geometric primitives
- Applications:
 - Simulate materials: wood, granite, bricks
 - Replace complex geometry
 - Simulating natural phenomena (reflection, refraction, lens flares, etc...)



Textures

- 1D
 - A pixel line
- 2D
 - Regular image
- 3D
 - Volumes, as if the object was sculpted from a material






Textures - Usage

- Definition
 - Load an image
 - Create a texture in OpenGL
 - Define texture parameters
- Application
 - Define geometric transformation for texture (if applicable)
 - Define texture coordinates



Textures - Application

- Textures have their own coordinate system (s , t and r axes)
- Define a mapping between the vertices and coordinates in the texture.





Textures - Application

- When defining vertex coordinates, specify also the texture coordinates.


```
glBindTexture(GL_TEXTURE_2D, texID);  
glBegin(GL_QUADS);  
    glTexCoord2f(0,0);glVertex3f(-1.0f, -1.0f, 0.0f);  
    glTexCoord2f(1,0);glVertex3f( 1.0f, -1.0f, 0.0f);  
    glTexCoord2f(1,1);glVertex3f( 1.0f,  1.0f,  0.0f);  
    glTexCoord2f(0,1);glVertex3f(-1.0f,  1.0f,  0.0f);  
glEnd();
```

Note: for each vertex, texture coordinates must be defined BEFORE vertex coordinates.



Textures - Application

```
glBindTexture(GL_TEXTURE_2D, texID);  
glBegin(GL_QUADS);  
    glTexCoord2f(0,0); glVertex3f(-1.0f, -1.0f, 0.0f);  
    glTexCoord2f(1,0); glVertex3f( 1.0f, -1.0f, 0.0f);  
    glTexCoord2f(1,1); glVertex3f( 1.0f,  1.0f, 0.0f);  
    glTexCoord2f(0,1); glVertex3f(-1.0f,  1.0f, 0.0f);  
glEnd();
```





Textures - Application


- Using VBOs
 - Setup:
 - Create an array with texture coordinates
 - Create a buffer and copy the array data to the buffer
 - Rendering
 - Bind buffer
 - Semantics
 - Draw



Textures - Application

- Applying geometric transformations to textures

```
glMatrixMode(GL_TEXTURE);  
glTranslatef(0.5,0,0);  
glRotatef(45,0,0,1);  
  
glMatrixMode(GL_MODELVIEW);  
glBegin(GL_QUADS);  
...  
glEnd();
```





Textures - Definition

```
// Assume an image has been loaded and that w and h contain the width
// and height of the image respectively.
// furthermore, assume that each pixel contains 4 unsigned bytes (RGBA)

int texName[1];

glGenTextures(1, texName);
glBindTexture(GL_TEXTURE_2D, texName[0]);
// wrapping parameters
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);
// filtering
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_LINEAR);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER, GL_LINEAR);


glTexImage2D(GL_TEXTURE_2D, 0, GL_RGBA, w, h,
             0, GL_RGBA, GL_UNSIGNED_BYTE, imageData);
```



Textures - Wrap


Clamp & Repeat

Original image




GL_CLAMP
GL_REPEAT


repeat both




repeat s, clamp t



repeat t, clamp s



clamp both






Textures - Filters: Mag

- When the texture needs to be expanded to fit the triangles on screen

GL_LINEAR **or** GL_NEAREST






Textures - Filters: Min

- When the texture is shrunk.

GL_LINEAR or GL_NEAREST





Textures - Filters

Mag:Nearest



May get too pixelated!





Textures - Filters

Mag: Linear




May get too blurry!





Textures - Mipmapping

- from Latin: “multum in parvo” (many things in a small place)
- Issue: when the texture is severely shrunk it glitters when the camera or objects move.
- Issue: aliasing



<http://www.tomshardware.com/reviews/ati,819-2.html>




http://http.developer.nvidia.com/GPUGems/gpugems_ch25.html



Textures - Mipmapping



- Mipmapping: Create multiple textures at different scales, as in a pyramid.
- For instance: original texture is 32 x 16
Provide also filtered textures: 16x8, 8x4, 4x2, 2x1, 1x1.





Textures - Mipmapping

- Mipmapping filtering:
 - choose more suitable level (NEAREST), or
 - A linear combination between the two more suitable levels (LINEAR)



Images taken from the Red Book



Textures - Mipmapping

4 filtering options for `GL_MIN_FILTER`:

`GL_NEAREST_MIPMAP_NEAREST`

`GL_LINEAR_MIPMAP_NEAREST`

`GL_NEAREST_MIPMAP_LINEAR`

`GL_LINEAR_MIPMAP_LINEAR`



Textures - Mipmapping

- GLU and GL (version 3.0+) allow the creation of mipmap levels.

- With GLU

```
// instead of glTexImage2D
gluBuild2DMipmaps(GL_TEXTURE_2D, GL_RGBA, imageWidth, imageHeight,
                  GL_RGBA, GL_UNSIGNED_BYTE, imageData);
```

- With GL

```
// call after glTexImage2D
glGenerateMipmap(GL_TEXTURE_2D);
```



Textures - Mipmapping

```
glBindTexture(GL_TEXTURE_2D, texName);

glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);

glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MAG_FILTER, GL_NEAREST);
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_MIN_FILTER,
                 GL_NEAREST_MIPMAP_NEAREST);

gluBuild2DMipmaps(GL_TEXTURE_2D, GL_RGB, imageWidth, imageHeight,
                  GL_RGB, GL_UNSIGNED_BYTE, imageData);
```



Textures: Final Color

- Mixing Texture and triangle's color.

- GL_REPLACE	$C = C_t$	$A = A_t$
- GL_MODULATE	$C = C_t * C_f$	$A = A_t * A_f$
- GL_BLEND	$C = C_f * (1 - C_t) + C_c * C_t$	$A = A_f * A_t$
- GL_DECAL	$C = C_f * (1 - A_t) + C_t * A_t$	$A = A_f$

f = fragment, t = texture, c = GL_TEXTURE_ENV_COLOR

```
glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, param);
```

```
glTexEnvfv(GL_TEXTURE_ENV, GL_TEXTURE_ENV_COLOR, param);
```



Textures: Transparency

- Drawing order is **relevant** for **partial** transparencies
- For **total** transparency the **alpha channel test** is an appropriate solution.
 - The test is performed before the Z-buffer is written and eliminates every pixel which fails the test ...
 - ... Hence, these pixels do not affect the Z buffer



Textures: Transparency

- Total Transparency total in OpenGL

```
glEnable(GL_ALPHA_TEST);  
glAlphaFunc(GL_GREATER, 0);
```





Textures: Transparency

- Partial transparency:
 - Ordering is crucial. Opaque elements must be drawn first
 - To compute the final color mix the two using weights for the fragment and textures colors.

$$Final\ color = C_t * S + C_f * D$$

$$S = Alphas; D = 1 - Alphas$$



Textures: Transparency

- OpenGL

```
glEnable(GL_BLEND);  
glBlendFunc(GL_SRC_ALPHA, GL_ONE_MINUS_SRC_ALPHA);
```

– Alternatively:

```
glEnable(GL_BLEND);  
glBlendFunc(GL_SRC_ALPHA, GL_ONE);
```



Textures

- 1D
 - `glTexImage1D(GL_TEXTURE_1D, ...)`
- 3D
 - `glTexImage3D(GL_TEXTURE_3D, ...)`



Textures

- OpenGL: The texturing functionality must be enabled.

```
glEnable(GL_TEXTURE_1D);  
glEnable(GL_TEXTURE_2D);  
glEnable(GL_TEXTURE_3D);
```




OpenGL – Environment Map

Cube Mapping



www.nvidia.com




Each texel represents a direction and its color is the color we would see if we were at the center of the cube looking in that direction



OpenGL – Environment Map

- Image Orientation





OpenGL – Environment Map





OpenGL – Environment Map

- Cube maps in OpenGL

```
glGenTextures(1, texName);  
glBindTexture(GL_TEXTURE_CUBE_MAP, texName[0]);  
  
for (i=0; i<6;i++) {
```

```
static GLenum faceTarget[6] = {  
    GL_TEXTURE_CUBE_MAP_POSITIVE_X,  
    GL_TEXTURE_CUBE_MAP_NEGATIVE_X,  
    GL_TEXTURE_CUBE_MAP_POSITIVE_Y,  
    GL_TEXTURE_CUBE_MAP_NEGATIVE_Y,  
    GL_TEXTURE_CUBE_MAP_POSITIVE_Z,  
    GL_TEXTURE_CUBE_MAP_NEGATIVE_Z  
};
```

```
    glTexParameteri(GL_TEXTURE_CUBE_MAP, GL_TEXTURE_MIN_FILTER, GL_LINEAR);  
    glTexParameteri(GL_TEXTURE_CUBE_MAP, GL_TEXTURE_MAG_FILTER, GL_LINEAR);  
  
    glTexImage2D(faceTarget[i], 0, GL_RGB, imageWidth, imageHeight,  
                 0, GL_RGB, GL_UNSIGNED_BYTE, imageData);  
}
```




OpenGL – Environment Map

- OpenGL: setup for reflective cube map

```
glEnable(GL_TEXTURE_CUBE_MAP);  
glEnable(GL_TEXTURE_GEN_S);  
glEnable(GL_TEXTURE_GEN_T);  
glEnable(GL_TEXTURE_GEN_R);  
glTexGeni(GL_S, GL_TEXTURE_GEN_MODE, GL_REFLECTION_MAP);  
glTexGeni(GL_T, GL_TEXTURE_GEN_MODE, GL_REFLECTION_MAP);  
glTexGeni(GL_R, GL_TEXTURE_GEN_MODE, GL_REFLECTION_MAP);
```




OpenGL – Environment Map

- Runtime (or not) cube map generation for rendered scenes:
 - Define a camera with a field of view of 90 degrees.
 - Aim the camera along the positive axis and capture the frame for the respective cube side
 - Repete for the remaining 5 directions



OpenGL – Environment Map

- In real time



www.nvidia.com



OpenGL – Environment Map

- “Ray Tracing”

