SPECIFICATIONS

1.0 Specifications Description: ***LED Greenhouse light fixture***

Quantity: 58+ one option to order 58 more.

Unit Type: *each*

Minimum Requirements: PTB8850LS41 PHOTOBIO CX 2125 850W (100-277V) with 10 cord w/ 5-15P plug

- 2125 umol/s Photon Flux @ 277V
- 2087 umol/s PPF
- 2.5 umol/J efficacy
- 850W high power LED with slim vertical profile (24.1L x 14.2W x 2.6H inches) and 22.7 lbs
- Superior canopy penetration by utilizing secondary optics
- Osram/Seoul diodes produce the S4 (Full) Spectrum
- 1:1 direct 1000W DE replacement utilizing similar footprint
- iLOC Integrated Light Output Control with digital screen for monitoring output levels
- Precisely control photon output when paired with Autopilot PX series controller (PX2 and above)
- Passive heat dissipating cooling fins
- Included LOC 0-10V control cable
- C clamps included
- Auto adjusting 120-277V input range
- 5 year warranty
- IP66 rated protection against water and dust
- Fully compatible with optional PHOTOBIO AC Power Distribution Tree cabling system 2125 umol/s Photon Flux @ 277V

2.0 Place of Delivery

USDA-ARS
ETSARC BRL
1616 Albrecht Blvd N
Fargo ND 58102

3.0 Delivery and Incidental Service Schedule

Item/Incidental Service	QTY	Unit	Place of Delivery	Delivery Date
PTB8850LS41 PHOTOBIO CX 2125 850W (100-277V) with 10 cord w/ 5-15P plug	58	each	1616 Albrecht Blvd N Fargo ND 58102	2 months after award
OPTION 1: PTB8850LS41 PHOTOBIO CX 2125 850W (100-277V) with 10 cord w/ 5-15P plug	58	each	1616 Albrecht Blvd N Fargo ND 58102	Within 180 days of award

4.0 Delivery Point of Contact

TBD

5.0 Additional Requirements

N/A