

Status

Finished

Started

Sunday, 12 January 2025, 6:57 PM

Completed

Sunday, 12 January 2025, 7:09 PM

Duration

12 mins 1 sec

Question 1

Correct

Flag question

You are transporting some boxes through a tunnel, where each box is a parallelepiped, and is characterized by its length, width and height.

The height of the tunnel **41** feet and the width can be assumed to be infinite. A box can be carried through the tunnel *only* if its height is strictly less than the tunnel's height. Find the volume of each box that can be successfully transported to the other end of the tunnel. Note: Boxes cannot be rotated.

Input Format

The first line contains a single integer  $n$ , denoting the number of boxes.  
 $n$  lines follow with three integers on each separated by single spaces - **length**, **width** and **height**, which are length, width and height in feet of the  $i$ -th box.

Constraints

$1 \leq n \leq 100$   
 $1 \leq \text{length}, \text{width}, \text{height}_i \leq 100$

Output Format

For every box from the input which has a height lesser than **41** feet, print its volume in a separate line.

Sample Input 0

```
4
5 5 5
1 2 40
10 5 41
7 2 42
```

Sample Output 0

```
125
80
```

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main() {
3     int n;
4     scanf("%d",&n);
5     for(int i=0;i<n;i++) {
6         int l,b,h;
7         scanf("%d %d %d",&l,&b,&h);
8         if(h<41) {
9             int v=l*b*h;
10            printf("%d\n",v);
11        }
12    }
13 }
```

	Input	Expected	Got	
✓	4 5 5 5 1 2 40 10 5 41 7 2 42	125 80	125 80	✓

Passed all tests! ✓

You are given  $n$  triangles, specifically, their sides  $a_i$ ,  $b_i$  and  $c_i$ . Print them in the same style but sorted by their areas from the smallest one to the largest one. It is guaranteed that all the areas are different.

The best way to calculate a volume of the triangle with sides  $a$ ,  $b$  and  $c$  is Heron's formula:

$$S = \sqrt{p(p-a)(p-b)(p-c)} \text{ where } p = (a+b+c)/2.$$

Input Format

First line of each test file contains a single integer  $n$ .  $n$  lines follow with  $a_i$ ,  $b_i$  and  $c_i$  on each separated by single spaces.

Constraints

$$1 \leq n \leq 100$$

$$1 \leq a_i, b_i, c_i \leq 70$$

$$a_i + b_i > c_i, a_i + c_i > b_i \text{ and } b_i + c_i > a_i$$

Output Format

Print exactly  $n$  lines. On each line print 3 integers separated by single spaces, which are  $a_i$ ,  $b_i$  and  $c_i$  of the corresponding triangle.

Sample Input 0

```
3
7 24 25
5 12 13
3 4 5
```

Sample Output 0

```
3 4 5
5 12 13
7 24 25
```

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 #include <math.h>
3 #include <stdlib.h>
4 typedef struct{
5     double area;
6     int a,b,c;
7 }Tri;
8
9 double cal_area(int a,int b,int c) {
10     double p=(a+b+c)/2.0;
11     return sqrt(p*(p-a)*(p-b)*(p-c));
12 }
13 int compare(const void*x,const void*y){
14     Tri *t1=(Tri *)x;
15     Tri *t2=(Tri *)y;
16     if(t1->area < t2->area) return -1;
17     if(t1->area > t2->area) return 1;
18     return 0;
19 }
20 int main() {
21     int n;
22     scanf("%d",&n);
23     Tri tris[n];
24
25     for (int i=0;i<n;i++) {
26         int a,b,c;
27         scanf("%d %d %d",&a,&b,&c);
28
29         tris[i].a=a;
30         tris[i].b=b;
31         tris[i].c=c;
32         tris[i].area=cal_area(a,b,c);
33     }
34     qsort(tris,n,sizeof(Tri),compare);
35     for(int i=0;i<n;i++) {
36         printf("%d %d %d\n",tris[i].a,tris[i].b,tris[i].c);
37     }
38     return 0;
39 }
```

	Input	Expected	Got	
✓	3 7 24 25 5 12 13 3 4 5	3 4 5 5 12 13 7 24 25	3 4 5 5 12 13 7 24 25	✓

Passed all tests! ✓