



Referencia de API

API REST sobre HTTP con cuerpos JSON. Este documento se genera directamente desde el esquema OpenAPI de la aplicación, así que refleja exactamente las rutas montadas en la versión indicada.

245

OPERACIONES

159

RUTAS

45

GRUPOS

0.0.1

VERSIÓN

ANTES DE EMPEZAR

Convenciones

Base y alcance por cuenta

Casi todo el API vive bajo una cuenta. El identificador de la cuenta va en la ruta, y el token debe tener acceso a esa cuenta o la respuesta es 401/403.

```
# patrón general
https://tu-dominio/api/v1/accounts/{account_id}/<recurso>
# los reportes viven en v2
https://tu-dominio/api/v2/accounts/{account_id}/reports/summary
```

Autenticación

Compatible con Devise Token Auth (el mismo esquema de Chatwoot). Tras POST /auth/sign_in se reciben tres valores que hay que reenviar en cada llamada:

```
access-token: <token>
client:       <client-id>
uid:         <email>
```

Los tokens no rotan por request: el par (client, access-token) se mantiene estable, así que se puede guardar y reutilizar.

Errores

El cuerpo del error se emite tal cual, **sin** envolverlo bajo una clave **detail** — compatible byte a byte con Chatwoot.

```
{ "message": "Conversation not found" }
{ "errors": ["You need to sign in or sign up before continuing."] }
```

Paginación

Los listados aceptan **page** (base 1). El tamaño depende del recurso: 25 para conversaciones, 15 para contactos, 100 para adjuntos. Cuando el listado devuelve totales, viajan en **meta**.

Sobre este documento. Está generado desde el esquema en vivo. Para el detalle completo de los cuerpos de cada petición y respuesta, la aplicación expone además la documentación interactiva en /docs (Swagger UI) y el esquema crudo en /openapi.json.

MAPA

Índice por área

Cuenta y acceso	26	Conversaciones	34
Contactos	17	Bandejas y canales	27
Automatización	47	Campañas	6
Help Center	15	Reportes	12
Extensibilidad	33	Endpoints públicos	19
Webhooks entrantes	9		

REFERENCIA

Cuenta y acceso

Autenticación, perfil, cuentas, agentes y equipos.

auth 6 operaciones

POST /auth/confirmation
Apply Confirmation Endpoint
POST /auth/confirmation — mark the user confirmed + sign them in.
[cuerpo JSON](#)

POST /auth/password
Request Password Reset Endpoint
POST /auth/password — always 200, no enumeration.
[cuerpo JSON](#)

PUT /auth/password
Apply Password Reset Endpoint
PUT /auth/password — apply the reset, mint a fresh session.
[cuerpo JSON](#)

POST /auth/sign_in
Sign In
Authenticate email+password, return user payload + auth headers.
[cuerpo JSON](#)

DELETE /auth/sign_out
Sign Out
DELETE /auth/sign_out — drop the current client's session.

POST /resend_confirmation
Resend Confirmation Endpoint
POST /resend_confirmation — always 204, no enumeration.
[cuerpo JSON](#)

profile 2 operaciones

GET /api/v1/profile
Show Profile
GET /api/v1/profile — renders _user.json.builder for the current user. Same body as the /auth/sign_in response sans the rotated auth headers (no token rotation on read).

PUT /api/v1/profile
Update Profile
PUT /api/v1/profile — partial update.
[cuerpo JSON](#)

accounts 7 operaciones

POST /api/v1/accounts
Create Account
Chatwoot's POST /api/v1/accounts — signup.
[cuerpo JSON](#)

GET /api/v1/accounts/{account_id}
Show Account
GET /api/v1/accounts/:id — account detail.

PATCH /api/v1/accounts/{account_id}
Update Account
PATCH /api/v1/accounts/:id — partial update.
[cuerpo JSON](#)

GET /api/v1/accounts/{account_id}/agents
List Agents
GET /api/v1/accounts/:id/agents — list of users in the account.

POST /api/v1/accounts/{account_id}/agents
Create Agent
POST /api/v1/accounts/:account_id/agents — invite an agent.
[cuerpo JSON](#)

PATCH /api/v1/accounts/{account_id}/agents/{user_id}
Update Agent
PATCH /api/v1/accounts/:account_id/agents/:id.
[cuerpo JSON](#)

DELETE /api/v1/accounts/{account_id}/agents/{user_id}
Destroy Agent
DELETE /api/v1/accounts/:account_id/agents/:id — remove the account membership. The User row stays (it may belong to other accounts; orphan sweep is a follow-up worker).

teams 9 operaciones

GET /api/v1/accounts/{account_id}/teams
List Teams
GET /api/v1/accounts/:account_id/teams — list all teams.

POST /api/v1/accounts/{account_id}/teams
Create Team Endpoint
POST /api/v1/accounts/:account_id/teams — admin-only.
[cuerpo JSON](#)

GET /api/v1/accounts/{account_id}/teams/{team_id}
Show Team
GET /api/v1/accounts/:account_id/teams/:id — any member.

PATCH /api/v1/accounts/{account_id}/teams/{team_id}
Update Team Endpoint
PATCH /api/v1/accounts/:account_id/teams/:id — admin-only.
[cuerpo JSON](#)

DELETE /api/v1/accounts/{account_id}/teams/{team_id}
Destroy Team
DELETE /api/v1/accounts/:account_id/teams/:id — admin-only.

GET /api/v1/accounts/{account_id}/teams/{team_id}/team_members**List Team Members**

GET .../teams/:team_id/team_members — list member agents.

POST /api/v1/accounts/{account_id}/teams/{team_id}/team_members**Create Team Members**

POST .../team_members — add agents.

cuerpo JSON

PATCH /api/v1/accounts/{account_id}/teams/{team_id}/team_members**Update Team Members**

PATCH .../team_members — replace the agent set (add new, drop missing).

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/teams/{team_id}/team_members**Destroy Team Members**

DELETE .../team_members — remove listed agents.

cuerpo JSON

health 2 operaciones**GET** /
Root

Chatwoot returns a JSON object at '/' with version info — mirror that shape.

GET /health
Health

Liveness + dependency status.

REFERENCIA**Conversaciones**

La bandeja: hilos, mensajes, participantes, filtros y acciones masivas.

conversations 19 operaciones**GET** /api/v1/accounts/{account_id}/conversations
Index Conversations

GET /conversations — delegates to conversation_finder.

assignee_type status inbox_id team_id labels q page

POST /api/v1/accounts/{account_id}/conversations**Create Conversation Endpoint**

POST /conversations.

cuerpo JSON

POST /api/v1/accounts/{account_id}/conversations/filter**Filter Conversations**

POST /conversations/filter — custom filter-DSL endpoint.

cuerpo JSON page

GET /api/v1/accounts/{account_id}/conversations/meta

Meta Conversations

GET /conversations/meta — counts only, no payload.

assignee_type status

GET /api/v1/accounts/{account_id}/conversations/search

Search Conversations

GET /conversations/search — text search across message content.

q assignee_type page

GET /api/v1/accounts/{account_id}/conversations/{display_id}

Show Conversation

PATCH /api/v1/accounts/{account_id}/conversations/{display_id}

Update Conversation

PATCH /conversations/:id.

cuerpo JSON

POST /api/v1/accounts/{account_id}/conversations/{display_id}/assignments

Create Assignment

POST /conversations/:id/assignments — assign agent or team.

cuerpo JSON

GET /api/v1/accounts/{account_id}/conversations/{display_id}/attachments

List Attachments

GET /conversations/:id/attachments.

page

POST /api/v1/accounts/{account_id}/conversations/{display_id}/custom_attributes

Set Custom Attributes

POST /conversations/:id/custom_attributes — replace the JSONB blob. Rails returns the show partial after save.

cuerpo JSON

GET /api/v1/accounts/{account_id}/conversations/{display_id}/labels

List Labels

GET /conversations/:id/labels — current label list.

POST /api/v1/accounts/{account_id}/conversations/{display_id}/labels

Set Labels

POST /conversations/:id/labels — replace the label set.

cuerpo JSON

POST /api/v1/accounts/{account_id}/conversations/{display_id}/mute

Mute Conversation

POST /conversations/:id/mute — Rails returns head :ok.

POST /api/v1/accounts/{account_id}/conversations/{display_id}/toggle_priority

Toggle Priority Endpoint

POST /conversations/:id/toggle_priority — Rails returns head :ok.

cuerpo JSON

POST /api/v1/accounts/{account_id}/conversations/{display_id}/toggle_status

Toggle Status Endpoint

POST /conversations/:id/toggle_status.

cuero **JSON**

POST /api/v1/accounts/{account_id}/conversations/{display_id}/toggle_typing_status

Toggle Typing Status

POST /conversations/:id/toggle_typing_status.

cuero **JSON**

POST /api/v1/accounts/{account_id}/conversations/{display_id}/unmute

Unmute Conversation

POST /conversations/:id/unmute — Rails returns head :ok.

POST /api/v1/accounts/{account_id}/conversations/{display_id}/unread

Mark Unread

POST /conversations/:id/unread.

POST /api/v1/accounts/{account_id}/conversations/{display_id}/update_last_seen

Update Last Seen Endpoint

POST /conversations/:id/update_last_seen.

messages 4 operaciones

GET /api/v1/accounts/{account_id}/conversations/{conversation_id}/messages

Index Messages

GET /conversations/:conv_id/messages.

before **after**

POST /api/v1/accounts/{account_id}/conversations/{conversation_id}/messages

Create Message Endpoint

POST /conversations/:conv_id/messages.

cuero **JSON**

PATCH /api/v1/accounts/{account_id}/conversations/{conversation_id}/messages/{message_id}

Update Message

PATCH /conversations/:conv_id/messages/:id — API inbox only.

cuero **JSON**

DELETE /api/v1/accounts/{account_id}/conversations/{conversation_id}/messages/{message_id}

Destroy Message

DELETE /conversations/:conv_id/messages/:id.

participants 4 operaciones

GET /api/v1/accounts/{account_id}/conversations/{conversation_id}/participants

Show Participants

GET .../participants — the conversation's watcher list.

POST /api/v1/accounts/{account_id}/conversations/{conversation_id}/participants

Create Participants

POST .../participants — add user_ids; renders the full list.

cuero **JSON**

PATCH /api/v1/accounts/{account_id}/conversations/{conversation_id}/participants**Update Participants**

PATCH .../participants — reconcile the set to exactly user_ids.

cuerpo **JSON****DELETE** /api/v1/accounts/{account_id}/conversations/{conversation_id}/participants**Destroy Participants**

DELETE .../participants — remove user_ids → Rails head :ok.

cuerpo **JSON****attachments** 2 operaciones**GET** /api/v1/accounts/{account_id}/attachments/{attachment_id}**Serve Attachment**

Stream a stored attachment's bytes (account-scoped).

GET /public/attachments/{attachment_id}**Serve Public Attachment**

Stream an attachment to an unauthenticated caller holding a valid signature.

exp**sig****custom_views** 4 operaciones**GET** /api/v1/accounts/{account_id}/custom_filters**Index Custom Views**

List the current user's saved views for this account + filter_type.

filter_type**POST** /api/v1/accounts/{account_id}/custom_filters**Create Custom View****cuerpo** **JSON****PATCH** /api/v1/accounts/{account_id}/custom_filters/{view_id}**Update Custom View****cuerpo** **JSON****DELETE** /api/v1/accounts/{account_id}/custom_filters/{view_id}**Destroy Custom View**

DELETE /custom_filters/:id — 200 + empty body (matches Rails).

filter_type**bulk_actions** 1 operaciones**POST** /api/v1/accounts/{account_id}/bulk_actions**Create Bulk Action**

Apply fields to the conversations named by ids (display ids).

cuerpo **JSON****REFERENCIA****Contactos**

Personas, sus atributos, notas y segmentos.

contacts 17 operaciones

POST /api/v1/accounts/{account_id}/actions/contact_merge**Contact Merge**

POST /actions/contact_merge — fold mergee into base.

cuero **JSON****GET** /api/v1/accounts/{account_id}/contacts**Index Contacts**

GET /contacts — paginated list, optionally filtered by company.

page**include_contact_inboxes****company****POST** /api/v1/accounts/{account_id}/contacts**Create Contact Endpoint**

POST /contacts — create contact (+ optionally ContactInbox).

cuero **JSON****GET** /api/v1/accounts/{account_id}/contacts/companies**Index Companies**

GET /contacts/companies — the account's contacts rolled up by company_name ([{"name", "count"}, ...], count desc).

POST /api/v1/accounts/{account_id}/contacts/filter**Filter Contacts Endpoint**

POST /contacts/filter — contact filter-DSL (backs segments).

cuero **JSON****page****GET** /api/v1/accounts/{account_id}/contacts/search**Search Contacts**

GET /contacts/search — ILIKE on name/email/phone/identifier.

q**page****include_contact_inboxes****GET** /api/v1/accounts/{account_id}/contacts/{contact_id}**Show Contact**

GET /contacts/:id.

include_contact_inboxes**PATCH** /api/v1/accounts/{account_id}/contacts/{contact_id}**Update Contact Endpoint**

PATCH /contacts/:id — update + deep-merge JSONB blobs.

cuero **JSON****include_contact_inboxes****DELETE** /api/v1/accounts/{account_id}/contacts/{contact_id}**Destroy Contact**

DELETE /contacts/:id — admin-only.

POST /api/v1/accounts/{account_id}/contacts/{contact_id}/contact_inboxes**Create Contact Inbox**

POST /contacts/:contact_id/contact_inboxes.

cuero **JSON****GET** /api/v1/accounts/{account_id}/contacts/{contact_id}/contactable_inboxes**Contactable Inboxes**

GET /contacts/:id/contactable_inboxes.

POST /api/v1/accounts/{account_id}/contacts/{contact_id}/destroy_custom_attributes

Destroy Custom Attributes

POST /contacts/:id/destroy_custom_attributes.

cuerpo **JSON**

GET /api/v1/accounts/{account_id}/contacts/{contact_id}/notes

Index Notes

GET /contacts/:contact_id/notes — latest-first.

POST /api/v1/accounts/{account_id}/contacts/{contact_id}/notes

Create Note

POST /contacts/:contact_id/notes.

cuerpo **JSON**

GET /api/v1/accounts/{account_id}/contacts/{contact_id}/notes/{note_id}

Show Note

GET /contacts/:contact_id/notes/:id.

PATCH /api/v1/accounts/{account_id}/contacts/{contact_id}/notes/{note_id}

Update Note

PATCH /contacts/:contact_id/notes/:id.

cuerpo **JSON**

DELETE /api/v1/accounts/{account_id}/contacts/{contact_id}/notes/{note_id}

Destroy Note

DELETE /contacts/:contact_id/notes/:id → head :ok.

REFERENCIA

Bandejas y canales

Alta y configuración de cada canal conectado.

inboxes 10 operaciones

POST /api/v1/accounts/{account_id}/inbox_members

Create Inbox Members

POST /inbox_members — add agents.

cuerpo **JSON**

PATCH /api/v1/accounts/{account_id}/inbox_members

Update Inbox Members

PATCH /inbox_members — replace the agent set.

cuerpo **JSON**

DELETE /api/v1/accounts/{account_id}/inbox_members

Destroy Inbox Members

DELETE /inbox_members — remove listed agents.

cuerpo **JSON**

GET /api/v1/accounts/{account_id}/inbox_members/{inbox_id}

Show Inbox Members

GET /inbox_members/:inbox_id — list member agents.

GET /api/v1/accounts/{account_id}/inboxes**List Inboxes**

GET /api/v1/accounts/:account_id/inboxes — list inboxes.

POST /api/v1/accounts/{account_id}/inboxes**Create Inbox**

POST /api/v1/accounts/:account_id/inboxes — admin-only.

cuerpo JSON**GET** /api/v1/accounts/{account_id}/inboxes/{inbox_id}**Show Inbox**

GET /api/v1/accounts/:account_id/inboxes/:id — show.

PATCH /api/v1/accounts/{account_id}/inboxes/{inbox_id}**Update Inbox Endpoint**

PATCH /api/v1/accounts/:account_id/inboxes/:id — admin-only.

cuerpo JSON**DELETE** /api/v1/accounts/{account_id}/inboxes/{inbox_id}**Destroy Inbox**

DELETE /api/v1/accounts/:account_id/inboxes/:id — admin-only.

POST /api/v1/accounts/{account_id}/inboxes/{inbox_id}/reset_secret**Reset Secret Endpoint**

POST /api/v1/accounts/:account_id/inboxes/:id/reset_secret.

whatsapp-templates 2 operaciones**GET** /api/v1/accounts/{account_id}/inboxes/{inbox_id}/whatsapp/templates**List Templates**

Approved templates cached on the channel.

POST /api/v1/accounts/{account_id}/inboxes/{inbox_id}/whatsapp/templates/sync**Sync Templates Endpoint**

Refresh the cached templates from Meta, then return the approved set.

instagram-connect 5 operaciones**GET** /api/v1/accounts/{account_id}/instagram_channels/connect/start**Connect Start**

Begin the Facebook Login OAuth — returns the dialog URL the admin's browser should be redirected to (with a signed state). Full feature set incl. delete media (requires a Facebook Page).

GET /api/v1/accounts/{account_id}/instagram_channels/connect/start_instagram**Connect Start Instagram**

Begin the Instagram Login OAuth — no Facebook Page required, but DELETE media is not available on this flow.

POST /api/v1/accounts/{account_id}/instagram_channels/connect_manual**Connect Manual Endpoint**

Create an Instagram inbox+channel from a pasted token and record its login_type (capabilities).

cuerpo JSON**GET** /api/v1/accounts/{account_id}/instagram_channels/{channel_id}/settings**Show Channel Settings**

Connection capabilities for a channel (login_type + whether DELETE media is available).

GET /api/v1/instagram/oauth/callback

Oauth Callback

Meta's OAuth redirect target. The account travels in the signed state; capability + channel creation happen here.

code state page_id error

instagram-publishing 5 operaciones

GET /api/v1/accounts/{account_id}/instagram_posts

Index Posts

state page

POST /api/v1/accounts/{account_id}/instagram_posts

Create Post Endpoint

Create a publish request.

cuerpo JSON

GET /api/v1/accounts/{account_id}/instagram_posts/{post_id}

Show Post

DELETE /api/v1/accounts/{account_id}/instagram_posts/{post_id}

Delete Post Endpoint

Delete a published post on Instagram + flip the row to deleted. Only published posts can be removed on Meta (other states 422). Meta-side restrictions (carousel children, ad-promoted posts, live video) surface as a 422 with the Meta error code.

GET /api/v1/accounts/{account_id}/instagram_posts/{post_id}/products

Index Post Products

The catalogue products linked to a post/story (CRM/AI context).

instagram-comments 5 operaciones

DELETE /api/v1/accounts/{account_id}/instagram_comments/{comment_id}

Delete Comment Endpoint

POST /api/v1/accounts/{account_id}/instagram_comments/{comment_id}/hide

Hide Comment Endpoint

cuerpo JSON

POST /api/v1/accounts/{account_id}/instagram_comments/{comment_id}/replies

Reply Comment Endpoint

cuerpo JSON

GET /api/v1/accounts/{account_id}/instagram_posts/{post_id}/comments

Index Comments

Live-fetch comments for the post's media from Meta, upsert the local mirror, and return the stored rows (hidden included).

POST /api/v1/accounts/{account_id}/instagram_posts/{post_id}/comments

Create Comment Endpoint

cuerpo JSON

REFERENCIA

Automatización

Reglas, macros, respuestas, etiquetas, bots y asignación.

automation-rules 6 operaciones

GET /api/v1/accounts/{account_id}/automation_rules

Index Rules

POST /api/v1/accounts/{account_id}/automation_rules

Create Rule Endpoint

POST returns the bare object — Rails' create.json.builder does not wrap. (show/update do.)

[cuerpo JSON](#)**GET** /api/v1/accounts/{account_id}/automation_rules/{rule_id}

Show Rule

PATCH /api/v1/accounts/{account_id}/automation_rules/{rule_id}

Update Rule Endpoint

[cuerpo JSON](#)**DELETE** /api/v1/accounts/{account_id}/automation_rules/{rule_id}

Destroy Rule Endpoint

DELETE → Rails head :ok (HTTP 200, empty body).

POST /api/v1/accounts/{account_id}/automation_rules/{rule_id}/clone

Clone Rule Endpoint

macros 6 operaciones

GET /api/v1/accounts/{account_id}/macros

Index Macros

POST /api/v1/accounts/{account_id}/macros

Create Macro Endpoint

[cuerpo JSON](#)**GET** /api/v1/accounts/{account_id}/macros/{macro_id}

Show Macro

PATCH /api/v1/accounts/{account_id}/macros/{macro_id}

Update Macro Endpoint

[cuerpo JSON](#)**DELETE** /api/v1/accounts/{account_id}/macros/{macro_id}

Destroy Macro Endpoint

DELETE /macros/:id → Rails head :ok (HTTP 200, empty body).

POST /api/v1/accounts/{account_id}/macros/{macro_id}/execute

Execute Macro Endpoint

POST /macros/:id/execute — Rails enqueues MacrosExecutionJob + head :ok. We run inline (see service docstring).

[cuerpo JSON](#)

canned_responses 4 operaciones

GET /api/v1/accounts/{account_id}/canned_responses

Index Canned Responses

[search](#)

POST /api/v1/accounts/{account_id}/canned_responses

Create Canned Response Endpoint

cuerpo JSON

PATCH /api/v1/accounts/{account_id}/canned_responses/{canned_response_id}

Update Canned Response Endpoint

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/canned_responses/{canned_response_id}

Destroy Canned Response Endpoint

DELETE → Rails head :ok (HTTP 200, empty body).

labels 5 operaciones

GET /api/v1/accounts/{account_id}/labels

Index Labels

GET /labels — admin OR agent.

POST /api/v1/accounts/{account_id}/labels

Create Label Endpoint

POST /labels — admin only.

cuerpo JSON

GET /api/v1/accounts/{account_id}/labels/{label_id}

Show Label

PATCH /api/v1/accounts/{account_id}/labels/{label_id}

Update Label Endpoint

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/labels/{label_id}

Destroy Label Endpoint

DELETE /labels/:id — Rails head :ok (200, empty body).

custom_attributes 5 operaciones

GET /api/v1/accounts/{account_id}/custom_attribute_definitions

Index Definitions

GET /custom_attribute_definitions — optionally filtered by model.

attribute_model

POST /api/v1/accounts/{account_id}/custom_attribute_definitions

Create Definition Endpoint

POST /custom_attribute_definitions.

cuerpo JSON

GET /api/v1/accounts/{account_id}/custom_attribute_definitions/{definition_id}

Show Definition

PATCH /api/v1/accounts/{account_id}/custom_attribute_definitions/{definition_id}

Update Definition Endpoint

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/custom_attribute_definitions/{definition_id}

Destroy Definition

DELETE /custom_attribute_definitions/:id → head :no_content.

working-hours 3 operaciones

GET /api/v1/accounts/{account_id}/inboxes/{inbox_id}/working_hours

Index For Inbox

PATCH /api/v1/accounts/{account_id}/inboxes/{inbox_id}/working_hours

Bulk Update Endpoint

Accepts {working_hours: [{...}, {...}, ...]} and bulk updates the inbox's 7 rows by day_of_week.

cuerpo JSON

PATCH /api/v1/accounts/{account_id}/working_hours/{working_hour_id}

Update One

cuerpo JSON

agent-bots 8 operaciones

GET /api/v1/accounts/{account_id}/agent_bots

Index Bots

POST /api/v1/accounts/{account_id}/agent_bots

Create Bot Endpoint

cuerpo JSON

GET /api/v1/accounts/{account_id}/agent_bots/{bot_id}

Show Bot

PATCH /api/v1/accounts/{account_id}/agent_bots/{bot_id}

Update Bot Endpoint

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/agent_bots/{bot_id}

Destroy Bot Endpoint

POST /api/v1/accounts/{account_id}/agent_bots/{bot_id}/reset_secret

Reset Secret Endpoint

POST /api/v1/accounts/{account_id}/inboxes/{inbox_id}/set_agent_bot

Set Agent Bot

POST /inboxes/{id}/set_agent_bot — attach a bot.

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/inboxes/{inbox_id}/set_agent_bot

Delete Agent Bot

assignment_policies 8 operaciones

GET /api/v1/accounts/{account_id}/assignment_policies

Index Assignment Policies

POST /api/v1/accounts/{account_id}/assignment_policies

Create Assignment Policy

cuerpo JSON

GET /api/v1/accounts/{account_id}/assignment_policies/{policy_id}

Show Assignment Policy

PATCH /api/v1/accounts/{account_id}/assignment_policies/{policy_id}

Update Assignment Policy

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/assignment_policies/{policy_id}

Destroy Assignment Policy

DELETE → Rails head :ok (HTTP 200, empty body).

GET /api/v1/accounts/{account_id}/inboxes/{inbox_id}/assignment_policy

Show Inbox Assignment Policy

POST /api/v1/accounts/{account_id}/inboxes/{inbox_id}/assignment_policy

Create Inbox Assignment Policy

Attach a policy to the inbox, replacing any existing one.

cuerpo JSON

DELETE /api/v1/accounts/{account_id}/inboxes/{inbox_id}/assignment_policy

Destroy Inbox Assignment Policy

DELETE → Rails head :ok (HTTP 200, empty body).

csat 2 operaciones**GET** /api/v1/accounts/{account_id}/csat_survey_responses

Index Responses

GET /csat_survey_responses → top-level array of resources.

rating user_ids inbox_id team_id since until page

GET /api/v1/accounts/{account_id}/csat_survey_responses/metrics

Metrics

GET /csat_survey_responses/metrics — aggregate counts.

since until

REFERENCIA**Campañas**

Envíos continuos por widget y envíos puntuales programados.

campaigns 6 operaciones**GET** /api/v1/accounts/{account_id}/campaigns

Index Campaigns

POST /api/v1/accounts/{account_id}/campaigns

Create Campaign Endpoint

cuerpo JSON

GET /api/v1/accounts/{account_id}/campaigns/{display_id}

Show Campaign

PATCH	<code>/api/v1/accounts/{account_id}/campaigns/{display_id}</code> Update Campaign Endpoint cuerpo JSON
DELETE	<code>/api/v1/accounts/{account_id}/campaigns/{display_id}</code> Destroy Campaign Endpoint
GET	<code>/api/v1/accounts/{account_id}/campaigns/{display_id}/analytics</code> Campaign Analytics Endpoint GET /campaigns:id/analytics — delivery metrics for the campaign: conversations created + the sent/delivered/read/failed breakdown of its outgoing messages.

REFERENCIA

Help Center

Portales, categorías y artículos.

portals 15 operaciones

GET	<code>/api/v1/accounts/{account_id}/portals</code> Index Portals
POST	<code>/api/v1/accounts/{account_id}/portals</code> Create Portal Endpoint cuerpo JSON
GET	<code>/api/v1/accounts/{account_id}/portals/{slug}</code> Show Portal
PATCH	<code>/api/v1/accounts/{account_id}/portals/{slug}</code> Update Portal Endpoint cuerpo JSON
DELETE	<code>/api/v1/accounts/{account_id}/portals/{slug}</code> Destroy Portal Endpoint
GET	<code>/api/v1/accounts/{account_id}/portals/{slug}/articles</code> Index Articles locale status category_id query
POST	<code>/api/v1/accounts/{account_id}/portals/{slug}/articles</code> Create Article Endpoint cuerpo JSON
GET	<code>/api/v1/accounts/{account_id}/portals/{slug}/articles/{article_id}</code> Show Article
PATCH	<code>/api/v1/accounts/{account_id}/portals/{slug}/articles/{article_id}</code> Update Article Endpoint cuerpo JSON
DELETE	<code>/api/v1/accounts/{account_id}/portals/{slug}/articles/{article_id}</code> Destroy Article Endpoint

GET	/api/v1/accounts/{account_id}/portals/{slug}/categories	Index Categories	locale
POST	/api/v1/accounts/{account_id}/portals/{slug}/categories	Create Category Endpoint	cuerpo JSON
PATCH	/api/v1/accounts/{account_id}/portals/{slug}/categories/{category_id}	Update Category Endpoint	cuerpo JSON
DELETE	/api/v1/accounts/{account_id}/portals/{slug}/categories/{category_id}	Destroy Category Endpoint	
POST	/api/v1/accounts/{account_id}/portals/{slug}/reindex	Reindex Portal Endpoint	Enqueue a semantic-search reindex of every article in the portal.

REFERENCIA

Reportes

Métricas, series temporales y exportes.

reports 12 operaciones

GET	/api/v2/accounts/{account_id}/live_reports/conversation_metrics	Live Conversation Metrics Endpoint	GET /live_reports/conversation_metrics — current snapshot.	team_id
GET	/api/v2/accounts/{account_id}/live_reports/grouped_conversation_metrics	Grouped Conversation Metrics	GET /live_reports/grouped_conversation_metrics?group_by=...	group_by team_id
GET	/api/v2/accounts/{account_id}/reports	Timeseries	GET /reports?metric=... — daily buckets for the line chart.	metric type id since until timezone_offset business_hours
GET	/api/v2/accounts/{account_id}/reports/bot_metrics	Bot Metrics Report	GET /reports/bot_metrics — the four bot-report numbers over the since..until window.	since until
GET	/api/v2/accounts/{account_id}/reports/conversation_traffic	Conversation Traffic	GET /reports/conversation_traffic — a heatmap of conversations created per (local date, hour-of-day) over the range.	since until timezone_offset

GET	/api/v2/accounts/{account_id}/reports/conversations	Conversations Metrics GET /reports/conversations?type=conversation — current-state counters used by the dashboard "live" widget when type=conversation. type
GET	/api/v2/accounts/{account_id}/reports/summary	Summary GET /reports/summary — the dashboard cards. type id since until business_hours timezone_offset
GET	/api/v2/accounts/{account_id}/summary_reports/agent	Agent Summary since until business_hours
GET	/api/v2/accounts/{account_id}/summary_reports/inbox	Inbox Summary since until business_hours
GET	/api/v2/accounts/{account_id}/summary_reports/label	Label Summary since until business_hours
GET	/api/v2/accounts/{account_id}/summary_reports/team	Team Summary since until business_hours
GET	/api/v2/accounts/{account_id}/summary_reports/{scope}/export	Export Summary Report GET /summary_reports/{scope}/export?format=csv xlsx — download the per-entity summary (agent/team/inbox/label) as a spreadsheet. format since until business_hours

REFERENCIA

Extensibilidad

Integraciones, webhooks salientes, tokens MCP y archivos.

integrations 5 operaciones

GET	/api/v1/accounts/{account_id}/integrations/apps	Index Apps GET /apps — static catalogue + each account's hooks.
GET	/api/v1/accounts/{account_id}/integrations/apps/{app_id}	Show App
POST	/api/v1/accounts/{account_id}/integrations/hooks	Create Hook Endpoint cuerpo JSON
PATCH	/api/v1/accounts/{account_id}/integrations/hooks/{hook_id}	Update Hook Endpoint cuerpo JSON

DELETE /api/v1/accounts/{account_id}/integrations/hooks/{hook_id}
Destroy Hook Endpoint

webhooks 4 operaciones

GET /api/v1/accounts/{account_id}/webhooks
Index Webhooks

POST /api/v1/accounts/{account_id}/webhooks
Create Webhook Endpoint
[cuerpo](#) [JSON](#)

PATCH /api/v1/accounts/{account_id}/webhooks/{webhook_id}
Update Webhook Endpoint
[cuerpo](#) [JSON](#)

DELETE /api/v1/accounts/{account_id}/webhooks/{webhook_id}
Destroy Webhook Endpoint

mcp-tokens 5 operaciones

GET /api/v1/accounts/{account_id}/mcp_tokens
Index Tokens

POST /api/v1/accounts/{account_id}/mcp_tokens
Create Token Endpoint
Mint a fresh token. The plain-text token value is included in the response body — this is the only time it's reachable.
[cuerpo](#) [JSON](#)

PATCH /api/v1/accounts/{account_id}/mcp_tokens/{token_id}
Update Token Endpoint
Rename or re-scope an existing token. The secret is **not** rotated — use POST /rotate for that. Response omits the secret.
[cuerpo](#) [JSON](#)

DELETE /api/v1/accounts/{account_id}/mcp_tokens/{token_id}
Destroy Token Endpoint
Revoke (hard-delete) a token. Empty 200 body — Chatwoot-style.

POST /api/v1/accounts/{account_id}/mcp_tokens/{token_id}/rotate
Rotate Token Endpoint
Mint a new secret in place. Returns the rotated row **WITH** the new secret in the body — clients still using the old one will start failing 401 immediately.

uploads 4 operaciones

POST /api/v1/accounts/{account_id}/uploads
Create Upload
Mint a pre-signed PUT URL for an attachment, namespaced under the account. Any account member may request one.
[cuerpo](#) [JSON](#)

POST /api/v1/accounts/{account_id}/uploads/blob**Upload Blob**

Server-side upload — the browser POSTs the file through our API and we store it. Use this when the object store isn't reachable from the browser (internal MinIO); returns {key, file_url}.

cuero **JSON****POST** /api/v1/accounts/{account_id}/uploads/instagram_media**Upload Instagram Media**

Stage media for an Instagram post.

cuero **JSON****GET** /public/media**Serve Public Media**

Stream an object-store blob to an unauthenticated caller holding a valid signature.

key**exp****sig****notifications** 7 operaciones**GET** /api/v1/accounts/{account_id}/notification_settings**Show Settings****PATCH** /api/v1/accounts/{account_id}/notification_settings**Update Settings Endpoint****cuero** **JSON****GET** /api/v1/accounts/{account_id}/notifications**Index Notifications**

GET /notifications — paginated, ?status=unread to filter.

page**status****POST** /api/v1/accounts/{account_id}/notifications/read_all**Mark All Notifications Read**

POST /notifications/read_all — Chatwoot returns head :ok; we mirror with an empty 200 body.

GET /api/v1/accounts/{account_id}/notifications/unread_count**Get Unread Count**

GET /notifications/unread_count — Rails returns a bare int.

DELETE /api/v1/accounts/{account_id}/notifications/{notification_id}**Destroy Notification****POST** /api/v1/accounts/{account_id}/notifications/{notification_id}/read**Mark Notification Read****notification_subscriptions** 3 operaciones**POST** /api/v1/notification_subscriptions**Create Subscription**

Register (or refresh) the caller's browser push subscription.

cuero **JSON**

DELETE /api/v1/notification_subscriptions**Destroy Subscription**

DELETE {endpoint} — drop the caller's subscription for that endpoint (Rails matches on the subscription token). head :ok.

cuerpo JSON**GET** /api/v1/notification_subscriptions/vapid_key**Vapid Key**

The public VAPID key the browser needs to subscribe. enabled is False when web-push isn't configured — the frontend hides the toggle.

products 5 operaciones**GET** /api/v1/accounts/{account_id}/products**Index Products**

enabled page

POST /api/v1/accounts/{account_id}/products**Create Product Endpoint****cuerpo** JSON**GET** /api/v1/accounts/{account_id}/products/{product_id}**Show Product****PATCH** /api/v1/accounts/{account_id}/products/{product_id}**Update Product Endpoint****cuerpo** JSON**DELETE** /api/v1/accounts/{account_id}/products/{product_id}**Delete Product Endpoint****REFERENCIA****Endpoints públicos**

Sin autenticación de agente: widget, encuestas y Help Center público.

widget 13 operaciones**GET** /api/v1/widget/campaigns**Widget Campaigns Index**

Mirror Api::V1::Widget::CampaignsController#index — the enabled ongoing campaigns on this widget's inbox. The SDK evaluates each campaign's trigger_rules client-side and posts a campaign.triggered event back when one matches.

website_token**POST** /api/v1/widget/config**Widget Config**

Bootstrap the widget — mint a contact + token if the request didn't carry a valid one.

website_token**GET** /api/v1/widget/contact**Widget Contact Show**

Mirror Api::V1::Widget::ContactsController#show.

website_token

PATCH /api/v1/widget/contact**Widget Contact Update**

Mirror Api::V1::Widget::ContactsController#update.

cuerpo JSON

website_token

POST /api/v1/widget/contact/set_user**Widget Contact Set User**

Mirror Api::V1::Widget::ContactsController#set_user.

cuerpo JSON

website_token

GET /api/v1/widget/conversations**Widget Conversation Index**

Mirror Api::V1::Widget::ConversationsController#index.

website_token

POST /api/v1/widget/conversations/toggle_status**Widget Toggle Status**

Mirror Api::V1::Widget::ConversationsController#toggle_status.

website_token

POST /api/v1/widget/conversations/toggle_typing**Widget Toggle Typing**

Mirror Api::V1::Widget::ConversationsController#toggle_typing.

cuerpo JSON

website_token

POST /api/v1/widget/conversations/update_last_seen**Widget Update Last Seen**

Mirror Api::V1::Widget::ConversationsController#update_last_seen.

website_token

POST /api/v1/widget/events**Widget Events**

Mirror Api::V1::Widget::EventsController#create — the widget's generic event bus. Today only campaign.triggered is handled: it runs the campaign conversation builder for the visitor's ContactInbox (ports CampaignListener#campaign_triggered).

cuerpo JSON

website_token

GET /api/v1/widget/messages**Widget Messages Index**

Mirror Api::V1::Widget::MessagesController#index.

before

website_token

POST /api/v1/widget/messages**Widget Messages Create**

Mirror Api::V1::Widget::MessagesController#create.

cuerpo JSON

website_token

POST /api/v1/widget/uploads**Widget Upload**

Pre-signed direct-upload URL for a widget visitor's attachment.

cuerpo JSON

website_token

GET /public/api/v1/csat_survey/{uuid}

Show Csat

PUT /public/api/v1/csat_survey/{uuid}

Update Csat

Extract the csat_survey_response block from message.submitted_values and persist via submit_csat_response.

cuerpo JSON

public-help-center 4 operaciones

GET /hc/{slug}

Show Portal

GET /hc/<slug> — the portal detail page payload.

GET /hc/{slug}/articles

Index Articles

Published articles for a portal, optionally filtered by locale, category slug, or a free-text query. Drafts + archived articles never surface here.

locale

category_slug

query

GET /hc/{slug}/articles/{article_slug}

Show Article

GET /hc/<slug>/articles/<article_slug> — single published article.

locale

GET /hc/{slug}/categories

Index Categories

Categories for a portal, optionally locale-filtered.

locale

REFERENCIA

Webhooks entrantes

Los proveedores publican acá. No se llaman desde tu código.

whatsapp-webhooks 2 operaciones

GET /webhooks/whatsapp/{phone_number}

Whatsapp Verify

Meta verification handshake.

hub.mode

hub.challenge

hub.verify_token

POST /webhooks/whatsapp/{phone_number}

Whatsapp Receive

Receive a WhatsApp webhook payload.

facebook-webhooks 2 operaciones

GET /bot

Facebook Verify

Meta verification handshake.

hub.mode

hub.challenge

hub.verify_token

POST

/bot

Facebook Receive

Receive a Messenger webhook payload.

instagram-webhooks 2 operaciones

GET

/webhooks/instagram

Instagram Verify

Meta verification handshake.

hub.modehub.challengehub.verify_token

POST

/webhooks/instagram

Instagram Receive

Receive an Instagram webhook payload.

twilio-webhooks 1 operaciones

POST

/twilio/callback

Twilio Receive

Receive a Twilio SMS webhook.

bandwidth-webhooks 1 operaciones

POST

/webhooks/sms/{phone_number}

Bandwidth Receive

Receive a Bandwidth SMS webhook.

telegram-webhooks 1 operaciones

POST

/webhooks/telegram/{bot_token}

Telegram Receive

Receive a Telegram Update payload.