



Incident report analysis

Summary	The company recently faced an incident where its internal network was compromised. Network services suddenly stopped responding, and the normal internal traffic was unable to access any resources for 2 hours until the issue could be resolved. Network logs show a flood of ICMP packets at the time of this incident, pointing towards a Denial of Service (DoS) attack. An investigation by the cybersecurity team suggests an unconfigured firewall to be the main vulnerability leading to this attack. To prevent such attacks from happening in future and to improve the company's security posture, several new policies and actions have been implemented.
Identify	To identify what caused this attack, an investigation was launched by the cybersecurity team. The investigation uncovered an unconfigured firewall, which allowed a malicious attacker to overwhelm the company's network by sending in a flood of ICMP pings in a DoS attack.
Protect	To protect the internal systems in future, the network security team has implemented several new steps. These include updating the firewall rules to limit the rate of incoming ICMP packets and verify source IP, implementing network monitoring software to detect abnormal network traffic patterns, and setting up Intrusion Detection and Prevention Systems to filter out suspicious ICMP packets.
Detect	The team will now use Intrusion Detection and Prevention Systems to detect and block suspicious ICMP traffic before it can cause any harm to internal network. In addition, network monitoring software will be used to detect abnormal patterns in network traffic to prevent DoS attacks.
Respond	The incident management team responded to the incident by blocking all

	incoming ICMP packets to halt the DoS attack. This was followed by stopping all non-critical network services offline to reduce internal traffic, providing more network resources for critical services to operate.
Recover	After containing the incident, enough resources were made available to restore critical services. Then once ICMP packets already in the network expired, other non-critical services were slowly restored, returning the network back to its normal functioning state.