We create chemistry

Safety Data Sheet
Luviset® P.U.R.

1. Identification

Product identifier used on the label

Luviset® P.U.R.

Recommended use of the chemical and restriction on use

Recommended use*: Polymer, cosmetic ingredient
Unsuitable for use: Not intended for sale to or use by the general public.

* The “Recommended use” identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:
BASF CORPORATION
100 Park Avenue
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

24 Hour Emergency Response Information
CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Synonyms:	not available use: cosmetic ingredient
INCI Name:	Polyurethane-1

2. Hazards Identification

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Flam. Liq.	3	Flammable liquids

Label elements

Pictogram:



Signal Word:
Warning

Hazard Statement:

H226	Flammable liquid and vapour.

Precautionary Statements (Prevention):

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves and eye protection or face protection.
P243	Take action to prevent static discharges.
P241	Use explosion-proof electrical, ventilating and lighting equipment.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P242	Use non-sparking tools.

Precautionary Statements (Response):

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder or water in copious quantities for extinction.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

3. Composition / Information on Ingredients

According to Regulation 2024 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Ethanol

CAS Number: 64-17-5
Content (W/W): >= 5.0 - <= 13.0%
Synonym: Ethanol; Ethyl alcohol

The actual concentration is withheld as a trade secret.
NJ TSRN: New Jersey Trade Secret Registry Number

4. First-Aid Measures

Description of first aid measures

General advice:
Remove contaminated clothing.

If inhaled:
Remove the affected individual into fresh air and keep the person calm. Seek medical attention.

If on skin:
Wash thoroughly with soap and water

If irritation develops, seek medical attention.

If in eyes:
Wash affected eyes for at least 15 minutes under running water with eyelids held open. If adverse health effects develop seek medical attention.

If swallowed:
Rinse mouth and then drink 200-300 ml of water.

Seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far
Hazards: No hazard is expected under intended use and appropriate handling.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:	Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
alcohol-resistant foam, carbon dioxide, dry powder, Water in copious quantities

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours
The product is combustible. Generation of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Further information:
Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures
Ensure adequate ventilation. Use breathing apparatus if exposed to vapours/dust/aerosol.

Environmental precautions
Do not empty into drains.

Substance/product is RCRA hazardous due to its properties.

Methods and material for containment and cleaning up
For large amounts: Dike spillage. Pump off product.
For residues: Pick up with suitable absorbent material.
Dispose of absorbed material in accordance with regulations.

7. Handling and Storage

Precautions for safe handling
Ensure thorough ventilation of stores and work areas. Keep container tightly sealed.

Protection against fire and explosion:
Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: Polyester resin, glass reinforced (Palatal A410), High density polyethylene (HDPE), Low density polyethylene (LDPE), Stove-lacquer RDL 50

Further information on storage conditions: Avoid all sources of ignition: heat, sparks, open flame.

Storage stability:
Storage temperature: 5 - 30 °C
Protect from temperatures below: 5 °C
Protect from temperatures above: 30 °C

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

Ethanol	ACGIH, US:	STEL value 1,000 ppm ;
	OSHA Z1:	PEL 1,000 ppm 1,900 mg/m3 ;
	NIO ID, US:	IDLH 3,300 ppm ; IDLH values based on the 1994 Revised Criteria
	NIO ID, US:	LEL 3.3 % ;

Advice on system design:
No further information, see section 7.

Personal protective equipment

Respiratory protection:
Wear respiratory protection if ventilation is inadequate. Gas filter for gases/vapours of organic compounds (boiling point >65 °C, e. g. EN 14387 Type A)

Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:
Wear chemical resistant protective gloves., Consult with glove manufacturer for testing data.

Eye protection:
Safety glasses with side-shields.

Body protection:
Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

9. Physical and Chemical Properties

Physical state:	liquid	
Form:	liquid	
Odour:	faint specific odour	
Odour threshold:	not determined	
Colour:	yellowish	
pH value:	8.0 - 9.0 (100 %(m)) (measured with the undiluted substance)	
Melting point:	approx. -10 °C	
Boiling point:	approx. 100 °C (1,013 mbar)	
Flash point:	41.5 °C	(DIN 51755)
Flammability:	Flammable.	
Lower explosion limit:	For liquids not relevant for classification and labelling.	
Upper explosion limit:	For liquids not relevant for classification and labelling.	
Autoignition:	not determined	
Vapour pressure:	37 mbar (20 °C) 197 mbar (50 °C)	
Density:	1.015 g/cm3 (15 °C)	
Relative vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not determined	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	not determined	

Viscosity, dynamic:	100 - 400 mPa.s (25 °C)
Viscosity, kinematic:	not determined
Solubility in water:	miscible
Evaporation rate:	Value can be approximated from Henry's Law Constant or vapor pressure.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section. No further information available.

10. Stability and Reactivity

Reactivity
When heated can give off ignitable vapours.

Oxidizing properties:
Based on its structural properties the product is not classified as oxidizing.

Chemical stability
The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions
Generation of flammable gases/vapours.

Conditions to avoid
See SDS section 7 - Handling and storage. Avoid all sources of ignition: heat, sparks, open flame.

Incompatible materials
No substances known that should be avoided.

Hazardous decomposition products

Decomposition products:
Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:
not determined

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. Virtually nontoxic after a single ingestion.

Oral
Type of value: LD50
Species: rat (male/female)
Value: > 2,000 mg/kg (OECD Guideline 423)

Dermal
Type of value: ATE
Value: > 5,000 mg/kg

Assessment other acute effects
Assessment of STOT single:
Based on available data, the classification criteria are not met.

Irritation / corrosion
Assessment of irritating effects: Not irritating to the skin. Not irritating to the eyes.

Skin
Species: rabbit
Result: non-irritant
Method: OECD Guideline 404

Eye
Species: rabbit
Result: non-irritant
Method: OECD Guideline 405

Sensitization
Assessment of sensitization: Skin sensitizing effects were not observed in animal studies.

Buehler test
Species: guinea pig
Result: Non-sensitizing.
Method: OECD Guideline 406

Aspiration Hazard
No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity
Assessment of repeated dose toxicity: Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses.

Genetic toxicity
Assessment of mutagenicity: The substance was not mutagenic in bacteria.

Carcinogenicity
Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect.

Information on: Ethanol
Assessment of reproduction toxicity: The potential to impair fertility cannot be excluded when given at high doses.
Significant overexposure during pregnancy may cause birth defects.

Teratogenicity
Assessment of teratogenicity: No data was available concerning toxicity to development.

Information on: Ethanol
Assessment of teratogenicity: At high doses there are indications of a developmental effect.
A teratogenic potential cannot be excluded.
---

12. Ecological Information

Toxicity

Aquatic toxicity
Assessment of aquatic toxicity:
There is a high probability that the product is not acutely harmful to aquatic organisms. The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Toxicity to fish
LC50 (96 h) > 10,000 mg/l, Brachydanio rerio (OECD 203; ISO 7346; 84/449/EWG, C.1, static)
The details of the toxic effect relate to the nominal concentration.

Aquatic invertebrates
EC50 (48 h) > 55.5 mg/l, Daphnia magna (OECD Guideline 202, part 1, static)
The statement of the toxic effect relates to the analytically determined concentration. The product has low solubility in the test medium. An eluate has been tested. No toxic effects occur within the range of solubility. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms
DIN EN ISO 8192-OECD 209-88/302/EEC,P. C aerobic
activated sludge, domestic/EC20 (0.5 h): > 1,000 mg/l

Persistence and degradability

Elimination information

20 - 30 % CO2 formation relative to the theoretical value (28 d) (ISO 14593) (aerobic, activated sludge, domestic)

Bioaccumulative potential

Assessment bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments
not applicable

13. Disposal considerations

Waste disposal of substance:
Dispose of in accordance with national, state and local regulations.

Container disposal:
Uncontaminated packaging can be re-used. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

RCRA: D001

14. Transport Information

Land transport
USDOT

Hazard class:	3
Packing group:	III
ID number:	UN 1170
Hazard label:	3
Proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Sea transport
IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1170
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

Air transport
IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1170
Hazard label:	3
Proper shipping name:	ETHANOL SOLUTION

15. Regulatory Information

Federal Regulations

Registration status:

Cosmetic	TSCA, US	released / exempt
Chemical	TSCA, US	blocked / not listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ	CAS Number	Chemical name
5000 LBS	71-36-3; 78-93-3	n-butanol; Methylethylketone
1000 LBS	75-07-0	acetaldehyde
100 LBS	64-17-5; 75-65-0	Ethanol; 2-methylpropan-2-ol

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including ETHANOL IN ALCOHOLIC BEVERAGES, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:
Health: 1 Fire: 2 Reactivity: 0 Special:

HMIS III rating
Health: 1 Flammability: 2 Physical hazard: 0

16. Other Information

SDS Prepared by:
BASF NA Product Regulations
SDS Prepared on: 2025/10/08

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Luviset® P.U.R. is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO

OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
Date / Revised: 2025/10/08 Version: 7.0
Date / Previous version: 2025/03/06 Previous version: 6.0

END OF DATA SHEET