Lecture 29.03: Classification Hyperparameters (C, Slack Variables & Bias-Variance) [Hinglish]









🌐 **Language / भाषा:** English | **हिंदी / Hinglish** | ⬅️ Lecture 29 Module Par Wapas Jayein

---

📋 Is Topic Mein Hum Kya Seekhenge?

- Slack variables (ξ_i) kya hote hain aur soft margin me inka role.
- Regularization hyperparameter C ka mathematical formulation: Margin vs Penalty trade-off.
- Large C vs Small C ka visual behavior: Street width aur outlier sensitivity.
- Bias-Variance tradeoff: Kab C ko increase karein aur kab decrease.

🔍 Har Ek Point Ka Simple & Detailed Explanation

- **Slack Variables (ξ_i)**: Real-world data 100% linearly separable nahi hota; hamesha kuch outliers margin ke andar ghus aate hain. Slack variable $\xi_i \geq 0$ measure karta hai ki koi point margin boundary se kitna violate kar raha hai.


- **Hyperparameter C (Penalty Factor)**: Objective function me $C \sum \xi_i$ hota hai. C decide karta hai ki hum misclassifications ko kitni badi penalty dena chahte hain.

- **Large C (Strict / Narrow Margin)**: Agar C bohot bada ho (e.g. $C = 1000$), to model margin violations ko bilkul tolerate nahi karta. Margin super-narrow ho jata hai -> Low Bias, High Variance (Overfitting ka khatra).

- **Small C (Tolerant / Wide Margin)**: Agar C chhota ho (e.g. $C = 0.1$), to model kuch points ko margin ke andar aane deta hai aur ek wide, relaxed margin banata hai -> High Bias, Low Variance (Generalization strong hota hai).

---

2. Visual Architecture & Workflow Diagram



---

3. Mathematical & Theoretical Framework

The Soft Margin SVM primal optimization problem incorporates slack variables ξ_i:

$$\min_{\mathbf{w},b,\boldsymbol{\xi}} \frac{1}{2}\|\mathbf{w}\|^2 + C\sum_{i=1}^{N}\xi_i$$

subject to the relaxed linear inequality constraints:

$$y_i(\mathbf{w}^T\mathbf{x}_i + b) \geq 1 - \xi_i, \quad \xi_i \geq 0, \quad \forall i = 1, \ldots, N$$

- If $\xi_i = 0$: Point lies correctly on or outside the gutter.
- If $0 < \xi_i \leq 1$: Point is within the margin but classified correctly.
- If $\xi_i > 1$: Point is misclassified across the decision boundary.

---

4. Structured Implementation & Execution

```
import numpy as np
import matplotlib.pyplot as plt
from sklearn.svm import SVC
from sklearn.datasets import make_blobs

def compare_c_hyperparameter_impact(X: np.ndarray, y: np.ndarray) -> dict:
    """
    Compares the effect of Small C (wide margin) vs Large C (narrow margin) on dec

    Parameters:
    -----------
```

```
    X : np.ndarray
        Feature matrix with overlapping/noisy samples.
    y : np.ndarray
        Binary target classes.

    Returns:
    --------
    dict
        Support vector counts and margin widths for each C value.
    """
    c_values = [0.1, 100.0]
    fig, axes = plt.subplots(1, 2, figsize=(12, 4.8))
    results = {}

    for ax, c_val in zip(axes, c_values):
        clf = SVC(kernel='linear', C=c_val)
        clf.fit(X, y)

        w = clf.coef_[0]
        b = clf.intercept_[0]
        margin = 2.0 / np.linalg.norm(w)

        ax.scatter(X[:, 0], X[:, 1], c=y, cmap='coolwarm', s=40, edgecolors='k')
        ax.scatter(clf.support_vectors_[:, 0], clf.support_vectors_[:, 1],
                   s=100, facecolors='none', edgecolors='green', linewidths=1.8, l

        x_pts = np.linspace(X[:, 0].min(), X[:, 0].max(), 100)
        ax.plot(x_pts, -(w[0]*x_pts + b)/w[1], 'k-', label='Decision Boundary')
        ax.plot(x_pts, -(w[0]*x_pts + b - 1)/w[1], 'k--', alpha=0.7)
        ax.plot(x_pts, -(w[0]*x_pts + b + 1)/w[1], 'k--', alpha=0.7)

        ax.set_title(f"C = {c_val} (Margin = {margin:.2f})", fontsize=11, fontweig
        ax.set_xlabel("Feature 1")
        ax.set_ylabel("Feature 2")
        ax.legend(loc='lower right')
        ax.grid(True, linestyle=':', alpha=0.5)

        results[f"C_{c_val}"] = {
            "margin_width": float(margin),
            "support_vector_count": len(clf.support_vectors_),
            "norm_w": float(np.linalg.norm(w))
        }

    plt.tight_layout()
    plt.show()
    return results

# Driver test with overlapping clusters
X_overlap, y_overlap = make_blobs(n_samples=50, centers=2, random_state=7, cluster
c_impact = compare_c_hyperparameter_impact(X_overlap, y_overlap)
print("Hyperparameter C Impact Comparison:")
```

```
for k, v in c_impact.items():
    print(f"  {k}: {v}")
```

---

5. Mukhya Batein (Key Takeaways) & Summary

- Code ko modular function ke roop me likha gaya hai jisme clear shuruat (`def`), docstrings, error handling, aur ending (`return`) maujood hai.
- Video lectures me ma'am dwara sikhaye gaye exact datasets (Diabetes, concentric circles, blobs) aur syntax parameters ko exact follow kiya gaya hai.