Lecture 28.07: Pruning Decision Trees

📌 Topic Overview

Decision Trees have a natural tendency to overfit because they greedily keep splitting until every single training sample is memorized. In this lecture, we explore why overfitting happens, the visual outlier node example, and the concept of **Pruning**.

⚠️ Why Decision Trees Overfit

A Decision Tree will continue splitting until every leaf node is 100% pure, even if it has to create deeply nested branches for a single noise sample!

The Blackboard Outlier Example

In the lecture, the instructor draws a node containing:

> $$[14y, 1n]$$

- 14 samples are `Yes`.
- Only 1 sample is `No` (an outlier or data error).

Without restrictions, the tree splits this node into:

- Branch 1: $[14y, 0n]$ (Leaf node)
- Branch 2: $[0y, 1n]$ (Leaf node)

Problem: The tree created an entirely new depth level just to isolate a single outlier! When evaluated:

- **Training accuracy**: 100%
- **Testing accuracy**: Very poor! This is the classic definition of **Overfitting**: $extTrainingAccuracy \gg extTestingAccuracy$.

✂️ What is Pruning?

> **Pruning is a technique used in Decision Trees to remove parts of the tree that are unnecessary, in order to reduce overfitting and improve performance on unseen test data.**

Just as a gardener prunes overgrown branches to keep a plant healthy, we cut off noisy branches of a decision tree.

🌲 Two Main Pruning Approaches

On the blackboard, the instructor explains the two fundamental pruning paradigms:

```
flowchart TD
P["Pruning Strategies"] --> Pre["1. Pre-Pruning (Early Stopping)"]
P --> Post["2. Post-Pruning (Cost-Complexity)"]

Pre --> Pre1["max_depth"]
Pre --> Pre2["min_samples_leaf"]
Pre --> Pre3["min_samples_split"]

Post --> Post1["Grow full tree first"]
Post --> Post2["Prune bottom-up using ccp_alpha"]
```

1. Pre-Pruning (Early Stopping)

- We stop the tree from growing before it becomes too complex.
- We draw a horizontal cutoff line using constraints like:
- `max_depth = 4`
- `min_samples_leaf = 5`

2. Post-Pruning

- We let the tree grow completely until all leaves are pure.
- Then, we inspect the tree from the bottom up and trim away branches that do not provide significant predictive benefit.

💻 Python Implementation: Demonstrating Overfitting

```
from sklearn.datasets import make_classification
from sklearn.model_selection import train_test_split
from sklearn.tree import DecisionTreeClassifier
```

```
X, y = make_classification(n_samples=500, n_features=15, n_informative=8, random_s
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.3, random_st

# Unpruned tree (default)
unpruned = DecisionTreeClassifier(random_state=42)
unpruned.fit(X_train, y_train)

print("--- UNPRUNED DECISION TREE ---")
print(f"Train Accuracy: {unpruned.score(X_train, y_train):.4f}")
print(f"Test Accuracy:  {unpruned.score(X_test, y_test):.4f}")
print("Overfitting Gap:", unpruned.score(X_train, y_train) - unpruned.score(X_test
```

🔑 Key Takeaways

1. Unconstrained decision trees memorize noise and outliers (e.g., splitting a $[14y, 1n]$ node).
2. Overfitting occurs when $extTrainingAccuracy \gg extTestingAccuracy$.
3. **Pruning** trims unnecessary branches to restore generalization.
4. Pruning can be done during growth (**Pre-pruning**) or after full growth (**Post-pruning**).