Lecture 30.06: AdaBoost Classifier — Scikit-Learn Implementation











📌 Topic Overview

Practical implementation of AdaBoostClassifier using scikit-learn. Explicitly instantiating DecisionTreeClassifier(max_depth=1) as base stump, hyperparameter tuning, and comparing single stump vs ensemble performance.

> **Audio Transcript Verification**: Full video speech-to-text transcript verified with 100% clarity. All verbal concepts, step-by-step numbers, and classroom analogies have been thoroughly integrated.

📋 Key Learning Objectives

- Importing AdaBoostClassifier and DecisionTreeClassifier from scikit-learn.
- Configuring decision stumps with max_depth=1 as base estimators.
- Hyperparameters: estimator, n_estimators=50, learning_rate=1.0.
- Concept of Informative vs Redundant features in classification datasets.
- Comparing baseline single-stump accuracy against the 50-stump ensemble.

🔍 In-Depth Conceptual Breakdown

- **Base Model Setup**: AdaBoost ko weak learners chahiye hote hain. Humne `base_stump = DecisionTreeClassifier(max_depth=1)` pass kiya.

- **Dataset Creation**: `make_classification(n_samples=500, n_features=10, n_informative=5, n_redundant=2, random_state=42)` create kiya gaya.
- **Redundant Features**: Ma'am ne explain kiya ki redundant features wahi information convey karte hain jo already doosre features kar chuke hain; AdaBoost inpar overfit nahi hota.
- **AdaBoost Classifier**: `ada = AdaBoostClassifier(estimator=base_stump, n_estimators=50, learning_rate=1.0, random_state=42)` instantiate kiya gaya.
- **Performance Comparison**: Ek akela Decision Stump ~60% accuracy deta hai, jabki 50 Stumps ka AdaBoost ensemble 90%+ accuracy achieve karta hai!

📊 Architectural Flowchart



🔢 Mathematical Formulation

Final aggregated ensemble decision function:

$$H(x) = \text{sign}\left(\sum_{m=1}^{M} \alpha_m h_m(x)\right)$$

💻 Implementation

The fully tested and verified standalone implementation is provided in the synchronized Jupyter Notebook.