Submodule 36.04: The Perceptron (In Depth)


1. Introduction & Historical Origins

The **Perceptron** is the simplest mathematical model of an artificial neuron and serves as the fundamental atomic building block of all modern deep learning architectures. It was invented in 1958 by **Frank Rosenblatt** at the Cornell Aeronautical Laboratory.

---

2. Mathematical Architecture of a Perceptron

A perceptron accepts multiple numerical input signals, computes a linear combination using synaptic weights and a bias term, and passes the result through an activation function to generate an output.



The Step-by-Step Mathematical Formulation:

Step 1: Input Features Vector

$$\mathbf{x} = \begin{bmatrix} x_1 \\ x_2 \\ \dots \\ x_n \end{bmatrix} \in \mathbb{R}^n$$

Step 2: Synaptic Weights Vector

$$\mathbf{w} = \begin{bmatrix} w_1 \\ w_2 \\ \dots \\ w_n \end{bmatrix} \in \mathbb{R}^n$$

- Weights quantify the importance or contribution of each corresponding input feature to the final prediction.

Step 3: Bias Term (b)

- Bias is an independent constant scalar added to the weighted sum.
- **Why is Bias Essential?** Without a bias term ($b = 0$), the linear decision boundary is constrained to pass through the origin $(0, 0, \ldots, 0)$. A non-zero bias shifts the activation threshold, allowing the model to fit data that does not pass through the origin.

Step 4: Net Input / Weighted Sum (z)

$$z = \sum_{i=1}^{n} w_i x_i + b = w_1 x_1 + w_2 x_2 + \cdots + w_n x_n + b$$

In compact vector dot-product notation:

$$z = \mathbf{w}^T \mathbf{x} + b$$

Step 5: Activation Function & Final Output

$$\hat{y} = f(z) = f(\mathbf{w}^T \mathbf{x} + b)$$

---

3. Why are Activation Functions Mandatory?


If an artificial neuron only calculated $z = \mathbf{w}^T \mathbf{x} + b$, stacking multiple layers of neurons would be mathematically equivalent to a single linear equation:

$$extLayer2Output = \mathbf{W}_2(\mathbf{W}_1 \mathbf{x} + \mathbf{b}_1) + \mathbf{b}_2 = (\mathbf{W}_2 \mathbf{W}_1)\mathbf{x} + (\mathbf{W}_2 \mathbf{b}_1 + \mathbf{b}_2) = \mathbf{W}'\mathbf{x}$$

No matter how many hidden layers are stacked, a purely linear network cannot solve non-linear problems. **Activation functions introduce non-linearity**, enabling neural networks to learn arbitrary, complex decision boundaries.

---

4. Key Activation Functions Introduced



1. Step Function (Threshold Logic Unit):

$$f(z) = \begin{cases} 1 & \text{if } z \ge 0 \\ 0 & \text{if } z < 0 \end{cases}$$

- *Limitation*: Non-differentiable at $z = 0$, with zero derivative everywhere else ($\frac{df}{dz} = 0$). Cannot be trained via modern gradient descent.

2. Sigmoid Activation Function:

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

- *Output Range*: $(0, 1)$
- *Properties*: Smooth, continuous, differentiable everywhere. Interpretable as a probability in binary classification.

3. ReLU (Rectified Linear Unit):

$$f(z) = \max(0, z)$$

- *Output Range*: $[0, \infty)$
- *Properties*: Computationally trivial ($O(1)$), does not saturate for positive inputs (mitigating vanishing gradients). Industry default for hidden layers.

---

5. The Complete Learning Cycle (Forward & Backward Pass)



1. **Forward Propagation**: Input data flows through weights, summation, and activation to compute prediction $\hat{y}$.
2. **Loss Calculation**: A loss function measures the discrepancy between predicted $\hat{y}$ and true ground-truth y.
3. **Backpropagation**: The chain rule of calculus propagates error gradients backward from output to input.
4. **Parameter Update (Optimizer)**: Optimization algorithms (like Stochastic Gradient Descent or Adam) update weights and biases to minimize loss:

$$w \leftarrow w - \eta \frac{\partial L}{\partial w}$$

where η represents the learning rate.

---

6. Visual Reference

