

INDEX

SL.No	Programs	Page No
PART A		
1	Write a C++ program to create a class with data members like principle amount,time and rate of interest. Create a member function to accept data values,to compute simple interest and to display the result.	4
2	Write a C++ program to perform the addition and subtraction of two complex numbers using member functions.	5-6
3	Write a C++ program to calculate the volume of cube,cylinder and cuboid using function overloading.	7
4	Write a C++ program to create a class 'distance' with data members feet and inches and member functions read() and show().Write a C++ program to add two distances by using object as function argument.(inches should not be >=12)	8
5	Write an object oriented program in C++ to create a library information system containing the following for a book in the library: Accession number,Author name,Title of book,Year of production,Publisher's name,cost of the book. Define a class with data members and suitable member functions for initializing and for destroying the data via constructor and destructor.	9-10
6	Create a class rectangle with length,breadth and area. Create another class cuboid that inherits rectangle and has additional members height and volume. Use single inheritance property.	11-12
7	Create a class containing the following data members Register No,Name and Fees. Also create a member function to read and display the data using the concept of pointers to object.	13
8	Write a C++ program to add, subtract, multiply and divide two numbers using class template.	14-15
9	Write a C++ program to create a class with data members a, b, c and member functions to input data, compute discriminants based on the following conditions and print the roots. <ul style="list-style-type: none"> ○ If discriminant = 0, print the roots are equal and their value. ○ If discriminant > 0, print the real roots and their values. ○ If discriminant < 0, print the roots are imaginary and exit the program 	16-17
10	Write a C++ program to compute the total marks and declare the results using array of objects. Assume that the class contains the data members - roll no, name, marks in 3 subjects. Result is calculated as follows. If student gets <35 fail. Otherwise various results are calculated on average as <ul style="list-style-type: none"> >=70 Distinction >=60 and <70 First class >=50 and <60 Second class else Pass class 	18-19
PART B		
11	Create a class 'Bank' which includes data members-Acno, Name, Balance and parameterized constructor to initialize the data members and other methods like deposit, withdrawal, and display the detail of the customer. (Note: Minimum balance of Rs. 500/- should be maintained.)	21-23
12	Using constructors and proper methods design a class graphics which stores shapes, area, back color and fore colors. Use this class in the main program to input any 'N' shapes and perform the following options and print the list in the neat format.	24-27

	<p>A.Sort according to Area.</p> <p>B. Search according to accepted shape.</p>	
13	<p>Write a program to accept two strings and using operator overloading perform the following.</p> <p>a. Concatenation of two strings.</p> <p>b. Comparison of two strings alphabetically.</p>	28-29
14	<p>Create a class called 'Time' which includes the data members – hours, minutes and seconds. Use the method</p> <ul style="list-style-type: none"> ▪ To accept the time. ▪ To display the time. ▪ To increment time by one second by overloading unary operator ++ ▪ To decrement time by one second by overloading unary operator - - <p>Write a menu driven program for the above operation, (Hint: Minutes and Seconds must be always within the range 0-59).</p>	30-32
15	<p>Multiple Inheritance: Write a program to create a class 'Personnel Information' which includes name, address and gender as the data members. Another class for 'Physical Information' with data members height, weight, blood group. Derive a class called 'Salary' with employee number, department and salary. Find increment in salary for an employee as follows.</p>	33-35

PART A

Program 1 :-

```
#include<iostream.h>
#include<conio.h>

class SI {
    int amount;
    float rate;
    int time;
    float result;
public:
    void getdata();
    void computeSI();
    void display();
};

void SI::getdata() {
    cout << "Enter Principle Amount: ";
    cin >> amount;
    cout << "Enter Rate of Interest: ";
    cin >> rate;
    cout << "Enter time period(in years): ";
    cin >> time;
}

void SI::computeSI() {
    result = amount * rate * time / 100;
}

void SI::display() {
    cout << "The Simple Interst is: " << result;
}

int main() {
    SI si;
    clrscr();
    si.getdata();
    si.computeSI();
    si.display();
    getch();
    return 0;
}
```

OUTPUT: -

```
Enter Principle Amount: 5000
Enter Rate of Interest: 7.5
Enter time period (in years): 3
The Simple Interest is: 1125.0
```

Program 2 : -

```
#include<iostream.h>
#include<conio.h>

class complex {
    int real, img;
    public:
        void getdata();
        void putdata();
        void add(complex, complex);
        void sub(complex, complex);
};

void complex::getdata() {
    cout << endl << "Enter the Real part:";
    cin >> real;
    cout << endl << "Enter the Imaginary part:";
    cin >> img;
}

void complex::putdata() {
    cout << real;
    if (img >= 0) {
        cout << "+" << img << "i";
    } else
        cout << img << "i";
}

void complex::add(complex c1, complex c2) {
    real = c1.real + c2.real;
    img = c1.img + c2.img;
}

void complex::sub(complex c1, complex c2) {
    real = c1.real - c2.real;
    img = c1.img - c2.img;
}

void main() {
    clrscr();
    complex c1, c2, c3;
    cout << endl << "Enter the First complex number:";
    c1.getdata();
    c1.putdata();
    cout << endl << "Enter the Second complex number:";
    c2.getdata();
    c2.putdata();
    cout << endl << "Sum of the complex numbers is:";
```

```
c3.add(c1, c2);  
  
c3.putdata();  
cout << endl << "Difference of the complex numbers is:";  
c3.sub(c1, c2);  
c3.putdata();  
getch();  
}
```

OUTPUT :-

Enter the first complex number:

Enter the real part:12

Enter the imaginary part:3

12+3i

Enter the second complex number:

Enter the real part:4

Enter the imaginary part:2

4+2i

Sum of complex number is: 17+5i

Difference of complex number is:8+1i

Program 3 :-

```
#include<iostream.h>
#include<conio.h>

const float PI = 3.14;
class shape {
    public: void volume(int);
    void volume(double, double);
    void volume(int, int, int);
};
void shape::volume(int s) {
    int vc = s * s * s;
    cout << "The Volume of a Cube is: " << vc;
}
void shape::volume(double r, double h) {
    double vcl = PI * r * r * h;
    cout << endl << "The Volume of Cylinder is: " << vcl;
}
void shape::volume(int l, int b, int h) {
    int vcd = l * b * h;
    cout << endl << "The Volume of a Cuboid is: " << vcd;
}
int main() {
    shape s;
    clrscr();
    s.volume(5);
    s.volume(5.1, 2.5);
    s.volume(2, 3, 4);
    getch();
    return 0
}
```

OUTPUT :-

Volume of the cube is:125
Volume of the cylinder is:204.179
Volume of the cuboid is:24

Program 4 : -

```
#include<iostream.h>
#include<conio.h>

class distance {
    int feet, inch;
public:
    void read();
    void show();
    void add(distance, distance);
};

void distance::read() {
    cout << endl << "Enter the feet and inch:";
    cin >> feet >> inch;
}

void distance::show() {
    cout << endl << "Distance is " << feet << " feets and " <<
        inch << " inches";
}

void distance::add(distance d1, distance d2) {
    inch = d1.inch + d2.inch;
    feet = inch / 12;
    inch = inch % 12;
    feet = feet + d1.feet + d2.feet;
}

void main() {
    clrscr();
    distance d1, d2, d3;
    d1.read();
    d1.show();
    d2.read();
    d2.show();
    d3.add(d1, d2);
    cout << endl << "Sum of the";
    d3.show();
    getch();
}
```

OUTPUT: -

```
Enter the feet and inch: 3 5
Distance is 3 feets and 5 inches
Enter the feet and inch:4 2
Distance is 4 feets and 2
```


Program 5 : -

```
#include<iostream.h>
#include<conio.h>

class library {
    int accno, price, yop;
    char author[15], title[20], pub[20];
public:
    void putdata();
    library();
    ~library() {
        cout << endl << "Object is Destroyed";
    }
};

library::library() {
    cout << endl << "Enter the accno,author,title,publisher,year of publishing and price:" << endl;
    cin >> accno >> author >> title >> pub >> yop >> price;
}

void library::putdata() {
    cout << endl << "Accno=" << accno;
    cout << endl << "Author=" << author;
    cout << endl << "Title=" << title;
    cout << endl << "Publisher=" << pub;
    cout << endl << "Year of publishing=" << yop;
    cout << endl << "Price=" << price;
}

void main() {
    clrscr();
    int n, i;
    cout << endl << "Enter the number of Books:";
    cin >> n;
    for (i = 0; i < n; i++) {
        cout << endl << "Enter the details of Book:" << i + 1;
        library l;
        cout << endl << "Details of Book:" << i + 1;
        l.putdata();
    }
    getch();
}
```

OUTPUT :-

Enter the number of Books:2

Enter the Details of Book:1

Enter the accno,author,title,publisher,year of publishing and price:101 Hari car dcbooks 2010 400

Details of Book:1

Accno=101

Author=Hari

Title=car

Publisher=dcbooks

Year of Publishing=2010

Price=400

Object is Destroyed

Enter the Details of Book:2

Enter the accno,author,title,publisher,year of publishing and price:102 Jacob bike acbooks 2011 550

Details of Book:1

Accno=102

Author=Jacob

Title=car

Publisher=acbooks

Year of Publishing=2011

Program 6: -

```

#include<iostream.h>
#include<conio.h>

class rectangle {
    float l, b, area1;
    public:
        void getdata();
        void putdata();
        float rarea();
};
class cuboid: public rectangle {
    float h, area2;
    public:
        void getdatac();
        void putdatac();
        float carea();
};
void rectangle::getdata() {
    cout << endl << "Enter the length:";
    cin >> l;
    cout << endl << "Enter the breadth:";
    cin >> b;
}
void rectangle::putdata() {
    cout << endl << "Length=" << l << endl << "Breadth=" << b << endl << "Area=" <<
rarea();
}
float rectangle::rarea() {
    area1 = l * b;
    return area1;
}
void cuboid::getdatac() {
    cout << endl << "Enter the height:";
    cin >> h;
}
void cuboid::putdatac() {
    cout << endl << "The height is:" << h << endl << "Area is:" << carea();
}
float cuboid::carea() {
    area2 = rarea() * h;
    return area2;
}
void main() {
    clrscr();
    cuboid c;
    c.getdata();
    c.putdata();
}

```

```
        c.getdatac();  
        c.putdatac();  
        getch();  
    }
```

OUTPUT :-

Length=12

Breadth=10

Area=120

Enter the height:20

The height is:20

Area is:2400

Program 7

```
#include<iostream.h>
#include<conio.h>
#include<string.h>

class student {
    int regno;
    char name[10];
    double fees;
public:
    void getdata(int r, char n[10], double f) {
        regno = r;
        strcpy(name, n);
        fees = f;
    }
    void show() {
        cout << "register number = " << regno << endl;
        cout << "name = " << name << endl;
        cout << "Fees = " << fees;
    }
};

main() {
    student * s = new student[1];
    clrscr();
    s -> getdata(011, "Rahul", 12500);
    s -> show();
    getch();
    return 0;
}
```

OUTPUT: -

Register number = 011

Name = Rahul

Fees = 12500

Program 8 :-

```
#include<iostream.h>
#include<conio.h>

template < class T >
class Calculator {
    private: T num1,
            num2;
    public: Calculator(T n1, T n2) {
        num1 = n1;
        num2 = n2;
    }
    void displayResult() {
        cout << "Numbers are: " << num1 << " and " << num2 << "." << endl;
        cout << "Addition is: " << add() << endl;
        cout << "Subtraction is: " << subtract() << endl;
        cout << "Product is: " << multiply() << endl;
        cout << "Division is: " << divide() << endl;
    }
    T add() {
        return num1 + num2;
    }
    T subtract() {
        return num1 - num2;
    }
    T multiply() {
        return num1 * num2;
    }
    T divide() {
        return num1 / num2;
    }
};

int main() {
    Calculator < int > intCalc(2, 1);
    Calculator < float > floatCalc(2.4, 1.2);
    clrscr();
    cout << "Int results:" << endl;
    intCalc.displayResult();
    cout << endl << "Float results:" << endl;
    floatCalc.displayResult();
    getch();
    return 0;
}
```

OUTPUT: -

Int results:

Numbers are : 2 and 1

Addition is: 3

Subtraction is : 1

Product is : 2

Division is :2

Float results:

Numbers are : 2.4 and 1.2

Addition is: 3.6

Subtraction is : 1.2

Product is : 2.88

Division is :2

Program 9 : -

```
#include<iostream.h>
#include<conio.h>
#include<math.h>

class Quadratic {
private:
    int a, b, c;
    float disc,x, x1,x2;
public: void readdata();
    void compute();
    void display();
};

void Quadratic::readdata() {
    cout << "Enter the values for a, b, c (Co-efficeient)" << endl;
    cin >> a >> b >> c;
}

void Quadratic::compute() {
    disc = b * b - 4 * a * c;
}

void Quadratic::display() {
    compute();
    if (disc == 0) {
        cout << "Equal Roots..." << endl;
        x = -b / (2 * a);
        cout << "Root is...." << x;
    } else if (disc > 0) {
        cout << "Real and Distinct Roots..." << endl;
        x1 = (-b + sqrt(disc)) / (2 * a);
        x2 = (-b - sqrt(disc)) / (2 * a);
        cout << "Root 1 is " << x1 << endl;
        cout << "Root 2 is " << x2 << endl;
    } else
        cout << "Imaginary Roots..." << endl;
}

void main() {
    Quadratic q;
    clrscr();
    q.readdata();
    q.display();
    getch();
}
```


OUTPUT :-

Enter the values for a, b, c (Co-efficient)

1 4 4

Equal Roots...

Enter the value for a, b, c (Co-efficient)

1-5 6

Root 1 is 3

Root 2 is 2

Enter the values for a, b, c (Co-efficient)

2 3 10

Imaginary Roots...

Program 10 : -

```
#include<iostream.h>
#include<conio.h>

class student {
    int regno, m1, m2, m3, total;
    float avg;
    char name[20];
public:
    void getdata();
    void putdata();
    void calculate();
};

void student::getdata() {
    cout << endl << "Enter the register number:";
    cin >> regno;
    cout << endl << "Enter the name:";
    cin >> name;
    cout << endl << "Enter the marks in three subjects:";
    cin >> m1 >> m2 >> m3;
}

void student::putdata() {
    cout << endl << "Register No:" << regno;
    cout << endl << "Name:" << name;
    cout << endl << "Mark1:" << m1 << endl << "Mark2:" << m2 << endl << "Mark3:" <<
        m3;
}

void student::calculate() {
    total = m1 + m2 + m3;
    cout << endl << "Total:" << total;
    avg = total / 3;
    cout << endl << "Average:" << avg;
    cout << endl << "Grade:";
    if (m1 > 35 && m2 > 35 && m3 > 35) {
        if (avg >= 70)
            cout << "Distinction";
        else if (avg >= 60)
            cout << "First class";
        else if (avg >= 50)
            cout << "Second class";
        else
```

```
        cout << "Pass";
    } else
        cout << "Failed";
}

void main() {
    clrscr();
    student s[20];
    int i, n;
    cout << endl << "Enter the number of students:";
    cin >> n;

    for (i = 0; i < n; i++) {
        cout << endl << "Enter the Details of student" << i + 1;
        s[i].getdata();
        s[i].putdata();
        s[i].calculate();
    }
    getch();
}
```

OUTPUT :-

Enter the number of student:2
Enter the details of student 1
Enter the register number:111
Enter the name:Ramesh
Enter the marks in three subjects:55 66 61

Register No:111
Name:Ramesh
Mark1:55
Mark2:66
Mark3:61
Total:182
Average:60

Enter the details of student 2
Enter the register number:222
Enter the name:Reshma
Enter the marks in three subjects:33 56 65

Register No:222
Name:Reshma

PART - B

Program 11 : -

```
#include<iostream.h>
#include<conio.h>
#include<stdlib.h>
#include<string.h>

class bank {
    int accno;
    float bal;
    char name[20];
public:
    bank(int acno, char name1[20], float balance) {
        accno = acno;
        strcpy(name, name1);
        bal = balance;
    }
    void dep(float);
    void withdraw(float);
    void display();
};

void bank::dep(float amount) {
    bal = bal + amount;
    cout << endl << "Transaction Processed" << endl << "Balance is:" << bal;
}

void bank::withdraw(float amount) {
    if (bal < amount) {
        cout << endl << "Transaction Failed";
    } else
    if ((bal - amount) < 500) {
        cout << endl << "Minimum balance of 500 should be maintained";
    } else {
        bal = bal - amount;
        cout << endl << "Transaction Processed" << endl << "Current balance is:" << bal;
    }
}

void bank::display() {
    cout << endl << "***Customer Details***";
    cout << endl << "Account number is:" << accno;
    cout << endl << "Name is:" << name;
    cout << endl << "Balance is:" << bal;
}

void main() {
    int a, n;
    float am, ba;
    char nam[20];
    clrscr();
```

```
cout << endl << "Enter the Accno:";
cin >> a;
cout << endl << "Enter the Name:";
cin >> nam;
cout << endl << "Enter the Balance:";
cin >> ba;
bank b(a, nam, ba);
while (1) {
    cout << endl << "1.Deposit" << endl << "2.Withdrawal" << endl << "3.Display" << endl
<< "4.Exit" << endl << "Enter your choice:";
    cin >> n;
    switch (n) {
        case 1:
            cout << "Enter the amount to be deposited:";
            cin >> am;
            b.dep(am);
            break;
        case 2:
            cout << "Enter the amount to be withdrawn:";
            cin >> am;
            b.withdraw(am);
            break;
        case 3:
            b.display();
            break;
        case 4:
            exit(0);
            break;
        default:
            cout << "invalid input";
            break;
    }
    getch();
}
```

OUTPUT :-

Enter the Accno:001

Enter the Name: Shahabas

Enter the balance: 13000

1.Deposit

2.Withdrawal

3. Display

4.Exit

Enter your choice: 1

Enter the amount to be deposited:
3000

Transaction Processed

Balance: 16000

1.Deposit

2.Withdrawal

3. Display

4.Exit

Enter your choice: 2

Enter the amount to be Withdrawal:
3000

Transaction Processed

Current balance is: 13000

1.Deposit

2.Withdrawal

3.Display

4.Exit

Enter your choice: 3

****Customer Details****

Account Number: 001

Name is: Shahabas

Balance is: 13000

1.Deposit

2.Withdrawal

3.Display

4.Exit

Enter your choice: 4

Program 12 :-

```
#include<iostream.h>
#include<conio.h>
#include<string.h>
#include<stdlib.h>

class graphics {
    int i, n, j;
    float area[20], temp;
    char shape[20][20], fc[20][20], bc[20][20], cmp[20];
public:
    graphics();
    void display();
    void search(char a[20]);
    void sort();
};

graphics::graphics() {
    cout << endl << "Enter the number of shapes:";
    cin >> n;
    for (i = 0; i < n; i++) {
        cout << endl << "Detail of shape" << i + 1;
        cout << endl << "enter the shape:";
        cin >> shape[i];
        cout << endl << "enter the area:";
        cin >> area[i];
        cout << "Enter the forecolor:";
        cin >> fc[i];
        cout << "Enter the backcolor:";
        cin >> bc[i];
    }
}

void graphics::display() {
    for (i = 0; i < n; i++) {
        cout << endl << "Detail of shape" << i + 1;
        cout << endl << shape[i] << endl << area[i] << endl << fc[i] <<
endl << bc[i];
    }
}

void graphics::search(char a[20]) {
    int flag = 0;
    for (i = 0; i < n; i++) {
        if (strcmpi(shape[i], a) == 0) {
            flag = 1;
            cout << shape[i] << endl << area[i] << endl << fc[i] << endl
<< bc[i];
            break;
        }
    }
}
```



```

        }
    }
    if (flag == 0)
        cout << "shape not found:";
}

void graphics::sort() {
    cout << endl << "Sorted";
    for (i = 0; i < n - 1; i++) {
        for (j = i + 1; j < n; j++) {
            if (area[i] > area[j]) {
                temp = area[i];
                area[i] = area[j];
                area[j] = temp;
                strcpy(cmp, shape[i]);
                strcpy(shape[i], shape[j]);
                strcpy(shape[j], cmp);
                strcpy(cmp, bc[i]);
                strcpy(bc[i], bc[j]);
                strcpy(bc[j], cmp);
                strcpy(cmp, fc[i]);
                strcpy(fc[i], fc[j]);
                strcpy(fc[j], cmp);
            }
        }
    }
}

void main() {
    clrscr();
    char a[20];
    int s;
    graphics g;
    while (1) {
        cout << endl << "Option 1:Display" << endl << "Option 2:Sort" <<
endl << "Option 3:Search" << endl << "Option 4:Exit";
        cout << endl << "Enter the option:";
        cin >> s;
        switch (s) {
            case 1:
                g.display();
                break;
            case 2:
                g.sort();
                g.display();
                break;
            case 3:
                cout << "enter the shape to be searched:";

```

```
        cin >> a;
        g.search(a);
        break;
    case 4:
        exit(0);
        break;
    default:
        cout << "Invalid input:";
    }
    getch();
}
```

OUTPUT :-

```
Enter the number of shapes:2
Detail of shape1
Enter the shape:rectangle
Enter the area 25
Enter the forecolor:red
Enter the backcolor:black
```

```
Detail of shape2
Enter the shape:circle
Enter the area :30
Enter the forecolor:green
Enter the backcolor:white
```

```
Option 1: Display
Option 2: Sort
Option 3: Search
Option 4: Exit
Enter the option:1
Detail of shape: 1
Rectangle
25 Red black
Detail of shape: 2
Circle
30
Green
White
```

```
Option 1: Display
Option 2: Sort
Option 3: Search
Option 4: Exit
Enter the option:2
Sorted
Detail of shape: 1
Rectangle
25 Red black
Detail of shape: 2
Circle
30
```

Green
White

Option 1: Display
Option 2: Sort
Option 3: Search
Option 4: Exit
Enter the option:3
Enter the shape to be searched:circle
Circle
30
Green
White

Option 1: Display
Option 2: Sort
Option 3: Search
Option 4: Exit
Enter the option:4

Program 13 :-

```
#include<iostream.h>
#include<conio.h>
#include<string.h>

class string {
    char str[20];
public:
    void getdata() {
        cin >> str;
    }
    void putdata() {
        cout << "String is:" << str;
    }
    friend string operator + (string s1, string s2);
    friend int operator < (string s1, string s2);
    friend int operator > (string s1, string s2);
    friend int operator == (string s1, string s2);
};

string operator + (string s1, string s2) {
    string t;
    strcpy(t.str, s1.str);
    strcat(t.str, " ");
    strcat(t.str, s2.str);
    return t;
}

int operator < (string s1, string s2) {
    if (strcmpi(s1.str, s2.str) < 0)
        return 1;
    else
        return 0;
}

int operator > (string s1, string s2) {
    if (strcmpi(s1.str, s2.str) > 0)
        return 1;
    else
        return 0;
}

int operator == (string s1, string s2) {
    if (strcmpi(s1.str, s2.str) == 0)
        return 1;
    else
        return 0;
}

void main() {
    clrscr();
    string s1, s2, s3;
    cout << endl << "Enter the First string:";
    s1.getdata();
    s1.putdata();
    cout << endl << "Enter the Second string:";

    s2.getdata();
```

```
s2.putdata();  
cout << endl << "concatenated";  
s3 = s1 + s2;  
s3.putdata();  
if (s1 == s2) {  
    cout << endl << "String is Equal";  
} else {  
    cout << endl << "String is not Equal";  
}  
if (s1 > s2)  
    cout << endl << "First string is greater than second string ";  
if (s1 < s2)  
    cout << endl << "First string is less than second string";  
getch();  
}
```

OUTPUT : -

```
Enter the first string:Oxford  
String is:Oxford  
Enter the second string:University  
String is:University  
Concatenated string is:Oxford University  
String is not Equal  
First string is less than second string
```

Program 14 :-

```
#include<iostream.h>
#include<conio.h>
#include<stdlib.h>

class time1 {
    int h, m, s;
    public:
        void getdata();
        void putdata();
        void operator++();
        void operator--();
};

void time1::getdata() {
    cout << endl << "Enter the hours:";
    cin >> h;
    if (h >= 24) {
        cout << endl << "Invalid hour, Try again:";
        cin >> h;
    }
    cout << endl << "Enter the minutes:";
    cin >> m;
    if (m >= 60) {
        cout << endl << "Invalid minutes, Try again:";
        cin >> m;
    }
    cout << endl << "Enter the second:";
    cin >> s;
    if (s >= 60) {
        cout << endl << "Invalid second, Try again:";
        cin >> s;
    }
}

void time1::putdata() {
    cout << endl << "Time is " << h << ":" << m << ":" << s;
}

void time1::operator++() {
    s = s + 1;
    if (s == 60) {
        s = 0;
        m = m + 1;
    }
    if (m == 60) {
        m = 0;
        h = h + 1;
    }
    if (h > 23) {
```

```
        h = 0;
    }
}

void time1::operator--() {
    s = s -
        1;
    if (s < 0) {
        s = 59;
        m = m -
            1;
    }
    if (m < 0) {
        m = 59;
        h = h - 1;
    }
    if (h < 0) {
        h = 23;
    }
}

void main() {
    clrscr();
    int n;
    time1 t;
    while (1) {
        cout << endl << "Option 1: Enter the time" << endl <<
"Option 2:Display" << endl << "Option 3:Add" << endl <<
"Option4:Sub" << endl << "Option 5:Exit";
        cout << endl << "Enter the Option:";
        cin >> n;
        switch (n) {
            case 1:
                t.getdata();
                break;
            case 2:
                t.putdata();
                break;
            case 3:
                t.operator++();
                t.putdata();
                break;
            case 4:
                t.operator--();
                t.putdata();
                break;
            case 5:
                exit(0);
            default:
                cout << endl << "Invalid Input";
        }
    }
}
```

```

    getch();
}
}

```

OUTPUT :-

```

Option 1.Enter the time
Option 2.Display
Option 3. Add
Option 4. Sub
Option 5. Exit
Enter the option:1

```

```

Enter the hours:2
Enter the minutes:25
Enter the seconds:34

```

```

Option 1.Enter the time
Option 2.Display
Option 3. Add
Option 4. Sub
Option 5. Exit
Enter the option:2

```

```

Enter the option:2

```

```

Time is 2:25:34
Option 1.Enter the time
Option 2.Display
Option 3. Add
Option 4. Sub
Option 5. Exit
Enter the option:3

```

```

Time is 2:25:35
Option 1.Enter the time
Option 2.Display
Option 3. Add
Option 4. Sub
Option 5. Exit
Enter the option:4

```

```

Time is 2:25:34
Option 1.Enter the time
Option 2.Display
Option 3. Add
Option 4. Sub
Option 5. Exit
Enter the option:5

```


Program 15 : -

```

#include<iostream.h>
#include<conio.h>
#include<string.h>

class personal_info {
protected: char name[30];
char gender[30];
char address[30];
public: void get_personal_info() {
    cout << "enter name,address and gender:" << endl;
    cin >> name >> address >> gender;
}
void put_personal_info() {
    cout << "name=" << name << endl;
    cout << "address=" << address << endl;
    cout << "gender=" << gender << endl;
}
};

class physical_info {
protected: float height,
weight;
char blood_group[10];
public: void get_physical_info() {
    cout << "enter height,weight and blood group:" << endl;
    cin >> height >> weight >> blood_group;
}
void put_physical_info() {
    cout << "height=" << height << endl;
    cout << "weight=" << weight << endl;
    cout << "blood_group=" << blood_group << endl;
}
};

class salary: public personal_info, public physical_info {
int emp_no;
char department[50];
float salary;
public:
    void get_info() {
        get_personal_info();
        get_physical_info();
        cout << "enter the empno,department and salary:" <<
endl;
        cin >> emp_no >> department >> salary;
    }
    void increment() {
        if (strcmpi(gender, "male") == 0) {
            if ((strcmpi(department, "sales") == 0) ||
                (strcmpi(department, "purchase") == 0))

```

```
        {
            float inc;
            inc = salary * 0.1;
            cout << "increment is:" << inc;
        } else
            cout << "no increment";
    } else {
        if ((strcmpi(department, "sales") == 0) ||
            (strcmpi(department, "purchase") == 0)) {
            float inc;
            inc = salary * 0.11;
            cout << "increment is:" << inc;
        } else
            cout << "no increment";
    }
}

void put_info() {
    put_personal_info();
    put_physical_info();
    cout << "employee number:" << emp_no << endl;
    cout << "department:" << department << endl;
    cout << "salary:" << salary << endl;
}

};

void main() {
    clrscr();
    salary s;
    s.get_info();
    s.put_info();
    s.increment();
    getch();
}
```

OUTPUT :-

Enter name, address, and gender:

Shahabas kanhangad male

Enter the height, weight, and blood group:

5.4 51 0

Enter the empno, deparment, and salary:

001 Manager 15000

Name=shahabas

Address=kanhangad

Gender=male

Height=5.4

Weight=51

Blood_group=0

Employee_number=001

Department=manager

Salary=15000

Increment is: 1200