1 "	
17 0	news of copying noving & renaving foly
26)	copying files: - They fuce is used to copy files
	Janu Sollette
2	Suntaxi- import shuhi
7	Shutil. copy (src., dest)
	7. west (felo. 1 and 3) 35 miles
	import shulill
	src-file = "path / to / source / file. 1226'
,	dest-der= 'pash / to / destination / new-file to bo
. /4	shufil. copy (src-file, dest-dir)
	(i) pidding so tile = +0 add 1967 o 500 toly
6) MM	suing fole: - used to move files from Source path
	to destil
Sy	yotan 3= (9mportiglautilgax") stanoz ologgaz will
	Shutil. move (sre dejt)
e	2:- Emport shutel
3 .	Brc-file = 1 pake 1 to 1 source / fole txt'
	dest-dir = partil to l'dyfination l'new fele. ext 1
7.2	Bit it is a second of the seco
3	Renduing file : 7 resame the existing.
	têle me Os. resam franction
- (Systan of Copport of a College
	os. resauci (src. dest) book to a shap
	Exi- import os
	deltastilland to I sourced old file txt to be
	destination pathe / to / source f new file. Int'
	3)9; 9
	THE PARTY OF THE P

rant and
27 en la completa de la desal a la la test xep lele
@ ouating zep file :- to create zep file use Ku
exptile. Zeptile (1 class & up wrik method
Dip file. 20p file () Clays a light work made
Syntax: - import zipfele
with zipfile. zipfile (zipfile parti", "w") of 2:
ex:- import zepfile
existimpost zepfile
with zepfile. Zepfile (Example. Zp , 10) as 2 ,
Z. write (" filez-tat")
Shall rong con provided
(b) Adding zip file i- to add files to zip files.
you can up zipfile. ziptile (? class up with nuke
System: - import zepfele Alsh of
with zipfile. Zipfile ("zipfile-path" a") of Zing
z. write ("tile_to_adds")
exi- import zipfile
with zipfile. zepfile ("example. zip", "a") of 28
the stand where (" files . Het") = 80 100
@ Reading a file :- use nead without to nead falce.
Syntax 3- import zipfile
with zepfele. Zepfele ("zepfele path", ">") ag z:
data = z. read (file-to-read)
(1) extracting zip files up to extract content of file
by using extractall () network
Sypton: - import zipfile
with. zigfile. Zipfile ("Zipfile-pathe", "z") of z:
Z. extractall ("path")]

			4
m di	If modules used to	scrape webpaque	By port (b)
@ Peg	wite in It's python	18hrary for make	eng HTTS reques
Wild	to fetch data	from websites	0
Syn	tax: Import req	rue Boin o Theo	9 4-10-1-10-2
	reponse =	requests get (url)	101 7 - 1 KS
exô	- import enquests	ALE STEELS OF THE	130)0
	unt= https:// exa	mple con	orn one
	x = requelleget ((101) HE 27 H 1'] -	Tau!
, 1'n	Print (x)	racy (ently serper	4.1
Br. :		7,207	
1 Page	utiful soup :- for	parling HTML 4 XI	Mr docuts.
Cunt	an & import from	bsu import Beauti	ful soup
277	soup = Beau	titul soup Chtml-worte	t, html. parse
0-10-	from 654 impost	Resultations	most 3 x story
O/L.	Content = https:	Il escample. Htmlo"	= 6
12.4	COURS = Republikal Son	of Costest, 11 html=f	parser")
	Paint (Sound te	t) we was the	1d" = 1d
1.5	19-8 1777 (300g) - 19-17 .		ع جـ النام
© Sele	enium 6- for autome		A
	dynamic conte	nt.	
Synt	an: - from Selenic	in impost webdin	residen
	driver = w	ebdriver.cherome ()) sobjective
17 18 181	driver get	(uri)	stricy C
ex:	from Selevium in	wort mebdstree	n ==0
1	dan usl = ! https:	llex.com'	
	d = webdsine	_	.8
	d. get (un1)		
2.0	prent (d. pe	age-Source)	4 4 4
		0	447

a scrapy 6- 21's python framework for cash scraping.
provides wigh level Apr for crawling websites
& extract of data.
Syntax 3- Create a scrapy speder class.
exist import scrapy stanger = Dinogar
class Myspides (scrapy.spides)
name = l'example-spider! = 100
uol = ['hHps: 11 ex.com']. Harry
det parge (self, response) & () 1963
Paul
Beautiful 2007 8- 10, rassing Him & non- docute.
@ Urlib: - Is pythos library for fetching data from Wels
it can be riged to download files, inages from web
Syntan :- from wolleb request laport wropes
S= Driopen (inx) = 5/1/2 / 1/11)
en :- from willib request import uslopen librar = quo
Usl = "https: Mex. com" (3) ort gipus) tologo
r = unlopen (unl)
a print (r. read O. decode ('uzj-8'))
Linguis Control
Decharical soup to the manual of mutings
(3) pardas (demondo, revirtedou - revirte
@ Lame (100) dop. worlds
enti- Pron Selinian Property webdiling

(29) parge HTML to Beautifulsoup
of parying HTML "-
a impost module
from 684 import Beautiful goup
6 Creak Beautiful Soup Object :-
8 = hHps ill ex.com'
soup = Beautiful soup (r, 'html-parger')
C natigate à gearch HTML douvert.
* Tag access:
tag = soup.p // access first tag
* Attribute access
attr-value = tag ['attr-name'] 11 Access malue
* Navigating parse tree:
parent-tag = tag. parent 11 Access parent tag
next-sibling = tag. next-sibling 11 access next
a = Soup. fend-all ('p') 11 fell all 2p> feagl
a = Soup. fend-all ('p') 11 fell all zp> toge
@ extract 90/602 3-
Print (soup. p. fext)
Evanuale o- Pro- 100 100 100 100 100
Brauple :- from 654 import Beautiful Soup
Content = 'https & html. com!
Soup = Beautifulsoup (contest, 'html-parses')
Lette = Soup. br. text 1/ entract 4 of 02
List = [1: text for 1: in soup find-all (1101)]
print (f'title; { title })
Print ('List Items: ', list-items)

30. Explain controlling the browser with the Selenium module.

Selenium is a powerful tool for controlling a web browser through the program.

→ It is commonly used for web scraping, automated testing of web applications, and various other tasks that involve browser automation. The `selenium` module provides a convenient API for interacting with web browsers.

Below are the basic steps and some examples to get you started:

Basic Steps:

- 1. Import the Selenium module: from selenium import webdriver
- 2. Create a WebDriver instance:

Selenium supports different web browsers like Chrome, Firefox, Safari, etc. You need to download the appropriate WebDriver executable and provide its path.

- → driver = webdriver.Chrome('path/to/chromedriver.exe')
- 3. Navigate to a URL:
- → driver.get('https://www.example.com')
- 4. Interact with elements on the page:
- **→** Find element by ID:

element = driver.find element by id('element id')

→ Find element by name:

element = driver.find element by name('element name')

→ Find element by class name:

element = driver.find element by class name('element class')

→ Find element by XPath:

element = driver.find element by xpath('//path/to/element')

- → Click on an element:
 - element.click()
- → Type text into an input field:

element.send_keys('Text to type')

- 5. Perform browser actions:
- **→** Navigate back:

driver.back()

→ Refresh the page:

driver.refresh()

→ Close the browser:

driver.quit()

Example:

from selenium import webdriver

Create a WebDriver instance (Chrome in this example)

driver = webdriver.Chrome('path/to/chromedriver.exe')

Navigate to Google

driver.get('https://www.google.com')

```
Find the search input field by name
search box = driver.find element by name('q')
Type 'Selenium' into the search box
search box.send keys('Selenium')
Submit the search form
search box.submit()
Print the titles of the search results
results = driver.find elements by css selector('h3')
for result in results:
  print(result.text)
Close the browser
driver.quit()
31. Explain the process of reading Excel documents with example.
import pandas as pd
// Specify the path to your Excel file
excel file path = 'path/to/your/excel file.xlsx'
//Read Excel file into a DataFrame
df = pd.read excel(excel file path)
//Display the entire DataFrame
print("DataFrame from Excel:")
print(df)
//Display basic information about the DataFrame
print("\nDataFrame Information:")
print(df.info())
//Display basic statistics about the DataFrame
print("\nDataFrame Statistics:")
print(df.describe())
//Access specific column
print("\nAccessing specific columns:")
print(df['ColumnName']) Replace 'ColumnName' with the actual column name
//Access specific row using iloc (index-based)
print("\nAccessing specific rows:")
print(df.iloc[0]) Access the first row
//Access specific rows using loc (label-based)
print("\nAccessing specific rows by label:")
print(df.loc[df['ColumnName'] == 'SpecificValue']) Replace 'ColumnName' and
'SpecificValue' as needed
```

32. How do you extract text from pdf and word documents using python.

To extract text from pdf use PyPDF2 library for pdf files and python-docu for word files.

```
→ Extract text from pdf using PyPDF2:-
   import PyPDF2
   def extract text from pdf(pdf file path):
     with open(pdf file path, 'rb') as file:
        //Create a PDF reader object
        pdf_reader = PyPDF2.PdfFileReader(file)
       // Get the total number of pages
       num pages = pdf reader.numPages
       // Extract text from each page
        text = "
        for page num in range(num pages):
          page = pdf_reader.getPage(page_num)
          text += page.extractText()
        return text
   // Specify the path to your PDF file
   pdf file path = 'path/to/your/pdf file.pdf'
   // Extract text from the PDF
   pdf text = extract text from pdf(pdf file path)
   // Display the extracted text
   print(pdf_text)
→ Extract text from word document using python-docu:-
   from docx import Document
   def extract text from word(docx file path):
     doc = Document(docx file path)
     // Extract text from paragraphs
     text = ''
     for paragraph in doc.paragraphs:
        text += paragraph.text + '\n'
     return text
   // Specify the path to your Word document
   docx_file_path = 'path/to/your/word_file.docx'
   // Extract text from the Word document
   word_text = extract_text_from_word(docx_file_path)
   // Display the extracted text
   print(word text)
```

33. What are the procedures for Connecting to an SMTP Server?

Connecting to an SMTP (Simple Mail Transfer Protocol) server is a common task when working with sending emails programmatically. Below are the general procedures for connecting to an SMTP server using Python. The example uses the built-in `smtplib` library.

Procedure for Connecting to an SMTP Server:

1. Import the necessary libraries:

import smtplib

from email.mime.text import MIMEText

from email.mime.multipart import MIMEMultipart

2. Set up your email and server details:

```
sender_email = "your_email@gmail.com"
receiver_email = "recipient_email@example.com"
subject = "Subject of the email"
body = "Body of the email"
smtp_server = "smtp.gmail.com" Update with your SMTP server address
smtp_port = 587 Update with the appropriate port for your SMTP server
username = "your_email@gmail.com"
password = "your email password"
```

3. Create a connection to the SMTP server:

```
server = smtplib.SMTP(smtp_server, smtp_port)
server.starttls() Use TLS (Transport Layer Security) for secure connection
```

4. Log in to your email account:

```
server.login(username, password)
```

5. Compose the email:

```
message = MIMEMultipart()
message["From"] = sender_email
message["To"] = receiver_email
message["Subject"] = subject
message.attach(MIMEText(body, "plain"))
```

6. Send the email:

```
server.sendmail(sender email, receiver email, message.as string())
```

7. Close the connection:

```
server.quit()
```

Full Example:

import smtplib

from email.mime.text import MIMEText

from email.mime.multipart import MIMEMultipart

```
// Set up your email and server details
sender_email = "your_email@gmail.com"
receiver_email = "recipient email@example.com"
subject = "Subject of the email"
body = "Body of the email"
//smtp server = "smtp.gmail.com"
smtp port = 587
username = "your_email@gmail.com"
password = "your email password"
//Create a connection to the SMTP server
server = smtplib.SMTP(smtp server, smtp port)
server.starttls() Use TLS (Transport Layer Security) for secure connection
// Log in to your email account
server.login(username, password)
// Compose the email
message = MIMEMultipart()
message["From"] = sender email
message["To"] = receiver email
message["Subject"] = subject
message.attach(MIMEText(body, "plain"))
//Send the email
server.sendmail(sender email, receiver email, message.as string())
// Close the connection
server.quit()
   35. How do you manipulate Images with Pillow.
              To manipulate images in Python, the 'Pillow' library is commonly used.
       -> `Pillow` is an updated fork of the Python Imaging Library (PIL) and provides a rich set of
       features for working with images.
   → Below are some common tasks you can perform using Pillow:
       Example Image Manipulation Tasks:
             from PIL import Image, ImageDraw, ImageFilter
       # Open an image file
             image path = "path/to/your/image.jpg"
              original_image = Image.open(image_path)
       # Display the original image
              original_image.show()
```

```
# Resize the image
       resized_image = original_image.resize((300, 200))
       resized_image.show()
# Crop a region from the image
       box = (100, 100, 400, 300) # (left, top, right, bottom)
       cropped_image = original_image.crop(box)
       cropped_image.show()
# Rotate the image
       rotated_image = original_image.rotate(45)
       rotated_image.show()
# Add text to the image
       draw = ImageDraw.Draw(original_image)
       font_size = 30
       font_path = "path/to/your/font.ttf"
       text position = (50, 50)
       text_color = (255, 255, 255)
       text_content = "Hello, Pillow!"
       font = ImageFont.truetype(font_path, font_size)
       draw.text(text_position, text_content, fill=text_color, font=font)
       original_image.show()
# Apply a blur filter
       blurred image = original image.filter(ImageFilter.BLUR)
       blurred_image.show()
# Save the manipulated image
       resized_image.save("path/to/your/resized_image.jpg")
       cropped_image.save("path/to/your/cropped_image.jpg")
       rotated_image.save("path/to/your/rotated_image.jpg")
       original_image.save("path/to/your/modified_image.jpg")
# Close the images
       original_image.close()
       resized_image.close()
       cropped_image.close()
       rotated_image.close()
       blurred_image.close()
```