

● string.cpp

```
int* z_function(char s[],int n)
{
    int* z = new int[n];
    memset(z, 0, sizeof(z));
    z[0] = n;
    int L = 0, R = 1;
    for (int i=1; i<n; ++i)
        if (R <= i || z[i-L] >= R-i){
            int x = (R <= i ? i : R);
            while (x < n && s[x] == s[x-i]) x++;
            z[i] = x-i;
            if (i < x) {L = i; R = x;}
        }
        else
            z[i] = z[i-L];
    return z;
}
/*banana*/
void IBWT(){
    vector<int> index[256];
    for(int i=0; i<N; i++) index[t[i]].push_back(i);

    for(int i=0, n=0; i<256; i++)
        for(int j=0; j<index[i].size(); j++)
            next[n++] = index[i][j];
}
/*kmp*/
for(int i=0, j=-1; i<t.size(); i++){
    while(j>=0 && p[j+1]!=t[i]) j = f[j];
    if(p[j+1]==t[i]) j++;
    if(j==p.size()-1){
        int ans = i - p.size();
        j = f[j];
    }
}
```

● 最小字典序表示法

```
void solve(){
    scanf("%s",t);
    s[0] = '\0';
    strcat(s, t);
    strcat(s+n, t);

    int j = 1, i = 0;
    while(i<n && j<n){
        if(s[j]<s[i]) i = j, j = i+1;
        else if(s[j]>s[i]) j++;
        else{
            int k = 0;
            while(k<n){
                if(s[i+k]==s[j+k]) k++;
                else if(s[i+k]<s[j+k]){
                    j = j+k + 1;
                    break;
                }
            }
            else{
                i = j;
                j = i + 1;
                break;
            }
        }
        if(k==n) break;
    }
    printf("%d\n", i);
}
```

● sa.cpp

```
int d2[maxn], d[maxn];
int ra[maxn], he[maxn], sa[maxn], c[maxn];
void build_sa(int n,int m){
    int *x = ra, *y = he;

    for(int i=0; i<m; i++) c[i] = 0;
    for(int i=0; i<n; i++) c[x[i]=d[i]]++;
    for(int i=1; i<m; i++) c[i] += c[i-1];
    for(int i=n-1; i>=0; i--) sa[--c[x[i]]] = i;

    for(int k=1; k<=n; k<=1){
        int p = 0;
        for(int i=n-k; i<n; i++) y[p++] = i;
        for(int i=0; i<n; i++) if(sa[i]>=k) y[p++] = sa[i]-k;

        for(int i=0; i<m; i++) c[i] = 0;
        for(int i=0; i<n; i++) c[x[y[i]]]++;
        for(int i=1; i<m; i++) c[i] += c[i-1];
        for(int i=n-1; i>=0; i--) sa[--c[x[y[i]]]] = y[i];

        swap(x, y);
        p = 0;
        x[sa[0]] = p++;
        for(int i=1; i<n; i++)
            x[sa[i]] = y[sa[i]]==y[sa[i-1]]&&sa[i]+k<n&&sa[i-1]+k<n&&y[sa[i]+k]==y[sa[i-1]+k]?
            p-1:p++;
        if(p>=n) break;
        m = p;
    }
}
void build_he(int n){
    for(int i=0; i<n; i++) ra[sa[i]] = i;
    // def he[i] = lcp(sa[i], sa[i-1])
    // --> he[ra[i]]>=he[ra[i-1]]-1
    he[0] = 0;
    for(int i=0,k=0; i<n; i++){
        if(ra[i]){
            if(k) k--;
            int j = sa[ra[i]-1];
            while(d[i+k]==d[j+k] && i+k < n && j+k < n) k++;
            he[ra[i]] = k;
        }
    }
}
```

● ACf.cpp

```
const int maxn = 100;
const int maxkind = 26;
const int maxlen = 100;
const int maxsize = maxn*maxlen + 10;
struct AC{
    int ch[maxsize][maxkind], f[maxsize],
    last[maxsize], val[maxsize];
    int root, memid;
    AC(){ clear(); }
    void newNode(){
        memset(ch[memid], 0, sizeof(ch[memid]));
        f[memid] = last[memid] = val[memid] = 0;
        return memid++;
    }
    void clear(){
        memid = 0;
        root = newNode();
    }
    void insert(const char* s,int v){
        int tmp = root;
        for(int i=0; s[i]; i++){
            int id(ID[s[i]]);
            if(!ch[tmp][id]) ch[tmp][id] = newNode();
            tmp = ch[tmp][id];
        }
    }
}
```

```

    val[tmp] = v;
}
void getfail(){
    queue<int> Q;
    f[root] = 0;
    for(int i=0; i<maxkind; i++) if(ch[root][i]){
        int u = ch[root][i];
        f[u] = last[u] = 0;
        Q.push(u);
    }
    while(!Q.empty()){
        int x = Q.front(); Q.pop();
        for(int i=0; i<maxkind; i++) if(ch[x][i]){
            int tmp = f[x], u = ch[x][i];
            while(tmp && !ch[tmp][i]) tmp = f[tmp];
            f[u] = ch[tmp][i];
            last[u] = val[f[u]]? f[u]:last[f[u]];
            Q.push(u);
        }
    }
}
void find(const char *s){
    int tmp = root;
    for(int i=0; s[i]; i++){
        int id = ID(s[i]);
        while(tmp && !ch[tmp][id]) tmp = f[tmp];
        tmp = ch[tmp][id];
        if(val[id]) // find
        if(last[id]) // find
    }
}
};

```

● Hash.cpp

```

#define MAXN 1000000
#define prime_mod 1073676287
typedef long long T;
char s[MAXN+5];
T h[MAXN+5];
T h_base[MAXN+5];
inline void hash_init(int len,T prime=0xdefaced){
    h_base[0]=1;
    for(int i=1;i<=len;++i){
        h[i]=(h[i-1]*prime+s[i-1])%prime_mod;
        h_base[i]=(h_base[i-1]*prime)%prime_mod;
    }
}
inline T get_hash(int l,int r){
    return (h[r+1]-(h[l]*h_base[r-
l+1])%prime_mod+prime_mod)%prime_mod;
}

```

● Treap.cpp

```

#include <iostream>
#include <algorithm>
#include <cstdio>
using namespace std;
const int INF = 9e9;
struct Node{
    int val, pri, size, mi, tag;
    bool rev;
    Node *l, *r;
    Node(){
        Node(int
v):val(v),pri(rand()),size(1),rev(0),mi(v),tag(0){ l =
r = NULL;}
    void down();
    void up();
}*root;

int Size(Node *o){ return o? o->size:0;}
int Min(Node *o){ return o? o->mi:INF;}
int Val(Node *o){ return o? o->val:-1;}

```

```

void Node::down(){
    if(tag){
        val += tag;
        mi += tag;
        if(l) l->tag += tag;
        if(r) r->tag += tag;
        tag = 0;
    }
    if(rev){
        swap(l,r);
        if(l) l->rev ^= 1;
        if(r) r->rev ^= 1;
        rev = 0;
    }
}

void Node::up(){
    if(l) l->down();
    if(r) r->down();
    size = 1 + Size(l) + Size(r);
    mi = std::min( min(Min(l), Min(r)),val );
}

void print(Node *o){
    if(o){
        print(o->l);
        printf("%d ", o->val);
        print(o->r);
    }
}

Node* merge(Node* a,Node *b){
    if(!a || !b) return a? a:b;
    if(a->pri < b->pri){
        a->down();
        a->r = merge(a->r, b);
        a->up();
        return a;
    }else{
        b->down();
        b->l = merge(a, b->l);
        b->up();
        return b;
    }
}

void spilt(Node *o, Node *&a, Node *&b, int k){
    if(!o) a = b = NULL;
    else{
        o->down();
        if(Size(o->l)>=k){
            b = o;
            spilt(o->l, a, b->l, k);
        }
        else{
            a = o;
            spilt(o->r, a->r, b, k-Size(o->l)-1);
        }
        o->up();
    }
}

void Insert(Node *&o, int k,int v){
    if(!o) o = new Node(v);
    else{
        Node* tmp = new Node(v);
        Node *a, *b;
        spilt(o, a, b, k);
        o = merge(merge(a,tmp), b);
    }
}

void Del(Node *&o, int k){
    if(!o) return;
}

```

```

else{
    Node *a, *b, *c;
    spilt(o, a, b, k);
    spilt(a, a, c, k-1);
    o = merge(a, b);
}
}

int Min(Node *&o, int x, int y){
    if(!o) return 0;
    else{
        Node *a, *b, *c;
        spilt(o, a, b, y);
        spilt(a, a, c, x-1);
        if(c==0) return 0;
        c->up();
        int ans = c->mi;
        o = merge(merge(a,c), b);
        return ans;
    }
}

void Add(Node *&o, int x, int y, int v){
    if(!o) return;
    Node *a, *b, *c;
    spilt(o, a, b, y);
    spilt(a, a, c, x-1);
    if(c) c->tag += v;
    o = merge(merge(a,c), b);
}

void Reverse(Node *&o, int x, int y){
    if(!o) return;
    Node *a, *b, *c;
    spilt(o, a, b, y); // a b c
    spilt(a, a, c, x-1);
    if(c) c->rev ^= 1;
    o = merge(merge(a,c), b);
}

void Rotate(Node *&o, int x, int y, int t){
    if(!o) return;
    Node *a, *b, *c;
    spilt(o, a, b, y);
    spilt(a, a, c, x-1);

    Node *d, *e;
    t %= (y-x+1);
    if(t<0) t = y-x+1+t;
    spilt(c,d,e, Size(c)-t);
    c = merge(e, d);
    o = merge(merge(a,c), b);
}

/*
ADD x y D: Add D to each number in sub-sequence
{Ax ... Ay}. For example, performing "ADD 2 4 1" on
{1, 2, 3, 4, 5} results in {1, 3, 4, 5, 5}
REVERSE x y: reverse the sub-sequence {Ax ... Ay}. For
example, performing "REVERSE 2 4" on {1, 2, 3, 4, 5}
results in {1, 4, 3, 2, 5}
REVOLVE x y T: rotate sub-sequence {Ax ... Ay} T
times. For example, performing "REVOLVE 2 4 2" on {1,
2, 3, 4, 5} results in {1, 3, 4, 2, 5}
INSERT x P: insert P after Ax. For example, performing
"INSERT 2 4" on {1, 2, 3, 4, 5} results in {1, 2, 4,
3, 4, 5}
DELETE x: delete Ax. For example, performing "DELETE
2" on {1, 2, 3, 4, 5} results in {1, 3, 4, 5}
MIN x y: query the participant what is the minimum
number in sub-sequence {Ax ... Ay}. For example, the
correct answer to "MIN 2 4" on {1, 2, 3, 4, 5} is 2
*/
int main()
{

```

```

int n;
while(scanf("%d",&n)==1){
    root = NULL;
    for(int i=0; i<n; i++){
        scanf("%d",&a);
        root = merge(root, new Node(a));
    }
    int m, x, y, c;
    char s[20];
    scanf("%d", &m);
    for(int i=0; i<m; i++){
        scanf("%s", s);
        if(s[0]=='A'){
            scanf("%d%d",&x,&y,&c);
            Add(root, x, y, c);
        }
        else if(s[0]=='R' && s[3]=='E'){
            scanf("%d",&x,&y);
            Reverse(root, x, y);
        }
        else if(s[0]=='R'){
            scanf("%d%d",&x,&y,&c);
            Rotate(root, x, y, c);
        }
        else if(s[0]=='I'){
            scanf("%d",&x,&y);
            n++;
            Insert(root, x, y);
        }
        else if(s[0]=='D'){
            scanf("%d",&x);
            Del(root, x);
            n--;
        }
        else{
            scanf("%d",&x,&y);
            printf("%d\n", Min(root, x, y));
        }
    }
}
return 0;
}

```

● LCA

```

// adj[u] : adjacency list of u
// par[u][i] : (2^i)-th parent pf u
int LOG = 20;
int time = 0;
void dfs(int u, int p) {
    par[u][0] = p;
    timer_in[u] = ++timer;
    for (int v : adj[u]) if (v!=p) dfs(v, u);
    time_out[u] = ++timer;
}
bool anc(int x, int y) {
    return time_in[x] <= time_in[y]
        && time_out[y] <= time_out[x];
}
int lca(int x, int y) {
    if (anc(y, x)) return y;
    for (int j = LOG; j >= 0; j--) {
        if (!anc(par[y][j], x)) y = par[y][j];
    }
    return par[y][0];
}
int main() {
    int root = 1; // set root node
    dfs(root, root);

    for (int j = 1; j <= LOG; j++)
        for (int i = 1; i <= n; i++)
            pair[i][j] = par[par[i][j-1]][j-1];
    return 0;
}

```

● 樹鍊剖分

```
vector<int> G[maxn];
int pa[maxn], maxson[maxn], son[maxn];
int dep[maxn];
int link[maxn], linkpa[maxn];
int linkcnt = 0;
void dfs(int x, int p){
    pa[x] = p;
    dep[x] = dep[p] + 1;
    son[x] = 1, maxson[x] = -1;
    for(int i=0; i<G[x].size(); i++) if(G[x][i] != p){
        dfs(G[x][i], x);
        son[x] += son[G[x][i]];
        if(maxson[x] == -1 ||
            son[G[x][i]] > son[maxson[x]]) maxson[x] = G[x][i];
    }
}
void build_link(int x, int plink){
    link[x] = ++linkcnt;
    linkpa[x] = plink;

    if(maxson[x] != -1) build_link(maxson[x], plink);
    for(int i=0; i<G[x].size(); i++){
        int u = G[x][i];
        if(u == maxson[x] || u == pa[x]) continue;
        build_link(u, u);
    }
}
ll cal(int a, int b, int type){
    ll ans = 0;
    int ta = linkpa[a], tb = linkpa[b];
    while(linkpa[a] != linkpa[b]){
        int A, B;

        if(dep[ta] <= dep[tb]){
            swap(a, b);
            swap(ta, tb);
        }
        A = link[ta];
        B = link[a];

        // if(type==1) T.add(1, n, 1, A, B);
        // else ans += T.query(1, n, 1, A, B);
        a = pa[linkpa[a]];
        ta = linkpa[a];
    }

    if(a == b) return ans;
    if(dep[a] > dep[b]) swap(a, b);

    int A = link[a] + 1, B = link[b];
    // if(type==1) T.add(1, n, 1, link[a]+1,
    link[b]);
    // else ans += T.query(1, n, 1, link[a]+1,
    link[b]);
    if(type == 0) return ans;
}

```

● SCC.cpp

```
struct Kosaraju {
    // Vertex i belong to which SCC, call findSCC to
    build.
    int SCCof[MAXV+5], V, cnt;
    bool vis[MAXV+5];
    vector<int> *G, *Grev;
    stack<int> stk;
    void dfs(vector<int> *Gcur, int v) {
        for (auto u : Gcur[v]) {
            if (!vis[u]) {

```

```
                vis[u] = true;
                dfs(Gcur, u);
            }
        }
        if (Gcur == G) stk.push(v);
        else SCCof[v] = cnt;
    }
    int findSCC(int _V, vector<int> *_G, vector<int>
    *_Grev) {
        // G: Adjacency List of graph. Grev: Reverse
        graph of G.
        // No need for init, return # of SCC, 1-based
        V = _V; G = _G; Grev = *_Grev;
        for (int i=1; i<=V; i++) vis[i] = 0;
        for (int i=1; i<=V; i++) {
            if (!vis[i]) {
                vis[i] = true;
                dfs(G, i);
            }
        }
        cnt = 0;
        for (int i=1; i<=V; i++) vis[i] = 0;
        while (!stk.empty()) {
            int v = stk.top();
            stk.pop();
            if (!vis[v]) {
                cnt++;
                vis[v] = true;
                dfs(Grev, v);
            }
        }
        return cnt;
    }
    void compress(vector<int> *Gtar) {
        // Pack SCC into one vertex, store into Gtar
        // Call findSCC before this, 1-based
        for (int i=1; i<=V; i++)
            for (auto j : G[i])
                if (SCCof[i] != SCCof[j])
                    Gtar[SCCof[i]].push_back(SCCof[j]);
    }
};

```

● Dinic flow

```
const int maxn = 1000+10;
const int INF = 2147483647;
template<class T>
struct Dinic{
    struct Edge{
        int f, to;
        T c;
        Edge(int _f, int _to, T _c): f(_f), to(_to), c(_c){}
    };

    vector<int> G[maxn];
    vector<Edge> es;
    int level[maxn], st, end, n;

    void init(int _n){
        n = _n;
        es.clear();
        for(int i=0; i<=n; i++) G[i].clear();
    }

    void addEdge(int f, int t, T c, bool
    directed=false){
        es.push_back(Edge(f, t, c));
        G[f].push_back(es.size()-1);
        es.push_back(Edge(t, f, directed?0:c));
        G[t].push_back(es.size()-1);
    }
    bool BFS(int s, int t){
        queue<int> Q;

```

```

for(int i=0; i<n; i++) level[i] = 0;
level[s] = 1;
Q.push(s);
while(!Q.empty()){
    int x = Q.front(); Q.pop();
    for(int i=0; i<G[x].size(); i++){
        Edge e = es[ G[x][i] ];
        if(e.c==0 || level[e.to]) continue;
        level[e.to] = level[x] + 1;
        Q.push(e.to);
    }
}
return level[t]!=0;
}
T DFS(int s,int cur_flow){ // can't exceed c
    if(s==end) return cur_flow;
    T ans = 0, temp, total = 0;
    for(int i=0; i<G[s].size(); i++){
        Edge &e = es[ G[s][i] ];
        if(e.c==0 || level[e.to]!=level[s]+1)
            continue;
        temp = DFS(e.to, min(e.c, cur_flow));
        if(temp!=0){
            e.c -= temp;
            es[G[s][i]^1].c += temp;
            cur_flow -= temp;
            total += temp;
            if(cur_flow==0) break;
        }
    }
    return total;
}
T maxFlow(int s,int t){
    T ans = 0;
    st = s, end = t;
    while(BFS(s,t)){
        while(true){
            T temp = DFS(s,INF);
            if(temp==0) break;
            ans += temp;
        }
    }
    return ans;
};

```

● 最小費用流

```

struct Min_cost_flow {
    // 0-base
    struct Edge {
        int fr,to,flow,cap,cost;
    };
    int V,E;
    vector<Edge> edge;
    vector<int> G[MAXV+5];

    void init(int _V) {
        V=_V;
        E=0;
        for (int i=0;i<V;i++) G[i].clear();
    }
    void add_edge(int fr, int to, int cap, int cost)
    {
        edge.pb({fr,to,0,cap,cost});
        edge.pb({to,fr,0,0,-cost});
        G[fr].pb(E);
        G[to].pb(E^1);
        E+=2;
    }
    bool SPFA(int src, int dest, int &ans_flow, int
    &ans_cost) {
        queue<int> que;

```

```

int dist[MAXV+5],pre[MAXV+5],flow[MAXV+5];
bool inque[MAXV+5];
for (int i=0;i<V;i++) {
    dist[i]=INF;
    pre[i]=-1;
    inque[i]=false;
    flow[i]=-1;
}
dist[src]=0;
flow[src]=INF;
inque[src]=true;
que.push(src);
while (!que.empty()) {
    int v=que.front(); que.pop();
    inque[v]=false;
    for (auto idx : G[v]) {
        Edge &e=edge[idx];
        if (e.flow<e.cap &&
        dist[e.fr]+e.cost<dist[e.to]) {
            flow[e.to]=min(flow[e.fr],e.cap-e.flow);
            dist[e.to]=dist[e.fr]+e.cost;
            pre[e.to]=idx;
            if (!inque[e.to])
                que.push(e.to);
            inque[e.to]=true;
        }
    }
}
if (dist[dest]==INF) return false;
int v=dest;
ans_flow+=flow[dest];
ans_cost+=(dist[dest]*flow[dest]);
while (v!=src) {
    static int num;
    edge[pre[v]].flow+=flow[dest];
    edge[pre[v]^1].flow-=flow[dest];
    v=edge[pre[v]].fr;
}
return true;
}
PII min_cost_flow(int src, int dest) {
    int ans_flow=0, ans_cost=0;
    while (SPFA(src,dest,ans_flow,ans_cost));
    return make_pair(ans_flow,ans_cost);
}
};

```

● Blossom matching

```

struct Blossom {
    #define MAXN 505 // Max solvable problem, DON'T
    CHANGE
    // 1-based, IMPORTANT
    vector<int> g[MAXN];
    int parent[MAXN], match[MAXN], belong[MAXN],
    state[MAXN];
    int n;
    int lca(int u, int v) {
        static int cases = 0, used[MAXN] = {};
        for (++cases; ; swap(u, v)) {
            if (u == 0)
                continue;
            if (used[u] == cases)
                return u;
            used[u] = cases;
            u = belong[parent[match[u]]];
        }
    }
    void flower(int u, int v, int l, queue<int> &q) {
        while (belong[u] != l) {
            parent[u] = v, v = match[u];
            if (state[v] == 1)
                q.push(v), state[v] = 0;

```

```

        belong[u] = belong[v] = 1, u =
parent[v];
    }
}
bool bfs(int u) {
    for (int i = 0; i <= n; i++)
        belong[i] = i;
    memset(state, -1, sizeof(state[0])*(n+1));
    queue<int> q;
    q.push(u), state[u] = 0;
    while (!q.empty()) {
        u = q.front(), q.pop();
        for (int i = 0; i < g[u].size(); i++) {
            int v = g[u][i];
            if (state[v] == -1) {
                parent[v] = u, state[v] = 1;
                if (match[v] == 0) {
                    for (int prev; u; v =
prev, u = parent[v]) {
                        prev = match[u];
                        match[u] = v;
                        match[v] = u;
                    }
                    return 1;
                }
                q.push(match[v]),
            } else if (state[v] == 0 &&
belong[v] != belong[u]) {
                int l = lca(u, v);
                flower(v, u, l, q);
                flower(u, v, l, q);
            }
        }
    }
    return 0;
}
int blossom() {
    memset(parent, 0, sizeof(parent[0])*(n+1));
    memset(match, 0, sizeof(match[0])*(n+1));
    int ret = 0;
    for (int i = 1; i <= n; i++) {
        if (match[i] == 0 && bfs(i))
            ret++;
    }
    return ret;
}
void addEdge(int x, int y) {
    g[x].push_back(y), g[y].push_back(x);
}
void init(int _n) {
    n = _n;
    for (int i = 0; i <= n; i++)
        g[i].clear();
}
} algo;

```

● 穩定婚姻

```

const int maxn = 1100;
int manWant[maxn][maxn], nextW[maxn];
int women[maxn][maxn], order[maxn][maxn];
int wife[maxn], husband[maxn];
queue<int> singleDog;

void engage(int m, int w){
    if(husband[w]!=0){
        wife[ husband[w] ] = 0;
        singleDog.push( husband[w] );
        husband[w] = 0;
    }
    husband[w] = m;
    wife[m] = w;
}

```

```

// cout << m << " --> " << w << endl;
}
int main()
{
    int Time, n, cas = 0;
    scanf("%d",&Time);

    while(Time-- && scanf("%d",&n)==1){
        for(int i=1; i<=n; i++){
            for(int j=1; j<=n; j++)
                scanf("%d",&manWant[i][j]);
            nextW[i] = 1;
            wife[i] = 0;
            singleDog.push(i);
        }

        for(int i=1; i<=n; i++){
            for(int j=1; j<=n; j++){
                scanf("%d",&women[i][j]);
                order[i][ women[i][j] ] = j;
            }
            husband[i] = 0;
        }

        while(!singleDog.empty()){
            int x = singleDog.front(); singleDog.pop();
            // cout << x << endl;
            int to = manWant[x][nextW[x]++];

            if(husband[to]==0) engage(x, to);
            else if(order[to][husband[to]] >
order[to][x]) engage(x, to);
            else singleDog.push(x);
        }
        if(cas++) printf("\n");
        for(int i=1; i<=n; i++) printf("%d\n",
wife[i]);
    }
    return 0;
}

```

● 計算幾何

```

template<class T>
int intersection(Segment<T> &s1, Segment<T> &s2,
Point<T> &inter) {
    // Return 0 -> one point, 1 -> infinity, -1 -> no
    // Store intersection into inter.
    Vector<T>
v1={s1.p1,s1.p2},v2={s1.p1,s2.p1},v3={s1.p1,s2.p2};
    Vector<T>
v4={s2.p1,s2.p2},v5={s2.p1,s1.p1},v6={s2.p1,s1.p2};
    bool b1=op_signed(cross(v1,v2),cross(v1,v3));
    bool b2=op_signed(cross(v4,v5),cross(v4,v6));
    if (b1&&b2) {
        T mul=cross({s1.p1,s2.p1},v4)/cross(v1,v4);
        inter={s1.p1.x+mul*v1.x,s1.p1.y+mul*v1.y};
        return 0;
    }

    vector<Point<T>> v;
    if (in_segment(s1.p1,s2) v.push_back(s1.p1);
    if (in_segment(s1.p2,s2) v.push_back(s1.p2);
    if (in_segment(s2.p1,s1) v.push_back(s2.p1);
    if (in_segment(s2.p2,s1) v.push_back(s2.p2);
    if (v.empty()) return -1;
    if (v.size()==1 || (v.size()==2&&v[0]==v[1])) {
        inter=v[0];
        return 0;
    }
    return 1;
}

```

● EXT_GCD

```
typedef long long LL;
typedef pair < LL, LL > ii;

ii exd_gcd( LL a, LL b) {
    if (a % b == 0) return ii(0, 1);
    ii T = exd_gcd(b, a % b);
    return ii( T.second, T.first - a / b * T.second);
}
```

● LUCAS

```
const int N = 100000;
ll n, m, p = 24851, fac[N];
void init() {
    int i;
    fac[0] = 1;
    for(i = 1; i <= p; i++)
        fac[i] = fac[i-1] * i % p;
}
ll q_pow(ll a, ll b) {
    ll ans = 1;
    while(b) {
        if(b & 1) ans = ans * a % p;
        b >>= 1;
        a = a * a % p;
    }
    return ans;
}
ll C(ll n, ll m) {
    if(m > n) return 0;
    return fac[n] * q_pow(fac[m] * fac[n-m], p-2) % p;
}

ll Lucas(ll n, ll m) {
    if(m == 0) return 1;
    else return (C(n/p, m/p) * Lucas(n%p, m%p)) % p;
}
```

● Miller Rabin

```
inline long long mod_mul(long long a, long long b, long long m){
    a %= m, b %= m;
    long long y = (long long)((double)a * b / m + 0.5); /*
    fast for m < 2^58 */
    long long r = (a * b - y * m) % m;
    return r < 0 ? r + m : r;
}

template<typename T>
inline T pow(T a, T b, T mod){ // a^b % mod
    T ans = 1;
    for(; b; a = mod_mul(a, a, mod), b >>= 1)
        if(b & 1) ans = mod_mul(ans, a, mod);
    return ans;
}

int sprp[3] = {2, 7, 61}; // int % d^3 != i, N
int
llsprp[7] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022}
; // !ÜÖÜ unsigned long long % d^3
template<typename T>
inline bool isprime(T n, int *sprp, int num){
    if(n == 2) return 1;
    if(n < 2 || n % 2 == 0) return 0;
    int t = 0;
    T u = n - 1;
    for(; u % 2 == 0; ++t) u >>= 1;
    for(int i = 0; i < num; ++i){
        T a = sprp[i] % n;
        if(a == 0 || a == 1 || a == n - 1) continue;
        T x = pow(a, u, n);
        if(x == 1 || x == n - 1) continue;
        for(int j = 0; j < t; ++j){
            x = mod_mul(x, x, n);

```

```
        if(x == 1) return 0;
        if(x == n - 1) break;
    }
    if(x == n - 1) continue;
    return 0;
}
return 1;
}
```

● Formulas

滿足 $\text{ceil}(n/i) = k$ 之最大 i :

INF, if $k = 1$
 $n / (k - 1) - 1$, else if $k - 1$ 整除 n
 $x / (k - 1)$, else

滿足 $\text{floor}(n/i) = k$ 之最大 i : $\text{floor}(n/k)$

尤拉函數: $\phi(n) = n$ 乘上所有 $(1 - 1/p)$, 對 n 之所有質因數 p

費馬小定理: $a * a^{(p-2)} = 1 \pmod{p}$, a, p 互質

次方同餘定理: $a^k \pmod{p} = (a \pmod{p})^{(k \pmod{p-1})}$ p 是質數

枚舉擴展歐幾里得之解:

若 x_0, y_0 為 $a * x + b * y = k$ 之一組解, 則

$x = x_0 + t * b / \text{gcd}(a, b)$, $y = y_0 + t * a / \text{gcd}(a, b)$ 亦為解, t

為整數

最大獨立集: 點的集合, 其內點不相鄰

最小點覆蓋: 點的集合, 所有邊都被覆蓋

最大匹配: 邊的集合, 其內邊不共用點

最小邊覆蓋: 邊的集合, 所有點都被覆蓋

最大獨立集 + 最小點覆蓋 = V (數值)

最大匹配 + 最小邊覆蓋 = V (數值)

最大匹配 = 最大流 (二分圖)

最大匹配 = 最小點覆蓋 (二分圖)

最小點覆蓋 + 最小邊覆蓋 = V (數值, 二分圖)