

Encoded Archival Description 4.0 Tag Library Version 4.0.0

July 2026

**Prepared and maintained by the
Technical Subcommittee on Encoded
Archival Standards (TS-EAS)
Society of American Archivists**



**SOCIETY OF
American
Archivists**

Chicago

Encoded Archival Description 4.0 Tag Library Version 4.0.0, July 2026

Available from

17 North State Street, suite 1425
Chicago, IL 60602-3315
USA
312-606-0722
Fax: 312-606-0728
info@archivists.org
www.archivists.org

©Society of American Archivists, 2026.

Edition : 2026 Edition

Born digital.



This work is licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). See <http://creativecommons.org/licenses/by/4.0/>. Some rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means, electronic, mechanical or photocopying, recording, or otherwise without attribution.

eISBN: 978-1-958954-32-4

Table of Contents

Preface to the Tag Library.....	8
--	----------

Elements.....	10
----------------------	-----------

abstract.....	11
accessConditions.....	13
accruals.....	15
address.....	17
addressLine.....	19
agencyCode.....	21
agencyName.....	23
agent.....	25
agents.....	28
appraisal.....	30
archDesc.....	32
arrangement.....	34
biogHist.....	36
c.....	38
c01.....	41
c02.....	43
c03.....	45
c04.....	47
c05.....	49
c06.....	51
c07.....	53
c08.....	55
c09.....	57
c10.....	59
c11.....	61
c12.....	63
citedRange.....	65
contact.....	67
contactLine.....	69
container.....	71
control.....	73
conventionDeclaration.....	77
custodHist.....	79
date.....	81
dateRange.....	84
dateSet.....	87
descriptionOfComponents.....	89

descriptiveNote.....	91
dimensions.....	93
ead.....	95
eventDateTime.....	96
eventDescription.....	98
extent.....	100
filePlan.....	102
findAidDesc.....	104
formattingExtension.....	106
formAvailable.....	108
formAvailableId.....	111
formsAvailable.....	113
fromDate.....	115
function.....	117
functions.....	119
genreForm.....	121
geographicCoordinates.....	123
head.....	125
identificationData.....	127
label.....	129
language.....	131
languageDeclaration.....	133
languageOfMaterial.....	135
languageSet.....	137
legalStatus.....	139
localTypeDeclaration.....	141
maintenanceAgency.....	143
maintenanceEvent.....	145
maintenanceHistory.....	147
narrativeEvent.....	149
objectXMLWrap.....	151
otherAgencyCode.....	153
otherDescription.....	155
otherDescriptiveInfo.....	158
otherIdentificationData.....	160
otherRecordId.....	162
p.....	164
part.....	166
physicalDescription.....	168
physicalFacet.....	170
physicalOrTechnicalRequirements.....	172
place.....	174
placeName.....	177
places.....	179
preferCite.....	181
processInfo.....	183

publicationNote.....	185
quantity.....	187
recordId.....	189
recordTypeSpecificStatement.....	191
reference.....	193
referringString.....	195
relatedMaterial.....	197
relation.....	199
relations.....	201
relationship.....	203
rightsDeclaration.....	205
role.....	207
scopeContent.....	209
separatedMaterial.....	211
shortCode.....	213
source.....	215
sourceOfAcquisition.....	217
sources.....	219
span.....	221
subject.....	223
subjectHeadings.....	225
term.....	227
textualDate.....	229
title.....	231
toDate.....	233
unitDate.....	235
unitId.....	237
unitOfMeasurement.....	239
unitTitle.....	241
useConditions.....	243
writingSystem.....	245
Attributes.....	247
addressLineType.....	248
addressLineTypeEncoding.....	249
agentType.....	250
agentTypeEncoding.....	251
approximate.....	252
audience.....	253
audienceEncoding.....	254
calendar.....	255
certainty.....	256
contactLineType.....	257
contactLineTypeEncoding.....	258
containerId.....	259
conventionDeclarationReference.....	260
coordinateSystem.....	261

countryCode.....	262
countryEncoding.....	263
coverage.....	264
coverageEncoding.....	265
dateChar.....	266
dateEncoding.....	267
descriptionOfComponentsType.....	268
descriptionOfComponentsTypeEncoding.....	269
detailLevel.....	270
detailLevelEncoding.....	271
era.....	272
extentType.....	273
extentTypeEncoding.....	274
formAvailableType.....	275
formAvailableTypeEncoding.....	276
functionType.....	277
functionTypeEncoding.....	278
href.....	279
id.....	280
languageCode.....	281
languageEncoding.....	282
languageOfElement.....	283
level.....	284
levelEncoding.....	285
linkRole.....	286
linkTitle.....	287
localType.....	288
localTypeDeclarationReference.....	289
maintenanceEventReference.....	290
maintenanceEventType.....	291
maintenanceEventTypeEncoding.....	292
maintenanceStatus.....	293
maintenanceStatusEncoding.....	294
normalizedForm.....	295
notAfter.....	296
notBefore.....	297
placeType.....	298
placeTypeEncoding.....	299
publicationStatus.....	300
publicationStatusEncoding.....	301
referredEntityRelationship.....	302
referredEntityType.....	303
referredEntityTypeEncoding.....	304
relationType.....	305
relationTypeEncoding.....	306
repositoryCode.....	307

repositoryEncoding.....	308
scriptCode.....	309
scriptEncoding.....	310
scriptOfElement.....	311
sourceReference.....	312
standardDate.....	313
standardDateTime.....	314
status.....	315
statusEncoding.....	316
style.....	317
target.....	318
targetType.....	319
targetTypeEncoding.....	320
unit.....	321
unitDateType.....	322
unitDateTypeEncoding.....	323
valueURI.....	324
vocabularySource.....	325
vocabularySourceURI.....	326
Examples.....	327

Preface to the Tag Library

Encoded Archival Description (EAD) is the international metadata transmission standard for descriptions of archival records. Developed and maintained by the Technical Subcommittee on Encoded Archival Standards (TS-EAS) of the Society of American Archivists (SAA), EAD is used around the globe for digitally encoding the description of archival records.

The fourth revision of EAD (EAD 4.0) recognizes that the methods of developing and maintaining archival description have changed since EAD 1.0 (1998). The revised standard is designed for a digital-first world, focusing on interoperability with other SAA standards (namely EAC-CPF 3.0 and EAC-F 1.0), support for linked open data, and incorporating external schemas into EAD. EAD 4.0 also removes support for "print-first" features directly within the EAS schema, streamlines mixed content, and limits more complex nesting.

This tag library reflects the schema of EAD 4.0 after integrating community feedback via two public call for comments (April to July 2024, April to May 2025). For more information on the comments received and how they have been addressed, please see the [Overview 1st call for comments](#) and the [Overview 2nd call for comments](#). To learn more about the vision behind the new version of EAD, please see the [Infograph](#); for a description of the main features of EAD 4.0, please see the [Editorial Changes](#). Other relevant documents that document the revision process can be found on the TS-EAS [GitHub](#) page.

With the alignment between EAD and the other Encoded Archival Standards, this tag library is the first to combine shared elements and attributes between TS-EAS standards. These elements and attributes are available in EAD, the Encoded Archival Context - Corporate Bodies, Persons, Families (EAC-CPF), and the Encoded Archival Context - Functions (EAC-F). Elements and attributes specific to the description of records are included as EAD-only items. The descriptions of shared elements and attributes in this tag library have been adapted based on their existing versions in the EAC-CPF 2.0.1 tag library.

Encoding examples are now presented per section within the EAS structure, rather than having element-based and attribute-based examples. For example, encoding examples for all elements available under `<control>` are presented in the `<control>` example. With this, elements and attributes can better be presented in their broader application context and repetition is avoided. These section-based encoding examples will be included in the Tag Libraries as an annex with references from the individual elements and attributes.

This tag library is focused on technical implementation of the EAD 4.0 standard. A companion document, the [Best Practices Guide](#) (BPG), provides guidance on applying the standard in archival practice. The BPG includes in-depth explanations of elements and attributes, use cases, and additional examples.

Comments on EAD 4.0 should be sent to TS-EAS at the [Report an Issue form](#) or via the TS-EAS repositories for the [EAS schemas](#) respectively the [EAS Tag Libraries](#) on GitHub.

Elements

< abstract >

Abstract

Summary

An optional element within narrative elements such as [<biogHist>](#) that contains a brief summary of the information contained within the narrative element as a whole.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[accessConditions](#), [accruals](#), [appraisal](#), [arrangement](#), [biogHist](#), [custodHist](#), [filePlan](#), [otherDescription](#), [otherDescriptiveInfo](#), [physicalOrTechnicalRequirements](#), [preferCite](#), [processInfo](#), [publicationNote](#), [recordTypeSpecificStatement](#), [relatedMaterial](#), [scopeContent](#), [separatedMaterial](#), [sourceOfAcquisition](#), [subjectHeadings](#), [useConditions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

The [<abstract>](#) is a brief synopsis of the information in the narrative element that it is used with. Its purpose is to help readers quickly identify

the most important aspects in each context. The content within this element may also be harvested by other systems to provide explanatory context when appearing e.g. in a set of search results.

[<abstract>](#) may include one or more [<reference>](#) elements to point to external resources that provide additional descriptive data. It may furthermore include one or more [<referringString>](#) elements to emphasize entities' names as part of the descriptive texts and to point to external vocabularies for more information about these, where applicable.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< accessConditions >

Access Conditions

Summary

An element for information about conditions that affect the availability and accessibility of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
dateRange	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@localType](#), if local use requires specification of the type of access conditions.

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the rules around access in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

Record in [<accessConditions>](#) information about the availability and accessibility of the described materials, whether due to the nature of the information in the materials being described, the physical condition of the materials, or the location of the materials. Examples include restrictions imposed by the donor, legal statute, repository, or other agency, as well as the need to make an appointment with repository staff. May also indicate that the materials are not restricted or that specific measures have been or need to be taken for the accessibility of the materials. Use the sub-element [<dateRange>](#) to provide information about the time span during which or until when these access conditions apply.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<accessConditions>](#). Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order for all child elements is:

[<abstract>](#)

[<dateRange>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<useConditions>](#), which records information about the conditions governing the use and re-use of the described materials after access has been granted.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< accruals >

Accruals

Summary

An element for information about anticipated additions to the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Used to indicate anticipated additions to the material already held by the repository. May indicate quantity and frequency of the accruals. The element may also be used to indicate no additions are expected.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<accruals>](#) . Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use

[<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<processInfo>](#) which describes the activities conducted by the staff of an institution with archival holdings in preparing the described materials for research and other use. This might or might not include activities related to processing any new additions to already existing record sets.

Do not confuse with [<maintenanceHistory>](#) which describes events in the lifetime of the EAD instance, not the materials being described.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< address >

Address

Summary

An optional child element of <place> that binds together one or more <addressLine> elements to encode a postal or other address.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
addressLine	1..n

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

<address> is an optional wrapper element within <place> used to encode a physical or analog address.

Ideally <address> should be bundled with a <label> element within <place> to provide both the name and address of a location.

<address> must include one or more <addressLine> element(s) that provide full or sufficient information identifying a postal or other physical address related to the entity being described.

Availability

Optional, repeatable

See also

Use [<contact>](#) to encode digital addresses and contact information.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< addressLine >

Address Line

Summary

A required child element of < address > used for recording one line of a postal or other address.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

address

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
addressLineType	Optional
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the optional @addressLineType attribute to encode the part of the address that the < addressLine > refers to, for example "street".

Use the optional @addressLineTypeEncoding in < control > to specify the source or rules for values supplied in @addressLineType.

Description and Usage

< addressLine > is used to encode parts or lines of a physical address within a parent < address > element.

[<addressLine>](#) may be repeated as many times as necessary to enter all parts of an address.

Availability

Required, repeatable

Examples

See [<archDesc>](#) , [<findAidDesc>](#) encoding

[Table of Contents](#)

< agencyCode >

Agency Code

Summary

An optional child element of [< maintenanceAgency >](#) that provides a code for the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceAgency](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
status	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@status](#) with values such as “authorized” or “alternative” to declare whether the [< agencyCode >](#) is using an authorized value, e.g. a registered ISIL code, or an alternative code. Use [@statusEncoding](#) in [< control >](#) to specify the source or rules for values supplied in [@status](#).

Description and Usage

Use [< agencyCode >](#) to record a code indicating the institution or service responsible for the creation, maintenance and/or dissemination of the EAS instance. Use of [< agencyCode >](#) is recommended, as the combination of

[<agencyCode>](#) and the required [<recordId>](#) can provide a globally unique identifier for the instance.

[<maintenanceAgency>](#) must include one or both of [<agencyCode>](#) and [<agencyName>](#) .

It is recommended that the code follows the format of the International Standard Identifier for Libraries and Related Organizations ([ISIL: ISO 15511](#)): a prefix, a dash, and an identifier. The code is alphanumeric (characters A-Z, 0-9, solidus, hyphen-minus, and colon) with a maximum of 16 characters. If appropriate to local or national convention, insert a valid ISIL for an institution, whether provided by a national authority (usually the national library) or a service (such as OCLC). If this is not the case then local institution codes may be given with the [ISO 3166-1 alpha-2](#) country code as the prefix to ensure international uniqueness in [<agencyCode>](#) .

Availability

Optional, not repeatable

See also

Use [<agencyName>](#) to record the name of the agency. Use [<otherAgencyCode>](#) to record any alternative codes representing the agency. Use [<recordId>](#) in combination with [<agencyCode>](#) to form a globally unique identifier for the EAS instance.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< agencyName >

Agency Name

Summary

An optional child element of [< maintenanceAgency >](#) that provides the name of the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceAgency](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [< agencyName >](#) to record the name of the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance. Examples include the repository name or the name of an aggregation service.

[< maintenanceAgency >](#) must include one or both of [< agencyName >](#) and [< agencyCode >](#) .

It is recommended to use the form of the agency name that is authorized by an appropriate national or international agency or service.

[<agencyName>](#) may be repeated in order to provide the name of the institution or service responsible for the EAS instance in multiple languages or name settings. If [<agencyName>](#) is repeated it is recommended to indicate the language of each name using [@languageOfElement](#).

Availability

Optional, repeatable

See also

Use [<agencyCode>](#) to record a code representing the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< agent >

Agent

Summary

An element that provides the name of a person, institution, or other type of agent related to the archival materials being described or relevant to the EAS instance itself or any instantiation of it, e.g. a printed or online finding aid. Also available in [<narrativeEvent>](#) to name a person, institution, or other type of agent of importance to the history and processing of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
label	1..n
placeName	0..n
relationship	0..n
role	0..n

May occur within

[agents](#), [findAidDesc](#), [maintenanceEvent](#), [narrativeEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
agentType	Optional
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use the `@agentType` attribute to specify whether the agent is, for example, a "corporateBody", "mechanism", or "person". Use the optional `@agentTypeEncoding` in `<control>` to specify the source or rules for values supplied in `@agentType`.

Use the attributes `@valueURI`, `@vocabularySource`, and `@vocabularySourceURI` with `<agent>` when referencing an entry of an external vocabulary, thesaurus, ontology applicable to the agent overall. In case of referencing different vocabularies or different entries within the same vocabulary for the name or the role of the agent, use the three attributes with the sub-elements `<label>` or `<role>` directly.

Description and Usage

`<agent>` is a required and repeatable sub-element of `<agents>` and can be used to name persons, organizations, and families related to the archival materials being described as well as their specific relationship with and role towards the materials. The required sub-element `<label>` is used to encode the name of the agent, while the optional `@agentType` and `<role>` allow for specifying the type of agent in question and for providing information about their role in relation to the materials being described (e.g., if a person is the "creator" of the materials or a "contributor" or if they are the "director" or the "cinematographer" of audiovisual material or the "defendant" or the "plaintiff" in court records). Use the sub-elements `<relationship>`, `<date>`, `<dateRange>`, or `<dateSet>`, and `<placeName>` along with the optional `<descriptiveNote>` to describe the relationship between the agent and the materials being described in more detail.

Use `<agent>` as a required sub-element of `<maintenanceEvent>` to name and describe the person, institution, or system responsible for a maintenance event. Examples include the name of the author or encoder, the database responsible for creating the EAS instance, and the style sheet used to update an instance to a new version of the EAS. Use `<agent>` as an optional and repeatable sub-element of `<findAidDesc>` to indicate any person, institution, or system relevant to the creation, publication, or dissemination of any instantiations of the EAS instance such as the author, publisher, or sponsor of a printed or online finding aid. Use `<agent>` as an optional sub-element in `<narrativeEvent>` to name a person, institution, or other type of agent of importance to a specific event in the history or the processing of materials being described.

The prescribed order of all child elements (both required and optional) is:

`<label>`

One of `<date>`, `<dateRange>`, or `<dateSet>`

`<placeName>`

[<role>](#)

[<relationship>](#)

[<descriptiveNote>](#)

Availability

Within [<agents>](#) : required, repeatable

Within [<findAidDesc>](#) and [<narrativeEvent>](#) : optional, repeatable

Within [<maintenanceEvent>](#) : required, not repeatable

Examples

See [<archDesc>](#) , [<control>](#) , and [<findAidDesc>](#) encoding

[Table of Contents](#)

< agents >

Agents

Summary

An optional child of < archDesc > and < c > that groups together agents related to the described records.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	1..n
descriptiveNote	0..1

May occur within

archDesc, c, c01, c02, c03, c04, c05, c06, c07, c08, c09, c10, c11, c12

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use < agents > to bind together one or more < agent > elements.
< agents > must include at least one < agent > element.

The prescribed order of all child elements (both required and optional) is:

< agent >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< appraisal >

Appraisal Information

Summary

An element for documenting decisions and actions related to assessing the archival value and disposition of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A statement of the rationale for decisions related to appraisal and disposition of the materials being described. Such decisions may be based upon the records' current administrative, legal, and fiscal use; their evidential, intrinsic, and informational value; their arrangement and condition; and their relationship to other records. May include information about destruction actions, sampling, and disposition schedules.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<appraisal>](#). Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML. Use [<narrativeEvent>](#) to provide a chronology of appraisal events.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

[<narrativeEvent>](#)

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< archDesc >

Archival Description

Summary

A required child element of [<ead>](#) that binds together all of the archival descriptive information in an EAD instance

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
custodHist	0..n
descriptionOfComponents	0..1
filePlan	0..n
formsAvailable	0..1
functions	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[ead](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

An element for binding together the bulk of an EAD instance, which typically should include elements describing the content, context, and extent of a body of archival materials, as well as containing administrative and supplemental information that facilitates use of the materials. The elements are organized in hierarchical levels that provide a descriptive overview of the whole, optionally followed by more specific description of the component parts. Descriptive information is inherited downward, from one hierarchical level to the next.

The first child of [<archDesc>](#) must be the required [<identificationData>](#) that provides core information about the overall unit being described in the finding aid. This may be followed by a variety of notes and controlled access elements that describe or provide administrative information about the whole of the materials being described. [<archDesc>](#) may also include information about subordinate units, which are bound together within [<descriptionOfComponents>](#) containing one or more levels of subordinate components. Use the component elements ([<c>](#) or [<c01>](#) - [<c12>](#)) within [<descriptionOfComponents>](#) to describe multiple levels of subordinate components. These use the same child elements as [<archDesc>](#) .

Availability

Required, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< arrangement >

Arrangement

Summary

An element for describing the organization or filing sequence of the records.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#),
[formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [< arrangement >](#) to record the logical or physical groupings within a hierarchical structure and their relationships. This includes how the described materials have been subdivided into smaller units, e.g., record groups into series. May also indicate the filing sequence of the described materials, for example chronological or alphabetical arrangement.

Use the element [< abstract >](#) to provide a brief summary of the information encoded in [< arrangement >](#) . Use the repeatable [< p >](#) element to

structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<filePlan>](#) , which includes information about any classification scheme used by the original creator.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< biogHist >

Biography or History

Summary

A concise essay and/or chronology that provides biographical or historical information about the creator(s) of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< biogHist >](#) includes significant details about the life of an individual or family, or the administrative history of a corporate body.

Use the element [< abstract >](#) to provide a brief summary of the information encoded in [< biogHist >](#) . Use the repeatable [< p >](#) element to structure longer texts in several paragraphs. If required and suitable, use [< formattingExtension >](#) to make use of more detailed formatting options

such as lists, tables, or section headers in XHTML. Use [<narrativeEvent>](#) to provide a chronology of the biography or history of the entity.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

[<narrativeEvent>](#)

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< c >

Component (unnumbered)

Summary

An element that designates a subordinate part of the materials being described

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c](#), [descriptionOfComponents](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

As a wrapper for a set of elements, `<c>` provides information about the content, context, and extent of a subordinate body of materials. It is always a child or descendant of `<descriptionOfComponents>` and often a child and/or parent of another `<c>`.

Each `<c>` identifies a logical section, or level, of the described materials. Components may be subdivided into smaller and smaller components and may eventually reach the level of a single item. For example, the components of a collection may be a series, components of series may be subseries, components of subseries may be files, and components of files may be items.

The physical filing separations between components need not always coincide with the intellectual separations. For example, a `<c>` that designates dramatic works might end in the same box in which the next `<c>` begins with short stories. Also, not every `<c>` directly corresponds to a folder or other physical entity. Some `<c>` elements simply represent a logical point in a hierarchical description.

Availability

Optional, repeatable

See also

The numbered elements `<c01>`, `<c02>`, etc. are an alternative way to designate components. Use either the unnumbered `<c>` or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See `<identificationData>` encoding

Table of Contents

< c01 >

Component (first level)

Summary

An element that designates the top or first-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c02	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[descriptionOfComponents](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c01>](#) is a first-level wrapper for subordinate components within [<descriptionOfComponents>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c01>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c02 >

Component (second level)

Summary

An element that designates a second-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c03	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c01](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c02>](#) is a second-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c01>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c02>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c03 >

Component (third level)

Summary

An element that designates a third-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c04	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c02](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c03>](#) is a third-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c02>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c03>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c04 >

Component (fourth level)

Summary

An element that designates a fourth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c05	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c03](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c04>](#) is a fourth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c03>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c04>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c05 >

Component (fifth level)

Summary

An element that designates a fifth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c06	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c04](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c05>](#) is a fifth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c04>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c05>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c06 >

Component (sixth level)

Summary

An element that designates a sixth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c07	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c05](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c06>](#) is a sixth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c05>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c06>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c07 >

Component (seventh level)

Summary

An element that designates a seventh-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c08	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c06](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c07>](#) is a seventh-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c06>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c07>](#) in one part of a finding aid may designate a series, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c08 >

Component (eighth level)

Summary

An element that designates a eighth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c09	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c07](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c08>](#) is a eighth-level wrapper for subordinate components within [<descriptionOfComponents>](#) . Its parent must be [<c07>](#) . Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c08>](#) in one part of a finding aid may designate a file, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c09 >

Component (ninth level)

Summary

An element that designates a ninth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c10	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c08](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c09>](#) is a ninth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c08>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c09>](#) in one part of a finding aid may designate a file, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c10 >

Component (tenth level)

Summary

An element that designates a tenth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c11	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c09](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c10>](#) is a tenth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c09>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c10>](#) in one part of a finding aid may designate a file, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c11 >

Component (eleventh level)

Summary

An element that designates a eleventh-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
c12	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c10](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c11>](#) is a eleventh-level wrapper for subordinate components within [<descriptionOfComponents>](#) . Its parent must be [<c10>](#) . Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c11>](#) in one part of a finding aid may designate a file, while in another part of the finding aid it may designate an item.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< c12 >

Component (twelfth level)

Summary

An element that designates a twelfth-level subordinate part of the materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
agents	0..1
appraisal	0..n
arrangement	0..n
biogHist	0..n
custodHist	0..n
filePlan	0..n
formsAvailable	0..1
functions	0..1
head	0..1
identificationData	1..1
otherDescription	0..n
otherDescriptiveInfo	0..n
places	0..1
preferCite	0..n
processInfo	0..n
publicationNote	0..n
recordTypeSpecificStatement	0..n
relatedMaterial	0..n
scopeContent	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
subjectHeadings	0..n
useConditions	0..n

May occur within

[c11](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
level	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<c12>](#) is a twelfth-level wrapper for subordinate components within [<descriptionOfComponents>](#). Its parent must be [<c11>](#). Numbering components may assist a finding aid encoder in accurately nesting them.

The numbering of components indicates hierarchy within the encoded finding aid, not the order of the components or a specific intellectual grouping. For instance, [<c12>](#) in one part of a finding aid may designate a file, while in another part of the finding aid it may designate an item.

[<c12>](#) is the lowest hierarchical level permitted when using numbered components.

Availability

Optional, repeatable

See also

The unnumbered element [<c>](#) is an alternative way to designate components. Use either the unnumbered [<c>](#) or the numbered alternatives. Do not mix the two in a single EAD instance.

Examples

See [<identificationData>](#) encoding (as c)

[Table of Contents](#)

< citedRange >

Cited Range

Summary

An optional child element of <source> and <findAidDesc> that identifies precisely where supporting evidence was found within the source or in which compilation the finding aid was published.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

findAidDesc, source

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
unit	Optional

Attribute usage

Use the optional @unit attribute to specify the format that the <citedRange> refers to, for example page number or volume number.

Description and Usage

The <citedRange> element can be used to refer to a specific location within a source where supporting evidence can be found. It may refer to a specific location such as a single page, or a broader location such as a range of pages.

When used in [<findAidDesc>](#) , [<citedRange>](#) might refer to the designated part of a compilation in the context of which a finding aid has been published.

Availability

Optional, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< contact >

Contact

Summary

An optional child element of < place > that binds together one or more < contactLine > elements to encode contact details or digital addresses.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
contactLine	1..n

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

< contact > is an optional wrapper element within < place > used to encode digital addresses and contact information.

< contact > must include one or more < contactLine > element(s) that provide relevant contact details for the entity being described.

Availability

Optional, repeatable

See also

Use [<address>](#) to encode a physical or analog address.

Examples

See [<archDesc>](#) and [<findAidDesc>](#) encoding

[Table of Contents](#)

< contactLine >

Contact Line

Summary

A required child element of [< contact >](#) used for recording one line of contact details or digital addresses.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[contact](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
contactLineType	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the optional [@contactLineType](#) attribute to encode the type of contact detail that the [< contactLine >](#) refers to, for example "phoneNumber".

Use [@contactLineTypeEncoding](#) in [< control >](#) to specify the source or rules for values supplied in [@contactLineType](#).

Description and Usage

[<contactLine>](#) is used to encode separate details or lines of contact details or digital addresses within a parent [<contact>](#) element.

[<contactLine>](#) may be repeated as many times as necessary to enter all relevant contact details.

Availability

Required, repeatable

Examples

See [<archDesc>](#) and [<findAidDesc>](#) encoding

[Table of Contents](#)

< container >

Container

Summary

An optional child element of [<identificationData>](#) and [<formAvailable>](#) for indicating the container in which the material being described is housed, e.g., box, folder.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[formAvailable](#), [identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
containerId	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
vocabularySource	Optional
vocabularySourceURI	Optional
valueURI	Optional

Attribute usage

Use [@target](#) to indicate the container in which the current container is housed, e.g., a box in which a folder is housed.

Description and Usage

[<container>](#) contributes to locating the described materials by indicating the kinds of containers that physically hold the materials and identifying any sequential numbers assigned to those containers. [<container>](#) is used most frequently at the component level. This storage information can help researchers understand how extensive the described material is, especially in the absence of a specific [<extent>](#) statement at the component level.

Availability

Optional, repeatable

See also

Use [<place>](#) to designate the shelves, stacks, rooms, buildings, or other places where the containers are stored.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< control >

Control

Summary

A required child element of the root element that contains information about the creation, maintenance, status and the rules and authorities used in the composition of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
conventionDeclaration	0..n
languageDeclaration	0..n
localTypeDeclaration	0..n
maintenanceAgency	1..1
maintenanceHistory	1..1
otherRecordId	0..n
recordId	1..1
rightsDeclaration	0..n
sources	0..1

May occur within

[ead](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
addressLineTypeEncoding	Optional (values limited to: EASList, otherAddressLineTypeEncoding)
agentTypeEncoding	Optional (values limited to: EASList, otherAgentTypeEncoding)
audience	Optional
audienceEncoding	Optional (values limited to: EASList, otherAudienceEncoding)
contactLineTypeEncoding	Optional (values limited to: EASList, otherContactLineTypeEncoding)
countryEncoding	Optional (values limited to: iso3166-1-alpha-2, iso3166-1-alpha-3, iso3166-1-numeric, iso3166-2, iso3166-3, other-CountryEncoding)

<i>Attribute name</i>	<i>Attribute values</i>
coverageEncoding	Optional (values limited to: EASList, otherCoverageEncoding)
dateEncoding	Optional (values limited to: iso8601, otherDateEncoding)
descriptionOfComponentsTypeEncoding	Optional (values limited to: EASList, otherDescriptionOfComponentsTypeEncoding)
detailLevel	Optional
detailLevelEncoding	Optional (values limited to: EASList, otherDetailLevelEncoding)
extentTypeEncoding	Optional (values limited to: EASList, otherExtentTypeEncoding)
formAvailableTypeEncoding	Optional (values limited to: EASList, otherFormAvailableTypeEncoding)
functionTypeEncoding	Optional (values limited to: EASList, otherFunctionTypeEncoding)
id	Optional
languageEncoding	Optional (values limited to: ietf-bcp-47, iso639-1, iso639-2, iso639-2b, iso639-2t, iso639-3, iso639-5, other-LanguageEncoding)
languageOfElement	Optional
levelEncoding	Optional (values limited to: EASList, otherLevelEncoding)
maintenanceEventTypeEncoding	Optional (values limited to: EASList, otherMaintenanceEventTypeEncoding)
maintenanceStatus	Optional
maintenanceStatusEncoding	Optional (values limited to: EASList, otherMaintenanceStatusEncoding)
placeTypeEncoding	Optional (values limited to: EASList, otherPlaceTypeEncoding)
publicationStatus	Optional
publicationStatusEncoding	Optional (values limited to: EASList, otherPublicationStatusEncoding)
referredEntityTypeEncoding	Optional (values limited to: EASList, otherReferredEntityTypeEncoding)
relationTypeEncoding	Optional (values limited to: EASList, otherRelationTypeEncoding)
repositoryEncoding	Optional (values limited to: iso15511, otherRepositoryEncoding)
scriptEncoding	Optional (values limited to: iso15924, otherScriptEncoding)
scriptOfElement	Optional
statusEncoding	Optional (values limited to: EASList, otherStatusEncoding)
target	Optional

Attribute name

[targetTypeEncoding](#)

[unitDateTypeEncoding](#)

Attribute values

Optional (values limited to: EASList, otherTargetTypeEncoding)

Optional (values limited to: EASList, otherUnitDateTypeEncoding)

Attribute usage

Use the optional [@maintenanceStatus](#), [@publicationStatus](#), and [@detailLevel](#) attributes to document the current version status of the EAS instance, its current editorial status and the current level of detail included in its descriptive sections.

Use the optional encoding attributes such as [@countryEncoding](#), [@maintenanceEventTypeEncoding](#) or [@relationTypeEncoding](#) to specify the source or rules for values supplied in those attributes used throughout the EAS instance that rely either on code lists from ISO standards or make use of the value lists defined and maintained by the Technical Subcommittee on Encoded Archival Standards (TS-EAS). Should you decide to use other authorized value lists in these attributes instead, it is highly recommended to indicate this by using the "other..." value in the encoding attributes and to name and refer to these other value lists in [<conventionDeclaration>](#) to still enable semantic interoperability.

Description and Usage

This required wrapper element within the root element of an EAS instance contains the information necessary to manage the instance itself. This includes information about its creation, maintenance and status as well as the languages, rules and authorities used in the composition of the description.

It must contain a unique identifier for the instance within the [<recordId>](#) element. Other associated identifiers may be given in [<otherRecordId>](#) . There must be a description of the agency responsible for its creation and maintenance in [<maintenanceAgency>](#) as well as statements about the creation, maintenance, and disposition of the instance, as applicable, in [<maintenanceHistory>](#) .

There are optional elements available to declare languages, rules, conventions and sources used in the EAS instance and licensing information about the EAS instance itself. Local types for certain elements used throughout the EAS instance are recommended to be defined in the [<localTypeDeclaration>](#) element.

The available child elements (both required and optional), in their prescribed order, are:

[<recordId>](#) - Required. Contains the unique identifier for the EAS instance.

[< maintenanceAgency >](#) - Required. Contains the name and coded information about the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

[< maintenanceHistory >](#) - Required. Contains information about the date, type and events within the life cycle of an EAS instance.

[< sources >](#) - Optional. Contains information about the sources consulted in creating the descriptive parts of the EAS instance.

The following elements may appear in any order after the above elements:

[< conventionDeclaration >](#) - Optional. Contains information on the rules or conventions used to construct the EAS instance.

[< languageDeclaration >](#) - Optional. Contains coded and natural language information about the language or languages of the EAS instance.

[< localTypeDeclaration >](#) - Optional. Contains information about local conventions used in the [@localType](#) attribute.

[< otherRecordId >](#) - Optional. An element that allows the recording of additional identifiers that may be associated with the EAS instance.

[< rightsDeclaration >](#) - Optional. Contains information about the usage rights of the EAS instance.

Availability

Required, not repeatable

Examples

See [< control >](#) encoding

[Table of Contents](#)

< conventionDeclaration >

Convention Declaration

Summary

An optional child element of [<control>](#) , used to declare the rules or conventions, including authorized controlled vocabularies and thesauri, applied in creating the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[< conventionDeclaration >](#) is used for declaring references to any rules and conventions, including authorized controlled vocabularies or thesauri, applied in the construction of the description. The element binds together the required [<reference>](#) element with optional [<shortCode>](#) and [<descriptiveNote>](#) elements that identify rules or conventions applied in compiling the EAS instance.

Each additional rule or set of rules, controlled vocabulary, or standard should be contained in a separate [< conventionDeclaration >](#) .

[<shortCode>](#) may be used to identify the standard or controlled vocabulary in a coded structure. Any notes relating to how these rules or conventions have been used may be given within [<descriptiveNote>](#) .

Use [<conventionDeclaration>](#) to name and refer to other authorized value lists, if you use these instead of the EAS lists or ISO standards available with the optional encoding attributes in [<control>](#) (e.g. [@countryEncoding](#), [@maintenanceEventTypeEncoding](#) or [@relationTypeEncoding](#)). It is recommended that [<reference>](#) includes a link to these other value lists to still enable semantic interoperability.

The prescribed order of all child elements (both required and optional) is:

[<reference>](#)

[<shortCode>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

See also

Use [<localTypeDeclaration>](#) to indicate any local or consortial value lists that you might use with [@localType](#) throughout the EAS instance.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< **custodHist** >

Custodial History

Summary

An element for information about the chain of ownership or custody of the materials being described, before they reached the archives.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< custodHist >](#) may be used to describe both physical possession and intellectual ownership, providing details of changes of ownership and/or custody that may be significant in terms of authority, integrity, and interpretation.

Use the element `<abstract>` to provide a brief summary of the information encoded in `<custodHist>`. Use the repeatable `<p>` element to structure longer texts in several paragraphs. If required and suitable, use `<formattingExtension>` to make use of more detailed formatting options such as lists, tables, or section headers in XHTML. Use `<narrativeEvent>` to provide a chronology of the custodial history.

The prescribed order of all child elements (both required and optional) is:

`<abstract>` (if used)

`<formattingExtension>` or `<p>`

`<narrativeEvent>`

Availability

Optional, repeatable

See also

Use `<sourceOfAcquisition>` to record information about the immediate source of the described materials and the circumstances under which they were received by the repository.

Examples

See `<archDesc>` encoding

[Table of Contents](#)

< date >

Date

Summary

An element for encoding a single date relating to the entity or materials being described, or in their relationship to other entities.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [dateSet](#), [findAidDesc](#), [formAvailable](#), [function](#), [legalStatus](#), [narrativeEvent](#), [place](#), [relation](#), [subject](#), [unitDate](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
era	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
notAfter	Optional
notBefore	Optional
scriptOfElement	Optional
standardDate	Optional
status	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.

Use [@standardDate](#) to provide a machine-processable form of the date.

Use [@status](#) e.g. with the value "unknown" to indicate where a date is unknown.

Description and Usage

An element for expressing a single date relating to the materials being described, or in their relationship to, e.g., a place, a function, a resource, or a subject.

The content of the element is intended to be a human-readable natural language date with a machine-readable date provided as the value of the [@standardDate](#) attribute, formulated according to ISO 8601 or another rule for encoding dates as defined by [@dateEncoding](#) within [<control>](#). Uncertain or approximate dates can be encoded in [@standardDate](#) using Extended Date/Time Format (EDTF).

Availability

Within [<agent>](#), [<formAvailable>](#), [<function>](#), [<legalStatus>](#), [<place>](#), [<relation>](#), [<subject>](#), [<unitDate>](#): one of [<date>](#), [<dateRange>](#), or [<dateSet>](#) optional, not repeatable

Within [<findAidDesc>](#): at least one of [<agent>](#), [<citedRange>](#), [<date>](#), [<formattingExtension>](#), [<place>](#) or [<title>](#) required, repeatable

Within [<narrativeEvent>](#): required, repeatable

Within [<dateSet>](#): at least two of [<date>](#) and/or [<dateRange>](#) required, repeatable

See also

If the event or relationship has inclusive dates use the [<dateRange>](#) element, while more complex dates (combining singles dates and date ranges) can be expressed in [<dateSet>](#).

Dates of creation or accumulation of the materials being described are encoded with the [<unitDate>](#) element, which also includes the [<textualDate>](#) element used with textual date information that cannot be expressed in a standardized format.

The date and time of a maintenance event in the history of the EAS instance are given in the [<eventDateTime>](#) element.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< dateRange >

Date Range

Summary

A wrapper element for binding together [< fromDate >](#) and [< toDate >](#) in order to represent a range of dates. Either [< fromDate >](#) or [< toDate >](#) must be present within a [< dateRange >](#) , but it is recommended to use both child elements whenever possible.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
fromDate	0..1
toDate	0..1

May occur within

[accessConditions](#), [agent](#), [dateSet](#), [formAvailable](#), [function](#), [legalStatus](#), [place](#), [relation](#), [subject](#), [unitDate](#), [useConditions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@localType](#) to supply a more specific characterization of the date range.

Description and Usage

An element that expresses a range of dates in the creation or contextual history of the described materials, or their relationships to other entities such as

persons, families, corporate bodies, resources, functions, places, and topics.
<dateRange> can also be used to express potential temporal characteristics of the conditions of access to and use of the materials and their instantiations.

<dateRange> contains <fromDate> and/or <toDate> , and therefore may express a range of dates as a starting point with no end point, a start and end point, or an end point with no starting point. Either <fromDate> or <toDate> must be present within a <dateRange> , but it is recommended to use both child elements whenever possible.

The content of the children of <dateRange> is intended to be a human-readable, natural language expression of the dates. If, however, indexing or other machine processing of dates is desired, @standardDate should be used on the children of <dateRange> to record the date in machine-processable form as well.

The prescribed order of all child elements (both required and optional) is:

<fromDate>

<toDate>

Availability

Within <accessConditions> , <useConditions> : optional, not repeatable

Within <agent> , <formAvailable> , <function> , <legalStatus> , <place> , <relation> , <subject> , <unitDate> : one of <date> , <dateRange> , or <dateSet> optional, not repeatable

Within <dateSet> : at least two of <date> and/or <dateRange> required, repeatable

See also

If the event or relationship has single dates use the <date> element, while more complex dates (combining singles dates and date ranges) can be expressed in <dateSet> .

Dates of creation or accumulation of the materials being described are encoded with the <unitDate> element, which also includes the <textualDate> element used with textual date information that cannot be expressed in a standardized format.

The date and time of a maintenance event in the history of the EAS instance are given in the <eventDateTime> element.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< dateSet >

Date Set

Summary

A wrapper element for encoding complex dates that cannot be adequately represented in one <date> or <dateRange> .

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange	2..n

May occur within

agent, formAvailable, function, legalStatus, subject, place, relation, unitDate

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

<dateSet> binds together single dates and date ranges, multiple single dates, or multiple date ranges. <dateSet> is used in situations where complex date information needs to be conveyed and requires at least two child elements. These can be any combination of <date> and <dateRange> .

Availability

Optional, not repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< descriptionOfComponents >

Description of Subordinate Components

Summary

A wrapper element that bundles information about the hierarchical groupings of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
c	0..n
c01	0..n
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
descriptionOfComponentsType	Optional
descriptionOfComponentsTypeEncoding	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@descriptionOfComponentsType](#) to identify the format or level of descriptive detail used in this `<descriptionOfComponents>` .

Use [@descriptionOfComponentsTypeEncoding](#) in `<control>` to specify the source or rules for values supplied in [@descriptionOfComponentsType](#).

Description and Usage

Use [<descriptionOfComponents>](#) to wrap subordinate components in the archival hierarchy of the materials being described.

This element may contain either a descriptive overview of the subordinate components, a hierarchical set of more detailed descriptions of the subordinate components, or both.

If a descriptive overview is included, it should sit within either [<p>](#) or [<formattingExtension>](#) elements.

A hierarchy of subordinate components should be nested within either unnumbered [<c>](#) elements or numbered [<c01>](#) , [<c02>](#) , etc. elements. Do not mix unnumbered and numbered component elements within a single EAD instance.

If [<p>](#) or [<formattingExtension>](#) elements are used they should come first, before any [<c>](#) or [<c01>](#) elements.

Availability

Optional, not repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< descriptiveNote >

Descriptive Note

Summary

An element used to provide general descriptive information related to its parent element, either as narrative text or encoded in a related standard.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
objectXMLWrap	0..1
p	1..n

May occur within

[agent](#), [agents](#), [conventionDeclaration](#), [extent](#), [formAvailable](#), [formsAvailable](#), [function](#), [functions](#), [identificationData](#), [languageDeclaration](#), [languageOfMaterial](#), [languageSet](#), [legalStatus](#), [localTypeDeclaration](#), [maintenanceAgency](#), [physicalDescription](#), [place](#), [places](#), [relation](#), [relations](#), [rightsDeclaration](#), [source](#), [sources](#), [subject](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

<[descriptiveNote](#)> provides additional descriptive information about the element in which it is contained. <[descriptiveNote](#)> must contain one or more <[p](#)> elements.

With the optional element <[objectXMLWrap](#)> , <[descriptiveNote](#)> also allows for the inclusion of information encoded in other formats and standards

that add further details to its parent element which could not be encoded in the EAS.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) , [<control>](#) , [<findAidDesc>](#) , and [<identificationData>](#) encoding

[Table of Contents](#)

< dimensions >

Dimensions

Summary

An optional child element of [< physicalDescription >](#) that provides information about the size of the material being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
quantity	0..1
unitOfMeasurement	0..1

May occur within

[physicalDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< dimensions >](#) may be used to specify the size, in two or three dimensions, of the units identified within [< extent >](#) . It usually includes numerical data. Express measurements in any convenient unit as indicated in the [< unitOfMeasurement >](#) sub-element of [< dimensions >](#) , for example, "inches" or "centimeters.". Multiple dimensions, for example, height-by-width, can be encoded in a single [< dimensions >](#) or in separate [< dimensions >](#) with distinctive [@localType](#) values.

Either the sub-element [<quantity>](#) or the sub-element [<unitOfMeasurement>](#) must be present within [<dimensions>](#) , but it is recommended to use both child elements whenever possible.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< ead >

Encoded Archival Description

Summary

The required root element of an EAD instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
archDesc	1..1
control	1..1
findAidDesc	0..n

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional

Attribute usage

If the [@audience](#) value is set to "external", data in all descendant elements will be displayed, unless the value is changed individually for specific elements.

Description and Usage

[< ead >](#) wraps all other elements in an Encoded Archival Description document (or finding aid). A finding aid (or inventory) establishes intellectual and physical control over many types of archival materials and helps researchers understand and access the materials being described.

[< ead >](#) must contain both [< control >](#) and [< archDesc >](#) elements. Use [< control >](#) first, followed optionally by [< findAidDesc >](#) with [< archDesc >](#) last.

Availability

Required, not repeatable

[Table of Contents](#)

<eventDateTime>

Maintenance Event Date and Time

Summary

A required child element of [<maintenanceEvent>](#) that records the date and time of a specific maintenance action for an EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
standardDateTime	Optional
target	Optional

Attribute usage

Use [@standardDateTime](#) to provide a machine-processable expression of the date or date and time, formulated according to the ISO 8601 standard.

Description and Usage

A required child element of [<maintenanceEvent>](#) , [<eventDateTime>](#) is for recording the date and time that a maintenance event occurred. Examples of maintenance events include the creation, update, revision, or other modification to an EAS instance, e.g. in the context of reparative description or as a result of applying Artificial Intelligence models for improving the description.

The date and time may be captured in natural language in the element. It is highly recommended to provide at least a human-readable date

in [<eventDateTime>](#) directly or a machine-processable date in [@standardDateTime](#), in case it is not possible to provide both.

Availability

Required, not repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

<eventDescription>

Event Description

Summary

An optional child element of <maintenanceEvent> and <narrativeEvent> that provides the description of a maintenance event in the life of the EAS instance respectively the description of an event in the lifecycle of the materials described or the life of the records creator(s).

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[maintenanceEvent](#), [narrativeEvent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A child element of <maintenanceEvent> used for describing the maintenance event and of <narrativeEvent> used for describing a chronology of events in the lifecycle of the materials described (<appraisal> , <custodHist> , <processInfo> , <sourceOfAcquisition>) and the life of the record creator(s) (<biogHist>). The element allows a full description of the event to be given alongside information about the time and date of the event, the agent involved, and - in the context of <maintenanceEvent> -

the type respectively - in the context of [<narrativeEvent>](#) - the place of the event.

Availability

Optional, repeatable

Examples

See [<archDesc>](#) and [<control>](#) encoding

[Table of Contents](#)

< extent >

Extent

Summary

An optional child of [<identificationData>](#) and [<physicalDescription>](#) used for information about the quantity of the materials being described or an expression of the space - physical as well as digital - they occupy.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
quantity	0..1
unitOfMeasurement	0..1

May occur within

[identificationData](#), [physicalDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
coverage	Optional
extentType	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the attributes [@id](#) and [@target](#) to relate two or more parallel statements of extent to each other. Use [@coverage](#) to indicate whether the extent statement refers to all or only part of the materials being described.

Description and Usage

An element to capture information about the quantity of the materials being described or an expression of the digital or physical space they occupy. Includes such traditional archival measurements as cubic and linear feet and meters; also includes counts of microfilm reels, photographs, or other special formats, the number of logical records in a database, or the volume of a data file in bytes. Repeat the element when more than one type or unit of extent is provided, such as, when both linear feet and quantity of containers are given.

Either the sub-element [<quantity>](#) or the sub-element [<unitOfMeasurement>](#) must be present within [<extent>](#), but it is recommended to use both child elements whenever possible. The sub-element [<descriptiveNote>](#) can be used to express physical description in a non-machine-processable form and in instances where data exchange is not a concern.

Availability

Within [<identificationData>](#) : optional, repeatable

Within [<physicalDescription>](#) : optional, not repeatable

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding

[Table of Contents](#)

< filePlan >

File Plan

Summary

An element for information about any classification scheme used by the original creator to arrange, store, and retrieve the materials described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A filing plan is usually identified by the type of system used, e.g., alphabetical, numerical, alpha-numerical, decimal, color-coded, etc. It is often hierarchical and may include the filing guidelines of the originating entity. Additional types include a drawing of a room layout or a scientific scheme.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<filePlan>](#) . Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use

[<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<arrangement>](#), which describes the current organization and/or filing sequence of the materials, as opposed to that imposed by the original creator.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< findAidDesc >

Finding Aid Description

Summary

An optional element that binds together a bibliographic description of an EAD instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	0..n
citedRange	0..n
date	0..n
formattingExtension	0..n
place	0..n
title	0..n

May occur within

[ead](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [< findAidDesc >](#) to record a bibliographic description of the finding aid. This may include its author, title, subtitle, sponsor, edition, publisher, publishing series, and related notes, each within appropriate sub-elements.

If [<findAidDesc>](#) is used, at least one sub-element must be included.

Availability

Optional, repeatable

See also

Do not confuse with [<control>](#) , which contains administrative information about the management of the EAD instance.

Examples

See [<findAidDesc>](#) encoding

[Table of Contents](#)

< formattingExtension >

Formatting Extension

Summary

An optional, wrapping element that may be utilized to encode more complex formatting features that are not part of the EAS data model such as lists, tables, nested headers, etc. When using the EAS-provided NVDL Schema validation procedure, this element will require that all elements encoded within are from the XHTML namespace.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[Any element that is in a namespace other than the current namespace]	

May occur within

[accessConditions](#), [accruals](#), [appraisal](#), [arrangement](#), [biogHist](#), [custodHist](#), [descriptionOfComponents](#), [filePlan](#), [findAidDesc](#), [otherDescription](#), [otherDescriptiveInfo](#), [physicalOrTechnicalRequirements](#), [preferCite](#), [processInfo](#), [publicationNote](#), [recordTypeSpecificStatement](#), [relatedMaterial](#), [scopeContent](#), [separatedMaterial](#), [sourceOfAcquisition](#), [subjectHeadings](#), [useConditions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
target	Optional

Description and Usage

[< formattingExtension >](#) provides the option to embed external namespaces directly within the source file, when complex formatting is required. It should preferably be used for embedding XHTML data.

When using this element, it is recommended that the EAS file is associated with the EAS NVDL for validation purposes.

Availability

Within [<findAidDesc>](#) : optional, repeatable.

Within all other elements: optional, not repeatable.

In [<findAidDesc>](#) , [<formattingExtension>](#) is optionally available to encode a narrative description next to the more specific elements [<agent>](#) , [<citedRange>](#) , [<date>](#) , [<place>](#) , and [<title>](#) . In all other contexts, the encoder must choose between using a [<formattingExtension>](#) element (to wrap XHTML content), or using one or more [<p>](#) elements that are defined within the current EAS schema.

Examples

See [<archDesc>](#) and [<findAidDesc>](#) encoding

[Table of Contents](#)

< formAvailable >

Form Available

Summary

A required child element of [< formsAvailable >](#) used to name and describe single instantiations of the described records such as digital representations, microfiches, copies, etc.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
accessConditions	0..n
accruals	0..n
arrangement	0..n
container	0..n
custodHist	0..n
date or dateRange or dateSet	0..1
descriptiveNote	0..1
formAvailableId	0..n
label	1..n
physicalDescription	0..n
physicalOrTechnicalRequirements	0..n
placeName	0..n
processInfo	0..n
relations	0..1
role	0..n
separatedMaterial	0..n
sourceOfAcquisition	0..n
useConditions	0..n

May occur within

[formsAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
coverage	Optional
formAvailableType	Optional
id	Optional

<i>Attribute name</i>	<i>Attribute values</i>
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to directly link to the available form in question, e.g. a digital object identified by an ARK (Archival Resource Key) or DOI (Digital Object Identifier). Use [@vocabularySource](#) to indicate the identifier scheme applied in this case.

If the available form in question consists of, for example, several individual image files, use the sub-element [<formAvailableId>](#) together with [@valueURI](#) available therein to link to each of these files separately. Alternatively, an aggregated form including these individual files such as a IIIF manifest, a PDF file, a METS XML file, etc. might be used, which would then be linked to from [@valueURI](#) within [<formAvailable>](#) as mentioned above.

Description and Usage

Use [<formAvailable>](#) within the wrapper element [<formsAvailable>](#) to specify single instances concerning the available form(s) of the described entities in [<archDesc>](#) or in [<c>](#) elements.

The available form(s), digital representations, microfiches or microfilms, copies, or originals - in case the materials described are copies themselves - need to be named using the element [<label>](#) and can be identified using the element [<formAvailableId>](#). Same as the other entity elements, [<formAvailable>](#) includes an option to encode the specific type and role of an instantiation ([@formAvailableType](#)) and [<role>](#)) and to provide a temporal or geographic dimension to the relation (date elements and [<placeName>](#)). With the sub-element [<relations>](#) , a more detailed description of the relationship itself is enabled.

Additionally, [<formAvailable>](#) includes elements to capture extent and other physical characteristics of each instantiation as well as elements such as [<accessConditions>](#) and [<useConditions>](#) or [<accruals>](#) , [<processInfo>](#) and [<sourceOfAcquisition>](#) , which might differ between the instantiations of the same record resource.

The prescribed order of all child elements (both required and optional) is:

[<label>](#)

[<date>](#) or [<dateRange>](#) or [<dateSet>](#)

relations

One or more of [<formAvailableId>](#) , [<placeName>](#) , [<role>](#)

One or more of [<container>](#) , [<physicalDescription>](#)

One or more of [<accessConditions>](#) ,
[<accruals>](#) , [<arrangement>](#) , [<custodHist>](#) ,
[<physicalOrTechnicalRequirements>](#) , [<processInfo>](#)
, [<separatedMaterial>](#) , [<sourceOfAcquisition>](#) ,
[<useConditions>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

<formAvailableId>

Identifier of the Form Available

Summary

An optional child element of [<formAvailable>](#) that provides an identifier for the instantiation being described, e.g. a microfiche number.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely and persistently identifies the instantiation in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use

[@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

[<formAvailableId>](#) may contain any alpha-numeric text string that serves as a unique reference point or control number for the described instantiation.

Availability

Optional, repeatable

See also

Use [<unitId>](#) to provide an identifier for the record resource in general, which is different from, though might provide a basis for the identifiers used for its specific instantiations encoded in [<formAvailableId>](#) .

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

<formsAvailable>

Forms Available

Summary

An optional child of <archDesc> and <c> that groups together single instantiations of the described records such as digital representations, microfiches, copies, etc.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
formAvailable	1..n
descriptiveNote	0..1

May occur within

archDesc, c, c01, c02, c03, c04, c05, c06, c07, c08, c09, c10, c11, c12

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional <formsAvailable> element to group together one or more occurrences of <formAvailable> . <formsAvailable> must include at least one <formAvailable> element.

The prescribed order of all child elements (both required and optional) is:

<formAvailable>

<descriptiveNote>

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< fromDate >

From Date

Summary

A child element of [< dateRange >](#) that records the starting point in a range of dates.

May contain

Element/content type
[text]

Occurrences

May occur within

[dateRange](#)

Attributes

Attribute name

Attribute values

[audience](#)

Optional

[calendar](#)

Optional

[certainty](#)

Optional

[conventionDeclarationReference](#)

Optional

[era](#)

Optional

[id](#)

Optional

[languageOfElement](#)

Optional

[localType](#)

Optional

[localTypeDeclarationReference](#)

Optional

[maintenanceEventReference](#)

Optional

[notAfter](#)

Optional

[notBefore](#)

Optional

[scriptOfElement](#)

Optional

[standardDate](#)

Optional

[status](#)

Optional

[sourceReference](#)

Optional

[target](#)

Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the start date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.

Use [@standardDate](#) to provide a machine-processable form of the date.

Use [@status](#) with the value "unknown" to indicate where the start of a date range is unknown.

Description and Usage

Use [<fromDate>](#) to record the beginning date in a range of dates. [<fromDate>](#) may contain actual, approximate or unknown dates. The content of the element is intended to be a human-readable, natural language expression of the date. If, however, indexing or other machine processing of dates is desired, the [@standardDate](#) should be used to record the date in machine-processable form as well. If the [<fromDate>](#) is not known, it may be omitted from [<dateRange>](#), or the [@status](#) attribute used.

Availability

Optional, not repeatable

See also

Use [<toDate>](#) to record the ending point of a date range.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

<function>

Function

Summary

A required child element of [<functions>](#) that provides information about a function, activity, process, role, or purpose.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
label	1..n
placeName	0..n
relationship	0..n
role	0..n

May occur within

[functions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
functionType	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

A [<function>](#) element is a wrapper element used to encode the name of a function, activity, process, role, or purpose related to the production of the described materials as well as further information about that relationship.

[<function>](#) must include at least one [<label>](#) element to identify the functions, activities and processes in order to provide useful access points to the materials, especially for corporate, government, or institutional records. [<label>](#) can be repeated within [<function>](#) to include translations of the same function. Use the [@languageOfElement](#) attribute to identify the language used in each [<label>](#). Examples include "collecting taxes" and "entertaining". Terms used in [<label>](#) may be drawn from controlled vocabularies or may be natural language terms.

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<role>](#) can be defined same as a [@functionType](#) and the [<relationship>](#) between the function and the materials being described can be specified. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed.

The prescribed order of all child elements (both required and optional) is:

[<label>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<role>](#)

[<relationship>](#)

[<descriptiveNote>](#)

Availability

Required, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< functions >

Functions

Summary

An optional child element used for grouping together one or more [<function>](#) elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
function	1..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional [<functions>](#) element to group together one or more occurrences of [<function>](#) . [<functions>](#) must include at least one [<function>](#) element.

The prescribed order of all child elements (both required and optional) is:

[<function>](#)

[<descriptiveNote>](#)

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< genreForm >

Genre or Form

Summary

An optional element for encoding a genre or form of material.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the genre or form in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

[<genreForm>](#) identifies the types of material being described by naming the style or technique of their intellectual content (genre), the order of information or the object function (form). Examples include: account books, architectural drawings, portraits, short stories, sound recordings, and videotapes.

Use [<genreForm>](#) to indicate a genre or form with major representation in the materials being described. It is recommended that the terms in [<genreForm>](#) be taken from authorized vocabularies (see “Attributes usage” for details).

Availability

Optional, Repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< geographicCoordinates >

Geographic Coordinates

Summary

An optional child element of [<place>](#) that encodes a set of geographic coordinates.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
coordinateSystem	Required
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use the required [@coordinateSystem](#) attribute to provide a commonly used code for the system used to express the coordinates. Examples include WGS84, OSGB36, ED50.

Description and Usage

Use [<geographicCoordinates>](#) to express a set of geographic coordinates such as latitude, longitude, and altitude representing a point, line, or area on the surface of the earth.

It is recommended that the values included in [<geographicCoordinates>](#) are based on a commonly used system for expressing geographic coordinates.

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< head >

Heading

Summary

An optional element of [< identificationData >](#) and the component elements that encodes a caption for the following section of text.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[identificationData](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< head >](#) can be used as an optional element at the start of [< identificationData >](#) and the component elements to encode a caption for the following part of the encoded description, e.g. when needing a generic section header for print or display, though the latter might usually be addressed via the general template and/or stylesheet of a web interface. When [< head >](#) is used, it must be the first child element, followed by one or more other elements.

Availability

Optional, not repeatable

[Table of Contents](#)

< identificationData >

Identification Data

Summary

A wrapper element that encloses information essential for identifying the material being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
container	0..n
descriptiveNote	0..1
extent	0..n
genreForm	0..n
head	0..1
languageOfMaterial	0..n
legalStatus	0..n
otherIdentificationData	0..n
unitDate	0..n
unitId	0..n
unitTitle	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

<[identificationData](#)> binds together other elements that provide core information needed for identifying the described materials.

[<identificationData>](#) occurs within [<archDesc>](#) and the component elements ([<c>](#) and [<c01>](#) to [<c12>](#)). The various [<identificationData>](#) child elements are intended for brief, clearly designated statements of information, whereas following sibling elements of [<identificationData>](#) such as [<custodHist>](#) , [<arrangement>](#) , or [<scopeContent>](#) allow for more detailed, narrative description.

[<identificationData>](#) groups elements that constitute a good basic description of an archival unit. This grouping ensures that the same data elements and structure are available at every level of description within the EAD hierarchy. It facilitates the retrieval or output of a coherent body of elements for resource discovery and recognition.

The [<identificationData>](#) in [<archDesc>](#) is sometimes called the high-level [<identificationData>](#) , because it covers the entirety of the materials described by the EAD instance. Consider using the following child elements in the high-level [<identificationData>](#) : [<unitTitle>](#) , [<unitId>](#) , [<unitDate>](#) , and [<extent>](#) . [<identificationData>](#) within components can have fewer elements, and might for example have only [<container>](#) or [<unitId>](#) and [<unitTitle>](#) .

Availability

Required, not repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

<label>

Label

Summary

A required child element of [<agent>](#) , [<formAvailable>](#) , [<function>](#) , [<place>](#) , and [<relation>](#) that indicates the name of the related entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [formAvailable](#), [function](#), [place](#), [relation](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

Use `<label>` to indicate the name of the related entity, either in the generic `<relation>` element or in one of the specific entity elements. Depending on the type of related entity, such a name can also take the form of a numeric denominator.

In `<agent>`, this can be the name of the agent responsible for the creation, modification, or deletion of an EAD instance, as captured in `<maintenanceEvent>`, or the name of the agent who has created, managed, used, or is mentioned in the archival materials. In `<formAvailable>`, this might e.g. be the file name of a digitised version of a record resource. In `<function>`, this might be the name of the function or subfunction that resulted in the creation of the materials being described. In `<place>`, this might be the name of the place where the archival materials being described are held, are stored, or relate to in other ways.

It is recommended to use authorized vocabularies in cases where the element is valorized with a well-known corporation (i.e. "Library of Congress").

Availability

Required, repeatable

See also

Use this element in combination with type and role information which can also be encoded within the parent elements of `<label>`. E.g.: `<label> : "John Bianchi"`, `@agentType: "person"`, `<role> : "author"`.

Examples

See `<archDesc>`, `<control>`, and `<findAidDesc>` encoding

[Table of Contents](#)

<language>

Language

Summary

An element that identifies the language or communication system used by the entity or in the materials described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[languageOfMaterial](#), [languageSet](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageCode	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@languageCode](#) to provide a code for the language itself.

Use [@languageOfElement](#) to provide a code for the language in which the element is given.

Description and Usage

Use either [<language>](#) or [<languageSet>](#) , if combining language and script information, as sub-element of [<languageOfMaterial>](#) to identify a language or communication system of the materials being described.

Availability

Within [<languageOfMaterial>](#) : optional, repeatable

Within [<languageSet>](#) : required, only repeatable when encoding one script with several languages

See also

Use [<writingSystem>](#) to specify, in a human-readable form, the script corresponding to the language.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

<languageDeclaration>

Language Declaration

Summary

An optional child element of [<control>](#) that indicates the language and script in which an EAS instance is written.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageCode	Required
languageOfElement	Optional
scriptCode	Optional
scriptOfElement	Optional
target	Optional

Attribute usage

Use the required [@languageCode](#) to provide a code for the language used in the EAS instance.

Use [@languageOfElement](#) to provide a code for the language in which the [<languageDeclaration>](#) element is given.

Use [@scriptCode](#) to provide a code for the writing system used in the EAS instance.

Use [@scriptOfElement](#) to provide a code for the writing system in which the [<languageDeclaration>](#) element is given.

Description and Usage

An optional child element of [<control>](#) that declares the languages and scripts in which an EAS instance is written in the [@languageCode](#) and [@scriptCode](#) attributes. Any comments about the languages and scripts in which the EAS instance is written may be included in the optional [<descriptiveNote>](#) element. While [<languageDeclaration>](#) states the language(s) and script(s) for the EAS instance in general, the [@languageOfElement](#) and [@scriptOfElement](#) attributes available with all elements may be used to encode language and script information specific to the content of one element in cases where this is different from the overall language(s) and script(s).

Availability

Optional, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

<languageOfMaterial>

Language of Material

Summary

A child element of [<identificationData>](#) that identifies languages represented in the materials described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
language	0..n
languageSet	0..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<languageOfMaterial>](#) records information about languages and writing systems represented in the materials being described. [<languageOfMaterial>](#) must contain one or more [<language>](#) or [<languageSet>](#) elements, but cannot contain text.

Any comments or notes about languages or writing systems represented in the materials described must be encoded in an optional [<descriptiveNote>](#) that follows all [<language>](#) and [<languageSet>](#) elements.

Availability

Optional, repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

<languageSet>

Language Set

Summary

Within [<identificationData>](#) , [<languageSet>](#) is a child element of [<languageOfMaterial>](#) that is used to pair one language with one or more writing systems, e.g. a text in Japanese language and in Kana, Hiragana, and Katakana scripts, or one writing system with one or more languages, e.g. a document in English, French and German, all using the Latin alphabet.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
language	1..n
writingSystem	1..n

May occur within

[languageOfMaterial](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@languageOfElement](#) and [@scriptOfElement](#) to indicate the language and written scripts of the information in [<languageSet>](#) , not the language of materials.

Description and Usage

Use [<languageSet>](#) within [<languageOfMaterial>](#) when it is necessary to associate [<language>](#) and [<writingSystem>](#). Possible combinations include one language and one writing system, multiple languages and one writing system, and one language and multiple writing systems. [<languageSet>](#) may be repeated as necessary. Optionally, any comments about the language(s) and writing system(s) being recorded may be captured in [<descriptiveNote>](#) at the end, particularly for display to finding aid users.

Availability

Optional, repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< legalStatus >

Legal Status

Summary

An element for indicating the statutorily defined status of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

The legal status is typically defined and granted by authorities or through authorized agencies. Enter terms in accordance with provisions of the controlling legislation. Terms may be drawn from controlled vocabularies or may be natural language terms.

[<legalStatus>](#) must include at least one [<term>](#) element, where the legal status is encoded. [<term>](#) can be repeated within [<legalStatus>](#) to include translations of the same term. Use the [@languageOfElement](#) attribute to identify the language used in each [<term>](#) .

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) element may be included if a fuller textual explanation is needed.

The prescribed order of all child elements (both required and optional) is:

[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

<localTypeDeclaration>

Local Type Declaration

Summary

An optional child element of [<control>](#) used to declare any local conventions or controlled vocabularies used in [@localType](#) in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

[<localTypeDeclaration>](#) specifies the local conventions and controlled vocabularies used in [@localType](#) attributes in the EAS instance.

Each additional rule or set of rules, controlled vocabulary, or standard should be contained in a separate [<localTypeDeclaration>](#) .

The child [<reference>](#) must be used to cite the resource that lists the local rules or controlled terms. Any notes relating to how these rules or conventions have been used may be given in [<descriptiveNote>](#) . The child

[<shortCode>](#) may be used to identify any abbreviation or code representing the local convention or controlled vocabulary.

The prescribed order of all child elements (both required and optional) is:

[<reference>](#)

[<shortCode>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

See also

Use [<conventionDeclaration>](#) to indicate any more broadly (i.e. nationally or internationally) used rules or conventions, including authorized controlled vocabularies and thesauri, applied in creating the EAS instance.

When using [@localType](#) throughout the EAS instance, use [@localTypeDeclarationReference](#) in parallel to refer back to the relevant [<localTypeDeclaration>](#) via its [@id](#) attribute.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< maintenanceAgency >

Maintenance Agency

Summary

A required child element of [< control >](#) that identifies the institution or service responsible for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agencyCode	0..1
agencyName	0..n
descriptiveNote	0..1
otherAgencyCode	0..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
countryCode	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
vocabularySource	Optional
vocabularySourceURI	Optional
valueURI	Optional

Attribute usage

Use [@countryCode](#) to indicate a unique code for the country of the maintenance agency.

Description and Usage

[< maintenanceAgency >](#) encodes information about the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance.

[< maintenanceAgency >](#) must include one or both of [< agencyCode >](#) or [< agencyName >](#) to provide the identifier or the name of the institution or service. It may also include the optional child element [< otherAgencyCode >](#) to provide any additional identifiers. Any general information about the institution or service in relation to the EAS instance may be given in [< descriptiveNote >](#) .

The prescribed order of all child elements (both required and optional) is:

[< agencyCode >](#) (if used)

[< agencyName >](#)

[< otherAgencyCode >](#)

[< descriptiveNote >](#)

Availability

Required, not repeatable

Examples

See [< control >](#) encoding

[Table of Contents](#)

< maintenanceEvent >

Maintenance Event

Summary

A required child element of [< maintenanceHistory >](#) used to record information about maintenance activities in the history of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	1..1
eventDateTime	1..1
eventDescription	0..n

May occur within

[maintenanceHistory](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
maintenanceEventType	Optional
scriptOfElement	Optional
target	Optional

Attribute usage

Use [@maintenanceEventType](#) to document the type of maintenance activity that the [< maintenanceEvent >](#) is recording. Use [@maintenanceEventTypeEncoding](#) in [< control >](#) to specify the source or rules for values supplied in [@maintenanceEventType](#).

Description and Usage

A required child element of [< maintenanceHistory >](#) , [< maintenanceEvent >](#) is used to record an activity in the creation and ongoing maintenance of an EAS instance, including revisions, updates, and deletions, e.g. as a result of reparative description or the application of Artificial Intelligence models. There

will always be at least one maintenance event for each instance, which will typically be its creation.

[<maintenanceEvent>](#) must include [<agent>](#) and [<eventDateTime>](#) child elements to record the agent that carried out the maintenance event, and the date and time the maintenance event occurred.

The prescribed order of all child elements (both required and optional) is:

[<agent>](#)

[<eventDateTime>](#)

[<eventDescription>](#)

Availability

Required, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< maintenanceHistory >

Maintenance History

Summary

A required child element of [< control >](#) that captures the history of the creation and maintenance of the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
maintenanceEvent	1..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

A required child element of [< control >](#) , [< maintenanceHistory >](#) is for recording the history of the creation, revisions, updates, and other modifications to the EAS instance.

There must be at least one child [< maintenanceEvent >](#) in [< maintenanceHistory >](#) , which usually will be a record of the creation of the instance. There may be many other [< maintenanceEvent >](#) elements documenting the milestone changes or activities in the maintenance of the instance.

Availability

Required, not repeatable

See also

Use [@maintenanceStatus](#) within [<control>](#) to reflect the current drafting status of the EAS instance as recorded in [<maintenanceHistory>](#) .

Use elements such as [<appraisal>](#) , [<custodHist>](#) , [<processInfo>](#) or [<sourceOfAcquisition>](#) within [<archDesc>](#) and the component elements to record the events in the lifecycle of the materials being described.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< narrativeEvent >

Narrative Event

Summary

An optional child element of < appraisal > , < biogHist > , < custodHist > , < processInfo > , and < sourceOfAcquisition > used to record a timeline of activities in the history of the materials being described or the biography of the records creator.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
agent	0..n
date	1..n
eventDescription	0..n
placeName	0..n

May occur within

appraisal, biogHist, custodHist, processInfo, sourceOfAcquisition

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use < narrativeEvent > to record an activity in the creation, management and ongoing maintenance of the materials being described or in the history of the records creator. This may include activities of appraisal and selection, sensitivity review, revisions, updates, retentions, etc.

The type of each event may be defined with the attribute [@localType](#). Use [@localTypeDeclarationReference](#) to refer to a [<localTypeDeclaration>](#) within [<control>](#) where you have defined those types. Use the required child element [<date>](#) to record when the event took place. Using the optional child element [<agent>](#) to provide information about who or what carried out, or was responsible for the activity is highly recommended. The child element [<placeName>](#) may be used to provide information about where the event happened. Information about the event may be described in [<eventDescription>](#) .

The prescribed order of all child elements (both required and optional) is:

[<date>](#)

[<agent>](#)

[<placeName>](#)

[<eventDescription>](#)

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< objectXMLWrap >

Object XML Wrap

Summary

An optional child element of [<descriptiveNote>](#) , [<recordTypeSpecificStatement>](#) , [<relation>](#) and [<source>](#) that allows for the inclusion of XML encoding from any other XML namespace.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[any element from any namespace]	

May occur within

[descriptiveNote](#), [recordTypeSpecificStatement](#), [relation](#), [source](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
target	Optional

Description and Usage

A wrapper element that provides a place to express data in any XML encoding language.

To facilitate interoperability the XML should conform to an open, standard XML schema and a namespace attribute should be present on the root element referencing the namespace of the standard.

If interoperability is not a main objective in a specific application context of the EAS, it is also possible to encode data in XML without a namespace within the [<objectXMLWrap>](#) element.

[<objectXMLWrap>](#) may be used to store related XML data locally rather than linking to external resources in order to facilitate processing or in cases where the related data may not be reliably accessible.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) and [<control>](#) encoding

[Table of Contents](#)

< otherAgencyCode >

Other Agency Code

Summary

An optional child element of [< maintenanceAgency >](#) that provides an alternative code for the institution or service responsible for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[maintenanceAgency](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
scriptOfElement	Optional
status	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the code in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system.

Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Use [@localType](#) to specify the type of code being provided.

Use [@status](#) to encode whether the [<otherAgencyCode>](#) is an authorized or alternative code.

Description and Usage

Use [<otherAgencyCode>](#) to provide an alternative and/or local code that represents the institution or service responsible for the creation, maintenance, and/or dissemination of the EAS instance. Any code other than that given in [<agencyCode>](#) may be provided in [<otherAgencyCode>](#). The addition of an ISO 3166-1 alpha-2 country code as the prefix to a local code is recommended to ensure international uniqueness.

Availability

Optional, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< otherDescription >

Other Description

Summary

Element used for identifying any other description of the materials being described that might exist next to the one in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n
relations	0..1

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the

source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

Use [<otherDescription>](#) to provide information about additional or alternative descriptions of the material, such as card files, dealers' inventories, a catalog record, or lists generated by the creator or compiler of the materials. On the level of a complete fonds or collection, this could be a complete finding aid; on the level of a single record or record part, this could also be descriptions that exist in other standards and formats than the EAS, e.g. MARC21, Dublin Core, METS/MODS, PREMIS, etc.

[<otherDescription>](#) is, however, only used to indicate the existence of additional descriptions; it is not designed to encode the content of those.

Such additional descriptions can either be described using narrative text in the elements [<abstract>](#) , [<p>](#) , and [<formattingExtension>](#) or they can be named within and, if applicable, linked to via [<relations>](#) . Using [<relations>](#) is especially useful when referring to several other descriptions at once and will also allow for a more detailed description of the relationship itself by including type and role information or a temporal or geographic dimension of the relationship.

If described in narrative text, the element [<reference>](#) within [<p>](#) may be used to refer to analog or digital resources.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<relations>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<otherDescriptiveInfo>](#) , which records additional information about the described materials that is not easily incorporated into one of the other named elements within [<archDesc>](#) and the component elements, but does not exist anywhere else.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< otherDescriptiveInfo >

Other Descriptive Information

Summary

For recording additional information about the described materials that is not easily incorporated into one of the other named elements within <archDesc> and <c> respectively <c01> to <c12> .

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@localType](#) to more specifically designate the type of information being provided.

Description and Usage

< otherDescriptiveInfo > may be useful in converting legacy finding aids to the EAD format, by designating as "other" information everything that does not

easily map to a more specific element. [<otherDescriptiveInfo>](#) may be used when information about the described materials does not correspond to another element's definition, when the information is heterogeneous enough to make a single classification difficult, and when shifting the information to permit more specific content designation would be too costly or burdensome.

Use [<otherDescriptiveInfo>](#) only after considering how the existence of unspecified content will affect search, retrieval, and display.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<otherDescriptiveInfo>](#). Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<otherDescription>](#), which allows you to identify and, if applicable, link to any other description of the materials being described that might exist next to the one in the EAS instance.

Use [<otherIdentificationData>](#) to capture short notes about the materials being described.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< otherIdentificationData >

Other Identification Data

Summary

A child element of [<identificationData>](#) for any details about the materials being described that are not more appropriately encoded in the other available elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@localType](#) to specify the type of data being conveyed in the element.

Description and Usage

[<otherIdentificationData>](#) is for capturing short notes about the materials being described that cannot be encoded more appropriately in any of the other elements available in [<identificationData>](#) .

Availability

Optional, repeatable

See also

For any more extensive or narrative information about the materials being described, for which there is no more appropriate element available, use [<otherDescriptiveInfo>](#) directly in [<archDesc>](#) or the component elements.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< otherRecordId >

Other Record Identifier

Summary

An optional child element of [< control >](#) that encodes any local identifier for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the alternative identifier in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system.

Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, e.g, the institution or service providing the associated record identifier, and [@vocabularySourceURI](#) to point univocally to the organization system used, if available.

Description and Usage

[<otherRecordId>](#) can be used to record an identifier that is an alternative to the mandatory identifier provided in [<recordId>](#) . These might include the identifiers of merged EAS instances representing the same entity or those of records that are no longer current but had some part in the history and maintenance of the EAS instance.

Availability

Optional, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< p >

Paragraph

Summary

A general purpose element used to encode blocks of text.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[accessConditions](#), [accruals](#), [appraisal](#), [arrangement](#), [biogHist](#), [custodHist](#), [descriptionOfComponents](#), [descriptiveNote](#), [filePlan](#), [otherDescription](#), [otherDescriptiveInfo](#), [physicalOrTechnicalRequirements](#), [preferCite](#), [processInfo](#), [publicationNote](#), [recordTypeSpecificStatement](#), [relatedMaterial](#), [scopeContent](#), [separatedMaterial](#), [sourceOfAcquisition](#), [subjectHeadings](#), [useConditions](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use <p> for blocks of text. A paragraph may be a subdivision of a larger composition or it may exist alone. It is usually typographically distinguished: a line space is often left blank before it; the text begins on a new line; and the first letter of the first word may be indented, enlarged, or both.

Availability

Within [<descriptiveNote>](#) : required, repeatable.

Within all other parents: optional, repeatable.

In all parents except [<descriptiveNote>](#) , the encoder must choose between using one or more [<p>](#) elements that are defined within the current EAS schema, or using a [<formattingExtention>](#) element (to wrap XHTML content) for more complex formatting.

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding

[Table of Contents](#)

< part >

Part

Summary

A required and repeatable child of < title > used to distinguish components of a name or title.

May contain

Element/content type
[text]

Occurrences

May occur within

title

Attributes

Attribute name

Attribute values

audience

Optional

conventionDeclarationReference

Optional

id

Optional

languageOfElement

Optional

localType

Optional

localTypeDeclarationReference

Optional

maintenanceEventReference

Optional

scriptOfElement

Optional

sourceReference

Optional

target

Optional

Attribute usage

The designation of the information contained in the < part > element can be specified by the attribute @localType.

Description and Usage

Within < title > components such as edition numbers or the number of an issue in a serial publication may be recorded in a separate < part > element. Subtitles or the full title of a serial publication should, however, be recorded in a < title > element of their own.

[<part>](#) cannot be empty and requires at least one non-whitespace character, such as a hyphen, if no actual name can be given.

Availability

Required, repeatable

Examples

See [<findAidDesc>](#) encoding

[Table of Contents](#)

< physicalDescription >

Physical Description

Summary

An optional child element of [<formAvailable>](#) to encode statements about the extent and physical characteristics specific to the instantiation being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
dimensions	0..1
extent	0..1
physicalFacet	0..1

May occur within

[formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[<physicalDescription>](#) creates structured statements describing the physical or logical extent or the medium of the instantiation described in [<formAvailable>](#) . While optional individually, one of the child elements [<dimensions>](#) , [<extent>](#) or [<physicalFacet>](#) has to be included when using [<physicalDescription>](#) . Next to the descriptive, human-readable information, the structured design of [<physicalDescription>](#) allows for quantifying the extent of the whole or a part of the instantiation described in a form that will also be machine-processable and that will facilitate

reporting, statistics, sorting, and importing and exporting data in a collection management system.

The prescribed order of all child elements (both required and optional) is:

[< extent >](#)

[< dimensions >](#)

[< physicalFacet >](#)

[< descriptiveNote >](#)

Use [<objectXMLWrap>](#) in [<descriptiveNote>](#) to include, where necessary, more detailed information encoded in another standard such as MIX, AudioMD, national standards focussed specifically on digital instantiations, etc.

Availability

Optional, repeatable

See also

When statements of extent relate to the record resource in general rather than being specific to an individual instantiation, use [<extent>](#) within [<identificationData>](#) . E.g. a photographic collection might consist of 1,200 photographs, a statement captured in [<extent>](#) within [<identificationData>](#) . Within [<physicalDescription>](#) in repeated [<formAvailable>](#) elements, this might then be specified as "1,2000 prints" for one analog instantiation, "1,200 negatives" for a second analog instantiation, and "1,200 image files (tiff)" for a digital instantiation.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< physicalFacet >

Physical Facet

Summary

A child element of [< physicalDescription >](#) that provides more detailed information about the physical nature or techniques and methods of creation of a specific instantiation of the material described in terms that are often taken from a controlled vocabulary list.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[physicalDescription](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the physical facet in a controlled vocabulary, taxonomy, ontology,

or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

[<physicalFacet>](#) records information about an aspect of the physical nature – such as color, style, marks, substances, materials, playback speed, duration, track configuration, and motion picture presentation format – or techniques and methods of creation of the units identified by [<unitOfMeasurement>](#) within [<extent>](#) . It generally should not be used for aspects of physical description that are covered more directly by [<extent>](#) and [<dimensions>](#) .

Physical facet terminology can be found in the Art and Architecture Thesaurus and other sources for authorized data values.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< physicalOrTechnicalRequirements >

Physical Characteristics or Technical Requirements

Summary

An optional child element of [<formAvailable>](#) for describing the physical condition of the materials and/or technical requirements that affect their use.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< physicalOrTechnicalRequirements >](#) is used to capture any physical or technical characteristics that affect the storage or use of the specific form of the archival record being described. This may hence be different for an analog or digital form. [< physicalOrTechnicalRequirements >](#) may include details of the specific form's physical composition, preservation requirements, or particular hardware or software needed to access the materials.

Use the element `<abstract>` to provide a brief summary of the information encoded in `<physicalOrTechnicalRequirements>`. Use the repeatable `<p>` element to structure longer texts in several paragraphs. If required and suitable, use `<formattingExtension>` to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

`<abstract>` (if used)

`<formattingExtension>` or `<p>`

Availability

Optional, repeatable

[Table of Contents](#)

< place >

Place

Summary

An element that provides information about a place or jurisdiction, including places where the records being described were created, are held, or with which they have some other significant connection.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
address	0..n
contact	0..n
date or dateRange or dateSet	0..1
descriptiveNote	0..1
geographicCoordinates	0..n
label	1..n
role	0..n
relationship	0..n

May occur within

[findAidDesc](#), [places](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
placeType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

A [<place>](#) element is a wrapper element used to encode information about a place or jurisdiction. This includes identifying the places or jurisdictions where the records being described were created or with which they have some other significant connection. It can also be used to encode address and contact information, the role that the place has with regard to the materials described, the relationship between both as well as a temporal dimension of that relationship.

[<place>](#) must include at least one [<label>](#) to name the geographic feature or location that is related to the entity being described. The [<role>](#) element is available to specify the nature of the place in relation with the entity being described, e.g. "birthplace" for CPF entities or "placeOfStorage" for record resources, and its use is strongly recommended. The [@placeType](#) attribute may be used to classify the type of place for clarification, e.g., indicating whether the place is a city or town or a first or second-order administrative division. Use [<relationship>](#) to describe the nature of connection between the place and the entity being described more generally. Terms in these elements may be drawn from controlled vocabularies or may be natural language terms. These controlled vocabularies can be identified with the [@vocabularySource](#) and/or [@vocabularySourceURI](#) attributes.

The [<address>](#) element is available for specifying a postal or other address, while a digital address or other contact information can be encoded using the [<contact>](#) element. Specific coordinates for the geographic feature or location may be provided using the element [<geographicCoordinates>](#).

Associated date or date range ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) information may be included to further constrain the place's meaning. A [<descriptiveNote>](#) may be included if a fuller explanation of the significance of the place to the records being described is needed.

The prescribed order of all child elements (both required and optional) is:

[<label>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<role>](#)

[<relationship>](#)

One or more of [<address>](#) , [<contact>](#) and
[<geographicCoordinates>](#)

[<descriptiveNote>](#)

Availability

Within [<places>](#) : required, repeatable.

Within [<findAidDesc>](#) : optional, repeatable.

Examples

See [<archDesc>](#) and [<findAidDesc>](#) encoding

[Table of Contents](#)

< placeName >

Place Name

Summary

An optional element used to encode the name of a place or geographic feature that is of importance in the relation between the materials being described and related named entities or in the history of the described materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [formAvailable](#), [function](#), [legalStatus](#), [narrativeEvent](#), [relation](#), [subject](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
countryCode	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use the attributes [@valueURI](#), [@vocabularySource](#), and [@vocabularySourceURI](#) with [< placeName >](#) when referencing an entry of an external vocabulary, thesaurus, ontology.

Description and Usage

[<placeName>](#) should be identified by the proper noun that commonly designates the place, natural feature, or political jurisdiction. It is recommended that place names be taken from authorized vocabularies.

Use [<placeName>](#) within [<agent>](#) , [<formAvailable>](#) , [<function>](#) , [<legalStatus>](#) , [<relation>](#) and [<subject>](#) to encode the name of a place or geographic feature that is of importance in the term's or the entity's relation with the records being described. Use [<placeName>](#) within [<narrativeEvent>](#) to encode the geographic dimension of the event.

Availability

Optional, repeatable

See also

Within [<place>](#) , the required element [<label>](#) is used to capture the name of the geographic feature or location. This is to align with the other entity elements such as [<agent>](#) , [<formAvailable>](#) , or [<relation>](#) which also use [<label>](#) to name the related entity. Use [@target](#) within [<placeName>](#) to link to the [@id](#) attribute of a [<place>](#) , which might include more detailed information about the same place.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< places >

Places

Summary

An optional child element of <archDesc> , <c> , and <c01> to <c12> used for grouping together one or more <place> elements.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
place	1..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use the optional <places> element to group together one or more occurrences of <place> . <places> must include at least one <place> element. A <descriptiveNote> element may be included if a fuller textual explanation is needed.

The prescribed order of all child elements (both required and optional) is:

<place>

<descriptiveNote>

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< preferCite >

Preferred Citation

Summary

An element for specifying how users should cite the described materials in publication credits.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [< preferCite >](#) to supply users with a prescribed wording or format for references to the described materials to be included in bibliographies, footnotes, screen credits, etc.

Use the element [< abstract >](#) to provide a brief summary of the information encoded in [< preferCite >](#) . Use the repeatable [< p >](#) element to structure longer texts in several paragraphs. If required and suitable, use

[<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< processInfo >

Processing Information

Summary

For encoding information about archival activities related to the described materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< processInfo >](#) is used for basic information about accessioning, arranging, describing, preserving, storing, conserving, or otherwise preparing the described materials for research use. Where appropriate, encode more specific information about each of these activities separately within other elements, such as [< sourceOfAcquisition >](#) , [< appraisal >](#) , [< arrangement >](#) , etc.

Depending on the context, e.g. differing national approaches, [<processInfo>](#) might also refer to activities conducted before the materials are transferred to the archives, e.g. when the records creators already conduct some of the activities around appraisal or sensitivity review.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<processInfo>](#). Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML. Use [<narrativeEvent>](#) to provide a chronology of processing events.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

[<narrativeEvent>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<accruals>](#) which lists anticipated additions to the material already held by the repository but does not go into details about the processing of such additions once they have been received.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< publicationNote >

Publication Note

Summary

For citing works based on the use or analysis of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n
relations	0..1

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

Use [<publicationNote>](#) to identify works that are based on, about, or of special value when using the materials being described, or works in which a citation to or brief description of the materials occurs.

These works can either be described using narrative text in the elements [<abstract>](#) , [<p>](#) , and [<formattingExtension>](#) or they can be named within and, if applicable, linked to via [<relations>](#) . Using [<relations>](#) is especially useful when referring to several publications at once and will also allow for a more detailed description of the relationship itself by including type and role information or a temporal or geographic dimension of the relationship.

If described in narrative text, the element [<reference>](#) within [<p>](#) may be used to refer to analog or digital publications.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<relations>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< quantity >

Quantity

Summary

An optional child element of [< extent >](#) and [< dimensions >](#) that indicates the number of units present as described by [< unitOfMeasurement >](#) .

May contain

Element/content type
[text]

Occurrences

May occur within

[dimensions](#), [extent](#)

Attributes

Attribute name

[approximate](#)
[audience](#)
[conventionDeclarationReference](#)
[id](#)
[languageOfElement](#)
[maintenanceEventReference](#)
[scriptOfElement](#)
[sourceReference](#)
[target](#)

Attribute values

Optional (values limited to: false, true)
Optional
Optional
Optional
Optional
Optional
Optional
Optional
Optional

Description and Usage

[< quantity >](#) is for indicating the number of [< unitOfMeasurement >](#) -s being described. The content of [< quantity >](#) should be a number. Use of [< quantity >](#) enables extent statements to be machine processable.

Either [< quantity >](#) or [< unitOfMeasurement >](#) must be present, but it is recommended to use both elements in conjunction with each other whenever possible. If the quantity is unknown, the element should remain empty.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding

[Table of Contents](#)

<recordId>

Record Identifier

Summary

A required child element of [<control>](#) that designates a unique identifier for the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

[<recordId>](#) is used for recording a unique identifier for the EAS instance. The institution assigning the identifier ensures uniqueness of the [<recordId>](#) value within the archival descriptions under its control. A globally unique identifier may be constructed within [<recordId>](#) according to various external protocols (e.g. HTTP URI, DOI, PURL, or UUID), or in combination with [<agencyCode>](#), which is an optional element within [<maintenanceAgency>](#).

[<recordId>](#) cannot be empty.

Availability

Required, not repeatable

See also

Use [<agencyCode>](#) in combination with [<recordId>](#) to provide a globally unique identifier for the EAS instance.

Any alternative or additional record identifiers may be recorded in [<otherRecordId>](#) .

Examples

See [<control>](#) encoding

[Table of Contents](#)

< recordTypeSpecificStatement >

Record Type Specific Statement

Summary

An element for providing record type specific details for the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
objectXMLWrap	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< recordTypeSpecificStatement >](#) is for capturing record type specific details that are unique to a particular class, form or type of material and which are not recorded in any other element of description. Examples include mathematical data, such as scale for cartographic and architectural records, jurisdictional and denominational data for philatelic records, and presentation data that describes the format of music manuscripts.

Use the child [<objectXMLWrap>](#) to include record type specific details in another XML format or standard that might allow for more detailed encoding of such details than the EAS.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

[<objectXMLWrap>](#)

Availability

Optional, Repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< reference >

Reference

Summary

An element that cites an external resource.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
referringString	0..n
span	0..n

May occur within

[abstract](#), [container](#), [conventionDeclaration](#), [eventDescription](#), [formAvailableId](#), [genreForm](#), [head](#), [localTypeDeclaration](#), [otherIdentificationData](#), [p](#), [physicalFacet](#), [rightsDeclaration](#), [source](#), [textualDate](#), [unitId](#), [unitTitle](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
href	Optional
id	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@href](#) to link to the cited resource, in case this is available online.

Description and Usage

An element used for referencing external resources that have been used to compile the EAS instance, that provide additional context to the EAS instance, or that identify rules or conventions that have been applied.

[<reference>](#) is a required child element of [<conventionDeclaration>](#) , [<localTypeDeclaration>](#) , and [<rightsDeclaration>](#) for identifying any rules and conventions applied in the compilation of the description. It is also a required child element of [<source>](#) , used to identify any sources used in compiling the description. [<source>](#) may include multiple child [<reference>](#) elements.

In [<abstract>](#) , [<container>](#) , [<eventDescription>](#) , [<formAvailableId>](#) , [<genreForm>](#) , [<head>](#) , [<otherIdentificationData>](#) , [<p>](#) , [<physicalFacet>](#) , [<textualDate>](#) , [<unitId>](#) , and [<unitTitle>](#) , [<reference>](#) may be used to reference any external resources that provide additional context to the content of these elements, which may include multiple [<reference>](#) elements.

Availability

Within [<conventionDeclaration>](#) , [<localTypeDeclaration>](#) , [<rightsDeclaration>](#) : required, not repeatable

Within [<source>](#) : required, repeatable

Within [<abstract>](#) , [<container>](#) , [<eventDescription>](#) , [<formAvailableId>](#) , [<genreForm>](#) , [<head>](#) , [<otherIdentificationData>](#) , [<p>](#) , [<physicalFacet>](#) , [<textualDate>](#) , [<unitId>](#) , [<unitTitle>](#) : optional, repeatable

See also

[<reference>](#) is used for external linking only. If any internal linking is required, use the [@target](#) attribute to point to the [@id](#) of the referenced element.

Examples

See [<control>](#) encoding

[Table of Contents](#)

<referringString>

Referring String

Summary

An element for marking words or phrases in a longer text as named entities.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[abstract](#), [container](#), [eventDescription](#), [formAvailableId](#), [genreForm](#), [head](#), [otherIdentificationData](#), [p](#), [physicalFacet](#), [reference](#), [textualDate](#), [unitId](#), [unitTitle](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
normalizedForm	Optional
referredEntityRelationship	Optional
referredEntityType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@referredEntityType](#) to indicate the type of entity that is named in the narrative text and [@referredEntityRelationship](#) to specify the relation between that named entity and the entity being described in the EAS instance. Use

[@normalizedForm](#) to provide a standardized form of the name following e.g. an external vocabulary.

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

Use [<referringString>](#) in longer texts to indicate that certain words or phrases within these texts represent named entities such as persons, organizations, places, functions, resources, etc.

Use [<referringString>](#) e.g. when the identification of such named entities within existing archival descriptions is the result of some natural language processing or when capturing the results of named entity recognition having been conducted as part of Optical Character Recognition or Handwritten Text Recognition tasks.

Availability

Optional, repeatable

See also

Only fall back on using [<referringString>](#) in the contexts mentioned above.

Use dedicated elements such as [<agents>](#) , [<functions>](#) , [<places>](#) , [<formsAvailable>](#) , [<relatedMaterial>](#) , [<separatedMaterial>](#) , [<otherDescription>](#) , or [<publicationNote>](#) to name related entities central to the understanding of the materials described and to provide more information about their relationship with the materials.

Examples

See [<archDesc>](#) and [<control>](#) encoding

[Table of Contents](#)

< relatedMaterial >

Related Material

Summary

Element used for identifying archival materials that may be related to the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n
relations	0..1

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide the sequence of characters (e.g., URI) that uniquely identifies the entity in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) to identify the

source where [@valueURI](#) comes from, and [@vocabularySourceURI](#) to point univocally to the organization system used.

Description and Usage

[<relatedMaterial>](#) is used to identify associated materials in the same repository or elsewhere. These materials may be related by sphere of activity, or subject matter.

These associated materials can either be described using narrative text in the elements [<abstract>](#) , [<p>](#) , and [<formattingExtension>](#) or they can be named within and, if applicable, linked to via [<relations>](#) . Using [<relations>](#) is especially useful when referring to several associated materials at once and will also allow for a more detailed description of the relationship itself by including type and role information or a temporal or geographic dimension of the relationship.

If described in narrative text, the element [<reference>](#) within [<p>](#) may be used to refer to such associated materials.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<relations>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<separatedmaterial>](#) , which provides information about materials that have been separated or physically removed from the described materials but that are related to them by provenance.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< relation >

Relation

Summary

A required child element of [<relations>](#) for describing a relationship between the entity or records described and a related entity.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
label	1..n
objectXMLWrap	0..1
placeName	0..n
role	0..n

May occur within

[relations](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
relationType	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
targetType	Optional

Description and Usage

[<relation>](#) records descriptive information about a relationship between the materials being described and archival, bibliographic, or other types of resources or any kind of digital representations, microfiches or microfilms, copies, etc. of the materials. Descriptive information about a relationship

between the materials being described and agents or functions are captured in the entity elements [<agent>](#) and [<function>](#) .

Use the required child element [<label>](#) to provide a textual identification of the related entity, such as a name or a title. Use the optional attribute [@targetType](#) to classify the type of the related entity, the optional attribute [@relationType](#) to specify the type of relation in its most generic form, and the optional child element [<role>](#) to specify the role of the related entity towards the entity or the materials being described more concretely.

It is recommended that the terms used in [<label>](#) and [<role>](#) be taken from an authorized vocabulary. When not using the EAS value lists for [@relationType](#) and [@targetType](#), any alternative value lists should ideally also be taken from authorized vocabularies.

Use [<objectXMLWrap>](#) to embed XML documenting the related entity from any other namespace. Use [<date>](#) , [<dateRange>](#) , or [<dateSet>](#) for specifying the time period of the relationship and [<placeName>](#) for relevant location information. [<descriptiveNote>](#) may be included for more detailed specifications or explanations of the relationship.

The prescribed order of all child elements (both required and optional) is:

[<label>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<role>](#)

[<descriptiveNote>](#)

[<objectXMLWrap>](#)

Availability

Required, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< relations >

Relations

Summary

An optional element that groups one or more [<relation>](#) elements, which identify external entities and characterize the nature of their relationships to the entity or records being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
relation	1..n

May occur within

[formAvailable](#), [otherDescription](#), [publicationNote](#), [relatedMaterial](#), [separatedMaterial](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

A wrapper element that groups together one or more [<relation>](#) elements, each of which encodes a specific relationship.

The prescribed order of all child elements (both required and optional) is:

[<relation>](#)

[<descriptiveNote>](#)

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< relationship >

Relationship

Summary

A child element of [<agent>](#) , [<function>](#) , and [<place>](#) used to specify the type of relationship that these entities have with the entity being described within the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [function](#), [place](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the relationship in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

Use [<relationship>](#) within [<agent>](#) , [<function>](#) , and [<place>](#) to specify the type of relation that these entities have with the entity being described within the EAS instance, e.g. "creation" for record creators, "maintenance" for holding institutions, "storage" for places. To more specifically indicate the role of the related entity towards the entity being described in the EAS instance (e.g. "director" or "playwright" for the record creator of an audiovisual record, "readingRoom" for places), the element [<role>](#) should be used instead of or in combination with [<relationship>](#) .

The [<relationship>](#) element contains a textual description of the relation. It is recommended that values used in [<relationship>](#) be taken from an authorized vocabulary.

Availability

Optional, Repeatable

See also

Use [<role>](#) to more specifically indicate the role of the related entity towards the entity being described in the EAS instance respectively towards the EAS instance itself.

Examples

See [<control>](#) encoding

[Table of Contents](#)

< rightsDeclaration >

Rights Declaration

Summary

An optional child element of [<control>](#) that indicates a standard rights statement associated with the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
reference	1..1
shortCode	0..1

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [<rightsDeclaration>](#) to provide structured information about the usage rights of the EAS instance. [<rightsDeclaration>](#) should only be used to reference shared published licenses, such as Creative Commons, RightsStatements.org, or published locally-defined licenses. In cases where different licenses apply depending on the type of descriptive metadata, e.g. the Public Domain Mark for any factual metadata, but CC BY for any more narrative metadata that requires an additional research effort in its creation such as scope and content notes or biographies of records creators, these can be encoded in two separate [<rightsDeclaration>](#) elements. Include an [@id](#)

for each [<rightsDeclaration>](#) element and use [@target](#) with descriptive elements to point to the license that applies.

[<reference>](#) must be used to provide a machine-readable reference to a license statement (for example, a URI). It may also be used to encode the name of the license statement.

[<shortCode>](#) may be used to provide the abbreviated name for the rights statement. The value of [<shortCode>](#) should align with the rights statement referenced by [<reference>](#) and [<descriptiveNote>](#) .

[<descriptiveNote>](#) may be used to provide a human-readable description of the license statement.

The prescribed order of all child elements (both required and optional) is:

[<reference>](#)

[<shortCode>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< role >

Role

Summary

An optional child element of [< agent >](#) , [< formAvailable >](#) , [< function >](#) , [< place >](#) , and [< relation >](#) that indicates the role of the related entity towards the entity being described in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[agent](#), [formAvailable](#), [function](#), [place](#), [relation](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [< role >](#) to indicate the role of the related entity towards the entity being described in the EAS instance or the EAS instance itself. It is recommended that the terms in [< role >](#) be taken from authorized vocabularies.

[< role >](#) might be used in combination with the specific type attribute available with each of the elements where [< role >](#) is available. While these attributes provide a generic typology of each entity class, e.g. "corporateBody",

"person", and "family" for [@agentType](#), [<role>](#) looks more specifically at the related entity itself in a certain context.

Furthermore, [<role>](#) may be used in combination with [<relationship>](#) which is available in [<agent>](#) , [<function>](#) , and [<place>](#) . While [<relationship>](#) is used to encode a more general denominator for the relation between the related entity and the entity being described in the EAS instance, e.g. "creation" or "authorship" for agents, [<role>](#) allows to be more specific to the individual related entity, e.g. by assigning the role of "director" to one [<agent>](#) and the role of "playwright" to another.

Availability

Optional, repeatable

See also

Use the element [<label>](#) to encode the related entity's name.

Examples

See [<archDesc>](#) , [<control>](#) , and [<findAidDesc>](#) encoding

[Table of Contents](#)

< scopeContent >

Scope and Content

Summary

An element that provides information about the nature of and activities reflected in the described materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

[< scopeContent >](#) contains a narrative statement that summarizes the range and topical coverage of the materials. It provides the researcher with the information necessary to evaluate the potential relevance of the materials being described. [< scopeContent >](#) may include information about the form and arrangement of the materials; dates covered by the materials; significant organizations, individuals, events, places, and subjects represented in the materials; and functions and activities that generated the materials being described. It may also identify strengths of or gaps in the materials.

Use the element `<abstract>` to provide a brief summary of the information encoded in `<scopeContent>`. Use the repeatable `<p>` element to structure longer texts in several paragraphs. If required and suitable, use `<formattingExtension>` to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

`<abstract>` (if used)

`<formattingExtension>` or `<p>`

Availability

Optional, repeatable

Examples

See `<archDesc>` encoding

[Table of Contents](#)

< separatedMaterial >

Separated Material

Summary

An element identifying materials associated by provenance that have been physically separated or removed.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n
relations	0..1

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

< [separatedMaterial](#) > identifies materials that are associated by provenance to the described materials, and that have been physically separated or removed from them. Examples include the separation of special formats; the destruction

of duplicate or nonessential material; and the deliberate or unintentional dispersal of a creator's records among different repositories.

These separated materials can either be described using narrative text in the elements [<abstract>](#) , [<p>](#) , and [<formattingExtension>](#) or they can be named within and, if applicable, linked to via [<relations>](#) . Using [<relations>](#) is especially useful when referring to several separated materials at once, and will also allow for a more detailed description of the relationship itself by including type and role information or a temporal or geographic dimension of the relationship.

If described in narrative text, the element [<reference>](#) within [<p>](#) may be used to refer to such separated materials.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<relations>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<relatedMaterial>](#) , which is used for references to materials that are not physically or logically included in the material described in the finding aid.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< shortCode >

Short Code

Summary

An optional element for encoding the shortened form of the rule, code list, vocabulary, rights statement etc applied in creating and maintaining the EAS instance and captured in [< conventionDeclaration >](#) , [< localTypeDeclaration >](#) and [< rightsDeclaration >](#) .

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[conventionDeclaration](#), [localTypeDeclaration](#), [rightsDeclaration](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

Use [< shortCode >](#) within [< conventionDeclaration >](#) or [< localTypeDeclaration >](#) to identify the shortened form, acronym, or code for a thesaurus, controlled vocabulary, or another standard used in creating the EAS description. Use within [< rightsDeclaration >](#) to provide an abbreviated name for the rights statement.

To improve interoperability, it is recommended that the value be selected from an authorized list of codes such as the MARC Field Index to Source Code Usage (<http://www.loc.gov/marc/sourcelist/>).

Availability

Optional, not repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< source >

Source

Summary

A required and repeatable child element of [<sources>](#) used to identify a particular source of evidence used for the establishment of the descriptive parts in an EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
citedRange	0..n
descriptiveNote	0..1
objectXMLWrap	0..1
reference	1..n

May occur within

[sources](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
href	Optional
languageOfElement	Optional
linkRole	Optional
linkTitle	Optional
scriptOfElement	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

In the case of online sources, use [@href](#) to provide a URL. In case an online source is identified via a persistent identifier (PID) such as a DOI or and ARK, use [@valueURI](#) instead and indicate the PID scheme in [@vocabularySource](#) and/or [@vocabularySourceURI](#).

Description and Usage

Use [<source>](#) to cite a published resource used in creating the descriptive parts of the EAS instance. Use the required child element [<reference>](#) to include a textual identification of the source. Use the optional child element [<citedRange>](#) to point to a specific location within a source.

Use the optional [<descriptiveNote>](#) for any additional notes about the source. Use the optional [<objectXMLWrap>](#) to embed XML documenting the source from any other namespace.

The prescribed order of all child elements (both required and optional) is:

[<reference>](#)

[<citedRange>](#)

[<descriptiveNote>](#)

[<objectXMLWrap>](#)

Availability

Required, repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< sourceOfAcquisition >

Source Of Acquisition

Summary

An element for encoding the immediate source of acquisition of the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
narrativeEvent	0..n
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [<sourceOfAcquisition>](#) to identify the source of the materials being described and the circumstances under which they were received, including donations, transfers, purchases, and deposits.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<sourceOfAcquisition>](#) . Use the repeatable [<p>](#) element

to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML. Use [<narrativeEvent>](#) to provide a chronology of processing events.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) (if used)

[<formattingExtension>](#) or [<p>](#)

[<narrativeEvent>](#)

Availability

Optional, repeatable

See also

Note that the accession number may be encoded in [<unitId>](#) within [<identificationData>](#) .

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< sources >

Sources

Summary

An optional child element of < control > that groups one or more < source > s of evidence used in the descriptive parts in the EAS instance.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
descriptiveNote	0..1
source	1..n

May occur within

[control](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
id	Optional
languageOfElement	Optional
scriptOfElement	Optional
target	Optional

Description and Usage

Use < sources > to bind together one or more < source > elements.
< sources > must include at least one < source > element.

The prescribed order of all child elements (both required and optional) is:

< source >

< descriptiveNote >

Availability

Optional, not repeatable

Examples

See [<control>](#) encoding

[Table of Contents](#)

< span >

span

Summary

Specifies the beginning and the end of a span of text.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

abstract, container, eventDescription, formAvailableId, genreForm, head, otherIdentificationData, physicalFacet, reference, p, textualDate, unitId, unitTitle

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
style	Optional
target	Optional

Attribute usage

Use the optional [@style](#) attribute to specify an arbitrary stylistic difference.

Description and Usage

[](#) is an optional formatting element for distinguishing words or phrases that are intentionally stressed or emphasized for linguistic effect or identifying some qualities of the words or phrases.

Availability

Optional, repeatable

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< subject >

Subject

Summary

An element for encoding controlled topics represented in the materials being described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet	0..1
descriptiveNote	0..1
placeName	0..n
term	1..n

May occur within

[subjectHeadings](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

A [<subject>](#) element is a wrapper element used to encode an index term, using the required child element [<term>](#) . Terms are used to identify the topics and themes represented in the described materials. Such terms often provide useful access points to the materials, especially for corporate,

government, or institutional records and may be drawn from controlled vocabularies or may be natural language terms.

[<subject>](#) must include at least one [<term>](#) element. [<term>](#) can be repeated within [<subject>](#) to include translations of the same term. Use the [@languageOfElement](#) attribute to identify the language used in each [<term>](#) .

Associated date(s) ([<date>](#) , [<dateRange>](#) , or [<dateSet>](#)) and place(s) ([<placeName>](#)) may be included to further constrain the term's meaning. A [<descriptiveNote>](#) may be included if a fuller textual explanation is needed.

A list of [<subject>](#) terms may also be used with reference pointers ([@id](#) and [@target](#)) to enhance navigation of and access to the materials being described.

The order of child elements of [<subject>](#) is:
[<term>](#)

One of [<date>](#) , [<dateRange>](#) , or [<dateSet>](#)

[<placeName>](#)

[<descriptiveNote>](#)

Availability

Optional, repeatable

[Table of Contents](#)

< subjectHeadings >

Subject Headings

Summary

An element that binds together information about subject headings for the described materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
formattingExtension	0..1
p	0..n
subject	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Description and Usage

Use [<subjectHeadings>](#) to bundle topical or thematic access points that represent the contexts of the materials described.

Although [<subjectHeadings>](#) is often used within [<archDesc>](#) to provide significant access terms for the entirety of the materials described, it may be used at the component level to provide terms specific to a component if so desired.

This element helps to provide more standardization enabling an authority-controlled searching across finding aids, in particular where terms are taken from internationally or nationally controlled vocabularies such as the Library of Congress Subject Headings (LCSH), the Getty Art & Architecture Thesaurus (Getty AAT), the UNESCO Thesaurus, the UK Archival Thesaurus (UKAT) or Wikidata.

Availability

Optional, repeatable

See also

Use the dedicated elements [<agent>](#) , [<function>](#) , and [<place>](#) to encode information about persons, corporate bodies, families, functions, and geographical locations or features that represent the contexts of the materials described.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< term >

Term

Summary

An element used to encode a descriptive term in accordance with authorized vocabularies or local rules.

May contain

Element/content type
[text]

Occurrences

May occur within

[legalStatus](#), [subject](#)

Attributes

Attribute name

[audience](#)

[conventionDeclarationReference](#)

[id](#)

[languageOfElement](#)

[maintenanceEventReference](#)

[scriptOfElement](#)

[sourceReference](#)

[target](#)

Attribute values

Optional

Optional

Optional

Optional

Optional

Optional

Optional

Optional

Description and Usage

< term > is a required child element of < [legalStatus](#) > and < [subject](#) > , used to specify a descriptive term in accordance with authorized vocabularies or local rules.

< term > can be repeated within its parent element to include translations of the same term. Use the [@languageOfElement](#) attribute to identify the language used in each < term > grouped within a single parent element.

Availability

Required, repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< textualDate >

Textual Date

Summary

A child element of [<unitDate>](#) that provides a textual statement of the date(s) covered by the described materials, or indicates when no date information is available.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[unitDate](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
status	Optional
target	Optional

Description and Usage

[< textualDate >](#) is for indicating the date or dates the described materials were created, issued, copyrighted, broadcast, etc, when these cannot be expressed in a more standardised or structured way. [< textualDate >](#) mainly takes the form of text representing a single date, a date range, or a combination of single dates and date ranges. [< textualDate >](#) may also be used to indicate that no date information is available.

Availability

Optional, not repeatable

See also

Use the other sub-elements of [<unitDate>](#) , i.e. [<date>](#) , [<dateRange>](#) or [<dateSet>](#) to provide a more granular, machine-processable statement for the dates of the materials being described. This includes uncertain and/or approximate dates.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< title >

Title

Summary

An element for encoding the formal name of a finding aid.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
part	1..n

May occur within

[findAidDesc](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
style	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@localType](#) to differentiate between the general title and a subtitle or the title of an overarching series.

Description and Usage

Use [< title >](#) to record the title of the finding aid.

Use the sub-element [<part>](#) to break a title down into aspects such as an edition statement (e.g. "2nd edition").

Use repeated [<title>](#) elements distinguished by their [@localType](#)-s when describing e.g. a .pdf or a .docx instantiation of a finding aid to give the publication title for display on the one hand and the file title of the .pdf or the .docx file on the other hand.

Availability

Optional, repeatable

See also

Do not confuse with [<unitTitle>](#) , which is used to encode the name of the described materials, such as the title of a collection or the title of an individual item.

Examples

See [<findAidDesc>](#) encoding

[Table of Contents](#)

< toDate >

To Date

Summary

A child element of [< dateRange >](#) that records the end point in a range of dates.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[dateRange](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
era	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
notAfter	Optional
notBefore	Optional
scriptOfElement	Optional
standardDate	Optional
status	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@certainty](#) to indicate the degree of precision in the dating, for example, "uncertain" or "approximate".

Use [@localType](#) to supply a more specific characterization of the end date.

Use [@notAfter](#) and [@notBefore](#) to capture the latest and earliest possible dates in machine-processable form in cases when the date is uncertain.

Use [@standardDate](#) to provide a machine-processable form of the date.

Use [@status](#) with the values "unknown" or "ongoing" to indicate where part of a date range is unknown, or the date range is ongoing.

Description and Usage

Use [<toDate>](#) to record the end date in a range of dates, whether they be known, approximate or unknown. The content of the element is intended to be a human-readable, natural language expression of the date. If, however, indexing or other machine processing of dates is desired, the [@standardDate](#) should be used to record the date in machine-processable form as well.

[<toDate>](#) may be omitted from [<dateRange>](#) , or the [@status](#) attribute used, if the date span is ongoing or the [<toDate>](#) is unknown.

Availability

Optional, not repeatable

See also

Use [<fromDate>](#) to record the starting point of a date range.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< unitDate >

Date of the Unit

Summary

A child element of [<identificationData>](#) that allows the encoding of either structured, machine-processable expressions of the dates of the materials being described or of a simple statement of these date(s).

May contain

<i>Element/content type</i>	<i>Occurrences</i>
date or dateRange or dateSet or textual	0..1

[Date](#)

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
calendar	Optional
certainty	Optional
conventionDeclarationReference	Optional
dateChar	Optional
era	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
unitDateType	Optional

Attribute usage

Use [@unitDateType](#) to indicate if [<unitDate>](#) represents inclusive dates or bulk (predominant) dates.

Description and Usage

[<unitDate>](#) is for indicating the date or dates the described materials were created, issued, copyrighted, broadcast, etc. [<unitDate>](#) may include date information in the form of text or numbers, and may consist of a single date, a date range, or a combination of single dates and date ranges.

Use the sub-elements [<date>](#) , [<dateRange>](#) or [<dateSet>](#) to provide a more granular, machine-processable statement for the dates of the materials being described. Alternatively, use the sub-element [<textualDate>](#) to capture a temporal statement that cannot easily be expressed in a standardised or structured way.

Availability

Optional, repeatable

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< unitId >

Identifier of the Unit

Summary

A child element of [<identificationData>](#) that provides an identifier for the materials being described, such as an accession number or a reference code.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
countryCode	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
repositoryCode	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Although not required, the [@countryCode](#) and [@repositoryCode](#) should be used in [<unitId>](#) to comply with ISAD(G) element 3.1.1.

Description and Usage

[<unitId>](#) may contain any alpha-numeric text string that serves as a unique reference point or control number for the described material, such as a lot number, an accession number, a classification number, a reference code, or an entry number in a bibliography or catalog. [<unitId>](#) is primarily a logical designation, which sometimes indirectly provides location information, as in the case of a classification number.

Availability

Optional, repeatable

See also

Use [<container>](#) and [<place>](#) to designate the physical housing or location of the described materials.

Use [<formAvailableId>](#) to provide identifiers used for the specific instantiations of the materials being described. The identifier in [<unitId>](#) will usually be different from, though might provide a basis for these identifiers.

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

< unitOfMeasurement >

Unit of Measurement

Summary

An optional child element of [<extent>](#) and [<dimensions>](#) that indicates the unit of measurement being quantified, e.g., boxes, linear feet, megabyte, gigabyte, etc.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[dimensions](#), [extent](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@valueURI](#) to provide a number, code, or string (e.g., URI) that uniquely identifies the unit type in a controlled vocabulary, taxonomy, ontology, or other knowledge organization system. Use [@vocabularySource](#) and/or [@vocabularySourceURI](#) to name and/or point to the organization system used.

Description and Usage

[<unitOfMeasurement>](#) identifies the unit being quantified. This can cover analog units such as boxes, linear feet or meters, cubic meters, etc. as well as digital units such as megabytes, gigabytes, etc. or types of items that are counted such as maps, photographs, posters, etc.

Either [<unitOfMeasurement>](#) or [<quantity>](#) must be present, but it is recommended to use both elements in conjunction with each other whenever possible.

Availability

Optional, not repeatable

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding

[Table of Contents](#)

< unitTitle >

Title of the Unit

Summary

A child element of [< identificationData >](#) that specifies a title for the described materials.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	
reference	0..n
referringString	0..n
span	0..n

May occur within

[identificationData](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Attribute usage

Use [@localType](#) if local use requires recording the type of [< unitTitle >](#) .

Description and Usage

[<unitTitle>](#) is for recording the title statement, either formal or supplied, of the described materials. The title statement may consist of a word or phrase. [<unitTitle>](#) is used at both the highest unit or [<archDesc>](#) level (e.g., collection, record set, or fonds) and at all the subordinate [<c>](#) levels (e.g., subseries, files, records, items, or other intervening stages within a hierarchical description).

Availability

Optional, repeatable

[Table of Contents](#)

< useConditions >

Conditions Governing Use

Summary

An element for indicating any conditions that affect the use of the described materials, such as in publications.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
abstract	0..1
dateRange	0..1
formattingExtension	0..1
p	0..n

May occur within

[archDesc](#), [c](#), [c01](#), [c02](#), [c03](#), [c04](#), [c05](#), [c06](#), [c07](#), [c08](#), [c09](#), [c10](#), [c11](#), [c12](#), [formAvailable](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
localType	Optional
localTypeDeclarationReference	Optional
maintenanceEventReference	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional
valueURI	Optional
vocabularySource	Optional
vocabularySourceURI	Optional

Description and Usage

Use [< useConditions >](#) for information about any limitations, regulations, or special procedures imposed by a repository, donor, legal statute, or other agency. These conditions may be related to reproduction, publication, or

quotation of the described materials after access to the materials has been granted. Use the sub-element [<dateRange>](#) to provide information about the time span during which or until when these conditions of use apply.

[<useConditions>](#) may also be used to indicate the absence of restrictions, such as when intellectual property rights have been dedicated to the public.

Use the element [<abstract>](#) to provide a brief summary of the information encoded in [<useConditions>](#). Use the repeatable [<p>](#) element to structure longer texts in several paragraphs. If required and suitable, use [<formattingExtension>](#) to make use of more detailed formatting options such as lists, tables, or section headers in XHTML.

The prescribed order of all child elements (both required and optional) is:

[<abstract>](#) if used

[<dateRange>](#)

[<formattingExtension>](#) or [<p>](#)

Availability

Optional, repeatable

See also

Do not confuse with [<accessConditions>](#), which contains information about conditions affecting the availability of the described materials.

Examples

See [<archDesc>](#) encoding

[Table of Contents](#)

< writingSystem >

Writing System

Summary

A required child element of [< languageSet >](#) that identifies the writing script for a language used in the materials described.

May contain

<i>Element/content type</i>	<i>Occurrences</i>
[text]	

May occur within

[languageSet](#)

Attributes

<i>Attribute name</i>	<i>Attribute values</i>
audience	Optional
conventionDeclarationReference	Optional
id	Optional
languageOfElement	Optional
maintenanceEventReference	Optional
scriptCode	Optional
scriptOfElement	Optional
sourceReference	Optional
target	Optional

Attribute usage

Use [@scriptCode](#) to provide a code for the writing system itself.

Use [@scriptOfElement](#) to provide a code for the writing system in which the element is given.

Description and Usage

An optional element within [< languageSet >](#) that gives the main script used by the records being described.

Availability

Required, only repeatable when encoding one language with several writing systems

Examples

See [<identificationData>](#) encoding

[Table of Contents](#)

Attributes

@addressLineType

Address Line Type

Summary

Used to specify the type of address line encoded in [<addressLine>](#) .

Description and Usage

Use [@addressLineType](#) with [<addressLine>](#) to specify the type of address line, e.g. "street", "country" or "postalCode". Use the attribute [@addressLineTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@addressLineType](#).

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@addressLineTypeEncoding

Address Line Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of address line given as part of a physical address.

Description and Usage

[@addressLineTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@addressLineType](#) within [<addressLine>](#) . If the value "EASList" is selected, [@addressLineType](#) will be expected with the values "county", "country", "district", "municipality", "postBox", "postalCode", "region", or "street". If the value "otherAddressLineTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherAddressLineTypeEncoding

Examples

See [<control>](#) encoding

[Table of Contents](#)

@agentType

Agent Type

Summary

An optional attribute of [<agent>](#) that indicates the type of agent relevant in a specific context.

Description and Usage

Use [@agentType](#) in [<agent>](#) to specify the type of agent responsible for the creation, modification, or deletion of an EAS instance, when used within [<maintenanceEvent>](#), the type of agent relevant in the context of a [<narrativeEvent>](#) or the type of agent important in relation to the creation, modification, publication, or use of record resources (within [<archDesc>](#) and the component elements) and of finding aids (within [<findAidDesc>](#)). Use the attribute [@agentTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@agentType](#).

Data Type

token

Examples

See [<archDesc>](#) and [<control>](#) encoding
[Table of Contents](#)

@agentTypeEncoding

Agent Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of agent.

Description and Usage

[@agentTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@agentType](#) within [<agent>](#) . If the value "EASList" is selected, [@agentType](#) will be expected with the values "corporateBody", "family", "group", "human", "mechanism", "person", "position", or "unknown". If the value "otherAgentTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherAgentTypeEncoding

Examples

See [<control>](#) encoding

[Table of Contents](#)

@approximate

Approximate

Summary

Indicates that the value provided is not exact. Available in [<quantity>](#) .

Values

false, true

[Table of Contents](#)

@audience

Audience

Summary

An optional attribute that helps control whether the information contained in the element should be available to all viewers or only to repository staff.

Description and Usage

Available as global attribute for all elements. The attribute can be set to "external" in e.g. [<cpfDescription>](#) in EAC-CPF, [<archDesc>](#) in EAD, or [<functionsDescription>](#) in EAF to allow access to all the information about the entity, materials, or functions being described, but specific elements within these sections can also be set to "internal" to reserve that information for repository access only. This feature is intended to assist application software in restricting access to particular information by explicitly identifying data that is potentially sensitive or may otherwise have a limited audience. Special software capability may be needed, however, to prevent the display or export of an element marked "internal" when a whole EAS instance is displayed in a networked environment. Use the attribute [@audienceEncoding](#) in [<control>](#) to identify the list of terms to be used as values of [@audience](#).

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@audienceEncoding

Audience Encoding

Summary

Specifies the authoritative source or rules for values used to indicate whether information encoded in a specific element is available for all or only for a restricted audience.

Description and Usage

[@audienceEncoding](#) specifies the authoritative source or rules for values supplied in [@audience](#) available in all elements. If the value "EASList" is selected, [@audience](#) will be expected with the values "external" or "internal". If the value "otherAudienceEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherAudienceEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@calendar

Calendar

Summary

System of reckoning time, such as Gregorian calendar or Julian calendar.

Description and Usage

Suggested values include, but are not limited to, "gregorian" and "julian".
Available in [<date>](#) , [<fromDate>](#) , [<toDate>](#) , [<unitDate>](#) .

Data Type

token

[Table of Contents](#)

@certainty

Certainty

Summary

The level of confidence for a date.

Description and Usage

The optional attribute [@certainty](#) provides level of confidence for the information given in [<date>](#) , [<fromDate>](#) , [<toDate>](#) , or [<unitDate>](#) , e.g., approximate or circa.

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@contactLineType

Contact Line Type

Summary

Used to specify the type of contact line encoded in [<contactLine>](#) .

Description and Usage

An attribute used to specify the type of contact line encoded in [<contactLine>](#) , e.g. "email", "phoneNumber" or "homepage".

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@contactLineTypeEncoding

Contact Line Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of contact line given as part of a digital address.

Description and Usage

[@contactLineTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@contactLineType](#) within [<contactLine>](#) . If the value "EASList" is selected, [@contactLineType](#) will be expected with the values "directions", "email", "fax", "homepage", "mobileNumber", or "phoneNumber". If the value "otherContactLineTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherContactLineTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@containerId

Container ID

Summary

An attribute for [<container>](#) that takes as its value a locally assigned identifier (e.g. barcode) for the container described. Unlike [@id](#), the value of [@containerId](#) does not need to be unique within the document, and does not have to conform to the rules for the ID data type.

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@conventionDeclarationReference

Convention Declaration Reference

Summary

Use [@conventionDeclarationReference](#) to provide a direct link to a [<conventionDeclaration>](#) element within [<control>](#) .

Description and Usage

The attribute can be used to link to a convention or rule that prescribes a method for converting one script into another script (transliteration). It also can be used to link to a national, international, or other rule that governs the construction of a name. This optional attribute is available in elements that can contain text.

Data Type

IDREFS

Examples

See [<findAidDesc>](#) encoding
[Table of Contents](#)

@coordinateSystem

Coordinate System

Summary

A code for a system used to express geographic coordinates.

Description and Usage

A code for a system used to express geographic coordinates, for example WGS84, (World Geodetic System), OSGB36 (Ordnance Survey Great Britain), or ED50 (European Datum). Required in [<geographicCoordinates>](#) .

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@countryCode

Country Code

Summary

A unique code representing a country.

Description and Usage

Content of the optional attribute should be a code taken from the part of ISO 3166 Country Codes or another controlled list specified in the [@countryEncoding](#) attribute in [<control>](#) . Available in [<maintenanceAgency>](#) and [<placeName>](#) . Also available in [<unitId>](#) , where it can be used together with [@repositoryCode](#) to comply with ISAD(G) element 3.1.1.

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@countryEncoding

Country Encoding

Summary

Specifies the authoritative source or rules for codes used to identify a country as part of the maintenance agency's location, of describing a geographic feature, or of the identifier of the materials described.

Description and Usage

[@countryEncoding](#) specifies the authoritative source or rules for values supplied in [@countryCode](#) within [<maintenanceAgency>](#) , [<placeName>](#) , and [<unitId>](#) . This can either be a specific part of the ISO standard 3166 or an alternative code list. If the value "otherCountryEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso3166-1-alpha-2, iso3166-1-alpha-3, iso3166-1-numeric, iso3166-2, iso3166-3, otherCountryEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@coverage

Coverage

Summary

Specifies whether a statement of extent or information about analog respectively digital instantiation(s) relates to the entire unit being described or only a part thereof.

Description and Usage

Use [@coverage](#) with [<extent>](#) to indicate whether the statement of physical description refers to the entire unit being described (e.g. with value "whole") or only a part thereof (e.g. with value "part"). Use [@coverage](#) with [<formAvailable>](#) to indicate whether the digital archival object or the copy or any other type of instantiation represents the entire set of records being described or a part of it. Use the attribute [@coverageEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@coverage](#).

Data Type

token

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding
[Table of Contents](#)

@coverageEncoding

coverageEncoding

Summary

Specifies the authoritative source or rules for values used to indicate whether extent information refers to or an instantiation reflects all the materials described or only part of them.

Description and Usage

[@coverageEncoding](#) specifies the authoritative source or rules for values supplied in [@coverage](#) within [<extent>](#) and [<formAvailable>](#) . If the value "EASList" is selected, [@coverage](#) will be expected with the values "part" or "whole". If the value "otherCoverageEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherCoverageEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@dateChar

Date Characterization

Summary

Term characterizing the nature of a date, such as dates of creation, accumulation, or modification. Available in [<unitDate>](#) .

Data Type

token

[Table of Contents](#)

@dateEncoding

Date Encoding

Summary

Specifies the authoritative source or rules used to normalize date information.

Description and Usage

[@dateEncoding](#) specifies the authoritative source or rules for normalized values supplied in [@standardDate](#) within [<date>](#) , [<fromDate>](#) and [<toDate>](#) as well as in [@standardDateTime](#) within [<eventDateTime>](#) . This can either be the ISO standard 8601 or an alternative code list. If the value "otherDateEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso8601, otherDateEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@descriptionOfComponentsType

Description of Subordinate Components Type

Summary

An optional attribute in [<descriptionOfComponents>](#) that indicates the approach used in describing components within a finding aid (e.g. "inDepth"). Use the attribute [@descriptionOfComponentsTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@descriptionOfComponentsType](#).

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@descriptionOfComponentsTypeEncoding

Description Of Components Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the approach used in describing components.

Description and Usage

[@descriptionOfComponentsTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@descriptionOfComponentsType](#) within [<descriptionOfComponents>](#) . If the value "EASList" is selected, [@descriptionOfComponentsType](#) will be expected with the values "analyticOverview", "combined" or "inDepth". If the value "otherDescriptionOfComponentsTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherDescriptionOfComponentsTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@detailLevel

Level of Detail

Summary

Provides information about the level of detail of the description encoded within the EAS instance.

Description and Usage

An optional attribute within [<control>](#) , used to provide information about the level of detail in accordance with relevant description guidelines and/or rules, e.g. "minimal" or "extended". Use the attribute [@detailLevelEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@detailLevel](#).

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@detailLevelEncoding

Detail Level Encoding

Summary

Specifies the authoritative source or rules for values used to indicate whether the EAS instance encodes minimal, basic, or extended information.

Description and Usage

[@detailLevelEncoding](#) specifies the authoritative source or rules for values supplied in [@detailLevel](#) within [<control>](#) . If the value "EASList" is selected, [@detailLevel](#) will be expected with the values "basic", "extended" or "minimal". If the value "otherDetailLevelEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherDetailLevelEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@era

Era

Summary

Period during which years are numbered and dates reckoned.

Description and Usage

Period during which years are numbered and dates reckoned, such as CE (Common Era) or BCE (Before Common Era). Suggested values include, but are not limited to, "ce" and "bce". This optional attribute is available in [<date>](#) , [<fromDate>](#) , [<toDate>](#) , [<unitDate>](#) .

Data Type

token

[Table of Contents](#)

@extentType

Extent Type

Summary

An optional attribute of [<extent>](#) that specifies the nature of the extent statement being provided.

Description and Usage

Use [@extentType](#) with [<extent>](#) to specify the nature of the statement being provided. Use e.g. "carrier" to refer to the number of containers; "materialType" to indicate the type and/or number of the material types; "spaceOccupied" to denote the two- or three-dimensional volume of the materials. Use the attribute [@extentTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@extentType](#).

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@extentTypeEncoding

Extent Type Encoding

Summary

Specifies the authoritative source or rules for values used to specify the nature of the extent statement being provided.

Description and Usage

[@extentTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@extentType](#) within [<extent>](#) . If the value "EASList" is selected, [@extentType](#) will be expected with the values "carrier", "materialType", or "spaceOccupied". If the value "otherExtentTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherExtentTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@formAvailableType

Form Available Type

Summary

An optional attribute of [<formAvailable>](#) that specifies the type of form or instantiation being described.

Description and Usage

Use [@formAvailableType](#) with [<formAvailable>](#) to specify the type of form or instantiation being described. Use e.g. "analogOriginal" for an analog original instantiation such as a charter, map, drawing, paper file, etc. Use the attribute [@formAvailableTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@formAvailableType](#).

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@formAvailableTypeEncoding

Form Available Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of form or format in which the archival record can be represented, i.e. the type of instantiation.

Description and Usage

[@formAvailableTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@formAvailableType](#) within [<formAvailable>](#) . If the value "EASList" is selected, [@formAvailableType](#) will be expected with the values "analogOriginal", "analogDerived", "digitalOriginal", "digitalDerived". If the value "otherFormAvailableTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherFormAvailableTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@functionType

Function Type

Summary

An optional attribute of [<function>](#) that specifies the type of function being described.

Description and Usage

Use [@functionType](#) with [<function>](#) to specify the type of function being described, e.g. as an "activity" or a "businessProcess". Use the attribute [@functionTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@functionType](#).

Data Type

token

[Table of Contents](#)

@functionTypeEncoding

Function Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of function.

Description and Usage

[@functionTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@functionType](#) within [<function>](#) . If the value "EASList" is selected, [@functionType](#) will be expected with the values "activity", "businessProcess", "function", "subfunction", "task", or "transaction". If the value "otherFunctionTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherFunctionTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@href

Hypertext Reference

Summary

The address for a remote resource.

Description and Usage

The optional [@href](#) attribute takes the form of a Uniform Resource Identifier (URI). Available in [<contactLine>](#) , [<findAidDesc>](#) , [<reference>](#) , and [<source>](#) . Being of type "anyURI", [@href](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@href](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

See [<findAidDesc>](#) encoding
[Table of Contents](#)

@id

ID

Summary

A unique identifier to name a specific element within an EAS instance.

Description and Usage

An identifier that must be unique within the current EAS instance and is used to name the element so that it can be referred to from somewhere else in the EAS instance. This facilitates building links between the element and other elements within the same XML file, though it can also be used to point to a specific element from outside of the EAS instance. Use [@target](#), [@conventionDeclarationReference](#), [@localTypeDeclarationReference](#), [@maintenanceEventReference](#), or [@sourceReference](#) to link to an [@id](#) attribute within the EAS instance.

Data Type

ID

Examples

See [<control>](#) encoding
[Table of Contents](#)

@languageCode

Language Code

Summary

The code for the language used in the EAS instance or by the records or entity being described.

Description and Usage

Content of the attribute should be a code taken from ISO 639-1, ISO 639-2, ISO 639-2b, ISO 639-2t, ISO 639-3, ISO 639-5, IETF BCP 47 or another controlled list, as specified in the [@languageEncoding](#) attribute in [<control>](#) . Required in [<languageDeclaration>](#) and optionally available in [<language>](#) .

Data Type

token

Examples

See [<control>](#) and [<identificationData>](#) encoding
[Table of Contents](#)

@languageEncoding

Language Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the language of the EAS instance as a whole, of a specific element, or represented in the materials being described.

Description and Usage

[@languageEncoding](#) specifies the authoritative source or rules for values supplied in [@languageCode](#) within [<languageDeclaration>](#) and [<language>](#) and in [@languageOfElement](#) available in all non-empty elements. This can either be one of the ISO standards 639-1, 639-2, 639-2b, 639-2t, 639-3, and 639-5, the IETF BCP 47 language tag or an alternative code list. If the value "otherLanguageEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso639-1, iso639-2, iso639-2b, iso639-2t, iso639-3, iso639-5, ietf-bcp-47, otherLanguageEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@languageOfElement

Language of Element

Summary

Indicates the language of the content of an element.

Description and Usage

Content of the attribute should be a code taken from ISO 639-1, ISO 639-2, ISO 639-2b, ISO 639-2t, ISO 639-3, ISO 639-5, IETF BCP 47 or another controlled list, as specified in the [@languageEncoding](#) attribute in [<control>](#) . May be used consistently in a multi-lingual EAS instance to specify which elements are written in which language. Optionally available on all non-empty elements.

Data Type

token

Examples

See [<archDesc>](#) , [<control>](#) , and [<identificationData>](#) encoding
[Table of Contents](#)

@level

Level

Summary

The hierarchical level of the materials being described by the element. This attribute is available in [<archDesc>](#) , where the highest level of material represented in the finding aid can be declared (e.g. collection, fonds, record set), and in [<c>](#) and [<c01>](#) - [<c12>](#) , where it may be used to declare the level of description represented by each component (e.g. subgroup, series, file, record). Use the attribute [@levelEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@level](#).

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@levelEncoding

Level Encoding

Summary

Specifies the authoritative source or rules for values used to indicate the hierarchical level of the materials being described.

Description and Usage

[@levelEncoding](#) specifies the authoritative source or rules for values supplied in [@level](#) within [<archDesc>](#) , [<c>](#) , and [<c01>](#) - [<c12>](#) . If the value "EASList" is selected, [@level](#) will be expected with the values "class", "collection", "file", "fonds", "item", "recordGroup", "series", "subfonds", "subgroup", or "subseries". If the value "otherLevelEncoding" is selected an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherLevelEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@linkRole

Link Role

Summary

A URI that characterizes the nature of the remote resource to which a linking element refers.

Description and Usage

A URI that characterizes, next to [@href](#), the nature of the remote resource to which a linking element refers. Optionally available in [<contactLine>](#) , [<findAidDesc>](#) , [<reference>](#) , and [<source>](#) . Being of type "anyURI", [@linkRole](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@linkRole](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

See [<findAidDesc>](#) encoding
[Table of Contents](#)

@linkTitle

Link Title

Summary

Viewable caption of a link text.

Description and Usage

Information that serves as a viewable caption which explains to users the part that a remote resource plays in a link. May be used alongside any [@href](#) attribute in order to support accessibility guidelines, such as those defined within the W3C's Web Content Accessibility Guidelines (WCAG). Optionally available in [<contactLine>](#) , [<findAidDesc>](#) , [<reference>](#) , and [<source>](#) .

Data Type

token

Examples

See [<findAidDesc>](#) encoding
[Table of Contents](#)

@localType

Local Type

Summary

This optional attribute provides a means to narrow the semantics of an element, or provide semantics for elements that are primarily structural or semantically weak.

Description and Usage

The value of [@localType](#) may be from a local or generally used external vocabulary. While the value of [@localType](#) may be any string, to facilitate exchange of data, it is recommended that the value be either the URI or the preferred label for a term defined in a formal vocabulary (e.g., SKOS), which is identified by an absolute URI, and is resolvable to a web resource that describes the semantic scope and use of the value. Local conventions or controlled vocabularies used in [@localType](#) may be declared in [<localTypeDeclaration>](#) within [<control>](#) . [@localTypeDeclarationReference](#) should always be used alongside [@localType](#) to provide a direct link to the [<localTypeDeclaration>](#) .

Data Type

token

Examples

See [<archDesc>](#) , [<findAidDesc>](#) , and [<identificationData>](#) encoding [Table of Contents](#)

@localTypeDeclarationReference

Local Type Declaration Reference

Summary

Use [@localTypeDeclarationReference](#) to provide a direct link to a [<localTypeDeclaration>](#) element within [<control>](#) from another element within the EAS instance using [@localType](#).

Description and Usage

[@localTypeDeclarationReference](#) should always be used when [@localType](#) is used, in order to link to the local type declaration.

Data Type

IDREFS

Examples

See [<archDesc>](#) , [<findAidDesc>](#) , and [<identificationData>](#) encoding
[Table of Contents](#)

@maintenanceEventReference

Maintenance Event Reference

Summary

Use [@maintenanceEventReference](#) to provide a direct link to a [<maintenanceEvent>](#) element within [<maintenanceHistory>](#) .

Description and Usage

The attribute can be used to link to a maintenance event in order to verify any assertion added to the entity's description. The attribute is optionally available in all elements that can contain text and are available outside of [<control>](#) .

Data Type

IDREFS

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@maintenanceEventType

Maintenance Event Type

Summary

An optional attribute of [< maintenanceEvent >](#) that identifies the type of maintenance activity.

Description and Usage

Identifies the type of maintenance event with values such as "created", "derived" or "updated". Use the attribute [@maintenanceEventTypeEncoding](#) in [< control >](#) to identify the list of authoritative terms that can be used as values of [@maintenanceEventType](#).

Data Type

token

Examples

See [< control >](#) encoding
[Table of Contents](#)

@maintenanceEventTypeEncoding

Maintenance Event Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of maintenance activity.

Description and Usage

[@maintenanceEventTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@maintenanceEventType](#) within [<maintenanceEvent>](#). If the value "EASList" is selected, [@maintenanceEventType](#) will be expected with the values "cancelled", "created", "deleted", "derived", "revised", "unknown", or "updated". If the value "otherMaintenanceEventTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#). This optional attribute is available only in [<control>](#).

Values

EASList, otherMaintenanceEventTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@maintenanceStatus

Maintenance Status

Summary

The current drafting status of the EAS instance.

Description and Usage

The maintenance status may occur on [<control>](#) . As an EAS instance is modified or other events happen to it (as recorded in the [<maintenanceHistory>](#) element), the maintenance status should also be updated to reflect the current drafting status. On first creation the status would e.g. be "new", which on revision could be changed to "revised". Use the attribute [@maintenanceStatusEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@maintenanceStatus](#).

Data Type

See [<control>](#) encoding
[Table of Contents](#)

@maintenanceStatusEncoding

Maintenance Status Encoding

Summary

Specifies the authoritative source or rules for values used to indicate the current version status of the EAS instance.

Description and Usage

[@maintenanceStatusEncoding](#) specifies the authoritative source or rules for values supplied in [@maintenanceStatus](#) within [<control>](#) . If the value "EASList" is selected, [@maintenanceStatus](#) will be expected with the values "cancelled", "deleted", "deletedMerged", "deletedReplaced", "deletedSplit", "derived", "new", or "revised". If the value "otherMaintenanceStatusEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherMaintenanceStatusEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@normalizedForm

Normalized Form

Summary

A standardized form of the content of [<referringString>](#) that is in uncontrolled or natural language.

Description and Usage

Use [@normalizedForm](#) to provide a standardized form, usually from a controlled vocabulary list, of the content of [<referringString>](#) e.g. to facilitate retrieval.

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@notAfter

Not After

Summary

A standard numerical form of an approximate date for which a latest possible date is known.

Description and Usage

Optionally available in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) . It is recommended that [@notAfter](#) values follow ISO 8601 or another standard date format as specified in [@dateEncoding](#).

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@notBefore

Not Before

Summary

A standard numerical form of an approximate date for which an earliest possible date is known.

Description and Usage

Optionally available in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) . It is recommended that [@notBefore](#) values follow ISO 8601 or another standard date format as specified in [@dateEncoding](#).

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@placeType

Place Type

Summary

An optional attribute of [<place>](#) that specifies the type of the geographic feature or location being described.

Description and Usage

Use [@placeType](#) with [<place>](#) to specify the type of geographic feature or location being described. Use the attribute [@placeTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@placeType](#).

Data Type

token

[Table of Contents](#)

@placeTypeEncoding

Place Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of geographic feature or location.

Description and Usage

[@placeTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@placeType](#) within [<place>](#) . If the value "EASList" is selected, [@placeType](#) will be expected with the values "administrativeDivision", "area", "bodyOfWater", "landElevation", "populatedPlace", "roadOrRailroad", "spot", "undersea", "vegetation". If the value "otherPlaceTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherPlaceTypeEncoding

Examples

See [<control>](#) encoding

[Table of Contents](#)

@publicationStatus

Publication Status

Summary

The current publication status of the EAS instance.

Description and Usage

The publication status may occur on [<control>](#) to indicate the current publication status of the EAS instance, for example "inProcess", "approved" or "published". As an EAS instance is modified or other events happen to it (as recorded in the [<maintenanceHistory>](#) element), the publication status should also be updated. Use the attribute [@publicationStatusEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@publicationStatus](#).

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@publicationStatusEncoding

Publication Status Encoding

Summary

Specifies the authoritative source or rules for values used to indicate the current publishing status of the EAS instance.

Description and Usage

[@publicationStatusEncoding](#) specifies the authoritative source or rules for values supplied in [@publicationStatus](#) within [<control>](#) . If the value "EASList" is selected, [@publicationStatus](#) will be expected with the values "approved", "inProcess", or "published". If the value "otherPublicationStatusEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherPublicationStatusEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@referredEntityRelationship

Referred Entity Relationship

Summary

An optional attribute of [<referringString>](#) that specifies the relationship between the entity named in a narrative text and the entity being described in the EAS instance.

Description and Usage

Use [@referredEntityRelationship](#) with [<referringString>](#) to specify the relationship between the entity named in a narrative text and the entity being described in the EAS instance. While [@referredEntityRelationship](#) does not come with a set of predefined values, it is highly recommended to use terms from controlled vocabularies whenever possible.

Data Type

token

[Table of Contents](#)

@referredEntityType

Referrered Entity Type

Summary

An optional attribute of [<referringString>](#) that specifies the type of entity named in a narrative text.

Description and Usage

Use [@referredEntityType](#) with [<referringString>](#) to specify the type of entity named in a narrative text. Use the attribute [@referredEntityTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@referredEntityType](#).

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@referredEntityTypeEncoding

Referred Entity Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of entity that is being referred to in a narrative text.

Description and Usage

[@referredEntityTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@referredEntityType](#) within [<referringString>](#) . If the value "EASList" is selected, [@referredEntityType](#) will be expected with the values "corpName", "famName", "function", "genreForm", "geogName", "name", "occupation", "persName", "subject" or "title". If the value "otherReferredEntityTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherReferredEntityTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@relationType

Relation Type

Summary

An optional attribute of [<relation>](#) that specifies the type of relation between the related entity and the entity being described in the EAS instance.

Description and Usage

Use [@relationType](#) with [<relation>](#) to specify the type of relation between the related entity and the entity being described in the EAS instance. Use the attribute [@relationTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@relationType](#).

Data Type

token

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@relationTypeEncoding

Relation Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of relation between the related entity and the entity being described in the EAS instance.

Description and Usage

[@relationTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@relationType](#) within [<relation>](#) . If the value "EASList" is selected, [@relationType](#) will be expected with the values "...". If the value "otherRelationTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherRelationTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@repositoryCode

Repository Code

Summary

A code in [<unitId>](#) that uniquely identifies the repository responsible for intellectual control of the materials being described.

Description and Usage

Use [@repositoryCode](#) in [<unitId>](#) to provide a number or code that uniquely identifies the repository responsible for intellectual control of the materials being described. The code should be taken from ISO/DIS 15511 Information and documentation—International Standard Identifier for Libraries and Related Organizations (ISIL), or another code as specified in [@repositoryEncoding](#) in [<control>](#) .

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@repositoryEncoding

Repository Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the maintenance agency of an EAS instance or the institution holding the materials being described.

Description and Usage

[@repositoryEncoding](#) specifies the authoritative source or rules for values used within [<agencyCode>](#) and supplied in [@repositoryCode](#) within [<unitId>](#). This can either be the ISO standard 15511 or an alternative code list. If the value "otherRepositoryEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#). This optional attribute is available only in [<control>](#).

Values

iso15511, otherRepositoryEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@scriptCode

Script Code

Summary

The code for the writing system, or script, used in the EAS instance or by the described entity or records.

Description and Usage

Content of the attribute should be a code taken from ISO 15924, or another controlled list, as specified in the [@scriptEncoding](#) attribute in [<control>](#) . Optionally available in [<languageDeclaration>](#) and [<writingSystem>](#) .

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@scriptEncoding

Script Encoding

Summary

Specifies the authoritative source or rules for codes used to identify the writing system of the EAS instance as a whole or, of a specific element, or represented in the materials being described.

Description and Usage

[@scriptEncoding](#) specifies the authoritative source or rules for values supplied in [@scriptCode](#) within [<languageDeclaration>](#) and [<writingSystem>](#) and in [@scriptOfElement](#) available in all non-empty elements. This can either be the ISO standard 15924 or an alternative code list. If the value "otherScriptEncoding" is selected, such an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

iso15924, otherScriptEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@scriptOfElement

Script of Element

Summary

Indicates the writing script of the content of an element (e.g., Cyrillic, Katakana).

Description and Usage

Content should be taken from ISO 15924, or another controlled list, as specified in the [@scriptEncoding](#) attribute in [<control>](#) . May be used consistently in a multi-lingual EAS instance to specify which elements are written in which script. Optionally available on all non-empty elements.

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@sourceReference

Source Reference

Summary

Use [@sourceReference](#) to provide a direct link to a [<source>](#) element within [<sources>](#) in [<control>](#) from an element within the EAS instance that uses the source.

Description and Usage

The attribute can be used to link any detailed information about the described entity to a source. The attribute is optionally available in elements which can contain text.

Data Type

IDREFS

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@standardDate

Standard Date

Summary

The standardized form of date.

Description and Usage

The standardized form of date expressed in [<date>](#) , [<fromDate>](#) , and [<toDate>](#) . It is recommended that [@standardDate](#) values follow ISO 8601, for example, 2011-07-22, 1963, or 1912-11, or another standard date format as specified in [@dateEncoding](#).

Data Type

token

Examples

See [<archDesc>](#) and [<identificationData>](#) encoding
[Table of Contents](#)

@standardDateTime

Standard Date and Time

Summary

Standardized form of a date, or date and time in [<eventDateTime>](#) .

Description and Usage

An ISO 8601 compliant form of the date, or date and time, of a specific maintenance event expressed in [<eventDateTime>](#) . For example, 2021-12-31, 2021, 2021-12, 2021-12-31T23:59:59. Optionally available only in [<eventDateTime>](#) . It is recommended to either have the date and time stated as a literal in [<eventDateTime>](#) or to provide a standardized date with [@standardDateTime](#), if not using both options in parallel. Note that the requirement of ISO 8601 compliance for [@standardDateTime](#) is different from the usage of the attribute [@standardDate](#), which can also follow other date encoding rules as specified in [@dateEncoding](#) within [<control>](#) .

Data Type

Constrained to the following patterns: YYYY-MM-DD, YYYY-MM, YYYY, or YYYY-MM-DDThh:mm:ss [with optional timezone offset from UTC in the form of [+|-][hh:mm], or "Z" to indicate the dateTime is UTC. No timezone implies the dateTime is UTC.]

Examples

See [<control>](#) encoding
[Table of Contents](#)

@status

Status

Summary

Attribute that follows controlled terminology detailing the status of elements.

Description and Usage

[@status](#) provides controlled terminology detailing the status of specific elements. The terms available for [@status](#) are defined in closed lists that can vary by element. Use [@statusEncoding](#) in [<control>](#) to identify lists of terms from EAS lists that can be used as values of [@status](#). It is also possible to define one's own list by using the value "otherStatusEncoding". Optionally available in [<agencyCode>](#) , [<otherAgencyCode>](#) , [<date>](#) , [<fromDate>](#) , [<toDate>](#) , [<textualDate>](#) .

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@statusEncoding

Status Encoding

Summary

The authoritative source or rules for values supplied in [@status](#).

Summary

Specifies the authoritative source or rules for values used to indicate the status and certainty of the information provided in various elements.

Description and Usage

[@statusEncoding](#) specifies the authoritative source or rules for values supplied in [@status](#) within [<agencyCode>](#) , [<otherAgencyCode>](#) , [<date>](#) , [<fromDate>](#) , [<toDate>](#) , and [<textualDate>](#) . If the value "EASList" is selected, [@status](#) will be expected with the values "authorized" and "alternative" (for agency codes), "unknown" or "ongoing" (for dates). If the value "otherStatusEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherStatusEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@style

Style

Summary

Used to specify a rendering style for a string. It is recommended that the value conforms to W3C CSS.

Description and Usage

The [@style](#) attribute may occur on [](#) to indicate rendering instructions. It is highly recommended that the value of [@style](#) be expressed as a W3C CSS style to facilitate interoperability. Additionally, [@style](#) may occur on [<title>](#) .

Data Type

normalizedString

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@target

Target

Summary

A pointer to the ID of another element.

Description and Usage

Used to create internal links within an XML instance. Optionally available in all elements except the root element.

Data Type

IDREFS

Examples

See [<archDesc>](#) encoding
[Table of Contents](#)

@targetType

Target Type

Summary

Identifies the type of entity related to the entity or records being described.

Description and Usage

An optional attribute of [<relation>](#) that specifies the type of entity that is related to the entity or records being described. Use the attribute [@targetTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@targetType](#).

Data Type

token

[Table of Contents](#)

@targetTypeEncoding

Target Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of related entity.

Description and Usage

[@targetTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@targetType](#) within [<relation>](#) . If the value "EASList" is selected, [@targetType](#) will be expected with the values "corporateBody", "family", "function", "group", "instantiation", "mechanism", "person", "place", "position", "record", "recordSet", "recordPart", or "resource". If the value "otherTargetTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherTargetTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@unit

Unit

Summary

Defines the format or unit specified in [<citedRange>](#) .

Description and Usage

Use [@unit](#) to document the format or unit that is specified in [<citedRange>](#) , for example page number ("pageNumber") or volume number ("volumeNumber").

Data Type

token

Examples

See [<control>](#) encoding
[Table of Contents](#)

@unitDateType

Unit Date Type

Summary

Identifies the type of date expressed in [<unitDate>](#) .

Description and Usage

Use [@unitDateType](#) with [<unitDate>](#) to specify the nature of the dates mentioned, e.g. "bulk" or "inclusive". Use the attribute [@unitDateTypeEncoding](#) in [<control>](#) to identify the list of authoritative terms that can be used as values of [@unitDateType](#).

Data Type

token

Examples

See [<identificationData>](#) encoding
[Table of Contents](#)

@unitDateTypeEncoding

Unit Date Type Encoding

Summary

Specifies the authoritative source or rules for values used to identify the type of date expressed.

Description and Usage

[@unitDateTypeEncoding](#) specifies the authoritative source or rules for values supplied in [@unitDateType](#) within [<unitDate>](#) . If the value "EASList" is selected, [@unitDateType](#) will be expected with the values "bulk" or "inclusive". If the value "otherUnitDateTypeEncoding" is selected, an alternate code list should be specified in [<conventionDeclaration>](#) . This optional attribute is available only in [<control>](#) .

Values

EASList, otherUnitDateTypeEncoding

Examples

See [<control>](#) encoding
[Table of Contents](#)

@valueURI

Value URI

Summary

An attribute for including a URI identifying the resource to be used as the element's value.

Description and Usage

Use the optional [@valueURI](#) attribute to provide the URI identifying the authority resource to be used as the element's content. Available in all elements that can contain any type of entity. Being of type "anyURI", [@valueURI](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@valueURI](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

See [<archDesc>](#) , [<control>](#) , [<findAidDesc>](#) , and [<identificationData>](#) encoding

[Table of Contents](#)

@vocabularySource

Vocabulary Source

Summary

An attribute for identifying a vocabulary that is the source of the element's value.

Description and Usage

Use the optional [@vocabularySource](#) attribute to provide a name or title of the authority or vocabulary source of the element's content. Available in all elements that can contain any type of entity.

Data Type

token

Examples

See [<archDesc>](#) , [<control>](#) , [<findAidDesc>](#) , and [<identificationData>](#) encoding
[Table of Contents](#)

@vocabularySourceURI

Vocabulary Source URI

Summary

An optional attribute for including a URI identifying the vocabulary source for the element's value.

Description and Usage

Use the optional attribute to provide the URI of the authority or vocabulary source given in [@vocabularySource](#). Available in all elements that can contain any type of entity. Being of type "anyURI", [@vocabularySourceURI](#) is meant to point to any dereferencable resource. The term resource is used in a general sense and includes, but is not limited to, electronic documents, images, services (e.g. an HTTP-to-SMS gateway), collections of other resources, etc. A resource is not necessarily accessible via the Internet, i.e. not every URI is a URL, and abstract concepts can be resources too, such as the operators and operands of a mathematical equation or numeric values (e.g., zero, one, and infinity). While the use of complete URIs is recommended, it is also possible to use relative references in [@vocabularySourceURI](#), e.g. only consisting of a string of numbers.

Data Type

anyURI

Examples

See [<control> encoding](#)
[Table of Contents](#)

Appendix :

Examples

archDesc

```
<archDesc level="fonds" localType="inventory"
  localTypeDeclarationReference="EADTypes">
  <identificationData>
    <unitTitle languageOfElement="nl"
      scriptOfElement="Latn">Nederlandsche Gist- en Spiritusfabriek
      en Pharmaceutische Fabrieken voorheen Brocades-Stheeman &
      Pharmacia, in 1967 gefuseerd tot Gist-Brocades</unitTitle>
    </identificationData>
    <agents>
      <agent agentType="group" valueURI="http://id.loc.gov/
      authorities/names/n80049704" vocabularySource="LCNAF">
        <label>National Association for the Advancement of
        Colored People</label>
        <role>Creator</role>
      </agent>
      <agent agentType="corporateBody" valueURI="http://
      id.loc.gov/authorities/names/n78089035" vocabularySource="LCNAF">
        <label>Library of Congress</label>
        <role>holdingInstitution</role>
      </agent>
      <agent>
        <label>Schweizerisches Bundesarchiv</label>
        <placeName target="place1">Bern</placeName>
        <role>holdingInstitution</role>
      </agent>
    </agents>
    <formsAvailable>
      <formAvailable formAvailableType="digitalOriginal"
      coverage="whole">
        <label>Photographs</label>
        <physicalDescription>
          <extent coverage="part" extentType="spaceOccupied"
          id="ext1" target="ext2 ext3">
            <quantity>650</quantity>
            <unitOfMeasurement>gigabytes</unitOfMeasurement>
          </extent>
        </physicalDescription>
        <physicalDescription>
          <extent coverage="part" extentType="carrier"
          id="ext2" target="ext1 ext3">
            <quantity>1</quantity>
            <unitOfMeasurement>hard disk</unitOfMeasurement>
            <descriptiveNote>
              <p>Password protected</p>
            </descriptiveNote>
          </extent>
        </physicalDescription>
        <physicalDescription>
```

```

        <extent coverage="part" extentType="materialType"
id="ext3" target="ext1 ext2">
        <quantity>7,500</quantity>
        <unitOfMeasurement>electronic files</
unitOfMeasurement>
        </extent>
        <physicalFacet valueURI="http://vocab.getty.edu/
page/aat/300391245" vocabularySource="AAT">>false-color infrared
photography</physicalFacet>
        </physicalDescription>
    </formAvailable>
    <formAvailable formAvailableType="analogDerived"
coverage="part">
        <label>Prints</label>
        <physicalDescription>
            <extent coverage="whole" extentType="materialType">
                <quantity>50</quantity>
                <unitOfMeasurement valueURI="http://
vocab.getty.edu/page/aat/300053443" vocabularySource="AAT">Aerial
photographs</unitOfMeasurement>
            </extent>
            <dimensions>
                <quantity>30 x 40</quantity>
                <unitOfMeasurement>cm</unitOfMeasurement>
            </dimensions>
        </physicalDescription>
    </formAvailable>
    <formAvailable valueURI="https://
collections.library.yale.edu/catalog/2008313" coverage="whole"
formAvailableType="digitalDerived">
        <label>The Pippa and Porthos</label>
        <formAvailableId valueURI="https://
collections.library.yale.edu/iiiif/2/1044151/full/full/0/
default.jpg">
            The Pippa and Porthos (cover)
        </formAvailableId>
        <formAvailableId valueURI="https://
collections.library.yale.edu/iiiif/2/1044153/full/full/0/
default.jpg">
            The Pippa and Porthos (titlepage)
        </formAvailableId>
        <formAvailableId valueURI="https://
collections.library.yale.edu/iiiif/2/1044154/full/full/0/
default.jpg">
            The Pippa and Porthos (p. 1)
        </formAvailableId>
    </formAvailable>
    <formAvailable>
        <label>Born digital archives (audiovisual)</label>
        <physicalDescription>
            <extent>
                <quantity>3</quantity>
                <unitOfMeasurement>MP4 files</unitOfMeasurement>
            </extent>
            <physicalFacet localType="technique"
localTypeDeclarationReference="physicalFacets">
                video

```



```

        </physicalFacet>
        <descriptiveNote>
            <p>Detailed technical metadata imported from
SEDA schema.</p>
            <objectXMLWrap>
                <seda:DataObjectGroup
id="aebaaaaaaiahioegaabzdoamtvkrlrwyaaaam">
                    <seda:BinaryDataObject
id="aeaaaaaaaahioegaabzdoamtvkrlrwqaaabq">

                        <seda:DataObjectVersion>BinaryMaster_1</seda:DataObjectVersion>
                        <seda:Uri>Content/
aeaaaaaaaahioegaabzdoamtvkrlrwqaaabq.mp3</seda:Uri>
                        <seda:MessageDigest
algorithm="SHA-512">

a6a34cf4fd36ff3bc9bdda6923f2380a80f4b015e905cae7ceff095ce4824705a682cb345c44e28f364.
                        </seda:MessageDigest>
                        <seda:Size>395736405</seda:Size>
                        <seda:FormatIdentification>
                            <seda:FormatLitteral>MPEG 1/2
Audio Layer 3</seda:FormatLitteral>
                            <seda:MimeType>audio/mpeg</
seda:MimeType>
                            <seda:FormatId>fmt/134</
seda:FormatId>
                                </seda:FormatIdentification>
                                <seda:FileInfo>
                                    <seda:Filename>vlc-
record-12h00m41s-1ere partie _ 5_juillet_2016.MP3-.mp3</
seda:Filename>

                                <seda:LastModified>2016-07-08T10:50:29.021</seda:LastModified>
                                </seda:FileInfo>
                                </seda:BinaryDataObject>
                            </seda:DataObjectGroup>
                        </objectXMLWrap>
                    </descriptiveNote>
                </physicalDescription>
            </formAvailable>
        </formsAvailable>
        <functions>
            <function vocabularySource="AAT" valueURI="http://
vocab.getty.edu/page/aat/300137609" functionType="function">
                <label>Legislating</label>
            </function>
            <function vocabularySource="AAT" valueURI="http://
vocab.getty.edu/page/aat/300138095" functionType="subfunction">
                <label>Law enforcing</label>
            </function>
            <function vocabularySource="AAT" valueURI="http://
vocab.getty.edu/page/aat/300137796" functionType="subfunction">
                <label>Convicting</label>
            </function>
        </functions>
        <places>
            <place>

```

```

        <label languageOfElement="en">Royal Court, Stockholm</
label>
        <address>
            <addressLine languageOfElement="se">Kungl.
Hovstaterna</addressLine>
            <addressLine languageOfElement="se">Kungl. Slottet</
addressLine>
            <addressLine addressLineType="postalCode">10770</
addressLine>
            <addressLine languageOfElement="se"
addressLineType="municipality">
                Stockholm
            </addressLine>
        </address>
        <contact>
            <contactLine contactLineType="phoneNumber">08-402 60
00</contactLine>
            <contactLine languageOfElement="se"
contactLineType="homepage">
                https://
www.kungahuset.se/2.1c3432a100d8991c5b80001816.html
            </contactLine>
            <contactLine languageOfElement="en"
contactLineType="homepage">
                https://www.kungahuset.se/
royalcourt.4.367010ad11497db6cba800054503.html
            </contactLine>
        </contact>
        <geographicCoordinates coordinateSystem="mgrs">34V VF
23840 65720</geographicCoordinates>
        <geographicCoordinates
coordinateSystem="WGS84">59.3268871784808, 18.07163893373358</
geographicCoordinates>
    </place>
    <place id="place1">
        <label>Bern</label>
        <role>Place of storage</role>
        <address>
            <addressLine addressLineType="street">Archivstrasse
24</addressLine>
            <addressLine addressLineType="postalCode">3005</
addressLine>
            <addressLine addressLineType="municipality">Bern</
addressLine>
        </address>
    </place>
</places>
<accessConditions>
    <p>University records are public records and once fully
processed are generally open to research use. Records that contain
personally identifiable information will be closed to protect
individual privacy. The closure of university records is subject to
compliance with applicable laws.</p>
</accessConditions>
    <accessConditions valueURI="https://www.wikidata.org/wiki/
Q232932">
        <p>Open access</p>

```

```

</accessConditions>
<accruals>
  <p>Noncurrent additions to this Record Group are transferred
from the Development Department annually at the end of the fiscal
year in June.</p>
</accruals>
<accruals maintenanceEventReference="revision2025">
  <formattingExtension>
    <xhtml:div>
      <xhtml:h3>Agreement on digital transfers</xhtml:h3>
      <xhtml:p>All transfers of records dating from 1999
and later will happen in digital form only. Regular transfers have
been agreed in intervals of three years at the end of the fiscal
year. Following the Public Records Act 2023, these transfers will
include all records that are - by then - older than 25 years, plus
potentially younger records that the Office of the Governor of
Queensland has deemed of permanent value and wishes to transfer
early.</xhtml:p>
      <xhtml:h4>Planned digital transfers</xhtml:h4>
      <xhtml:p>Already planned transfers are scheduled
for:</xhtml:p>
      <xhtml:ul>
        <xhtml:li>June 2026</xhtml:li>
        <xhtml:li>June 2029</xhtml:li>
        <xhtml:li>June 2032</xhtml:li>
        <xhtml:li>June 2035</xhtml:li>
      </xhtml:ul>
    </xhtml:div>
  </formattingExtension>
</accruals>
<appraisal>
  <p>The records of the Mid-Ocean Dynamics Experiment came to
the Institute Archives in two accessions in 1980 and 1982. During
processing the collection was reduced from fifteen cubic feet to
four by discarding duplicate materials, financial records, and
publications not authored by MODE participants. Forty charts and
six inches of raw data presented the primary appraisal issues.
The raw data consisted of bulletins and reports referring to float
positions, moorings, isotherms, geostrophic velocity calculations,
ships' summaries, and work proposed and work carried out during
the MODE-I experiment. As this raw data was recapitulated in weekly
<referringString referredEntityType="publication">MODE Hot Line
Bulletins</referringString>, only a sampling was retained in the
collection. Also discarded were ten charts for which there were no
descriptions of indicated data points, nor were dates or test site
locations provided.</p>
  <p>The appraisal of this collection was carried out in
consultation with Robert Heinmiller, a research associate at Woods
Hole Oceanographic Institution during MODE.</p>
</appraisal>
<appraisal>
  <narrativeEvent>
    <date standardDate="1975">1975</date>
    <eventDescription>Appraisal provided by donor,
$12,500.</eventDescription>
  </narrativeEvent>
</narrativeEvent>

```

```

        <date standardDate="2008">2008</date>
        <eventDescription>Appraised for insurance purposes,
$15,750.</eventDescription>
    </narrativeEvent>
</appraisal>
<arrangement>
    <p>The filing system for the Braman Collection has been
kept substantially in its original form. That is, original folders
and their titles have been retained. The processor devised the
basic organization scheme for the collection and, where necessary,
reorganized the papers within the various component groups.</p>
</arrangement>
<arrangement>
    <formattingExtension>
        <xhtml:div>
            <xhtml:h3>Arrangement of the Collection</xhtml:h3>
            <xhtml:p>This collection is arranged in five groups
composed of twenty-five series followed by restricted and oversize
series:</xhtml:p>
            <xhtml:h4>Group I:</xhtml:h4>
            <xhtml:ul>
                <xhtml:li>Correspondence, 1891-1940
                    <xhtml:ul>
                        <xhtml:li>Incoming Correspondence
                            <xhtml:ul>
                                <xhtml:li>A-E</xhtml:li>
                                <xhtml:li>F-J</xhtml:li>
                                <xhtml:li>K-R</xhtml:li>
                                <xhtml:li>S-Z</xhtml:li>
                            </xhtml:ul>
                        </xhtml:li>
                        <xhtml:li>Outgoing Correspondence
                            <xhtml:ul>
                                <xhtml:li>A-E</xhtml:li>
                                <xhtml:li>F-J</xhtml:li>
                                <xhtml:li>K-R</xhtml:li>
                                <xhtml:li>S-Z</xhtml:li>
                            </xhtml:ul>
                        </xhtml:li>
                    </xhtml:ul>
                </xhtml:li>
                <xhtml:li>Administrative Files, 1913-1921</
xhtml:li>
                    <xhtml:li>Printed Matter, 1889-1936</xhtml:li>
                    <xhtml:li>Photographs, 1911-1935</xhtml:li>
                    <xhtml:li>Medals and Ribbons, undated</xhtml:li>
                </xhtml:ul>
            <xhtml:h4>Group II:</xhtml:h4>
            <xhtml:ul>
                <xhtml:li>Correspondence, 1877-1974</xhtml:li>
                <xhtml:li>Minutes, 1917-1972</xhtml:li>
                <xhtml:li>Addendum, 1912-1972</xhtml:li>
            </xhtml:ul>
            <xhtml:h4>Other series:</xhtml:h4>
            <xhtml:p>Restricted, 1889-1942</xhtml:p>
            <xhtml:p>Oversize, 1863-1999</xhtml:p>

```

```

        </xhtml:div>
    </formattingExtension>
</arrangement>
<biogHist>
    <abstract>Robert Carlton Brown II (June 14, 1886 - August 7,
1959) was an American writer and publisher in many forms from comic
squibs to magazine fiction to advertising to avant-garde poetry to
business news to cookbooks to political tracts to novelized memoirs
to parodies and much more.</abstract>
    <p> During 1918, Brown traveled extensively in Mexico
and Central America, writing for the U.S. Committee of Public
Information in Santiago de Chile. In 1919, he moved with his
wife, Rose Brown, to Rio de Janeiro, where they founded <span
style="font-style:italic"> Brazilian American</span>, a weekly
magazine that ran until 1929. With Brown's mother, Cora, the
Browns also established magazines in Mexico City and London: <span
style="font-style:italic">Mexican American</span> (1924-1929)
and <span style="font-style:italic">British American</span>
(1926-1929).</p>
</biogHist>
<biogHist>
    <formattingExtension>
        <xhtml:div xmlns:xhtml="http://www.w3.org/1999/xhtml
https://www.w3.org/2002/08/xhtml/xhtml1-strict.xsd">
            <xhtml:h4>Biography Johann Sebastian Bach</xhtml:h4>
            <xhtml:p>[...]</xhtml:p>
            <xhtml:h3>Family life</xhtml:h3>
            <p>Bach was married twice and had 20 children, 10 of
whom survived into adulthood.</p>
            <xhtml:ul>
                <xhtml:h4>Children of Johann Sebastian Bach and
Maria Barbara Bach</xhtml:h4>
                <xhtml:li>Catharina Dorothea Bach</xhtml:li>
                <xhtml:li>Wilhelm Friedemann Bach</xhtml:li>
                <xhtml:ul>
                    <xhtml:h5>Children of Wilhelm Friedemann
Bach</xhtml:h5>
                    <xhtml:li>Friederica Sophia Bach</xhtml:li>
                    <xhtml:li>Two sons who did not live past
infancy</xhtml:li>
                </xhtml:ul>
                <xhtml:li>Carl Philipp Emanuel Bach</xhtml:li>
                <xhtml:ul>
                    <xhtml:h5>Children of Carl Philipp Emanuel
Bach</xhtml:h5>
                    <xhtml:li>Johann Adam Bach</xhtml:li>
                    <xhtml:li>Anna Carolina Philippina Bach</
xhtml:li>
                    <xhtml:li>Johann Sebastian Bach ("the
Younger")</xhtml:li>
                    <xhtml:li>Other children who did not live to
adulthood</xhtml:li>
                </xhtml:ul>
                <xhtml:li>Johann Gottfried Bernhard Bach</
xhtml:li>
                <xhtml:li>Three more children who did not live
to their first birthday</xhtml:li>
            </xhtml:ul>
        </xhtml:div>
    </formattingExtension>
</biogHist>
</biogHist>
    </formattingExtension>
</xhtml:div>

```

```

        </xhtml:ul>
        <xhtml:ul>
            <xhtml:h4>Children of Johann Sebastian Bach and
Anna Magdalena Wilcken</xhtml:h4>
            <xhtml:li>Gottfried Heinrich Bach</xhtml:li>
            <xhtml:li>Johann Christoph Friedrich Bach</
xhtml:li>
                <xhtml:ul>
                    <xhtml:h5>Children of Johann Christoph
Friedrich Bach</xhtml:h5>
                    <xhtml:li>Anna Philippiana Friederica Bach</
xhtml:li>
                        <xhtml:li>Wilhelm Friedrich Ernst Bach</
xhtml:li>
                            <xhtml:ul>
                                <xhtml:h6>Children of Wilhelm Friedrich
Ernst Bach</xhtml:h6>
                                <xhtml:li>Carolina Auguste Wilhelmine
Bach</xhtml:li>
                                    <xhtml:li>Juliane Friederica Bach</
xhtml:li>
                                        </xhtml:ul>
                                <xhtml:li>Christine Luise Bach</xhtml:li>
                                </xhtml:ul>
                                <xhtml:li>Johann Christian Bach</xhtml:li>
                                <xhtml:li>Elisabeth Juliane Friederica Bach</
xhtml:li>
                                    <xhtml:ul>
                                        <xhtml:h5>Children of Elisabeth Juliane
Friederica Bach</xhtml:h5>
                                        <xhtml:li>Johann Sebastian Altnickol</
xhtml:li>
                                            </xhtml:ul>
                                        <xhtml:li>Johanna Carolina Bach</xhtml:li>
                                        <xhtml:li>Regina Susanna Bach</xhtml:li>
                                        <xhtml:li>Six more children who did not live to
adulthood</xhtml:li>
                                            </xhtml:ul>
                                        </xhtml:div>
                                    </formattingExtension>
                                </biogHist>
                                <biogHist>
                                    <p>Ilma Mary Brewer, nee Pidgeon, was Lecturer in Botany/
Biology, University of Sydney 1963-70 and Senior Lecturer in
Biological Sciences 1970-78. She developed new methods of teaching
based on the recognition that a student learnt more by working at
his/her own place and instruction him/her self. Her findings were
published as a book, "Learning More and Teaching Less."</p>
                                    <narrativeEvent>
                                        <date standardDate="1936">1936</date>
                                        <eventDescription>Bachelor of Science (BSc) completed at
the University of Sydney</eventDescription>
                                    </narrativeEvent>
                                    <narrativeEvent>
                                        <date standardDate="1937">1937</date>
                                        <eventDescription>Master of Science (MSc) completed at
the University of Sydney</eventDescription>

```

```

        </narrativeEvent>
        <narrativeEvent>
            <date standardDate="1937/1941">until 1941</date>
            <eventDescription>Linnean Macleay Fellow</
eventDescription>
        </narrativeEvent>
    </biogHist>
    <custodHist>
        <p>The George Franklin Papers were maintained by the staff
of the Mayor's Office, City of Irvine, California, in the records
storage facility at City Hall from the time of Franklin's death
in 1972 until they were transferred, at his family's request,
to Special Collections and Archives, The UC Irvine Libraries, in
1988.</p>
    </custodHist>
    <custodHist>
        <narrativeEvent>
            <date standardDate="1972">1972</date>
            <agent>
                <label>Mayor's Office</label>
            </agent>
            <placeName>Irvine, California</placeName>
            <eventDescription>Records are held by the Mayor's Office
from 1972 onwards.</eventDescription>
        </narrativeEvent>
        <narrativeEvent>
            <date standardDate="1988">1988</date>
            <agent>
                <label>The UC Irvine Libraries</label>
            </agent>
            <placeName>Irvine, California</placeName>
            <eventDescription>Records are held by the Special
Collections and Archives, The UC Irvine Libraries, from 1988
onwards.</eventDescription>
        </narrativeEvent>
        <narrativeEvent>
            <date standardDate="2009">2009</date>
            <agent>
                <label>Harry Ransom Center</label>
            </agent>
            <placeName>Austin, Texas</placeName>
            <eventDescription>Records are held by the Harry Ransom
Center since 2009.</eventDescription>
        </narrativeEvent>
    </custodHist>
    <custodHist>
        <formattingExtension>
            <xhtml:div>
                <xhtml:h3>Custodial History</xhtml:h3>
                <xhtml:p>Before being transferred to the University
Archives, the materials were:</xhtml:p>
                <xhtml:ul>
                    <xhtml:li>Held by faculty members</xhtml:li>
                    <xhtml:li>Collected by departmental secretaries
as informal archive</xhtml:li>
                </xhtml:ul>
            </xhtml:div>
        </formattingExtension>
    </custodHist>

```

```

        <xhtml:p>In 1989, the University Archives conducted
a Departmental Records Collection Initiative. Since then, the
records have been held by the University Archives.</xhtml:p>
    </xhtml:div>
</formattingExtension>
</custodHist>
<filePlan>
    <formattingExtension>
        <xhtml:div>
            <xhtml:h3>File List</xhtml:h3>
            <xhtml:p> The list below outlines the classification
system used for the central files of Vice President Mondale's
office. This structure assigned alpha-numeric codes to primary
subjects and to secondary and tertiary subdivisions thereunder.</
xhtml:p>
                <xhtml:h4>AGRICULTURE (AG)</xhtml:h4>
                <xhtml:ol>
                    <xhtml:li>Home Economics</xhtml:li>
                    <xhtml:li>Horticulture</xhtml:li>
                    <xhtml:li>Marketing</xhtml:li>
                    <xhtml:li>Price Support</xhtml:li>
                </xhtml:ol>
                <xhtml:h4>ARTS (AR)</xhtml:h4>
                <xhtml:ol>
                    <xhtml:li>Languages</xhtml:li>
                    <xhtml:li>Museums</xhtml:li>
                    <xhtml:li>Music</xhtml:li>
                </xhtml:ol>
                <xhtml:h4>URBAN PLANNING (UP)</xhtml:h4>
                <xhtml:ol>
                    <xhtml:li>Communications</xhtml:li>
                    <xhtml:li>Distribution Networks</xhtml:li>
                    <xhtml:li>Infrastructure</xhtml:li>
                    <xhtml:li>Public Welfare</xhtml:li>
                    <xhtml:li>Transportation</xhtml:li>
                </xhtml:ol>
            </xhtml:div>
        </formattingExtension>
    </filePlan>
    <otherDescription valueURI="https://agatha.arch.be/data/ead/BE-
A0518_104297_104557">
        <p languageOfElement="fr">L'inventaire est également
disponible en néerlandais.</p>
    </otherDescription>
    <otherDescription>
        <relations>
            <relation>
                <label languageOfElement="fr">Archives antérieurs à
1945, archives photographiques et audiovisuelles - Fonds d'archives
manuscrites</label>
                <role>Printed finding aid</role>
            </relation>
            <relation>
                <label valueURI="https://calames.abes.fr/pub/
#details?id=FR751142302-M001061">
                    Calames - Online catalogue of archives and
manuscripts in French University and Research libraries

```



```

        </label>
        <role>Online presentation</role>
    </relation>
    <relation>
        <label valueURI="https://francearchives.gouv.fr/fr/
facomponent/405d30ade8dd7535b1fbe03c231e175b1bd682b8.csv">
            CSV format on FranceArchives
        </label>
        <role>Download</role>
    </relation>
    <relation>
        <label valueURI="https://francearchives.gouv.fr/fr/
facomponent/405d30ade8dd7535b1fbe03c231e175b1bd682b8/rdf.xml">
            RDF/XML format on FranceArchives
        </label>
        <role>Download</role>
    </relation>
</relations>
</otherDescription>
<otherDescriptiveInfo>
    <formattingExtension>
        <xhtml:div>
            <xhtml:h3>Selected list of correspondents</xhtml:h3>
            <xhtml:p>All correspondence in the collection
is arranged chronologically. Following is a list of notable
correspondents, with dates.</xhtml:p>
            <xhtml:ul>
                <xhtml:li>Adams, Samuel
                    <xhtml:ul>
                        <xhtml:li>1870 Mar 3</xhtml:li>
                        <xhtml:li>1871 Jan 15</xhtml:li>
                    </xhtml:ul>
                </xhtml:li>
                <xhtml:li>Barlow, Christine
                    <xhtml:ul>
                        <xhtml:li>1872 Feb 15</xhtml:li>
                        <xhtml:li>1872 Nov 24</xhtml:li>
                    </xhtml:ul>
                </xhtml:li>
            </xhtml:ul>
        </xhtml:div>
    </formattingExtension>
</otherDescriptiveInfo>
<otherDescriptiveInfo>
    <p>There is no recorded notetaker on most minutes. Styles
vary from brief bullet points to longform notes.</p>
</otherDescriptiveInfo>
<preferCite>
    <p>[Identification of item], Arequipa Sanatorium Records,
BANC MSS 92/894c, The Bancroft Library, University of California,
Berkeley.</p>
</preferCite>
<processInfo>
    <p>Material was processed over several years.</p>
<narrativeEvent>
    <date>1982</date>

```

```

        <eventDescription>Correspondence processed.</
eventDescription>
    </narrativeEvent>
    <narrativeEvent>
        <date>1984</date>
        <eventDescription>Published material transferred to Rare
Books for cataloging.</eventDescription>
    </narrativeEvent>
    <narrativeEvent>
        <date>1989</date>
        <eventDescription>Processing completed, including
integration of 1986 and 1987 accessions.</eventDescription>
    </narrativeEvent>
</processInfo>
<publicationNote>
    <relations>
        <relation relationType="resourceRelation">
            <label>Charles Darwin, On the Origin of Species by
Means of Natural Selection, or the Preservation of Favoured Races
in the Struggle for Life (London, John Murray, 1859)</label>
            <role valueURI="https://www.ica.org/standards/
RiC/RiC-0_1-1.html#hasOrHadSubject" vocabularySource="RiC-0"
vocabularySourceURI="https://www.ica.org/standards/RiC/ontology">
hasOrHadSubject
            </role>
            <placeName countryCode="GB">London</placeName>
        </relation>
    </relations>
</publicationNote>
<publicationNote>
    <relations>
        <relation targetType="resource">
            <label>Mémorial du colonel Gustafsson. - 1829</
label>
        </relation>
        <relation>
            <label>Paris d'hier et d'aujourd'hui</label>
            <objectXMLWrap>
                <tei:bibl>
                    <tei:title>
                        <tei:emph rend="italic">Paris d'hier et
d'aujourd'hui</tei:emph>
                    </tei:title>
                    <tei:respStmt>
                        <tei:resp>photographes</tei:resp>
                        <tei:name>Roger Henrard</tei:name>
                        <tei:name>Yann Arthus-Bertrand</
tei:name>
                    </tei:respStmt>
                </tei:bibl>
            </objectXMLWrap>
        </relation>
    </relations>
    <p>See the following publication for background
information: <referringString referredEntityType="person"
normalizedForm="Bernier, Pierre-François (1779-1803)">P.-
F. BERNIER</referringString>, <referringString

```

```

referredEntityType="work">Études particulières</referringString></
p>
  </publicationNote>
  <recordTypeSpecificStatement>
    <p>Autograph conductor's full score (pencil), with
mimeographed conductor's short score of certain sections
interleaved. Selections, including deletions.</p>
  </recordTypeSpecificStatement>
  <recordTypeSpecificStatement>
    <objectXMLWrap>
      <mods:cartographics>
        <mods:scale>1:10000</mods:scale>
        <mods:projection>Universal Transverse Mercator
(UTM)</mods:projection>
      </mods:cartographics>
    </objectXMLWrap>
  </recordTypeSpecificStatement>
  <relatedMaterial>
    <abstract>Several genealogies and biographies of the
Smith family have been published and are held in the Rare Books
Department.</abstract>
    <relations>
      <relation relationType="https://www.ica.org/
standards/RiC/ontology#RecordResourceToRecordResourceRelation"
targetType="recordSet">
        <label valueURI="4569982" vocabularySource="Rare
Books Department">Kavanaugh, Carol. The Smith Family in Johnson
County (New York: Penguin)</label>
      </relation>
      <relation sourceReference="source1">
        <label valueURI="336712" vocabularySource="Rare
Books Department">Llewellyn, Gareth. Smythe, Smith: What's the
Difference? (London: Jonathan Cape)</label>
      </relation>
    </relations>
  </relatedMaterial>
  <scopeContent>
    <p>Fonds includes records relating to the Department of
Plant Ecology's administration, teaching and research; extension
work relating to the Saskatchewan Weed Survey; and correspondence
with a variety of institutions and individuals. A series of
minutes and correspondence relating to the Saskatchewan Committee
on the Ecology and Preservation of Grasslands (established in
1935) documents the efforts to establish permanent reserves of
significant grasslands in Saskatchewan.</p>
  </scopeContent>
  <scopeContent>
    <formattingExtension>
      <xhtml:div>
        <xhtml:p>Production score - excerpted reductions,
photostats:</xhtml:p>
        <xhtml:ul>
          <xhtml:li>PROD. #306 M:10 Main title / before
the fact</xhtml:li>
          <xhtml:li>PROD. #306 M:60 Melbeck's office /
before the fact</xhtml:li>

```

```

        <html:li>PROD. #306 M:74 Looking for Johnny /
before the fact</html:li>
        <html:li>PROD. #306 M:85 Lina alone / before
the fact</html:li>
        <html:li>PROD. #306 M:94 The morning mail /
before the fact</html:li>
        <html:li>PROD. #306 M:106 Too fast / before the
fact</html:li>
        <html:li>PROD. #306 M:74 Looking for Johnny /
before the fact</html:li>
    </html:ul>
</html:div>
</formattingExtension>
</scopeContent>
<separatedMaterial>
    <abstract>Other papers of Earl Warren, which relate chiefly
to his early years and public service in California, have been
deposited in the California State Archives in Sacramento.</
abstract>
    <relations>
        <relation>
            <label valueURI="https://oac.cdlib.org/findaid/
ark:/13030/tf4b69n6gc" vocabularySource="OAC">Earl Warren Papers,
1924-53</label>
        </relation>
    </relations>
</separatedMaterial>
<sourceOfAcquisition>
    <narrativeEvent>
        <date>1945</date>
        <eventDescription>Transfer from <referringString
referredEntityType="corporateBody" valueURI="http://id.loc.gov/
authorities/names/n79022809" vocabularySource="LCNAF">National
Park Service</referringString>, Accession number 45.22</
eventDescription>
    </narrativeEvent>
</sourceOfAcquisition>
<sourceOfAcquisition>
    <p>Source unknown. Originally deposited in University
Library, transferred to Department of Palaeography in 1958.</p>
</sourceOfAcquisition>
<subjectHeadings>
    <p>These records are indexed under the following headings
in the catalog of the Minnesota Historical Society. Researchers
wishing to find related materials should search the catalog under
these index terms.</p>
    <subject valueURI="http://id.loc.gov/authorities/subjects/
sh85048694" vocabularySource="LCSH">
        <term>Fishery law and legislation</term>
        <placeName>Minnesota</placeName>
    </subject>
    <subject valueURI="https://id.loc.gov/authorities/subjects/
sh85052932" vocabularySource="LCSH">
        <term>Game laws</term>
        <placeName>Minnesota</placeName>
    </subject>
</subjectHeadings>

```

```

    <useConditions>
      <p>Until 2055 permission to photocopy some materials from
this collection has been limited at the request of the donor.
Please ask repository staff for details if you are interested in
obtaining photocopies from Series 1: Correspondence.</p>
    </useConditions>
    <useConditions valueURI="https://rightsstatements.org/vocab/NoC-
NC/1.0/" vocabularySource="rightsStatements">
      <dateRange>
        <toDate standardDate="2030-05">May 2030</toDate>
      </dateRange>
      <p>Non-commercial use only</p>
      <p>While the records themselves are free of copyright,
they have been digitised in a public-private partnership as part
of which, the partners have agreed to limit commercial uses of
these digital representations by third parties until May 2053
including.</p>
    </useConditions>
  </archDesc>

```

control

```

<control coverageEncoding="EASList"
descriptionOfComponentsTypeEncoding="EASList"
extentTypeEncoding="EASList" formAvailableTypeEncoding="EASList"
functionTypeEncoding="EASList" levelEncoding="EASList"
unitDateTypeEncoding="EASList"
agentTypeEncoding="otherAgentTypeEncoding"
countryEncoding="iso3166-1-alpha-2" dateEncoding="iso8601"
languageEncoding="iso639-1" scriptEncoding="iso15924"
repositoryEncoding="iso15511" addressLineTypeEncoding="EASList"
audience="internal" audienceEncoding="EASList"
contactLineTypeEncoding="EASList" detailLevelEncoding="EASList"
detailLevel="extended" maintenanceEventTypeEncoding="EASList"
maintenanceStatusEncoding="EASList" maintenanceStatus="revised"
placeTypeEncoding="otherPlaceTypeEncoding"
publicationStatusEncoding="EASList" publicationStatus="approved"
referredEntityTypeEncoding="otherReferredEntityTypeEncoding"
relationTypeEncoding="otherRelationTypeEncoding"
targetTypeEncoding="EASList" statusEncoding="EASList">
  <recordId>F10219</recordId>
  <maintenanceAgency countryCode="IE">
    <agencyCode status="authorized">IE-NAI</agencyCode>
    <agencyName languageOfElement="en">National Archives of
Ireland</agencyName>
    <agencyName languageOfElement="ga">An Cartlann Náisiúnta na
hÉireann </agencyName>
    <otherAgencyCode status="alternative">NAI-CNE</
otherAgencyCode>
  </maintenanceAgency>
  <maintenanceHistory>
    <maintenanceEvent maintenanceEventType="derived">
      <agent agentType="prov:SoftwareAgent">
        <label>export.xsl/Saxon B9</label>
      </agent>
    </maintenanceEvent>
  </maintenanceHistory>
</control>

```

```

        <eventDateTime
standardDateTime="2021-08-30T09:37:17.029-04:00"/>
        <eventDescription>Derived from local collection
management system</eventDescription>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="updated">
        <agent>
            <label>Tanya Smith</label>
            <role>Archivist</role>
            <relationship
valueURI="https://www.ica.org/standards/RiC/
ontology#AuthorshipRelation"
vocabularySourceURI="https://www.ica.org/
standards/RiC/ontology"/>
        </agent>
        <eventDateTime standardDateTime="2021-09">September
2021</eventDateTime>
        <eventDescription>Editing the encoded archival
description with additional data not included in the export from
the local collection management system</eventDescription>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="revised">
        <agent>
            <label>T. Baker</label>
        </agent>
        <eventDateTime standardDateTime="2022-10">October 2022</
eventDateTime>
        <eventDescription>The archival description encoded
in this document has been reviewed and, where necessary, updated
following the <reference href="https://guides.library.yale.edu/
reparativearchivaldescription"> Reparative Archival Description
Working Group: Guiding Principles</reference>.</eventDescription>
    </maintenanceEvent>
    <maintenanceEvent>
        <agent>
            <label>Gregory Miller</label>
            <role>Volunteer</role>
            <relationship valueURI="https://
www.ica.org/standards/RiC/ontology#CreationRelation"
vocabularySourceURI="https://www.ica.org/standards/RiC/ontology"/>
        </agent>
        <eventDateTime standardDateTime="2023-05">May 2023</
eventDateTime>
        <eventDescription>Marking persons and organisations
named in narrative texts as part of a crowdsourcing project</
eventDescription>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="updated">
        <agent agentType="unknown">
            <label/>
        </agent>
        <eventDateTime standardDateTime="2024-11-27"/>
    </maintenanceEvent>
    <maintenanceEvent maintenanceEventType="revised"
id="revision2025">
        <agent agentType="person">
            <label>Marianne Cousteau</label>

```

```

        </agent>
        <eventDateTime>October 2025</eventDateTime>
    </maintenanceEvent>
</maintenanceHistory>
<sources>
    <source id="source1">
        <reference>R. Greene, S.Cushman (ed.): The Princeton
Handbook of World Poetries</reference>
    </source>
    <source id="source2" href="https://www.theguardian.com/
books/2018/aug/10/langston-hughes-born-a-year-before-accepted-date-
poet">
        <reference>Flood, Alison <referringString
referredEntityType="title">"Langston Hughes 'born a year before
accepted date', researcher finds,"</referringString> The Guardian.
Published 10 August 2018.</reference>
        <citedRange unit="page">11</citedRange>
        <descriptiveNote>
            <p>Poet researching archives of local African
American newspaper finds story reporting on 'little Langston'
before his recorded birth date.</p>
        </descriptiveNote>
    </source>
    <source>
        <reference href="https://de.wikipedia.org/wiki/
Gustav_IV._Adolf_(Schweden)" languageOfElement="de"> Wikipedia-Seite
zu Gustav IV. Adolf</reference>
    </source>
    <source href="https://sok.riksarkivet.se/sbl/
Presentation.aspx?id=13318">
        <reference languageOfElement="sv">Svenskt biografiskt
lexikon</reference>
        <descriptiveNote>
            <p languageOfElement="de">Stand: 03.12.2020</p>
        </descriptiveNote>
    </source>
    <source>
        <reference/>
        <objectXMLWrap>
            <tei:bibl>
                <tei:title>
                    <tei:emph rend="italic">Paris d'hier et
d'aujourd'hui</tei:emph>
                </tei:title>
                <tei:respStmt>
                    <tei:resp>photographes</tei:resp>
                    <tei:name>Roger Henrard</tei:name>
                    <tei:name>Yann Arthus-Bertrand</tei:name>
                </tei:respStmt>
            </tei:bibl>
        </objectXMLWrap>
    </source>
</sources>
<conventionDeclaration>
    <reference href="https://www.loc.gov/aba/rda/">Resource
Description and Access</reference>
    <shortCode>RDA</shortCode>

```

```

    </conventionDeclaration>
    <conventionDeclaration>
      <reference>Anglo-American Cataloging Rules, Revised</
reference>
      <shortCode>AACR2</shortCode>
    </conventionDeclaration>
    <conventionDeclaration id="administrativeRegions">
      <reference href="https://www.legifrance.gouv.fr/loda/id/
JORFTEXT000033553530/" languageOfElement="fr">
        Décret n°2016-1689 du 8 décembre 2016 fixant le nom, la
        composition et le chef-lieu des circonscriptions administratives
        régionales - Légifrance
      </reference>
    </conventionDeclaration>
    <conventionDeclaration id="localAuthorities">
      <reference href="https://cnig.gouv.fr/IMG/pdf/collectivites-
territoriales_cnt_10-decembre-2021.pdf" linkRole="document/pdf"
        languageOfElement="fr">
        Commission nationale de toponymie: Collectivités
        territoriales françaises
      </reference>
    </conventionDeclaration>
    <conventionDeclaration id="repositoryCode">
      <reference href="https://www.rara.ee/wp-content/uploads/
koik_koodid_22.04.2025.csv">
        Kataloogimiskohad
      </reference>
      <descriptiveNote>
        <p languageOfElement="et">Kataloogimiskohad (välja
        andnud Eesti Rahvusraamatukogu)</p>
        <p>Cataloguing Source Codes (issued by the National
        Library of Estonia)</p>
      </descriptiveNote>
    </conventionDeclaration>
    <conventionDeclaration id="agentType">
      <reference href="https://www.w3.org/TR/2013/REC-prov-
dm-20130430/#term-agent">
        PROV-DM agent types
      </reference>
    </conventionDeclaration>
    <conventionDeclaration id="placeType">
      <reference>Geographic Association Place Types</reference>
      <descriptiveNote>
        <p>The Geographic Association uses its own, in-house
        classification systems for types of places. At the moment, this is
        an internal document that is not available online.</p>
      </descriptiveNote>
    </conventionDeclaration>
    <conventionDeclaration id="entityType">
      <reference>List of entity types (referrals)</reference>
    </conventionDeclaration>
    <conventionDeclaration id="relationType">
      <reference href="https://www.ica.org/standards/RiC/
ontology">
        Records in Contexts Ontology - Relationships properties
      </reference>
      <shortCode>RiC-0</shortCode>

```



```

</conventionDeclaration>
<languageDeclaration languageCode="en" scriptCode="Latn"/>
<languageDeclaration languageCode="el" scriptCode="Grek">
  <descriptiveNote>
    <p>This finding aid's main descriptive language is
English. Parts of the finding aid that describe materials related
to the Embassy in Greece additionally include a small set of
elements using Greek as the descriptive language.</p>
  </descriptiveNote>
</languageDeclaration>
<localTypeDeclaration id="containers">
  <reference>List of values to identify types of containers</
reference>
  <shortCode>ContainerTypes</shortCode>
</localTypeDeclaration>
<localTypeDeclaration id="identifiers">
  <reference href="https://example.org/value-lists/
identifiers.xml">
    List of values to identify types of identifiers
  </reference>
  <descriptiveNote>
    <p>The list of types of identifiers has been defined
in the context of the "Our history", where it was used to identify
records, record versions and record enrichments depending on their
source and provenance.</p>
  </descriptiveNote>
</localTypeDeclaration>
<otherRecordId valueURI="https://pares.mcu.es/ParesBusquedas20/
catalogo/autoridad/140149" vocabularySource="PARES">140149</
otherRecordId>
<otherRecordId localType="original"
localTypeDeclarationReference="identifiers">AUBT-ISAAR-C-002</
otherRecordId>
<rightsDeclaration>
  <reference href="https://creativecommons.org/publicdomain/
zero/1.0/deed.de">Creative Commons CC0 1.0 Universal (CC0 1.0)
Public Domain Dedication</reference>
  <shortCode>CC0 1.0</shortCode>
  <descriptiveNote>
    <p>All existing copyrights and related rights to this
finding aid have been waived and the finding aid is licensed under
the CC0 1.0 Universal (CC0 1.0) Public Domain Dedication. This
means, you can copy, modify, and distribute this finding aid, even
for commercial purposes, all without asking permission.</p>
  </descriptiveNote>
</rightsDeclaration>
</control>

```

findAidDesc

```

<findAidDesc href="https://archives.piecemaking.edu/finding-
aids/quilting-technologies-department/quilting-technologies-
department.xml" linkTitle="Download the encoded finding aid (XML)"
linkRole="text/xml">

```

```

<title localType="mainTitle"
localTypeDeclarationReference="titles">
  <part>Guide to Quilting Technologies Department Records,
1978-2020</part>
  <part localType="edition"
localTypeDeclarationReference="titles">2nd edition</part>
</title>
<title localType="subtitle"
localTypeDeclarationReference="titles">
  <part>A guide to the records of the Quilting Technologies
Department at Piecemaking University</part>
</title>
<title localType="seriesTitle"
localTypeDeclarationReference="titles">
  <part>Piecemaking University Departmental Records, 13</part>
</title>
<agent agentType="person">
  <label>Ruth Tillman</label>
  <role valueURI="aut" vocabularySource="MARC Code List for
Relators">Author</role>
</agent>
<agent agentType="prov:Organization"
conventionDeclarationReference="agentType">
  <label>National Alliance of Peace Quilters</label>
  <role valueURI="spn" vocabularySource="MARC Code List for
Relators">Sponsor</role>
  <descriptiveNote>
    <p>Funding for the initial creation of this electronic
finding aid was made possible in 1992 by a generous gift of the
National Alliance of Peace Quilters.</p>
  </descriptiveNote>
</agent>
<agent agentType="prov:Organization"
conventionDeclarationReference="agentType">
  <label>Piecemaking University</label>
  <role valueURI="pbl" vocabularySource="MARC Code List for
Relators">Publisher</role>
  <role valueURI="spn" vocabularySource="MARC Code List for
Relators">Sponsor</role>
  <descriptiveNote>
    <p>Funding for encoding was made possible in 2008 by a
Piecemaking University Digital Initiatives Grant.</p>
  </descriptiveNote>
</agent>
<date standardDate="2020-06-08">June 8, 2020</date>
<place>
  <label>Lancaster, Pennsylvania</label>
  <address>
    <addressLine>University Archives</addressLine>
    <addressLine>Piecemaking University</addressLine>
    <addressLine>Lancaster, PA 17603</addressLine>
  </address>
  <contact>
    <contactLine contactLineType="phoneNumber">
+1-717-555-1313</contactLine>
    <contactLine
contactLineType="email">archivist@piecemaking.edu</contactLine>

```

```

        </contact>
    </place>
    <formattingExtension>
        <xhtml:div>
            <xhtml:p>Edition was updated during EAD3 encoding to
conform to DACS standards.</xhtml:p>
            <xhtml:p>To submit corrections or request
clarifications, please use the <xhtml:a href="https://
archives.piecemaking.edu/contact/finding-aid-feedback"> University
Archives' feedback form</xhtml:a>.</xhtml:p>
        </xhtml:div>
    </formattingExtension>
</findAidDesc>
<findAidDesc href="https://archives.piecemaking.edu/finding-aids/
quilting-technologies-department" linkTitle="View the finding aid
online" linkRole="application/xhtml+xml">
    <date standardDate="2024-10-11">October 11, 2024</date>
</findAidDesc>
<findAidDesc href="https://archives.piecemaking.edu/finding-
aids/quilting-technologies-department/quilting-technologies-
department.pdf" linkTitle="Download the finding aid in PDF format"
linkRole="application/pdf">
    <date standardDate="2024-10-11">October 11, 2024</date>
</findAidDesc>

```

identificationData

```

<descriptionOfComponents descriptionOfComponentsType="combined">
    <c>
        <identificationData>
            <head>Descriptive Summary</head>
            <container containerId="33433117009781"
id="aspace_3e98d60dfc5e7ef6c017b677f6616965" localType="box"
localTypeDeclarationReference="containers">3</container>
            <extent coverage="whole" extentType="spaceOccupied">
                <quantity>3.32</quantity>
                <unitOfMeasurement>linear feet</unitOfMeasurement>
            </extent>
            <extent coverage="whole" extentType="spaceOccupied">
                <quantity>6</quantity>
                <unitOfMeasurement>terabytes</unitOfMeasurement>
            </extent>
            <extent coverage="whole" extentType="carrier">
                <quantity>12</quantity>
                <unitOfMeasurement>hard drives</unitOfMeasurement>
            </extent>
            <extent coverage="part" extentType="materialType">
                <quantity approximate="true">1,800</quantity>
                <unitOfMeasurement>electronic files</
unitOfMeasurement>
            </extent>
            <genreForm valueURI="http://vocab.getty.edu/page/
aat/300027401" vocabularySource="AAT">Birth registers</genreForm>
            <genreForm vocabularySource="LCGFT">Aerial photographs</
genreForm>

```

```

        <languageOfMaterial>
            <languageSet>
                <writingSystem scriptCode="Latn">Latin</
writingSystem>
                <language languageCode="en">English</language>
                <language languageCode="la">Latin</language>
            </languageSet>
            <languageSet>
                <language languageCode="el">Greek</language>
                <writingSystem scriptCode="Grek">Greek</
writingSystem>
            </languageSet>
            <descriptiveNote>
                <p>The majority of the documents are written
in Modern English. Roberts copied multiple passages from original
manuscripts in Latin and Greek.</p>
            </descriptiveNote>
        </languageOfMaterial>
        <languageOfMaterial>
            <language languageCode="nl">Dutch</language>
            <language languageCode="fr">French</language>
            <descriptiveNote>
                <p>The materials are in Dutch and French.</p>
            </descriptiveNote>
        </languageOfMaterial>
        <languageOfMaterial>
            <languageSet>
                <language languageCode="ja">Japanese</language>
                <writingSystem scriptCode="Hira">hiragana</
writingSystem>
                <writingSystem scriptCode="Kana">katakana</
writingSystem>
            </languageSet>
            <descriptiveNote>
                <p>This file contains documents in Japanese, in
both the hiragana and katakana scripts.</p>
            </descriptiveNote>
        </languageOfMaterial>
        <legalStatus>
            <term>Public Record(s)</term>
        </legalStatus>
        <legalStatus>
            <term>Student records</term>
            <descriptiveNote>
                <p>Student records are governed by the Family
Educational Rights and Privacy Act (FERPA), 20 U.S.C. § 1232g.</p>
            </descriptiveNote>
        </legalStatus>
        <legalStatus>
            <term>Patient records</term>
            <descriptiveNote>
                <p>Patient records are governed by the Health
Insurance Portability and Accountability Act, Pub.L. 104-191 and
110 Stat. 1936. Article 8 ECHR may also apply.</p>
            </descriptiveNote>
        </legalStatus>
        <otherIdentificationData>

```

The notebooks contain months and days, not years. Estimated dates are based on the years Scully attended the University of Maryland.

```

    </otherIdentificationData>
    <unitDate certainty="circa" unitDateType="inclusive">
      <dateRange>
        <fromDate notBefore="1971"
notAfter="1975">around 1973</fromDate>
        <toDate standardDate="1992">1992</toDate>
      </dateRange>
    </unitDate>
    <unitDate unitDateType="bulk">
      <dateSet>
        <date certainty="uncertain"
standardDate="1968?">c.1968</date>
        <dateRange>
          <fromDate standardDate="1973">1973</
fromDate>
            <toDate standardDate="1992">1992</toDate>
          </dateRange>
          <date standardDate="1997">1997</date>
        </dateSet>
      </unitDate>
    <unitDate>
      <date notBefore="1532-03-30">April 1532</date>
      <textualDate languageOfElement="la">Anno Domini
millesimo quingentesimo trissessimo secundo post festum Paschatis</
textualDate>
    </unitDate>
    <unitDate>
      <textualDate status="unknown">No date given</
textualDate>
    </unitDate>
    <unitDate>
      <dateRange>
        <fromDate standardDate="1609-07-04"
languageOfElement="fr">4 juillet 1609</fromDate>
        <toDate standardDate="1640-07-07"
languageOfElement="fr">7 juillet 1640</toDate>
      </dateRange>
    </unitDate>
    <unitDate certainty="circa" unitDateType="inclusive">
      <dateRange>
        <fromDate standardDate="2016-09"
languageOfElement="de">September 2016</fromDate>
        <toDate status="ongoing"/>
      </dateRange>
    </unitDate>
    <unitId countryCode="US" repositoryCode="US-cbgtu">GTU
2001-8-03</unitId>
    <unitTitle>Donald C. Stone Papers</unitTitle>
  </identificationData>
</c>
</descriptionOfComponents>

```

