Configuration and Retrieval Parameters

Source of truth: config/settings.py (../config/settings.py), coordinator (../backend/coordinator.py), retriever (../core/retrieval/retriever.py), prompt builder (../core/rag/prompt_builder.py), evaluator (../core/evaluation/evaluator.py).

Parameter	Actual implementation/default
Embedding model	all-MiniLM-L6-v2
Embedding device	cpu
Gemini model	gemini-3-flash-preview Settings default vs gemini-2.5-flash in .env.example
LLM default	mock, can select gemini
Vector path	./data/chroma_db
SQLite path	./data/autosar_assistant.db
Retriever top_k	5 default
Retriever similarity threshold	None default (no filter until explicitly passed)
Coordinator query threshold	None default
Golden evaluator threshold	0.3 function default; application differs
Prompt context	12,000 characters max by default (approximate token budget)
Q&A temperature	0.0 supplied by coordinator
API / UI	127.0.0.1:8000 / localhost:8501

Distinctions: Top-k is a candidate count, not relevance confidence. Similarity is not a calibrated probability of correctness. The evaluator's keyword-match ratio is not a semantic correctness score. In core/evaluation/evaluator.py, the relevance-threshold argument is treated differently for answerable/unanswerable items; inspect its implementation before quoting system-wide results.

Do not upload actual .env or runtime credentials. Verify the model and retrieval settings displayed during each real demonstration.