

Introduction to Relational Database Management Systems

Objectives

- ◆ In this session, you will learn to:
 - ◆ Map an ER diagram to a table

Introduction to Relational Database Management Systems

Conceptual Model




What is the
conceptual model?

Introduction to Relational Database Management Systems

Conceptual Model (Contd.)

The conceptual model reflects entities and their relationships based on the data-processing needs of an organization.



Introduction to Relational Database Management Systems

Conceptual Model (Contd.)

- ◆ The conceptual model can be mapped to a relational, hierarchical, or network model.
- ◆ Data analysis is the first step in designing a conceptual model.
- ◆ Data analysis involves identifying entities, their attributes, and relationships between entities based on the data collected.
- ◆ After you complete data analysis, you draw the entity-relationship diagram that gives a detailed overview of the database design.

Mapping ER Diagrams to Tables

- ◆ The following components play an important part while mapping an ER diagram to table:
 - ◆ Regular entities
 - ◆ Attributes
 - ◆ Relationships
 - ◆ Weak entities
 - ◆ Subtypes and supertypes

Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ Regular entities:

- ◆ They can exist alone, independent of any other entity.
- ◆ They are the “building blocks” of the database.
- ◆ Each regular entity maps to a table.
- ◆ For example, STUDENT and BOOKS are two separate entities in the following ER diagram.




Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ Attributes:

- ◆ Each property or attribute shown in the ER diagram maps to an attribute in the appropriate table.
- ◆ In the following ER diagram, STUDENT and BOOKS individually has different attributes.



Entity becomes the table and the attributes of the entity become columns of the table.

STUDENT		
ROLL_NO	NAME	ADDRESS

BOOKS		
CODE	DESC	PRICE

Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ Relationships:

◆ There are the following types of relationships:


- ◆ One-to-One
- ◆ One-to-Many
- ◆ Many-to-Many

Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ One-to-one relationship:

- ◆ One instance of an entity can relate to only one instance of the related entity.
- ◆ For example:



If frequent queries require data from the two tables, then it is better to merge the two tables to improve query performance.

STUDENT

ROLL_NO	NAME	ADDRESS	PROJECT	PROJECT DURATION
R0011	Paul	Shanghai	Banking	16
R0012	Martha	Beijing	Sales Order	20
R0013	Chris	Nanjing	Invoicing	16


Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ One-to-many relationship:

◆ One instance of an entity can relate to more than one instance of the related entity.


◆ For example:



Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

- ◆ Many-to-many relationship:
 - ◆ Many instances of an entity can relate to more than one instance of the related entity.
 - ◆ For example:




The primary keys, *ROLL_NO* and *CODE* of the STUDENT and BOOKS table will act as the foreign keys in the ISSUE table.

Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ Weak entity:

- ◆ It is an entity whose existence depends on some other entity.
- ◆ For example:



The EMPLOYEEADDRESS entity can be mapped to a separate table.


DEPNO	EMPNO	DNAME

- ◆ Subtypes and supertypes:
 - ◆ A subtype is a subset of another entity.
 - ◆ A subtype is always dependent on supertype for its existence.
 - ◆ The primary key of the supertype creates a link between the supertype and subtypes.

Introduction to Relational Database Management Systems

Mapping ER Diagrams to Tables (Contd.)

◆ For example:



Supertype

EMPLOYEE

EMPNO	NAME	ADDRESS

Subtypes

HOURLY EMPLOYEE

EMPNO	WAGES	OVERTIME

SALARIED EMPLOYEE

EMPNO	SALARY	BONUS	CONV_ALLOW

Foreign Key

Each subtype and supertype maps to a separate table.

Introduction to Relational Database Management Systems

Summary

- ◆ In this session, you learned that:
 - ◆ The conceptual model reflects entities and their relationships. Data analysis helps determine entities and relationships. The conceptual model is independent of the system where it is to be implemented.
 - ◆ Regular entities are not dependent. They can exist in isolation, independent of any other entity.
 - ◆ Each entity maps to a table. Each attribute in an ER diagram maps to a column in a table.
 - ◆ Entities with common attributes should be merged. Attributes may acquire further attributes and become entities.
 - ◆ The mapping of relationships depends on the type of relationship. Each type of relationship maps to tables in a different manner in the relational database management system.

Introduction to Relational Database Management Systems

Summary (Contd.)

- ◆ In one-to-one relationship, one instance of an entity can relate to only one instance of the related entity.
- ◆ In one-to-many relationship, one instance of an entity can relate to more than one instance of the related entity.
- ◆ Many-to-many relationships map to tables. One-to-one relationships are not very common and may map to foreign keys in tables.
- ◆ A weak entity is an entity whose existence depends on some other entity.
- ◆ A subtype is a subset of another entity. A subtype is always dependent on supertype for its existence.
- ◆ The primary key of the supertype is the foreign key of the subtype. It creates a link between the two.