



Animal Identification

														
Product Name	Glass Tag Ultra*1)	Glass Tag								E-Unit Rod	E-Unit Disc	E-Unit Packaged	Ear Tag	
Application	Glass Tube with up to 35% better read range than standard tube of same size	Small size with high chemical resistance provides an ideal solution for injection and long term immersion								Embeddable RFID tags - designed for customized enclosure			Reusable RAIN RFID management ear tag for cattle or industrial applications	
Size	Ø2x9 mm, Ø2x12.5 mm	Nano Ø1.2x8 mm	Mini Ø1.4x8 mm Ø1.4x10 mm	Sensor Ø1.5x11 mm Ø2x13 mm	Ø2x12 mm	Ø3x15 mm	Ø3.85x22.5 mm, Ø3.85x32 mm	Ø4x22 mm	Ø4x34 mm	1.55 x 9 mm, 1.8 x 15 mm or 3.8 x 15 mm	Ø20, 24 mm or custom	Ø17.4 or 29 mm	116 x 77 x 1.7 mm	
Frequency	134.2 kHz				125 kHz or 134.2 kHz		134.2 kHz			134.2 kHz			860 MHz to 960 MHz	
Standards / Protocol Support	ISO 11784, ISO 11785								ISO 11784, ISO 11785			IEC 62262-IK08, EPC Gen2, ISO/IEC 18000-6C		
Chip type	EM4305			FDX-B BDE	HITAG S, EM4305, Unique		HITAG S	HDX	HITAG S, EM4305		HITAG S, EM4305, HDX	EM 4305, HDX		Monza M5/M7
Memory	512 bit EEPROM			128 bit read only	256 bit RW, 512 bit RW, 2048 bit RW 64 bit read-only		256 bit RW	128 bit OTP	256 bit RW, 512 bit RW		256 bit RW, 512 bit RW, 128 bit OTP	512 bit RW, 128 bit OTP		128 bit
Tagging Method	subcutaneous			external housing	external housing, subcutaneous		subcutaneous	external housing		ear tag or custom application			Ear Tag	
Operating Temperature	-25° to +85°C	40° to +85°C	-25° to +85°C							-25° to + 60°C			-40° to +85° C	
Storage Temperature	-40° to +90°C									-40° to + 60°C			-40° to +85° C	
Operating Temperature Sensor				25° to +50°C										
Housing Material	BIO Glass											Thermoplastics Polyurethane (TPU)		
Chemical and Environmental Resistances	Water, IP68 (1m, 24h), Saltwater, Alcohol, HCL, Fuel, Ammoniak								Resist on injection process			Mineral oil, Petroleum, Salt mist, UV ligh		
Parylene Coating Available (better tissue adhesion)	Yes						No							
Warranty *2)	2 Years								2 Years			2 Years		

* For further specification details, please see datasheets of the respective products

*1) Optionally available with on-demand custom programming, see <http://www.hidglobal.com/main/services/on-demand/pet-programming/>

*2) Warranty: Storage condition must not exceed specification for temperature, chemical, mechanical, electrical condition, storage from -25°C to + 50°C, humidity 20% to 80%

For unpackaged tags: Warranty would depend on finished product and can only be given as long as raw product is not processed / packaged

FINDING WHAT YOU NEED

HID Global has many more products to offer than fit on this page. Please refer to hidglobal.com/rfid or contact an HID representative for further assistance in evaluating these tags or selecting a solution that best fits your particular requirements.

FINDING WHAT YOU NEED:

HID Global is has many more products to offer than fits on this page. Please refer to hidglobal.com or contact an HID representative for further assistance in evaluating these tags or selecting a solution that best fits your particular requirements.