

AN/SSQ-57SPC

- 99 Channel Capability
- High Reliability
- Improved Low-Noise Suspension System
- Factory-Calibrated Hydrophone



The Sparton AN/SSQ-57SPC is the latest generation of the AN/SSQ-57, produced by Sparton for over 25 years. We updated the buoy to a 99-channel version. Channel selection is made via an Electronic Function Selector (EFS). The AN/SSQ-57SPC is factory calibrated to allow measurement of underwater acoustic sound pressure levels over its entire frequency range. The unit's VHF transmitter is rated at 1 watt.

The unit is powered by a sea water battery which activates at water entry. Operating life is selectable to 1, 3, or 8 hours, with an automatic scuttle at the end of 8 hours. Other optional life setting selections are available within the 8-hour maximum.

Standard depth capabilities allow choices of either 90 or 400 feet, also selectable by EFS prior to launch. Other optional depth suites are available, with up to three depth choices in a suite.

These buoys can also be modified for special applications to include fixed, calibrated attenuators up to a maximum of 80 dB.

The AN/SSQ-57SPC is air launchable from fixed or rotary-wing aircraft. Descent of the sonobuoy is stabilized and slowed by a parachute. It is also easily deployable from the deck of a surface vessel.

Sparton Government Business Division

5612 Johnson Lake Road - DeLeon Springs, FL 32130 - government@sparton.com
Phone 386-985-4631 - Toll Free 800-952-7589 - FAX 386-985-9855

SP  **STON**

