Non-Malleable Cryptography

String Commitment and Zero-Knowledge Proofs of Knowledge

Based on: Dolev, Dwork & Naor (2003)
SIAM Journal on Computing, Vol. 30, No. 2

Report

1. Abstract

This report provides a focused academic analysis of the concept of non-malleable cryptography as introduced by Danny Dolev, Cynthia Dwork, and Moni Naor in their landmark paper. The study deliberately excludes the public-key encryption component and concentrates exclusively on two primitives: string commitment schemes and zero-knowledge proofs of knowledge.

Non-malleability is an extension of semantic security — the dominant security notion at the time of the paper's original presentation at STOC 1991. While semantic security guarantees that an adversary cannot learn anything about a plaintext from its ciphertext, it does not prevent the adversary from generating a different but meaningfully related cryptographic object. Non-malleability closes this gap.

For string commitment, non-malleability ensures that an adversary who observes a commitment to a string s cannot produce a commitment to a related string s' with any greater probability than an adversary who has never seen the original commitment. For zero-knowledge proofs of knowledge, non-malleability guarantees that a prover who observes another party's proof cannot use that observation to construct a related proof, preventing attacks such as the transparent prover scenario.

The paper presents formal definitions, constructions, and proofs of non-malleability for each primitive. A single unified definition of non-malleability is introduced that can be instantiated across all three settings. The schemes presented require no trusted centre, and no party needs knowledge of the number or identity of other system users — a significant departure from prior work in this space.

2. Motivation and Problem Statement

2.1 The Insufficiency of Semantic Security

The dominant security notion for cryptographic primitives at the time of this work was semantic security, introduced by Goldwasser and Micali. Semantic security, also referred to as indistinguishability under chosen-plaintext attack (IND-CPA), asserts that any information about the plaintext that is computable from the ciphertext is equally computable without the ciphertext. In formal terms, no probabilistic polynomial-time adversary can distinguish between encryptions of two chosen messages.

While this definition is powerful, the authors identify a critical gap: semantic security says nothing about what an adversary can do with a cryptographic object in a relational sense. That is, given a commitment or a proof, can an adversary produce a different but related object? In distributed systems, where multiple parties interact concurrently and the mutual independence of messages often plays a critical security role, semantic security alone is insufficient.

This observation motivates the introduction of a stronger security notion — non-malleability — which governs not only what can be learned from an object, but what can be derived or constructed from it relationally.

2.2 Motivating Scenario: The String Commitment Problem

The core problem with a malleable string commitment scheme arises in concurrent execution environments. Consider two parties, each running an instance of a string commitment protocol simultaneously. An adversary A, coordinating the agents of both parties, observes the commitment made by the first party to a string s and uses that observation to make the second party's commitment depend on s in a non-trivial way.

More concretely, suppose Party A commits to a secret bid value s. Party B, controlled by the adversary, can create a commitment to a value s' such that s' is always slightly less than s — thereby consistently underbidding A without ever learning s. This is the string commitment analogue of the bidding attack described in the paper's introduction.

The goal of a non-malleable string commitment scheme is to prevent precisely this: even if the adversary sees the commitment C(s), the probability that it can create a commitment C(s') for a string s' that is related to s by some relation R should be no greater than if it had never seen C(s) at all.

2.3 Motivating Scenario: The Zero-Knowledge Proof of Knowledge Problem

Zero-knowledge proof systems allow a prover to demonstrate knowledge of a secret without revealing the secret itself. While standard zero-knowledge protocols are powerful, they are vulnerable to a class of attacks in concurrent settings that non-malleability is designed to address.

The paper illustrates this with the transparent prover scenario. Suppose Researcher A has proved P ≠ NP and wishes to demonstrate this to Professor B using a zero-knowledge protocol. Professor B, dishonestly acting as a transparent prover, relays every question posed by A to an eminent Professor E, and relays E's responses back to A. In this way, B can claim credit for A's proof to Professor E — even though B has no knowledge of the underlying proof.

This is a man-in-the-middle attack on zero-knowledge proof systems. A non-malleable zero-knowledge proof of knowledge is designed so that even if B observes A's proof interaction, B cannot produce a related proof to E. Researcher A will therefore receive proper credit, even without knowing of E's existence, and even if Professor E is unaware of Researcher A.

2.4 Why Existing Approaches Were Inadequate

Prior to this paper, research that touched on related problems — including work by Bellare and Goldwasser, and others — required at least one of two assumptions: either a trusted center exists in the system, or all parties know the identities of every other party using the system. These assumptions are highly restrictive and unrealistic in open, distributed network environments.

The authors note that their construction is the first to require neither assumption. A user need not know anything about the number or identity of other system users. This makes the scheme applicable to real-world settings such as the internet, where users connect anonymously and without pre-established identity infrastructure.

Semantically secure cryptography	**Dolev-Dwork-Naor Approach**
Trusted center required	No trusted center assumed
Parties must know each other's identities	No identity knowledge required
Secure only against passive adversaries	Secure against active, coordinated adversaries
Single-session security	Concurrent multi-session security

3. Formal Definitions and Cryptographic Constructions

3.1 Foundational Framework: The Adversarially Coordinated System

The paper introduces a general framework called the adversarially coordinated system, which serves as the setting for all three non-malleability definitions. This system is denoted:

$$W = < (A, B), (C, D), A : \psi(B) \leftrightarrow \psi(C) >$$

Here, (A, B) and (C, D) are two interactive protocols, and A is an adversary controlling the agents $\psi(B)$ and $\psi(C)$. The adversary controls the communication between these agents and the times at which these controlled agents take steps. This general model captures concurrent execution of two instances of the same protocol, with an adversary sitting in the middle.

In this framework, $\psi(A)$ sends an intended value α in its conversation with $\psi(B)$, and $\psi(C)$ sends an intended value β in its conversation with $\psi(D)$. The goal of non-malleability is to ensure that β is unrelated to α when $\alpha \neq \beta$.

To formally measure the relationship between two values, the paper introduces a relation approximator R, defined as a probabilistic polynomial-time Turing machine taking two inputs and producing as output either zero or one. The purpose of R is to measure the correlation between α and β.

The authors restrict attention to the special class of relation approximators which on input pairs of the form (x, x) or (x, 0n) always output zero. This restriction reflects two key intuitions:

- Exact copying cannot be ruled out and should not count as a successful attack.
- If $\psi(C)$ refuses to send an intended value (outputs 0n), this is not a meaningful attack.

The relation approximator R on input pairs (α, β) generated in the adversarial setting is compared to its behavior on pairs (α, γ), where γ is generated without access to α. The difference in these probabilities defines the adversary's advantage.

3.2 The General Non-Malleability Definition

A scheme S for a primitive P is defined to be non-malleable with respect to itself if for all relation approximators R and all adversarially coordinated systems of interactive proof systems:

$$< (A,B), (C,D), A : \psi(B) \leftrightarrow \psi(C) > \text{ where } (A,B) = (C,D) = S$$

there exists an adversary simulator A' such that:

$$| \pi(A, R) - \pi'(A', R) | \text{ is subpolynomial}$$

where $\pi(A, R)$ denotes the probability that $R(\alpha, \beta)$ outputs 1 in the adversarially coordinated system, and $\pi'(A', R)$ denotes the corresponding probability when A' operates without access to the sending of α.

This definition captures the intuition that seeing one instance of the primitive gives no meaningful advantage in producing a related instance.

3.3 String Commitment: Definition and Construction

3.3.1 What Is a String Commitment Scheme?

A string commitment scheme is an interactive protocol between a committer C and a receiver R. It proceeds in two stages:

- Commit stage: The committer selects a string s and sends a commitment C(s) to the receiver. After this stage, the committer is bound to s.
- Reveal stage: The committer reveals s and the randomness used. The receiver verifies the opening is consistent with the original commitment.

A commitment scheme must satisfy two standard properties: binding (the committer cannot change s after committing) and hiding (the commitment C(s) reveals no information about s to the receiver).

The input s is drawn from a probability distribution D. A polynomial-time computable function hist models information about the generator's input to which the receiver may have access.

3.3.2 The Non-Malleable String Commitment Scheme

The scheme S constructed in the paper is built from two components: a regular string commitment protocol (taken from prior work by Naor) and multiple instances of a protocol called BCK, each applied to the committed string. The construction is denoted:

```
S = (Committer, Receiver) using BCK protocol instances
```

The commit stage of S proceeds as follows. The committer selects random values r1, r2 from {0,1}^(poly(n)), commits to the string s using the base protocol, and then executes several instances of BCK to prove consistency. The receiver engages in each BCK instance as verifier.

The BCK protocol instances serve a critical role: they force the committer to prove, in zero-knowledge, that the committed value under all the various commitment keys is the same. This proof of consistency is what prevents malleability.

3.3.3 The Sextuple Protocol

The core of the non-malleable commitment scheme is the BCK protocol, which the paper treats as operating on a sextuple: commit, challenge, response, executed for two instances simultaneously. The paper denotes each application of this protocol as a triple (BCK1, BCK2, BCK3).

A triple is defined as exposed if specific timing conditions hold between the two concurrent instances — specifically, if the first BCK instance in one session completes step BCK3 before the second instance in the other session begins. The existence of exposed triples is what enables the knowledge extractor to work.

3.3.4 The Exposed Triple and Knowledge Extraction

The proof of non-malleability for the string commitment scheme relies on the construction of a knowledge extractor — a procedure that, given access to an adversary A's random tape and the ability to fork executions, extracts the value β committed to by A.

The key structural insight is captured by the following lemma from the paper. For any two sequences of scheduling pairs in the concurrent execution, there exists an exposed triple. This is established through a combinatorial analysis of the possible interleavings of the protocol steps.

> Claim: For any sigma ≠ sigma', for indices from sets X and Y,
> there exists an exposed triple j in sigma_y.

The extractor runs the system repeatedly, branching at points of high success probability, and uses the answers from two independent forks to extract the committed value. The probability of successful extraction is shown to be arbitrarily close to the adversary's own success probability.

3.4 Zero-Knowledge Proofs of Knowledge: Definition and Construction

3.4.1 Definition 2.1: Non-Interactive Zero-Knowledge Proof System

The paper adopts the following formal definition of a non-interactive zero-knowledge proof system for a language L in NP. A triple (P, V, U) where P is a probabilistic machine, V is a polynomial-time machine, and U is a polynomial-time sampleable probability distribution, is a non-interactive ZK proof system for L if it satisfies three conditions:

- Completeness: If x is in L, then for all z in WL(x), with overwhelming probability for U drawn from U(n) and proof p drawn from P(x, z, U), p is in ACCEPT(U, x).
- Soundness: If y is not in L, then no prover can generate a proof that V accepts. Formally, for all y not in L_n, with overwhelming probability over U drawn from U(n), for all p in {0,1}*, p is in REJECT(U, y).

- Zero-knowledge: There exists a probabilistic polynomial-time simulator Sim such that for all PPT machines C, if C generates x in L and z in WL(x), then | Pr[C(w) = 1 | w from Sim(x)] - Pr[C(w) = 1 | w from CONV(x, z)] | < 1/p(n) for all polynomials p and sufficiently large n.

$$|Pr[C(w)=1 \mid w \in_R Sim(x)] - Pr[C(w)=1 \mid w \in_R CONV(x,z)]| < 1/p(n)$$

3.4.2 The Non-Malleable Zero-Knowledge Proof Scheme

The non-malleable zero-knowledge proof of knowledge scheme is constructed by combining the non-malleable string commitment scheme S with non-interactive zero-knowledge proof systems. The construction follows the structure of the commitment scheme closely, but instantiated for the proof-of-knowledge setting.

The core idea is that instead of committing to a string, the prover commits to its witness using the non-malleable commitment scheme. The verifier then challenges the prover, and the prover responds using both its committed value and the zero-knowledge proof of consistency.

The scheme S for proving possession of knowledge is constructed as follows. The prover P first runs the key generator and generates a public signature key. The message is encrypted under several encryption keys chosen as a function of this public key. A non-interactive zero-knowledge proof of consistency is provided — that the encryption under all keys is the same. The encryptions plus the proof are then signed using the private key of the chosen signature scheme.

3.4.3 The Adversary Simulator for Zero-Knowledge

The adversary simulator for the zero-knowledge proof scheme is defined as follows. Given a history hist(x) and the public parameters, the simulator must produce a conversation distribution that is computationally indistinguishable from the real proof conversation.

In the non-malleable zero-knowledge proof construction, the simulator has access to the distribution D and the value hist(α), but does not have access to the commitment itself. The simulator:

- Generates an intended value γ from the distribution D.
- Produces a conversation that is statistically close to the real conversation distribution.
- Operates in polynomial time.

The key property is that even with access to the conversation between the prover and verifier in one session, the adversary gains no advantage in the other session. This is exactly the non-malleability condition applied to the proof-of-knowledge setting.

3.4.4 The Compiler: Converting Zero-Knowledge to Non-Malleable

A particularly elegant result in the paper is the construction of a compiler that takes any zero-knowledge interactive protocol (A, B) and produces a non-malleable version. The compiled protocol uses a pseudo-random generator as a building block.

Each party commits to its input using the non-malleable commitment scheme, and then proves, using the zero-knowledge proof of consistency, that the message sent at each step is the one it should have sent given its committed input and the messages received so far. Since proving the consistency of the new message with the conversation so far can be done effectively (given the random tape and the input), this proof has a malleable zero-knowledge proof of knowledge to the string.

4. Limitations of the Proposed Schemes

4.1 Computational Efficiency Limitations

The non-malleable commitment scheme constructed in the paper is significantly more computationally expensive than standard string commitment protocols. The scheme requires running multiple instances of the BCK protocol concurrently — the paper specifies that for a string s of length poly(n), the protocol requires O(n) instances of BCK, each of which is itself a three-move protocol. This results in a commitment that is substantially larger than the string being committed to.

More precisely, the number of rounds in the non-malleable commitment protocol is proportional to the security parameter n, whereas a standard Naor commitment requires only a constant number of rounds. The overhead introduced is not merely a constant factor — it grows with the security parameter, making the scheme impractical for applications requiring low-latency commitment.

4.2 Communication Complexity

The communication complexity of both the non-malleable string commitment and the zero-knowledge proof of knowledge schemes is substantially higher than their malleable counterparts. Each instance of the BCK protocol requires sending messages of length O(n), and O(n) such instances are required. The total communication is therefore O(n^2) bits, compared to O(n) bits for a standard commitment.

For the zero-knowledge proof scheme, the overhead is compounded further. The prover must send a vector of ciphertexts (f1, f2, ...), a cleartext string σ, and a signature — each of polynomial size. When composed within the compiler for non-malleable zero-knowledge proofs, the total message size grows with the number of steps in the underlying protocol.

4.3 The Identities Problem

The paper explicitly acknowledges a subtle limitation regarding the treatment of identities in the adversarially coordinated system. While the schemes do not require parties to know each other's identities, the definition of the adversary simulator assumes that if identity pairs (i, j) have names, then the non-malleable scheme ensures that the committed value β is independent of α.

However, the paper notes that there are many possible interpretations of what constitutes a 'name' — timestamps, locations, message histories, and so on. If the players are anonymous, or if the names they claim cannot be verified, then it becomes impossible to solve the proper-credit problem described in the transparent prover scenario. The scheme works only when there is at least some form of verifiable identity component in the first input.

4.4 Limitations

Non-malleability as defined in this paper is not automatically preserved under arbitrary composition. The paper notes that non-malleable protocols for commitments and zero-knowledge proofs are non-malleable with respect to themselves. However, the general question of whether non-malleable protocols compose — that is, whether two non-malleable protocols executed concurrently remain non-malleable with respect to each other — is left largely open.

The paper offers a brief mention of a more general composability result in Section 3.5 (which we have not covered in this report as it pertains to encryption), but the detailed composition theory for string commitment and zero-knowledge was left for subsequent work. This is a significant limitation because real-world protocols are always composed with other protocols.

This limitation was addressed in subsequent decades by work on universally composable security (Canetti, 2001) and simulation-based security frameworks, which provide composition guarantees that the Dolev-Dwork-Naor framework does not.

The definition of non-malleability restricts the class of relations R that are considered. Specifically, R must output zero on input pairs of the form (x, x) (exact copy) and (x, 0n) (commitment to zero). This restriction is necessary to make the definition achievable — without it, no scheme could be non-malleable, since an adversary can always copy an observed commitment exactly.

However, this restriction means that certain types of relational attacks are explicitly excluded from the security definition. If an adversary can exploit a relationship that falls outside the restricted class of relation approximators, the scheme provides no guarantee. The authors acknowledge this in a footnote, noting that certain kinds of relations — such as R(α, β) holding precisely when β is in E(α) — cannot be ruled out.

4.5 Dependence on Non-Interactive Zero-Knowledge

The non-malleable zero-knowledge proof of knowledge scheme relies critically on the existence of non-interactive zero-knowledge proof systems. At the time of writing, such systems were known to exist only in the common random string model — a setting where all parties have access to a shared random string generated by a trusted setup.

This dependence on a common random string (CRS) is itself a form of trusted setup assumption, which somewhat undermines the paper's claim of operating without a trusted center. While the CRS model is much weaker than a traditional trusted center — the setup is one-time and the string can be generated by a public coin-flipping protocol — it is not entirely assumption-free.

4.7 Scheme Complexity for Zero-Knowledge

The non-malleable zero-knowledge proof of knowledge scheme is described at a relatively high level in the paper, with the detailed proof of non-malleability relying on the non-malleability of the underlying commitment scheme. The construction involves a compiler that adds a proof-of-consistency layer to any zero-knowledge protocol, but the resulting protocol is significantly more complex than the original.

In particular, the compiled protocol requires the committer to run concurrent invocations of the BCK protocol for each step of the underlying zero-knowledge proof, plus additional rounds for the non-interactive proof of consistency. This results in a protocol whose round complexity is a polynomial in both the security parameter and the round complexity of the original protocol.

Limitation	Impact	Severity
High computational overhead (O(n) BCK instances)	Impractical for real-time applications	High
Communication complexity O(n^2)	Bandwidth-intensive, poor scalability	High
Identity verification dependency	Cannot solve credit problem with anonymous parties	Medium
Non-composability with arbitrary protocols	Unsafe in complex multi-protocol environments	High
Restricted relation class	Some relational attacks not covered	Medium
Dependence on common random string model	Requires weak trusted setup for ZK proofs	Medium
Compiled protocol complexity	ZK scheme is complex and hard to implement	Medium

5. Conclusion

The paper by Dolev, Dwork, and Naor represents a fundamental advancement in the theory of cryptographic security. By identifying the gap between semantic security and the security requirements of real-world distributed systems, and by formalizing the notion of non-malleability, the authors laid the groundwork for a large body of subsequent research in provably secure cryptography.

For string commitment, the paper provides the first formal definition of non-malleable commitment and a construction that achieves it without any trusted infrastructure. The construction uses concurrent instances of the BCK protocol to force the committer to prove consistency, making it impossible for an adversary to relationally derive a new commitment from an observed one.

For zero-knowledge proofs of knowledge, the paper addresses the transparent prover attack — a concrete and natural attack that arises in settings where provers and verifiers interact concurrently. The non-malleable zero-knowledge proof of knowledge ensures that observing a proof interaction gives no advantage in constructing a related proof, directly addressing this vulnerability.

The limitations of the constructions — primarily their computational inefficiency and lack of composability — have motivated decades of subsequent work. The theory of universally composable security, efficient non-malleable commitments based on trapdoor permutations, and non-malleable codes are all direct intellectual descendants of this paper's foundational ideas.

In summary, Dolev, Dwork, and Naor's work on non-malleable cryptography is a cornerstone of modern theoretical cryptography. Its impact is felt not only in the specific constructions it provides, but in the security philosophy it establishes: that security in isolation is insufficient, and that cryptographic primitives must remain secure even when observed and potentially exploited by a computationally powerful adversary operating across multiple concurrent sessions.

References

[1] D. Dolev, C. Dwork, M. Naor. Non-Malleable Cryptography. SIAM Journal on Computing, 30(2):391-437, 2003.

[2] S. Goldwasser, S. Micali. Probabilistic Encryption. Journal of Computer and System Sciences, 28(2):270-299, 1984.

[3] M. Blum, P. Feldman, S. Micali. Non-Interactive Zero-Knowledge and Its Applications. STOC 1988.

[4] R. Canetti. Universally Composable Security: A New Paradigm for Cryptographic Protocols. FOCS 2001.

[5] M. Naor. Bit Commitment Using Pseudorandomness. Journal of Cryptology, 4(2):151-158, 1991.