EXP 15

```
#include<string.h>
#include<stdlib.h>
#include<stdio.h>
struct
{
char dname[10],fname[10][10];
int fcnt;
}dir[10];
int main()
int i,ch,dcnt,k;
char f[30], d[30];
dcnt=0;
while(1)
printf("\n\n1. Create Directory\t2. Create File\t3. Delete File");
printf("\n4. Search File\t\t5. Display\t6. Exit\tEnter your choice -- ");
scanf("%d",&ch);
switch(ch)
case 1: printf("\nEnter name of directory -- ");
scanf("%s", dir[dcnt].dname);
dir[dcnt].fcnt=0;
dcnt++;
printf("Directory created");
break;
case 2: printf("\nEnter name of the directory -- ");
scanf("%s",d);
for(i=0;i<dcnt;i++)
if(strcmp(d,dir[i].dname)==0)
printf("Enter name of the file -- ");
scanf("%s",dir[i].fname[dir[i].fcnt]);
printf("File created");
break;
}
if(i==dcnt)
printf("Directory %s not found",d);
break;
case 3: printf("\nEnter name of the directory -- ");
scanf("%s",d);
for(i=0;i<dcnt;i++)
if(strcmp(d,dir[i].dname)==0)
printf("Enter name of the file -- ");
```

```
scanf("%s",f);
for(k=0;k<dir[i].fcnt;k++)</pre>
if(strcmp(f, dir[i].fname[k])==0)
printf("File %s is deleted ",f);
dir[i].fcnt--;
strcpy(dir[i].fname[k],dir[i].fname[dir[i].fcnt]);
goto jmp;
}
printf("File %s not found",f);
goto jmp;
}
}
printf("Directory %s not found",d);
jmp : break;
case 4: printf("\nEnter name of the directory -- ");
scanf("%s",d);
for(i=0;i<dcnt;i++)</pre>
if(strcmp(d,dir[i].dname)==0)
printf("Enter the name of the file -- ");
scanf("%s",f);
for(k=0;k<dir[i].fcnt;k++)</pre>
{
if(strcmp(f, dir[i].fname[k])==0)
printf("File %s is found ",f);
goto jmp1;
printf("File %s not found",f);
goto jmp1;
}
printf("Directory %s not found",d);
jmp1: break;
case 5: if(dcnt==0)
printf("\nNo Directory's ");
else
printf("\nDirectory\tFiles");
for(i=0;i<dcnt;i++)
printf("\n%s\t\t",dir[i].dname);
for(k=0;k<dir[i].fcnt;k++)</pre>
```