

ASU ROAR

Continuous Global Planner Performance & Path Geometry Evaluation

OVERALL SYSTEM EVALUATION: SYSTEM STABLE / PERFORMANCE ENVELOPE MAINTAINED

System Summary Diagnostics

PATH SUCCESS RATE	SIGNAL SMOOTHNESS	MAX TURN ANGLE	MIN OBSTACLE CLEARANCE
100.0%	0.5099 s	45.0°	10.00 m

Whole-System Statistical Analysis

Metric Metric Vector	Minimum Recorded	Mean Average	Maximum Peak
Path Compilation Time (s)	0.5006	0.5099	0.5228
Turn Angle (deg)	0.0°	2.2°	45.0°
Turn Radius (m)	0.08	0.08	0.08
Path Length / Euclidean Ratio	1.782	1.782	1.782
Nearest Distance to Obstacle (m)	10.000	10.000	10.000
Path Cost	0.0	0.0	0.0

Per-Test Breakdown

Test Case	Status	Time (s)	Dist (m)	Ratio	Avg T (°)	Max T (°)	Avg R (m)	Min R (m)	Clear (m)	Cost
general	PASS	0.523	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0
general	PASS	0.501	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0
general	PASS	0.501	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0
general	PASS	0.502	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0
general	PASS	0.514	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0
general	PASS	0.518	20.16	1.78	2.2°	45.0°	0.1	0.1	10.00	0.0