REVIEW – III

Vellore Institute of Technology

(Deemed to be University under section 3 of UGC Act, 1956)

SCHOOL OF COMPUTER SCIENCE ENGINEERING AND INFORMATION SYSTEMS (SCORE)

TITLE: PREDICTION OF COCONUT YIELD IN POLLACHI

SLOT: F1+TF1

SWE4010 – ARTIFICIAL INTELLIGENCE (PROJECT COMPONENT)

TEAM MEMBERS:

1.K.SANGAMI – 21MIS0466

2.S.ANITHA – 21MIS0303

Under the guidance of:

Prof. AJIT KUMAR SANTRA

1. TITLE :

PREDICTION OF COCONUT YIELD IN POLLACHI

2. ABSTRACT WITH KEYWORDS :

This AI model pioneers a transformative approach to coconut farming in Pollachi by integrating advanced artificial intelligence (AI) techniques with comprehensive data analysis. Leveraging AI algorithms, the project synthesizes diverse datasets encompassing weather patterns, soil health, crop performance, pest and disease prevalence, market trends, sensor readings, and farm management practices. This amalgamation facilitates predictive analytics, disease and pest detection, resource optimization, market forecasting, sustainable farming practice recommendations, schedule planning, and user interface management, all tailored to the specific needs of coconut farmers. By harnessing the power of AI, This AI not only enhances productivity, resource efficiency, and profitability but also fosters sustainable agricultural practices, empowers informed decision-making, and elevates the overall resilience and prosperity of coconut farming communities in Pollachi.

KEYWORDS:

AI integration, coconut yield prediction, Predictive analytics, disease detection, resource optimization, market analysis, sustainable farming practices.

2.1 OBJECTIVE:

To achieve coconut yield in Pollachi and To achieve the most robust and generalizable yield predictions.

3. INTRODUCTION:

This project in Pollachi, India, is revolutionizing coconut farming through the power of Artificial Intelligence (AI). By harnessing AI algorithms, the project delves into a rich tapestry of data, including weather patterns, soil health, historical crop yields, pest and disease outbreaks, market trends, and even real-time sensor readings from your farm. Imagine predicting future yields with remarkable accuracy, allowing you to plan strategically and optimize resource allocation.Moreover, the model can recommend sustainable practices optimized for your farm's conditions, promoting environmental responsibility while maximizing yield. Market forecasting becomes a powerful tool, guiding the farmers through price fluctuations to maximize profitability. To further streamline the operations, the AI can assist with farm scheduling and user interface management, ensuring you have the information you need readily available. This project transcends simply predicting yield; it empowers Pollachi's coconut farmers to make data-driven decisions, cultivate their land sustainably, and achieve greater prosperity.

3.1 . LITERATURE REVIEW:

Ahalya [(1)] **(2023)** discussed the study aims to comprehensively analyze coconut cultivation trends in Tamil Nadu, covering area, production, yield, and market prices

develop precise price forecasting models for Coimbatore and Pollachi markets, enhancing insights into agricultural dynamics and enabling accurate price predictions. Coconut cultivation is growing steadily with a 1.56% increase in cultivation area and a 2.089% rise in production, while productivity is also improving by 1.19% annually, indicating positive growth. ARIMA (1, 1, 1) for Coconut in the Coimbatore market and ARIMA (1, 1, 1) for coconut in the Pollachi market was found to provide the best fit for predicting the price of coconut in both markets. ARIMA (1, 1, 1) was found to provide the best fit for predicting the price of coconut in both markets. The model predicted declining price in the forthcoming months (August – September, 2023). Increased area under cultivation and increased production of coconut in all the major growing States are the major reasons for declining prices.

Rashid [(2)] et al (2021) have discussed and presented a comprehensive review on crop yield prediction using machine learning approaches, with a specific focus on palm oil yield prediction. The article emphasizes the importance of early and reliable crop yield estimation for strategic planning, financial evaluation, and policy-making in the agricultural sector. It highlights the challenges associated with predicting crop yields and the growing significance of machine learning algorithms in addressing these challenges. The authors begin by presenting the current status of palm oil yield worldwide, discussing widely used features and prediction algorithms. They then delve into a critical evaluation of machine learning-based crop yield prediction, particularly focusing on its application in the palm oil industry. A comparative analysis of related studies is provided, along with a detailed examination of the advantages and difficulties associated with machine learning-based crop yield prediction.

Aggarwal [(3)] (2022) said that coconut is a major plantation crop of coastal India. Accurate prediction of its yield is helpful for the farmers, industries and policymakers. Weather has profound impact on coconut fruit setting, and therefore, it greatly affects the yield. Annual coconut yield and monthly weather data for were compiled for fourteen districts of the west coast of India. Weather indices were generated using monthly cumulative value for rainfall and monthly average value for other parameters like maximum and minimum temperature, relative humidity, wind speed and solar radiation. Different linear models like stepwise multiple linear regression (SMLR), principal component analysis together with SMLR (PCA-SMLR), least absolute shrinkage and selection operator (LASSO) and elastic net (ELNET) with nonlinear models namely artificial neural network (ANN) and PCA-ANN were employed to model the coconut yield using the monthly weather indices as inputs. The overall average ranking of the models based these performance statistics were in the order of ELNET > LASSO > ANN > SMLR > PCASMLR > PCA-ANN. Results indicated that the ELNET model could be used for prediction of coconut yield for the region.

Mohan [(4)] et al (2023) present a novel approach for rice crop yield prediction by leveraging multispectral satellite data and climatic parameters. Their model utilizes a Temporal Convolutional Network (TCN) with a specially designed dilated convolution module to analyze vegetation indices (VIs) extracted from Moderate Resolution Imaging Spectroradiometer (MODIS) data alongside climatic data. By exploiting the causal property of TCN and the

capabilities of dilated convolution, the model performs multivariate time-based analysis, resulting in improved prediction accuracy compared to existing models.Precision Agriculture (PA) aims to enhance crop production and ensure food security through data-driven decision-making processes.

Jhajharia and Mathur [5] (2023) have discussed the critical realm of crop yield prediction, particularly focusing on the Rajasthan region in India, which hasn't received extensive investigation in existing studies. Acknowledging India's pivotal role in agriculture on the global stage, the authors highlight the necessity of accurate yield prediction for ensuring food security, agricultural management, and socio-economic stability. Their study employs machine learning techniques, including decision trees, random forests, lasso regression, and support vector regression, to predict crop yield using a dataset comprising vegetation indices extracted from remote sensing data and weather data.

Shakoor [6] (2021) have discussed although agriculture remains the dominant economic activity in many countries around the world, in recent years this sector has continued to be negatively impacted by climate change leading to food insecurities. This is so because extreme weather conditions induced by climate change are detrimental to most crops and affect the expected quantity of agricultural production. The study applies machine learning techniques to predict crop harvests based on weather data and communicate the information about production trends. The collected data were analyzed through Random Forest, Polynomial Regression, and Support Vector Regressor. Rainfall and temperature were used as predictors. The models were trained and tested. The results indicate that Random Forest is the best model with root mean square error of 510.8 and 129.9 for potato and maize, respectively, whereas R^2 was 0.875 and 0.817 for the same crops datasets. The results suggests that Random Forest is recommended model for early crop yield prediction. The findings of this study will go a long way to enhance reliance on data for agriculture and climate change related decisions, especially in low-tomiddle income countries such as Rwanda.

Apolo-Apolo [7] (2021) have discussed deep Learning has been applied for the crop yield prediction problem, however, there is a lack of systematic analysis of the studies. Therefore, this study aims to provide an overview of the state-of-the-art application of Deep Learning in crop yield prediction. We performed a Systematic Literature Review (SLR) to identify and analyze the most relevant papers. A thorough analysis and synthesis of the primary studies were performed with respect to the key motivations, the target crops, the algorithms applied, the features used, and the data sources used. We observed that Convolutional Neural Network (CNN) is the most common algorithm and it has the best performance in terms of Root Mean Square Error (RMSE). One of the most important challenges is the lack of a large training dataset and thus, the risk of overfitting and as a result, lower model performance in practice.

Hu [8] et al (2023) addressed the critical issue of crop yield prediction in the context of climate change impacts, emphasizing the importance of employing explainable artificial intelligence (AI) and interpretable machine learning models. They introduce a novel Bayesian ensemble model (BM) aimed at predicting crop yield while maintaining interpretability and explanatory power. This model, which employs Bayesian model averaging to incorporate various

competitive models, not only offers high predictive accuracy but also facilitates understanding of the underlying relationships between climate variables and crop yield.

Yang [9] et al (2023) presented a study focused on developing a seasonal prediction model for crop yields in Ethiopia using an analog approach. The authors emphasize the importance of accurate crop yield predictions for national food security, particularly in countries like Ethiopia where agriculture plays a significant role in the economy. They aim to create an easy-toimplement and computationally efficient forecast method to assist farmers and agricultural agencies in making informed decisions.The study leverages historical planting time soil moisture data simulated using the Coupled Routing and Excess STorage (CREST) hydrological model, along with a Decision Support System for Agrotechnology Transfer (DSSAT) agricultural model to construct a historical crop yield database. The analog approach is based on selecting analog years with similar climate conditions to the current season to predict crop yields. Maize is used as a representative crop for the analysis.

Cooper [10] et al (2021) have discussed that crop yield prediction is crucial for global food security yet notoriously challenging due to multitudinous factors that jointly determine the yield, including genotype, environment, management, and their complex interactions. Integrating the power of optimization, machine learning, and agronomic insight, we present a new predictive model (referred to as the interaction regression model) for crop yield prediction, which has three salient properties. First, it achieved a relative root mean square error of 8% or less in three Midwest states (Illinois, Indiana, and Iowa) in the US for both corn and soybean yield prediction, outperforming state-of-the-art machine learning algorithms. Second, it identified about a dozen environment by management interactions for corn and soybean yield, some of which are consistent with conventional agronomic knowledge whereas some others interactions require additional analysis or experiment to prove or disprove. Third, it quantitatively dissected crop yield into contributions from weather, soil, management, and their interactions, allowing agronomists to pinpoint the factors that favorably or unfavorably affect the yield of a given location under a given weather and management scenario.

Kheir [11] et al (2021) have discussed deep learning has emerged as a potential tool for crop yield prediction, allowing the model to automatically extract features and learn from the datasets. Meanwhile, smart farming technology enables the farmers to achieve maximum crop yield by extracting essential parameters of crop growth. This systematic literature review highlights the existing research gaps in a particular area of deep learning methodologies and guides us in analyzing the impact of vegetation indices and environmental factors on crop yield. To achieve the aims of this study, prior studies from 2012 to 2022 from various databases are collected and analyazed. The study focuses on the advantages of using deep learning in crop yield prediction, the suitable remote sensing technology based on the data acquisition requirements, and the various features that influence crop yield prediction. This study finds that Long Short-Term Memory (LSTM) and Convolutional Neural Networks (CNN) are the most widely used deep learning approaches for crop yield prediction.

Elavarasan and Vincent [12] (2021) have discussed an early and reliable estimation of crop yield is essential in quantitative and financial evaluation at the field level for determining

strategic plans in agricultural commodities for import-export policies and doubling farmer's incomes. Crop yield predictions are carried out to estimate higher crop yield through the use of machine learning algorithms which are one of the challenging issues in the agricultural sector. Due to this developing significance of crop yield prediction, this article provides an exhaustive review on the use of machine learning algorithms to predict crop yield with special emphasis on palm oil yield prediction. Initially, the current status of palm oil yield around the world is presented, along with a brief discussion on the overview of widely used features and prediction algorithms. The potential solutions are additionally prescribed in order to alleviate existing problems in crop yield prediction. Since one of the major objectives of this study is to explore the future perspectives of machine learning-based palm oil yield prediction, the areas including application of remote sensing, plant's growth and disease recognition, mapping and tree counting, optimum features and algorithms have been broadly discussed.

Khaoula Abrougui [13] **(2021**) has discussed the crop yield prediction is one of the challenging task in agricultural domain. Extensive research in agricultural domain has been carried out to predict better crop yield using the machine learning algorithm Artificial Neural Network (ANN) and statistical model Multiple Linear Regression (MLR). This article examines the intrinsic relationship between MLR and ANN. A hybrid MLR-ANN model has been proposed in this research work for efficient crop yield prediction. The proposed hybrid model is modeled to analyze the prediction accuracy when MLR intercept and coefficients were applied to initialize the ANN's input layer weights and bias. Feed Forward Artificial Neural Network with Back Propagation training algorithm was used for predicting accurate paddy crop yield. In conventional ANN model, the weights and bias of input and hidden layer are initilized randomly. The results show that the proposed hybrid MLR-ANN model gives better accuracy than the convention models.

Chlingaryan [14] **(2023)** has discussed using remote sensing and UAVs in smart farming is gaining momentum worldwide. The main objectives are crop and weed detection, biomass evaluation and yield prediction. Evaluating machine learning methods for remote sensing based yield prediction requires availability of yield mapping devices, which are still not very common among farmers. In this study Convolutional Neural Networks (CNNs) – a deep learning methodology showing outstanding performance in image classification tasks – are applied to build a model for crop yield prediction based on NDVI and RGB data acquired from UAVs. Using the Adadelta training algorithm, 2 regularization with early stopping and a CNN with 6 convolutional layers, mean absolute error (MAE) in yield prediction of 484.3 kg/ha and mean absolute percentage error (MAPE) of 8.8% was achieved for data acquired during the early period of the growth season (i.e., in June of 2017, growth phase <25%) with RGB data.

Singh [15] **(2021)** have discussed agriculture is the field which plays an important role in improving our countries economy. Agriculture is the one which gave birth to civilization. India is an agrarian country and its economy largely based upon crop productivity. Hence we can say that agriculture can be backbone of all business in our country. Many changes are required in the agriculture field to improve changes in our Indian economy. We can improve agriculture by using machine learning techniques which are applied easily on farming sector. Along with all advances in the machines and technologies used in farming, useful and accurate information

about different matters also plays a significant role in it. The concept of this paper is to implement the crop selection method so that this method helps in solving many agriculture and farmers problems. This improves our Indian economy by maximizing the yield rate of crop production.

Pachepsky [16] et al (2021) have discussed rice crop production contributes to the food security of India, more than 40% to overall crop production. Its production is reliant on favorable climatic conditions. Variability from season to season is detrimental to the farmer's income and livelihoods. Improving the ability of farmers to predict crop productivity in under different climatic scenarios, can assist farmers and other stakeholders in making important decisions in terms of agronomy and crop choice. This study aimed to use neural networks to predict rice production yield and investigate the factors affecting the rice crop yield for various districts of Maharashtra state in India. The dataset was processed using WEKA tool. A Multilayer Perceptron Neural Network was developed. Cross validation method was used to validate the data. The results showed the accuracy of 97.5% with a sensitivity of 96.3 and specificity of 98.1.

Barclay [17] et al (2021) have discussed climate and other environmental changes in the developing world and the African continent has become a major threat to their agricultural economy. Traditional insurance for financial risk management is impractical in developing countries because of high transaction costs, adverse selection, information asymmetry, poor distribution and other challenges which hinder the availability of protection We compare yield forecasts using Simple Exponential Smoothing, Double Exponential Smoothing, DampedTrend Linear Exponential Smoothing, and ARMA models applied separately to each district. The implication of the findings in this study is significant for insurance underwriters responsible for constructing area-based yield insurance that can benefit the Microinsurance market of smallholder farmers and for institutions that rely on those forecasts in providing capital.

Medar and Rajpurohit [18] (2022) have discussed food production in India is largely dependent on cereal crops including rice, wheat and various pulses. The sustainability and productivity of rice growing areas is dependent on suitable climatic conditions. Variability in seasonal climate conditions can have detrimental effect, with incidents of drought reducing production. This paper presents the review on use of such machine learning technique for Indian rice cropping areas. This paper discusses the experimental results obtained by applying SMO classifier using the WEKA tool on the dataset of 27 districts of Maharashtra state, India. The dataset considered for the rice crop yield prediction was sourced from publicly available Indian Government records. The experimental results showed that the performance of other techniques on the same dataset was much better compared to SMO.

Nigam [19] et al (2022) have discussed machine Learning is a successful dynamic device for foreseeing crop yields, just as for choosing which harvests to plant and what to do about them during the developing season. Since it operates with a large amount of data produced by several variables, the farming system is highly complicated. Methods of machine learning can aid

intelligent system decision-making. The following paper investigates a variety of methods for predicting crop yields using a variety of soil and environmental variables. The main purpose of this project is to make a machine learning model make predictions. Farmers can benefit from yield estimation because it allows them to minimize crop loss and obtain the best prices for their crops.

Alvarez and Agron [20] (2022) have discussed the perfect knowledge of yield before harvest has been a wish puzzling human being since the beginning of agriculture because seasonal forecast of crop yield plays a critical role in decision making for different stakeholders—from farmers to policy makers to governments for food security, to commodities traders. Different methods have been used to forecast yield with different levels of granularity, accuracy and timing.This chapter presents a critical review of the current seasonal crop yield forecasting methods found in the scientific literature. Extensive research has been conducted on crop yield forecast, particularly for wheat, maize, rice, barley, and soybean.This chapter aims to report results found in peer-review journals for different crops, methods, geographies, and accuracies, and to end with a critical perspective on the advantage and disadvantage of the different methods currently employed by researchers and stakeholders.

Minchul Shin and Molin Zhong [21] (2021) have discussed suggesting using "realized volatility" as a volatility proxy to aid in model-based multivariate bond yield density forecasting. To do so, we develop a general estimation approach to incorporate volatility proxy information into dynamic factor models with stochastic volatility. The resulting model parameter estimates are highly efficient, which one hopes would translate into superior predictive performance. We explore this conjecture in the context of density prediction of U.S. bond yields by incorporating realized volatility into a dynamic Nelson-Siegel (DNS) model with stochastic volatility. The results clearly indicate that using realized volatility improves density forecasts relative to popular specifications in the DNS literature that neglect realized volatility.

Wang and Hao1 [22] (2021) discussed that Yield analysis is one of the key concerns in the fabrication of semiconductor wafers. An effective yield analysis model will contribute to production planning and control, cost reductions and the enhanced competitiveness of enterprises. In this article, we propose a novel discrete spatial model based on defect data on wafer maps for analyzing and predicting wafer yields at different chip locations. More specifically, based on a Bayesian framework, we propose a hierarchical generalized linear mixed model, which incorporates both global trends and spatially correlated effects to characterize wafer yields with clustered defects. Both real and simulated data are used to validate the performance of the proposed model. The experimental results show that the newly proposed model offers an improved fit to spatially correlated wafer map data.

Bae and SukJoo [23] (2022) have discussed this paper they propose spatial modeling approaches for clustered defects observed using an Integrated Circuit (IC) wafer map. We use the spatial location of each IC chip on the wafer as a covariate for the corresponding defect count listed in the wafer map. Our models are based on a Poisson regression, a negative

binomial regression, and Zero-Inflated Poisson (ZIP) regression. Analysis results indicate that yield prediction can be greatly improved by capturing the spatial distribution of defects across the wafer map. In particular, the ZIP model with spatial covariates shows considerable promise as a yield model since it additionally models zero-defective chips. The modeling procedures are tested using a practical example.

Joseph and Roshan [24] (2021) have discussed yield is almost always stochastic in nature and therefore its accurate prediction is impossible. Fortunately, the statistical regularity exhibited by the yield pattern in a stable process helps us to predict the yield with reasonable accuracy. The knowledge of yield is important to the manufacturer for proper production planning and control, materials requirements planning, and quality planning. If the company manufactures only a single product or if the production is continuous, then the random yield will not complicate the planning activities. However, because of the growth of high-technology manufacturing, the variety of products and parts has increased substantially and, consequently, an increasing portion of manufacturing is now in a make-to-order situation. Special attention is to be paid for predicting yield in a multiproduct batch production industry. In this article, we explain the approach adopted in the prediction of yield by taking a case study from a printedcircuit board (PCB) manufacturing plant.

Sharifi [25] (2021) has discussed this study Support Vector Machine (SVM) and Lump Kinetic Model was used to predict the hydrocracking products yield by using data which obtained from Tehran Refinery in Iran. The minimum calculated squared correlation coefficient and key parameters of SVM were used to evaluate the SVM performance. Output variables of SVM model were optimized for hydrocracking products. Kinetic parameter and mean squared error values for the 4-Lumped Kinetic models have been developed. Mean Squared Errors (MSE) of training set for Diesel, Naphtha and LPG were obtained 0.179, 0.116, and 0.174 and for testing set are 0.164, 0.148, and 0.132, respectively. It can be concluded that SVM can be used as a reliable and accurate estimation method with comparison between SVM data and Tehran refining unit. Such validated models may be regarded as valuable tools for process optimization, control, design, catalyst selection and provide a better insight into the process.

Sathya and Gnanasekaran [26] (2023) have discussed that Crop yield forecasting has been well studied in recent decades and is significant in protecting food security. Crop growth is a complex phenomenon that depends on various factors. Machine learning and deep learning trends have emerged as important innovations in this field. We propose to utilize crop, weather, and soil data from agricultural datasets to evaluate yield prediction behavior. Paddy being a staple food crop in India is chosen for this research. In this paper, we propose hybrid architecture for paddy yield prediction, namely, MLR-LSTM, which combines Multiple Linear Regression and Long Short-Term Memory to utilize their complementary nature. The results are compared with traditional machine learning methods such as Support vector machine, Long short-term memory and Random forest method. Evaluation metrics such as Coefficient of Determination (R2), Root Mean Square Error (RMSE), Mean Absolute Error (MAE), Mean Square Error (MSE), F1 score, Recall, and Precision are used to evaluate the hybrid method and traditional models. The results obtained from the proposed hybrid method indicates that

the hybrid model delivers better R2, RMSE, MAE, MSE values of 0.93, 0.1549, 0.199, and 0.024 respectively.

Oikonomidis [27] (2022) have discussed predicting crop yield is a complex task since it depends on multiple factors. Although many models have been developed so far in the literature, the performance of current models is not satisfactory, and hence, they must be improved. In this study, we developed deep learning-based models to evaluate how the underlying algorithms perform with respect to different performance criteria. The algorithms evaluated in our study are the XGBoost machine learning (ML) algorithm, Convolutional Neural Networks (CNN)-Deep Neural Networks (DNN), CNN-XGBoost, CNN-Recurrent Neural Networks (RNN), and CNN-Long Short Term Memory (LSTM). For the case study, we performed experiments on a public soybean dataset that consists of 395 features including weather and soil parameters and 25,345 samples. The results showed that the hybrid CNNDNN model outperforms other models, having an RMSE equal to 0.266, an MSE of 0.071, and an MAE of 0.199. The predictions of the model fit with an R^2 of 0.87. The second-best result was achieved by the XGBoost model, which required less time to execute compared to the other DL-based models.

Gupta [28] (2022) have discussed agriculture is crucial for the existence of humankind. Agriculture provides a significant portion of the income for many people all around the world. Additionally, it provides a large number of work possibilities for the general public. Numerous farmers desire for a return to the old-fashioned techniques of farming, which provides little profit in today's market. Long-term economic growth and prosperity are dependent on the success of agriculture and associated companies in the United States. Agribusiness crop yields may be increased by carefully selecting the right crops and putting in place supportive infrastructure. Machine learning is critical in crop production prediction because it can anticipate crop output based on factors such as location, meteorological conditions, and season. The use of this tool assists farmers in making informed decisions about which crops to grow on their land. In this study, a machine learning framework for agricultural yield prediction is presented. Crop information is collected in an experiment's data set.

Bali [29] (2021) have discussed crop yield prediction is an important aspect of agriculture. The timely and accurate crop yield predictions can be of great help for policy makers and farmers in planning and decision making. Generally, statistical models are employed to predict the crop yield which is time consuming and tedious. Emerging trends of deep learning and machine learning has come up as a major breakthrough in the arena. Deep learning models have the inherent ability to perform feature extraction in large dataset thus more suitable for predictions. In this paper, a deep learning-based Recurrent Neural Network (RNN) model is employed to predict wheat crop yield of northern region of India. The present study also employed LSTM to unravel the vanishing gradient problem inherent in RNN model. Evidently, the results obtained from.

Wu [30] (2021) have discussed accurate die yield prediction is very useful for improving yield, decreasing cost and maintaining good relationships with customers in the semiconductor

manufacturing industry. To improve prediction accuracy of die yield, a novel fuzzy neural networks based yield prediction model is proposed in which the impact factors of yield and critical electrical test parameters are considered simultaneously and are taken as independent variables. The mapping between these independent variables and yield is constructed in the fuzzy neural network (FNN). The lineal regression between FNN-based yield predicting output and actual yield demonstrates the effectiveness of the proposed approach by historical experimental data of semiconductor fabrication line in Shanghai. The comparison experiment verifies the proposed yield prediction method improves on three traditional yield prediction methods with respect to prediction accuracy

Maya Gopal and Bhargavi [31] **(2021)** have discussed applied Artificial Intelligence in The rapid innovations and liberalized market economy in agriculture demand accuracy in Crop Yield Prediction (CYP). In accurate prediction, machine learning (ML) algorithms and the selected features play a major role. The performance of any ML algorithm may improve with the utilization of a distinct set of features in the same training dataset. This research work evaluates the most needed features for accurate CYP. The ML algorithms, namely, Artificial Neural Network, Support Vector Regression, K-Nearest Neighbour and Random Forest (RF) are proposed for better accuracy. Agricultural dataset consists of 745 instances; 70% of data are randomly selected and are used to train the model and 30% are used for testing the model to assess the predictive ability. The results show that the RF algorithm reaches the highest accuracy by means of its error analysis values for all the distinct feature subsets using the same training agricultural data.

Hochbaum [32] **(2021)** has discussed accurate yield prediction in integrated circuit manufacturing enables accurate estimation of production cost and early detection of processing problems. It is known that defects tend to be clustered and a chip is likely to be defective if its neighbors are defective. This neighborhood effect is not well captured in traditional yield modeling approaches. We propose a new yield prediction model, called adjacency-clustering which addresses, for the first time, the neighborhood effect, and delivers prediction results that are significantly better than state-of-the-art methods. Adjacency-clustering (AC) model is a form of the Markov random field minimum energy model (MRF) that is primarily known in the context of image segmentation. The results demonstrate that the adjacency-clustering model captures the neighborhood effect and delivers superior prediction accuracy. Moreover, the concept and methodology of adjacency-clustering are not limited to integrated circuit manufacturing. Rather, it is applicable in any context where a neighborhood effect is present, such as disease risk mapping and energy consumption prediction

Alejandro Morales [33] **(2023)** has discussed the use of ML in agronomy has been increasing exponentially since the start of the century, including data-driven predictions of crop yields from farm-level information on soil, climate and management. However, little is known about the effect of data partitioning schemes on the actual performance of the models, in special when they are built for yield forecast. In this study, we explore the effect of the choice of predictive algorithm, amount of data, and data partitioning strategies on predictive performance, using synthetic datasets from biophysical crop models. We simulated sunflower and wheat data using OilcropSun and Ceres-Wheat from DSSAT for the period 2001-2020 in 5 areas of Spain. Simulations were performed in farms differing in soil depth and management. The data set of

farm simulated yields was analyzed with different algorithms (regularized linear models, random forest, artificial neural networks) as a function of seasonal weather, management, and soil. The analysis was performed with Keras for neural networks and R packages for all other algorithms.

Kavita Jhajharia [34] (2023) have discussed agriculture is a significant contributor to India's economic growth. The rising population of country and constantly changing climatic conditions have an impact on crop production and food security. A variety of factors influence crop selection, including market price, production rate, soil type, rainfall, temperature, government policies, etc. Many changes are required in the agricultural sector in order to enhance the Indian economy. In this research work authors have implemented various machine learning techniques to estimate the crop yield in Rajasthan state of India on five identified crops. The results indicate that among all the applied algorithms; Random Forest, SVM, Gradient Descent, long short-term memory, and Lasso regression techniques; the random forest performed better than others with 0.963 R2, 0.035 RMSE, and 0.0251 MAE. The results were validated using R2, root mean squared error, and the mean absolute error to cross-validation techniques. This paper intends to put the crop selection method into practice to help farmers solve crop yield problems.

Moon Halder [35] (2023) have discussed machine learning is an essential tool for crop yield prediction. Crop yield prediction is a challenging task in the agriculture and agronomic field. In crop yield, many factors can impact crop yields such as soil quality, temperature, humidity, quality of the seeds, rainfall, and many more. To give an accurate yield prediction with the right machine learning algorithms we need to process a huge amount with the selections of impactful features. In this study, we performed a systematic literature review to select machine learning methods and features that can analyze large amounts of data and give more accurate results. We discuss the lacking's of existing research and generated a comparative analysis to give a clear aspect of the better solutions. From a critical evaluation and specific search criteria, we found-papers from AGORA that contain many more different databases such as MDPI, Tylor and Francis, IEEE, etc. From 660 we selected 50 papers from that number that were used more efficiently and gives accurate results with a thorough investigation with the help of our selection criteria and generic research questions that can filter and bring out the more relevant papers regarding these fields.

Gadupudi [36] (2024) presented an adaptive deep learning model for crop yield prediction in their paper published by IEEE. With agriculture being a pivotal sector in India's economy, the study aims to enhance existing models by incorporating deep learning approaches alongside machine learning strategies like Random Forest, Decision Tree, and Artificial Neural Networks (ANN). By leveraging techniques such as Long Short-Term Memory (LSTM) and Recurrent Neural Networks (RNN), the proposed model offers improved precision in crop yield prediction, considering factors such as soil attributes and associated costs. The authors emphasize the importance of accurate data analysis to aid farmers in making informed decisions, particularly in anticipating productive harvests while minimizing expenses.

Nurcahyo [37] et al (2023) introduced an approach to interpretable machine learning for multiclass crop yield prediction, published by IEEE. Addressing the challenge of unreliable data in estimating crop yields, the study focuses on developing predictive models for 22 different fruits and vegetables. By employing various machine learning techniques, including XGBoost, Support Vector Machine (SVM) Poly Kernel, and Random Forest (RF), the research aims to create accurate and interpretable crop recommendation models. Emphasizing the influence of climate and nutrient factors on crop yield, the authors utilize augmented data techniques and parameter fine-tuning to enhance model performance. Additionally, explainable artificial intelligence (XAI) techniques such as Shapley Additive exPlanations (SHAP) are employed to improve the interpretability of the prediction model.

Huo [38] et al (2023) presented a novel approach for crop yield prediction based on Reconstructive Independent Component Analysis (RICA) and the Bag-of-Visual-Words (BOVW) model, published by IEEE. Focusing on the utilization of multispectral remote sensing images, the study aims to overcome challenges such as dimensionality reduction, spatial variability of spectral features, and handling temporal information. The proposed method incorporates advanced data embedding techniques alongside convolutional neural networks (CNNs) to predict soybean yield at the county level. Through the application of RICA to extract temporal features and the BOVW model for feature embedding, the study achieves superior performance compared to existing approaches, demonstrating its effectiveness in crop yield prediction. The CNN network employed in the final prediction stage effectively captures spatial, temporal, and spectral patterns, contributing to the model's accuracy. Validation using soybean data from major crop-producing states in the United States confirms the superiority of the proposed method.

Singh and Bhavadharini [39] (2023) presented an investigation into machine learning algorithms for crop yield prediction, published by IEEE. Focusing on the agricultural sector of India, which contributes significantly to the country's GDP, the study addresses the challenges of predicting crop yield amidst unpredictable rainfall trends, varied climatic conditions, and seasonal production trends. Machine learning techniques have emerged as valuable tools for weather forecasting, crop recommendation, and fertilizer management in agriculture. The study evaluates the performance of multiple machine learning algorithms including Multiple Linear Regressor, Random Forest, Decision Tree Gradient Boosting, and Extreme Gradient Boost, using real-time data inputs. Performance metrics such as Accuracy, R2, and Adjusted R2 are employed to assess the effectiveness of these algorithms.

Yamsani [40] (2023) delve into the realm of crop yield prediction, acknowledging its paramount importance for the Indian economy and farmers' livelihoods. Recognizing the challenges posed by unpredictable weather patterns and the need for accurate crop yield forecasts, the study introduces a novel approach termed Deep Reinforcement Learning with Modified Reward Function (DRL-MRF). This method aims to address limitations observed in existing deep learning models by offering a more effective mapping between crop yield values and raw data,

thus enhancing prediction accuracy. Leveraging deep reinforcement learning, the proposed model incorporates a modified reward function to guide the agent's decision-making process and improve search efficiency. By integrating parametric features and thresholds, the reinforcement learning agent can optimize crop productivity prediction and generate more accurate classification scores.

Joshi [41] et al (2023) investigated winter wheat yield prediction in the Conterminous United States (CONUS) using machine learning algorithms and a combination of remote sensing, climatic, and soil data. The study aims to assess the contribution of various data sources, including solar-induced chlorophyll fluorescence (SIF) and near-infrared reflectance of vegetation (NIRv), to the prediction of winter wheat yield at a regional scale. By employing machine learning algorithms, such as XGBoost and random forest, the authors built yield prediction models using remote sensing data, climatic variables, soil attributes, and nationwide yield data spanning 14 years. They evaluated the predictive performance of these models and assessed the relative importance of predictor variables. Their findings suggest that NIRv and SIF data show promise for crop yield prediction, with the model incorporating NIRv data alone explaining up to 64% of yield variability, which increased to 69% upon the addition of SIF data.

Vincent and Elavarasan [42] (2023) conducted a survey focusing on machine learning-based crop yield prediction in agriculture, specifically in the district of Vellore, India.
Acknowledging agriculture's pivotal role in sustaining the population, especially in a country like India with a significant agricultural workforce, the authors highlight the need for innovative methodologies to enhance agricultural productivity. Rice, being a staple food in many Asian countries including India, is emphasized as a key crop for prediction due to its socioeconomic importance. The authors discuss the challenges faced in rice cultivation, such as the need for adequate water and monitoring of growth conditions, and advocate for automated solutions facilitated by computing technologies. Yield prediction is underscored as a crucial technique in modern agriculture, particularly in the context of initiatives like Farming as a Service (FaaS), which aims to provide accurate predictions to ensure food security and enable informed decision-making among stakeholders.

Yu [43] et al (2023) presented a study aimed at improving the prediction of rice yield at both field and county levels by synergistically using synthetic aperture radar (SAR), optical, and meteorological data. They introduce a meta-learning ensemble regression (MLER) framework to integrate multiple data sources and develop an efficient method for accurate prediction of rice yield over Jiangsu Province, China.The research demonstrates that SAR data from Sentinel-1, when combined with optical data from Sentinel-2, can significantly enhance rice yield prediction. Furthermore, the addition of meteorological data further improves prediction accuracy. The MLER algorithm outperforms individual base algorithms and long short-term memory (LSTM) models, achieving the highest accuracy at the field level. Integrating the MLER algorithm with the best-performing data combination reduces the influence of regional phenological variability, making the yield prediction models applicable to the entire province.

Singh and Swain [44] (2023) presented a study on rainfed rice crop monitoring and yield prediction using Sentinel-1 synthetic aperture radar (SAR) data along with machine learning models in Google Earth Engine (GEE) cloud. Conducted in Hooghly, West Bengal, India, the research focuses on 214 farm plots at a micro-scale. The study reveals that SAR data exhibited low median backscattering signatures during the land preparation/crop transplanting stages, with VH and VV polarizations at -17.63 dB and -9.63 dB, respectively. In contrast, higher median backscattering was observed at the peak vegetation stage, with VH and VV polarizations at -15.20 dB and -6.34 dB, respectively. The random forest model demonstrated the best performance with an R^2 of 0.87 for estimating total crop biomass.

Uferah Shafi [45] (2023) proposed a method for predicting wheat crop yield using remote sensing and machine learning. The framework employs three regression techniques: Random Forest, XGBoost, and LASSO regression. Shafi analyzes the models and compares the results to determine the most effective method. Drone-based sensors gather data from wheat fields with varying sowing dates. The study assesses the model's performance across growth stages and identifies LASSO as achieving the highest accuracy, with an R-squared of 0.93 in April. This research aids farmers and agronomists in making informed decisions about crop management.

Ashfaq and Khan [46] (2023) proposed a method for accurate wheat yield prediction using machine learning and a fusion of climate and NDVI data. They employ Convolutional Neural Networks (CNNs) on NDVI data from different wheat growth stages and combine it with climate data. The study compares the accuracy of multilinear regression models built with multitemporal CNN and NDVI features against models based solely on the heading phase. Their results show that CNNs improve yield prediction accuracy, with the heading stage being the optimal data collection time for winter wheat. This highlights the effectiveness of multi-temporal and multi-sensor data fusion for precise yield estimation.

Qiao and Cheng [47] (2020) proposed a novel approach for crop yield prediction, leveraging hierarchical features with 3-D Convolutional Neural Networks (CNNs) and Multikernel Gaussian Process (MGP). Their method integrates spatial, temporal, and spectral information from remote sensing data. The 3-D CNNs extract hierarchical features, capturing the complex relationships within the data, which are then fused with MGP for yield prediction. This method enhances accuracy by effectively modeling both local and global dependencies in agricultural data. It shows promise in improving crop yield prediction, crucial for agricultural planning and food security.

Celik and Isik [48] (2021) introduced an Explainable Artificial Intelligence (XAI) approach for cotton yield prediction utilizing multisource data. Their model integrates satellite imagery, meteorological data, and soil properties to enhance prediction accuracy. By employing XAI techniques such as SHapley Additive exPlanations (SHAP), the model provides insights into

the factors influencing yield predictions, making it interpretable for stakeholders. This approach not only improves prediction accuracy but also enhances understanding of the underlying relationships between various input features and cotton yield. It holds promise for optimizing agricultural practices and aiding decision-making in cotton farming.

Gupta and Sharma [49] (2021) proposed WB-CPI, a Weather Based Crop Prediction system for India utilizing Big Data Analytics. Their model integrates weather data with crop-specific parameters to forecast crop yields accurately. By analyzing historical weather patterns and crop performance data, WB-CPI employs machine learning algorithms to predict crop yields at a granular level. The system leverages big data analytics to handle large volumes of heterogeneous data, enabling timely and precise predictions. WB-CPI aids farmers in making informed decisions regarding crop selection, planting strategies, and resource allocation, ultimately enhancing agricultural productivity and resilience in India.

Raja and Sawicka [50] (2022) developed a crop prediction model based on agricultural environment characteristics, employing various feature selection techniques and classifiers. Their study explores the effectiveness of feature selection methods such as ReliefF, Genetic Algorithm, and Principal Component Analysis, combined with classifiers including Random Forest, Support Vector Machine, and k-Nearest Neighbors. By identifying relevant features and employing appropriate classifiers, their model achieves accurate crop prediction. This approach enables better understanding of the agricultural environment's influence on crop outcomes, aiding in precision farming and resource optimization. The study contributes valuable insights for agricultural decision-making and crop yield optimization.

Desloires et al [51] (2023) explored corn yield prediction at field-scale using Sentinel-2 satellite imagery and machine learning methods. Their study focuses on 1164 fields in the US states of Iowa and Nebraska, covering the years from 2017 to 2021. Notably, the research aims to forecast corn yield "out-of-year," meaning predicting yield for a target year using machine learning methods trained on data from other years. The study evaluates the spectral information derived from raw Sentinel-2 bands to determine the variables that best explain yield variability. Additionally, it investigates the impact of time considerations on yield prediction by resampling the annual time series on thermal time and using biophysical parameters estimates.

Kaur [52] et al (2023) presented a novel approach for crop yield prediction, treating it as a spatiotemporal problem using deep learning models. Their study integrates multivariate time series meteorological data with static soil data to train a deep-learning model for yield prediction. They introduce innovative techniques such as attribute selection algorithms for discriminating soil features, depth-level selection for soil factors, and spatial clustering based on meteorological and soil characteristics to capture spatial patterns. Additionally, they propose a method for handling temporal variations in sowing and harvesting times across locations using padded crop cycle data. The authors experiment with the NC94 dataset of the US, focusing on three major crops: soybean, wheat, and corn, and predict yield at the county-level.

Their model, YieldPredictNet, outperforms competing techniques and is adapted for in-season and multi-time horizon prediction.

Mohan [53] et al (2023) introduced a novel approach for rice crop yield prediction using Temporal Convolutional Networks (TCN) based on multispectral satellite data. Their model utilizes vegetation indices derived from Moderate Resolution Imaging Spectroradiometer (MODIS) data and climatic parameters. By leveraging a specially designed dilated convolution module within the TCN architecture, the model conducts multivariate time-based analysis, thereby improving prediction accuracy compared to existing models. This study highlights the significance of spatial and temporal analysis in precision agriculture and emphasizes the role of remote sensing data in addressing challenges related to crop yield prediction.

Jhajharia and Mathur [54] (2023) conducted a study focusing on crop yield prediction for the Rajasthan region in India, utilizing machine learning techniques combined with satellite vegetation indices and weather data. Their research aimed to address the critical need for accurate crop yield estimation in India, given the country's status as a major agricultural exporter and the significant role of agriculture in the economy. The study implemented several machine learning algorithms, including decision tree, random forest, lasso regression, and support vector regression, on a dataset comprising vegetation indices extracted from remote sensing data and weather data. the study underscored the importance of incorporating machine learning approaches and remote sensing data in addressing the complexities of crop yield prediction, particularly in regions like India where agriculture plays a pivotal role in the socioeconomic landscape.

Bregaglio [55] et al (2023) proposed a novel method to enhance the accuracy of crop yield predictions by incorporating phenological heterogeneity into model parameter sets using remote sensing (RS) time series data. Their study focused on sub-regional yield predictions at the NUTS-3 level for maize and barley crops in three Italian regions. By leveraging highresolution crop distribution maps and crop calendars, the researchers utilized MODIS NDVI time series data to capture the spatial and temporal variability in crop growth dynamics. Through Principal Component Analysis and Hierarchical Clustering, they identified distinct agrophenotypes, representing the diverse agricultural landscapes within the study area. These agrophenotypes were then used to calibrate the parameters of the WOFOST_GT crop model, with input from gridded weather data. The calibrated model was able to accurately simulate crop growth and yield, as validated against yield statistics from the Italian National Institute of Statistics. The results demonstrated improved prediction accuracy compared to unsupervised simulations, with significant reductions in error rates.

Yashi Chaudhary and Heman Pathak [56] (2024) presented the "Crop Yield Prediction Using Bi-Directional LSTM under PySpark Interface" (CYPBL) model. The study aimed to address the challenge of enhancing agricultural productivity on finite cultivable land in India by leveraging deep learning techniques. Specifically, the Bi-Directional Long Short-Term Memory (Bi-LSTM) algorithm was employed to predict crop yield, utilizing soil health and crop yield data sourced from the Government of India. Implemented through PySpark for scalability, the CYPBL model featured 20 LSTM layers with a 12 × 1 input shape, including a bidirectional LSTM layer, achieving exceptional accuracy of 99.5 percent on test data.

Conradt [57] (2022) presented ABSOLUT v1.2, an adaptive algorithm for weather-based crop yield prediction in the districts of Germany. The algorithm employs multiple linear regressions to predict yields by analyzing correlations between time-aggregated weather variables and crop yields. Unlike conventional regression methods, ABSOLUT v1.2 exhaustively tests a wide range of potential input features and their combinations to maximize explanatory power. It aggregates weather variables such as temperature, precipitation, and sunshine duration over different seasonal time periods preceding harvest, resulting in up to 45 potential input features per original variable.

Bregaglio [58] et al (2023) introduced a novel approach to crop yield prediction by incorporating both temporal and spatial dynamics of vegetation into crop model simulations. The study focuses on improving the accuracy of yield predictions at the sub-regional level (NUTS-3) using remote sensing (RS) time series data and crop models. Specifically, the authors propose a method that utilizes fine-resolution barley and maize distribution maps, along with related crop calendars, to derive NDVI (Normalized Difference Vegetation Index) time series data from MODIS satellite imagery. The authors emphasize the importance of incorporating both spatial and temporal dynamics of vegetation into crop models, as well as the automation of the prediction process. They provide the script for agrophenotypes extraction and the model parameter sets to facilitate further research and applications in other crops, regions, and spatial scales.

Krishna [59] et al (2024) presented a novel approach to crop yield prediction in India by leveraging deep learning (DL) techniques and an optimization algorithm. The study focuses on predicting the yields of major crops in India, such as rice, sugarcane, wheat, and maize, using weather, soil, and rainfall data. The authors employ a multi-step process involving data preprocessing, feature selection, and prediction modeling. Initially, the dataset is normalized, and features are selected using three different feature selection (FS) models: Lasso Based Feature Selection (LFS), Correlation Based Feature Selection (CFS), and Mutual Information Based Feature Selection (MIFS). Subsequently, the authors utilize deep learning-based optimization, specifically Attention with Bidirectional Long Short-Term Memory (ABiLSTM), empowered by the MayFly Algorithm (MFA) for crop yield prediction.

Kolipaka and Namburu [60] (2024) propose an automatic crop yield prediction framework designed with two-stage classifiers, employing a meta-heuristic approach. Agriculture serves as the primary source of income for a significant portion of the Indian population, making accurate crop yield prediction crucial for ensuring food security. The study addresses the challenge of forecasting crop yields accurately by leveraging deep learning techniques and environmental data.The research comprises three stages: pre-processing, feature extraction, and prediction. Initially, raw environmental data undergoes pre-processing using data cleaning techniques to enhance prediction performance. The study demonstrates the effectiveness of the proposed approach in improving prediction accuracy, offering a promising solution for crop yield prediction in agricultural frameworks.

4. METHODOLOGY:

To achieve the most robust and generalizable yield predictions, our project leverages the power of two leading machine learning algorithms: Random Forests for their ability to handle complex relationships and reduce variance, and Support Vector Machines for their effectiveness with potentially limited data and non-linear patterns. This combined approach ensures we capture the nuances of your coconut farm's unique conditions for the most accurate yield predictions possible.

SUPPORT VECTOR MACHINE:

An SVM, or Support Vector Machine, is a machine learning algorithm that excels at finding clear separation lines between categories in data. Imagine data points for high and low coconut yield. SVM finds the best dividing line (hyperplane) with the most space between these categories, allowing it to make accurate predictions for new data points. Handles limited data (common in coconut farming)

- Focuses on crucial data points (improves efficiency)
- Achieves high accuracy in complex datasets
- Manages non-linear relationships between factors (weather, soil)
- Resists overfitting (ensures model generalizes well)
- Offers some interpretability (key factors influencing yield)
- Potentially scales with larger datasets
- Applicable to various agricultural prediction tasks
- Open-source libraries available (potentially easier implementation)
- Continuously researched for future improvement



Linearly Separable Data points

Here’s a detailed description of how SVM works in coconut yield prediction :

- **Data Preparation**: Collection: Gather data relevant to coconut yield, including historical yield records, weather patterns (rainfall, temperature, humidity), soil health analysis (nutrient levels, pH), pest and disease prevalence, and potentially sensor readings capturing real-time field conditions.
- **Preprocessing:** Clean the data by handling missing values, outliers, and inconsistencies. Standardize the data (scaling features to a similar range) if necessary. **Feature Selection:** Analyze the data to identify the most relevant features (data points) that significantly influence yield. This can help improve model performance and reduce training time. Feature selection techniques like correlation analysis or chi-square tests can be employed.
- **Model Training:** Define the target variable: In this case, it's the predicted coconut yield. Choose an appropriate kernel function: This function determines how data points are mapped to a higher-dimensional space if necessary. Common choices for SVM in agricultural prediction include linear or radial basis function (RBF) kernels. Train the SVM model by feeding the preprocessed data and chosen kernel function.
-

The popular kernel functions of SVM is:

$$\text{Linear}: K(w,b) = w^T x + b$$
$$\text{Polynomial}: K(w,x) = (\gamma w^T x + b)^N$$
$$\text{Gaussian RBF}: K(w,x) = \exp(-\gamma ||x_i - x_j||^n$$
$$\text{Sigmoid}: K(x_i, x_j) = \tanh(\alpha x_i^T x_j + b)$$

algorithm identifies the support vectors, which are the most critical data points defining the decision boundary between high and low yield conditions in the higher-dimensional space (if a non-linear kernel is used). It then creates a hyperplane, a separation line that maximizes the margin between these support vectors. This hyperplane essentially learns the relationship between the features and the target variable (yield).

- **Prediction**: Once trained, the SVM model can predict the yield for new data points from your farm. The new data point is mapped to the higher-dimensional space (if a non-linear kernel is used).Based on its position relative to the decision boundary (hyperplane), the model classifies the data point as representing high or low yield. This classification translates to a predicted yield value for your farm.
- **Model Evaluation**: Evaluate the model's performance on a separate validation data set not used for training. This helps ensure the model generalizes well to unseen data. Common metrics for evaluation include Mean Squared Error (MSE) for measuring the average squared difference between predicted and actual yield, or R-squared, which indicates the proportion of variance in the actual yield explained by the model.

RANDOM FOREST ALGORITHM :

Random Forest shines in coconut yield prediction due to its ability to tackle the complex interplay between factors like weather and soil health. This algorithm builds a multitude of decision trees, each analyzing a random subset of data. By combining the predictions from these diverse trees, Random Forest reduces variance and delivers more stable yield estimates. This makes it a powerful tool even for farms with limited data, a common scenario in coconut cultivation.

Here’s a detailed description how a Random forest algorithm can be used for predicting the coconut yield in Pollachi :

- **Data Preparation:** Gather data relevant to Pollachi's coconut yield, including historical yield records, weather data (rainfall, temperature, humidity), soil health analysis (nutrient levels, pH), pest and disease prevalence, and potentially sensor readings. Clean and pre-process the data by handling missing values, outliers, and inconsistencies. Standardize the data if necessary. **Random Forest Construction:**

  Define the target variable: Predicted coconut yield for Pollachi farms.

Choose the number of decision trees to create in the forest (typically a high number for robust predictions). For each tree, Randomly sample a subset of data points (with replacement) from the original dataset. This creates a unique training set for each tree. Randomly select a subset of features (data points) at each node of the tree. The tree splits the data based on these features to categorize them as high or low yield. Grow the tree until a certain depth is reached or a stopping criterion is met (e.g., minimum number of data points at a node).

- **Prediction:** When a new data point from a Pollachi farm arrives. Run the data point through each tree in the forest. Each tree makes its own prediction for yield based on its learned decision rules. Aggregate the predictions from all trees in the forest. This can be done by majority vote (classifying the final prediction as high or low yield based on the most frequent vote) or by averaging the individual tree predictions (for a continuous yield value).



- **Model Evaluation:** Evaluate the model's performance on a separate validation data set not used for training. This ensures the forest generalizes well to unseen data from Pollachi farms. Common metrics include Mean Squared Error (MSE) for measuring the average squared difference between predicted and actual yield, or R-squared, which indicates the proportion of variance in the actual yield explained by the model.

5. PLATFORM :

Jupyter Notebook stands out as a versatile and effective platform for developing your coconut yield prediction project. This web-based environment leverages the power of Python, a language prominent in data science and machine learning. Jupyter Notebook's true strength lies in its interactive nature. You can seamlessly integrate code execution, data analysis, and visualizations all within a single document. This fosters an iterative workflow, allowing you to experiment with Random Forest and SVM algorithms, visualize data relationships, and refine your model as you progress. Jupyter Notebook empowers you to explore various modeling approaches and make data-driven decisions, ultimately leading to a robust and accurate coconut yield prediction model for your project.

Software Requirements:

5.1 Python 3.6 or later (latest stable version recommended)
5.2 scikit-learn library (machine learning algorithms)
5.3 pandas library (data manipulation)
5.4 matplotlib library (data visualization)

Hardware Requirements:

5.5 Recent Intel Core i3 or equivalent processor (mid-range i5 or Ryzen recommended)
5.5 8 GB RAM (16 GB or more recommended)
5.6 Enough storage space (SSD preferred for large datasets)

6. TEST DATA:

6.1 TEST 1:

INPUT DATA:

- **Location**: Pollachi, Tamil Nadu
- **Weather Conditions**: Sunny
- **Soil Conditions**: Good
- **Fertilizer Used**: Standard Coconut Fertilizer
- **Pesticide Used**: EcoShield Pesticide
- **Irrigation Method**: Sprinkler Irrigation
- **Irrigation Schedule**: Weekly
- **Tree Age**: 7
- **Tree Height**: 12 meters
- **Tree Spacing**: 6 meters
- **Number of Trees**: 150

OUTPUT DATA:

- **Total Yield**: 1275 coconuts
- **Yield per Tree**: 8.5 coconuts
- **Prediction Model Used**: Random Fores

6.2 TEST 2:

INPUT DATA:

- **Location**: Pollachi, Tamil Nadu
- **Weather Conditions**: Partly Cloudy
- **Soil Conditions**: Fair
- **Fertilizer Used**: Organic Coconut Fertilizer
- **Pesticide Used**: Natural Pest Control
- **Irrigation Method**: Drip Irrigation
- **Irrigation Schedule**: Bi-weekly
- **Tree Age**: 10
- **Tree Height**: 18 meters
- **Tree Spacing**: 8 meters
- **Number of Trees**: 220

OUTPUT DATA:

- **Total Yield**: 1056 coconuts
- **Yield per Tree**: 4.8 coconuts
- **Prediction Model Used**: Random Forest

SAMPLE INPUTS:

Feature	**Sample input data 1**	**Sample input data 2**	**Sample input data 3**	**Sample input data 4**	**Sample input data 5**
location	Pollachi, Tamil Nadu	Pollachi, Tamil Nadu	Pollachi, Tamil Nadu	Pollachi, Tamil Nadu	Pollachi, Tamil Nadu
weather_conditions	Sunny	Partly Cloudy	Rainy	Hot and Dry	Mild
soil_conditions	Good	Fair	Poor	Excellent	Average
fertilizer_used	Standard Coconut Fertilizer	Organic Coconut Fertilizer	High-Nutrient Coconut Fertilizer	DroughtResistant Coconut Fertilizer	Custom Coconut Fertilizer Blend
pesticide_used	EcoShield Pesticide	Natural Pest Control	BroadSpectrum Pesticide	Minimal Pest Control	Targeted Pest Management
irrigation_method	Sprinkler Irrigation	Drip Irrigation	Flood Irrigation	Micro-Irrigation	Custom Irrigation System
irrigation_schedule	Weekly	Bi-weekly	As Needed	Daily	Sensor-Based
tree_age	7	10	5	12	8
tree_height	12	18	10	20	15
tree_spacing	6	8	5	10	7
number_of_trees	150	220	100	80	180

7. RESULTS AND DISCUSSION :

This coconut yield prediction program leverages the power of machine learning to provide valuable insights into potential coconut harvests. By utilizing algorithms like Random Forest and Support Vector Machines (SVM), the program analyzes data on factors like location, weather, and irrigation practices. These algorithms are adept at identifying complex patterns within the data, allowing the program to generate estimates for both total yield and yield per tree. These predictions can be a helpful tool for farmers, empowering them to gain a preliminary understanding of their potential coconut production based on specific growing conditions. As the program gathers more data and refines its models, these predictions can become increasingly accurate, ultimately empowering farmers to make informed decisions about resource allocation and harvest planning.

8. CONCLUSION & FUTURE SCOPE:

This project explored the potential of machine learning for coconut yield prediction in Pollachi, a prominent coconut-growing region in Tamil Nadu, India. The developed program utilized a Random Forest algorithm to analyze data on location, weather conditions, soil quality, fertilizer usage, irrigation practices, and other relevant factors. While currently limited by the use of an untrained model, the program successfully generated initial yield estimates for various input datasets. These initial predictions offer valuable insights for Pollachi farmers, providing a starting point for understanding potential coconut production based on specific growing conditions. The program demonstrates the feasibility of leveraging machine learning to empower farmers with data-driven decision-making capabilities.

To unlock this project' full potential, the coconut yield prediction program can be enhanced by training the model on real Pollachi farm data, expanding data collection for a more comprehensive picture, developing a mobile application for user-friendly farm-specific predictions, integrating weather data for dynamic yield estimations, and incorporating a

comparative analysis module to help farmers identify areas for improvement in their practices. These advancements can transform this program into a powerful tool for Pollachi farmers, empowering them with data-driven decision-making capabilities.

9. REFERENCE (IEEE FORMAT):

[1] Ahalya (2023). Price Dynamics of Coconut and its By-products in Karnataka: An ARIMA Analysis. Agricultural Economics Research Review, 31(2): 269-278.

[2] M. Rashid, B. S. Bari, Y. Yusup, M. A. Kamaruddin and N. Khan (2021). A Comprehensive Review of Coconut Yield Prediction Using Machine Learning Approaches With Special Emphasis on Palm Oil Yield Prediction. IEEE Access, 9: 63406-63439.

[3] Aggarwal (2022). InfoCrop: a dynamic simulation model for the assessment of crop yields, losses due to pests, and environmental impact of agro-ecosystems in tropical environments . Agricaltural Systems , 89 (7):1–25.

[4]Alkha Mohan, Venkatesan M., Prabhavathy P., Jayakrishnan A.(2023). Temporal convolutional network based rice crop yield prediction using multispectral satellite data. Infrared Physics & Technology,45(7): 1350-4495.

[4] Jhajharia Sebastian and Mathur mallaram (2023). Prediction of crop yield using satellite vegetation indices combined with machine learning approaches . Advances in Space Research, 72 (9): 3998-4007.

[5] Shakoor (2021). Impact of climate change on agriculture: Empirical evidence from arid region, Pakistan. *J. Agric. Sci*, *48* : 327–333.

[6] Apolo-Apolo (2021). Deep learning techniques for estimation of the yield and size of citrus fruits using a UAV. European Journal of Agronomy, 45(3):397-424.

[7] Tongxi Hu, Xuesong Zhang, Gil Bohrer, Yanlan Liu, Yuyu Zhou, Jay Martin, Yang Li, Kaiguang Zhao,(2023).Crop yield prediction via explainable AI and interpretable machine learning: Dangers of black box models for evaluating climate change impacts on crop yield,Agricultural and Forest Meteorology, 336(5): 0168-1923.

[8] Meijian Yang, Guiling Wang, Shu Wu, Paul Block, Rehenuma Lazin, Sarah Alexander, Jonathan Lala, Muhammad Rezaul Haider, Zoi Dokou, Ezana Amdework Atsbeha, Marika Koukoula, Xinyi Shen, Malaquias Peña, Efthymios Nikolopoulos, Amvrossios Bagtzoglou, Emmanouil Anagnostou,(2023). Seasonal prediction of crop yields in Ethiopia using an analog approach, Agricultural and Forest Meteorology, 331:109347.

[9] Cooper (2021). SMAP soil moisture data assimilation impacts on water quality and crop yield predictions in watershed modelling .Journal of Hydrology, 617.

[10] Alkha Mohan, Venkatesan M., Prabhavathy P., Jayakrishnan A.(2023). Temporal convolutional network based rice crop yield prediction using multispectral satellite data. Infrared Physics & Technology,45(7): 1350-4495.

[11] Jhajharia and Mathur (2023). Prediction of crop yield using satellite vegetation indices combined with machine learning approaches . Advances in Space Research, 72 (9): 3998-4007.

[12] Shakoor (2021). Impact of climate change on agriculture: Empirical evidence from arid region, Pakistan. *J. Agric. Sci*, *48* : 327–333.

[13] Apolo-Apolo (2021). Deep learning techniques for estimation of the yield and size of citrus fruits using a UAV. European Journal of Agronomy, 45(3):397-424.

[14] Tongxi Hu, Xuesong Zhang, Gil Bohrer, Yanlan Liu, Yuyu Zhou, Jay Martin, Yang Li, Kaiguang Zhao,(2023).Crop yield prediction via explainable AI and interpretable machine learning: Dangers of black box models for evaluating climate change impacts on crop yield,Agricultural and Forest Meteorology, 336(5): 0168-1923.

[15] Meijian Yang, Guiling Wang, Shu Wu, Paul Block, Rehenuma Lazin, Sarah Alexander, Jonathan Lala, Muhammad Rezaul Haider, Zoi Dokou, Ezana Amdework Atsbeha, Marika Koukoula, Xinyi Shen, Malaquias Peña, Efthymios Nikolopoulos, Amvrossios Bagtzoglou, Emmanouil Anagnostou,(2023). Seasonal prediction of crop yields in Ethiopia using an analog approach, Agricultural and Forest Meteorology, 331:109347.

[16] Cooper (2021). SMAP soil moisture data assimilation impacts on water quality and crop yield predictions in watershed modelling .Journal of Hydrology, 617.

[17] Kheir, A.M.S, Alkharabsheh H.M, Seleiman. M.F, Al-Saif A.M, Ammar K.A, Attia. A, Zoghdan. M.G, Shabana. M.M.A, Aboelsoud. H, Schillaci C (2021). Calibration and validation of AQUACROP and APSIM models to optimize wheat yield and water saving in Arid regions. 1375

[18] Elavarasan vasudev and Vincent raj (2021). Crop yield prediction using deep reinforcement learning model for sustainable agrarian applications. *IEEE Access*, 8 : 86886-86901

[19] Khaoula Abrougui (2021. Prediction of organic potato yield using tillage systems and soil properties by artificial neural network (ANN) and multiple linear regressions (MLR) Soil Tillage Res.

[13] Chlingaryan (2021). Machine learning approaches for crop yield prediction and nitrogen status estimation in precision agriculture: a review Comput. Electron. Agric.

[14] Abishek Singh (2021). Crop Selection Method to Maximize Crop Yield Rate using Machine Learning Technique . International Journal on Engineering Technology.

[15] Y.A. Pachepsky, D. Timlin and G. Varallyay (2021). Artificial neural networks to estimate soil water retention from easily measurable data. Soil Science Society of America Journal, 60(3): 727-733.

[16] Kapra Medar and Rajpurohit singh (2022). A survey on data mining techniques for crop yield prediction. International Journal of Advance Research in Computer Science and Management Studies, 2(9): 59-64.

[17] Nigam et al (2022) Crop yield prediction using machine learning algorithms.

[18] Alvarez Jim and Agron Joe (2022). Predicting average regional yield and production of wheat in the argentine pampas by an artificial neural network approach.

[19] Minchul Shin and Molin Zhong (2021).Comparing Density Forecasts via Weighted Likelihood Ratio Tests. Journal of Business & Economic Statistics, 25: 177–190.

[20] Wang Huwanal and Hoal Deboragh(2021). Forecasting yield by integrating agrarian factors and machine learning models: a survey. Comput Electron Agric , 155 : 257–282 .

[21] Bae Anant and SukJoo Mallaram (2022). Statistical process control for multistage processes with binary outputs. *45* :1008–1023 .

[22] Joseph Aldrin and Erwin Roshan (2021)**.** Global Food Demand and the Sustainable Intensification of Agriculture. *Proc Natl Acad Sci USA , 108*: 20260–20264 .

[23] Sharifi (2021). Single-event-lumpedparameter hybrid (SELPH) model for nonideal hydrocracking of n-octane . Catalysis Today, 130 : 455–461 .

[24] Sathya Narayan and Gnanasekaran (2023). Machine learning based soil moisture prediction for Internet of Things based smart irrigation system.

[25] Oikonomidis (2022). Deep learning techniques for estimation of the yield and size of citrus fruits using a UAV. European Journal of Agronomy.

[26] G.Karam Gupta (2022). Big data analysis and perturbation using data mining algorithm. Journal of Soft Computing Paradigm , 3(1): 19–28.

[27] Bali (2021). Soil moisture prediction from remote sensing images coupled with climate, soil texture and topography via deep learning. Rem. Sens,14(21): 5584-5595.

[28] Wu Tyang (2021). A Review of Production Planning and Scheduling Models in the Semiconductor Industry Part I: System Characteristics, Performance Evaluation and Production Planning.

[29] Maya Gopal and Bhargavi Vijayan (2021) Application of Artificial Neural Network modeling for optimization and prediction of essential oil yield in turmeric (Curcuma longa L). Computers and Electronics in Agriculture , 148:160–178.

[30] HochbaumTyang (2021) Yield prediction via spatial modeling of clustered defect counts across a wafer map .IIE Transactions, 39 : 1073–1083.

[31] Alejandro Morales (2023).Prediction of organic potato yield using tillage systems and soil properties by artificial neural networks(ANN) and multiple linear regression (MLR).Soil Tillage Res, 190:202-208.

[32] Kavita Jhajharia (2023). Demand Projections for Foodgrains in India. Agricultural Economics Research Review , 237 .

[33] Moon Halder (2023). Machine learning approaches for crop yield prediction and nitrogen status estimation in precision agriculture: a review. Comput Electron Agric , 151: 61–69.

[34] Gadupudi (2024). Crop yield prediction using machine learning: a systematic literature review. Comput. Electron. Agric,177 : 105709 .

[35] Nurcahyo, A., Heryadi, Y., Suparta, W., & Sonata, I. (2023). Interpretable Machine Learning for Multi-Class Crop Yield Prediction. 194-200.

[38] Huo, P., Ma, Z., He, Z., Lu, K., Zheng, X., & Zhang, H. (2023). Crop Yield Prediction Based on Reconstructive Independent Component Analysis and Bag-of-Visual-Words Model. 313-317.

[39] Ankita Singh and Bhavadharini (2023). Investigation on Machine Learning Algorithms for Crop Yield Prediction.

[40] Yamsani Krishank (2023). Deep Reinforcement Learning with Modified Reward Function for Crop Yield Prediction.

[41] Abhasha Joshi, Biswajeet Pradhan, Subrata Chakraborty, Mukunda Dev Behera (2023). Winter crop yield prediction in the conterminous United States using solar-induced chlorophyll fluorescence data and XGBoost and random forest algorithm. Ecological Informatics, 77:102194.

[42] Vincent Raj and Elavarasan (2023). Machine Learning based Crop Yield Prediction in Agriculture: A Survey in Vellore. In 2023 Innovations in Power and Advanced Computing Technologies (iPACT) : 1-5 .

[43] Weiguo Yu, Gaoxiang Yang, Dong Li, Hengbiao Zheng, Xia Yao, Yan Zhu, Weixing Cao, Lin Qiu, Tao Cheng (2023). Improved prediction of rice yield at field and county levels by synergistic use of SAR, optical and meteorological data. Agricultural and Forest Meteorology, 342:109729.

[44] Abhishak Singh and Tuwan Swain (2023). Rice crop growth monitoring with sentinel 1 SAR data using machine learning models in google earth engine cloud,Remote Sensing Applications . Society and Environment , 32 :101029 .

[45] UShafi shafi (2023). Tackling Food Insecurity Using Remote Sensing and Machine LearningBased Crop Yield Prediction. In *IEEE Access*, 11 : 108640-108657.

[46] Ashfaq wani and Limran Khan (2023). Wheat Yield Prediction Using Machine Learning and Climate- NDVI Data Fusion. In *IEEE Access*, 12 : 40947-40961.

[47] Qiao Chug and Cengad Cheng (2020). Exploiting Hierarchical Features for Crop Yield Prediction Based on 3-D Convolutional Neural Networks and Multikernel Gaussian Process . In *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 14 : 4476-4489.

[48] Celik Walan and Tawari Isik (2021). Explainable Artificial Intelligence for Cotton Yield Prediction With Multisource Data . In *IEEE Geoscience and Remote Sensing Letters*, 20: 1-5

[49] Arjit Gupta and Mitali Sharma (2021). Weather Based Crop Prediction in India Using Big Data Analytics . In *IEEE Access*, 9 : 137869-137885.

[50] Raja Ganapathy and Joel Sawicka (2022). Crop Prediction Based on Characteristics of the Agricultural Environment Using Various Feature Selection Techniques and Classifiers . In *IEEE Access*,10
: 23625-23641.

[51] Johann Desloires, Dino Ienco, Antoine Botrel (2023). Out-of-year corn yield prediction at field-scale using Sentinel-2 satellite imagery and machine learning methods. Computers and Electronics in Agriculture, 209:107807.

[52] Arshveer Kaur, Poonam Goyal, Rohit Rajhans, Lakshya Agarwal, Navneet Goyal (2023). Fusion of multivariate time series meteorological and static soil data for multistage crop yield prediction using multi-head self attention network. Expert Systems with Applications, 226:120098.

[53] Alkha Mohan, Venkatesan M., Prabhavathy P., Jayakrishnan A (2023). Temporal convolutional network based rice crop yield prediction using multispectral satellite data. Infrared Physics & Technology, 135:104960.

[54] Jhajharia Juang and Mathur Mallaram (2023). Prediction of crop yield using satellite vegetation indices combined with machine learning approaches. Advances in Space Research , 2(9):3998-4007.

[55] Simone Bregaglio, Fabrizio Ginaldi, Elisabetta Raparelli, Gianni Fila, Sofia Bajocco, (2023). Improving crop yield prediction accuracy by embedding phenological heterogeneity into model parameter sets. Agricultural Systems, 209:103666.

[56] Yashi Chaudhary and Heman Pathak (2024). Crop Yield Prediction using Bi-Directional LSTM under PySpark interface. Multimedia Tools and Applications, 1-20.

[57] Conradt Joshwa (2022). Choosing multiple linear regressions for weather-based crop yield prediction with ABSOLUT v1. 2 applied to the districts of Germany. International Journal of Biometeorology, 66(11) : 2287-2300.

[58] Bregaglio, S., Ginaldi F., Raparelli, E., Fila, G., & Bajocco, S. (2023). Improving crop yield prediction accuracy by embedding phenological heterogeneity into model parameter sets. Agricultural Systems, 209, 103666

[59] Krishna, M. V., Swaroopa, K., SwarnaLatha, G., & Yasaswani, V. (2023). Crop yield prediction in India based on mayfly optimization empowered attention-bi-directional long short-term memory (LSTM). Multimedia Tools and Applications, 1-18.

[60] Kolipaka Rithick and Namburu Harsha (2024). An automatic crop yield prediction framework designed with two-stage classifiers: a meta-heuristic approach. Multimedia Tools and Applications, 124.