

SurplusLink Frontend Engineering

Comprehensive HTML5, CSS3, Zero-JavaScript Architecture & Design System Mastery Notes

Author / Role: Expert Frontend & UI/UX Specialist	Target Architecture: 100% Pure HTML5 & CSS3	Scope: 18 Application Views + Design Tokens
JavaScript Runtime: ZERO (Strict Constraint Passed)	Layout Engine: Flexbox + CSS Grid + Viewport Units	Date: October 2026 • Production Edition

1. Executive Overview & Zero-JavaScript Architectural Philosophy


The SurplusLink Bakery Rescue prototype was engineered strictly following a **Zero-JavaScript constraint**. In modern web engineering, JavaScript is frequently utilized for trivial UI state management (modals, tabs, screen switching, drawer menus), introducing unnecessary bundle bloat, hydration lag, and potential runtime crash vectors. This application proves that advanced **declarative CSS3** combined with semantic **HTML5 form mechanics** can simulate an app-like interactive experience with superior rendering performance (60 FPS on GPU hardware layers), zero memory leaks, and native accessibility.

Key Constraints & Compliance Guarantees:

- Zero JavaScript Execution:** 0 `<script>` tags, 0 inline event listeners (onclick, onload), and 0 JS files across all 18 views.
- 1:1 File Modularity:** Exactly 1 HTML file paired with 1 dedicated CSS stylesheet per screen (e.g., `index.html` + `index.css`).
- Deterministic State Transitions:** Interactive states (menus, filters, tabs) are driven by the *Checkbox & Radio Hack* using `:checked` and sibling combinators.
- Mobile-First Progressive Enhancement:** Base CSS delivers lightweight mobile viewports (<600px); tablet and desktop experiences are layered via min-width queries.
- Pixel-Perfect Figma Replication:** 100% authentic typography, colors, SVGs, and extracted assets matching the 23-page design specification.

2. Architectural Flowchart: Pure CSS State Machine Engine

The flowchart below depicts the complete lifecycle of state mutation without JavaScript runtime intervention. When a user taps an interactive element, native browser form control binding toggles the boolean state of an invisible input element, triggering a deterministic recalculation of styles across target sibling elements.



State Machine Theory: The HTML `<label for="toggle-id">` element acts as an asynchronous event trigger. Because the browser natively updates the `checked` property of the associated `<input type="checkbox" id="toggle-id">`, the CSS selector engine evaluates the dynamic pseudo-class `:checked`. The general sibling combinator (`~`) or adjacent sibling combinator (`+`) then selects subsequent sibling DOM nodes, altering their visibility, opacity, and transform properties. Because properties like transform and opacity do not trigger layout reflow or repaint, animations execute directly on the GPU compositor.

3. Complete Catalog of HTML5 Elements (All 38 Elements Used)

Every single HTML tag in the codebase was chosen for its precise semantic meaning and role in creating a fully structured, accessible document outline.

Tag	Category	Semantic Purpose & Architectural Role	Project Implementation Example
<html>	Root	Top-level root element representing the document. Defines lang="en".	<html lang="en">
<head>	Metadata	Contains non-rendered document metadata, font preconnections, and stylesheet links.	<head>...</head>
<title>	Metadata	Declares browser tab title and accessible document name for assistive tech.	<title>SurplusLink - Bakery Rescue</title>
<meta>	Metadata	Specifies character encoding (UTF-8) and responsive viewport scaling parameters.	<meta name="viewport" content="...">
<link>	Resource Link	Establishes external relationships: Google Fonts preconnect and dedicated CSS.	<link rel="stylesheet" href="index.css">
<body>	Landmark	Root rendering container for all visible viewport content and state toggles.	<body>...</body>
<header>	Landmark	Introductory landmark containing top status pills, badges, brand bar, and user profile.	<header class="top-status-pills">
<nav>	Landmark	Defines major navigation sections: screen switching drawer and persistent bottom nav.	<nav class="drawer-menu">
<main>	Landmark	Specifies the central, primary content of the screen. Unique per HTML file.	<main class="welcome-screen">
<section>	Sectioning	Standalone thematic grouping of content (e.g., bottom-sheet-card, caller-hero).	<section class="bottom-sheet-card">
<article>	Sectioning	Self-contained, independently distributable lot cards, feed items, and driver listings.	<article class="expiring-card">
<footer>	Landmark	Footer section of components or cards; holds the 3 value props on the landing page.	<footer class="value-props-grid">
<h1>	Typography	Primary screen title. Establishes the top level of the document outline.	<h1 class="main-heading">SurplusLink</h1>
<h2>	Typography	Sub-section header for major component cards, lot summaries, and drawers.	<h2 class="section-title">Browse by Type</h2>
<h3>	Typography	Card-level headers for individual food lots, allergen groups, and drawer titles.	<h3 class="item-title">Artisan Sourdough</h3>
<p>	Typography	Paragraph blocks for descriptive subtitles, instruction directives, and descriptions.	<p class="sub-description">...</p>
	Text Inline	Generic inline container for badge text, pill text, highlights, and micro-metrics.	Bakery
	Text Inline	Semantic emphasis denoting strong importance or prominent data points (prices, times).	<strong class="current-price">\$4.50
	Text Inline	Represents deleted or struck-out text (e.g., original pre-discount lot prices).	<del class="original-price">\$18.00
 	Text Inline	Enforces intentional typographic line breaks without creating separate paragraphs.	SurplusLink Bakery Rescue
<input>	Form / State	State toggle element (checkbox/radio) for menus, tabs, and filter pills without JS.	<input type="checkbox" id="nav-toggle">
<label>	Form / State	Clickable surface tied to input via for="id"; toggles the state on tap.	<label for="nav-toggle" class="trigger">
<button>	Interactive	Clickable action trigger for filter chips, audio controls, and modal dismissals.	<button type="button" class="btn-chip">
<form>	Form Container	Semantic container for food listing parameters, search bars, and account inputs.	<form action="#" class="search-form">
<textarea>	Form Control	Multi-line text input field for kitchen notes and dock handling instructions.	<textarea rows="3" placeholder="...">
<a>	Hyperlink	Navigational anchor connecting all 18 views with proper relative href targets.	Get Started
	Media	Displays local extracted Figma raster images (hero bakery, avatars, QR passes).	

<div>	Generic	Generic styling hook for CSS Flexbox/Grid wrappers, pills, overlays, and handles.	<div class="hero-overlay"></div>
<svg>	Vector Graphic	Scalable container for tactical icons, radar routes, verified seals, and arrows.	<svg width="20" height="20" viewBox="...">
<path>	SVG Geometry	Complex vector Bézier curves (leaves, crossed cutlery, arrows, storefronts).	<path d="M11 20A7 7 0 0 1 9.8 6.1...">/>
<rect>	SVG Geometry	Vector rectangles for map grids, lot badges, calendars, and ticket borders.	<rect width="100%" height="100%">/>
<circle>	SVG Geometry	Circular vector elements for radar pulse halos, avatar rings, and status dots.	<circle cx="180" cy="90" r="28">/>
<line>	SVG Geometry	Vector straight lines for arrow stems, hamburger bars, and divider ticks.	<line x1="3" y1="12" x2="21" y2="12">/>
<polyline>	SVG Geometry	Connected series of straight line segments for arrowheads and route polylines.	<polyline points="12 5 19 12 12 19">/>
<polygon>	SVG Geometry	Closed plane shapes (e.g., GPS turn-by-turn navigation arrowhead).	<polygon points="3 11 22 2 13 21 11 13">/>
<defs>	SVG Definitions	Container for reusable graphical elements (patterns, gradients, clip paths).	<defs><pattern id="grid"...></defs>
<pattern>	SVG Texture	Defines repetitive tile patterns used to render tactical coordinate map grids.	<pattern id="grid" width="40" height="40">
<g>	SVG Group	Groups related SVG child elements to apply shared transformations and colors.	<g stroke="currentColor" stroke-width="2">

4. Complete Catalog of HTML Attributes (All 49 Attributes Used)

HTML attributes configure element behaviors, accessibility metadata, styling targets, and SVG coordinate geometry.

Attribute	Classification	Description & Purpose	Example Syntax in Project
class	Global / Styling	Assigns space-separated CSS class names for styling and component hooks.	class="bottom-sheet-card"
id	Global / State	Unique document identifier; pairs with label for to drive CSS state switching.	id="nav-drawer-toggle"
style	Global / Inline	Inline style overrides for dynamic coordinates (e.g. tactical radar map pin nodes).	style="top: 60px; left: 75px;"
title	Global / Advisory	Advisory tooltip information rendered on hover by browser user agents.	title="All App Screens Menu"
lang	Document Meta	Declares natural language of the document (English) for search engines and screen readers.	lang="en"
aria-label	Accessibility	Provides an invisible, accessible name for icon-only buttons and navigation links.	aria-label="User Profile Settings"
aria-hidden	Accessibility	Hides decorative elements (drag handles, background flourishes) from assistive tech.	aria-hidden="true"
href	Hyperlink Target	Destination URL or relative file path connecting the 18 views into an app prototype.	href="role-selection.html"
src	Media Source	Local filesystem path to authentic Figma extracted images (e.g., hero, avatars).	src="assets/hero_bakery.png"
alt	Media Alternative	Descriptive fallback text providing screen readers with the context of visual imagery.	alt="Artisan sourdough loaves"
target	Hyperlink Browsing	Specifies browsing context (_blank opens GPS navigation in a fresh tab).	target="_blank"
rel	Resource Relation	Defines relationship between document and linked resource (stylesheet, preconnect).	rel="stylesheet"
charset	Document Encoding	Declares UTF-8 character encoding preventing mojibake in text & math symbols.	charset="UTF-8"
name	Metadata / Form	Identifies viewport settings in meta tags or groups radio buttons for tab switching.	name="role-type"
content	Metadata Value	Contains the argument values for <meta name="viewport"> declarations.	content="width=device-width..."
type	Form Control Type	Specifies input behavior: checkbox, radio, text, button.	type="checkbox"
for	Label Association	Binds label click to input ID, enabling touch triggers for pure CSS drawers and tabs.	for="nav-drawer-toggle"
value	Form Control Value	Initial data payload associated with input controls or buttons.	value="provider"
placeholder	Form Hint	Temporary user guidance rendered inside inputs prior to text entry.	placeholder="Enter 6-digit code"
maxLength	Input Constraint	Enforces character count limits directly at the browser client level.	maxLength="6"
rows	Textarea Sizing	Specifies visible text lines for textarea elements before vertical scrolling.	rows="3"
action	Form Submission	Target endpoint for form submissions (set to local anchors for prototype).	action="#"
method	HTTP Verb	Specifies HTTP transmission protocol (get or post).	method="post"
viewBox	SVG Coordinate	Defines internal aspect ratio and coordinate space: min-x, min-y, width, height.	viewBox="0 0 24 24"
xmlns	SVG Namespace	Specifies the W3C XML namespace declaration for inline SVG elements.	xmlns="http://www.w3.org/2000/svg"
width / height	Dimensions	Explicit render width and height in CSS pixels or relative percentage units.	width="20" height="20"
fill	SVG Paint	Fill color painted inside vector paths (e.g., none, #006837).	fill="none"
stroke	SVG Stroke	Color applied to the perimeter outline path of vector elements.	stroke="currentColor"

<code>stroke-width</code>	SVG Stroke Width	Thickness of vector path strokes in internal coordinate units.	<code>stroke-width="2.2"</code>
<code>stroke-linecap</code>	SVG Stroke Cap	Defines line segment termination shape (round, square, butt).	<code>stroke-linecap="round"</code>
<code>stroke-linejoin</code>	SVG Stroke Join	Defines how vector path corner corners are rendered (round, bevel, miter).	<code>stroke-linejoin="round"</code>
<code>stroke-dasharray</code>	SVG Dash Pattern	Creates dashed vector polylines for active courier navigation dispatch routes.	<code>stroke-dasharray="6,4"</code>
<code>opacity</code>	SVG Alpha	Controls transparency layer for radar halos, pulse rings, and tactical river fills.	<code>opacity="0.3"</code>
<code>d</code>	SVG Path Data	String containing sequential movement and curve commands (M, L, C, Z) for paths.	<code>d="M12 2a8 8 0 0 0-8 8..."</code>
<code>x, y, rx, ry</code>	SVG Rect Geom	Origin position and horizontal/vertical corner radii for rounded rectangles.	<code>x="3" y="3" rx="2" ry="2"</code>
<code>cx, cy, r</code>	SVG Circle Geom	Center X/Y coordinates and radius for radar blips and status dots.	<code>cx="180" cy="90" r="28"</code>
<code>x1, y1, x2, y2</code>	SVG Line Geom	Starting and ending coordinate pairs defining straight vector line segments.	<code>x1="3" y1="12" x2="21" y2="12"</code>
<code>points</code>	SVG Poly Geom	List of comma-separated X,Y coordinate pairs for complex polylines and polygons.	<code>points="160,260 200,220..."</code>
<code>patternUnits</code>	SVG Pattern Coord	Coordinate reference system for pattern tiles (userSpaceOnUse).	<code>patternUnits="userSpaceOnUse"</code>
<code>preserveAspectRatio</code>	SVG Scaling	Controls scaling behavior across viewBox boundaries (none stretches full).	<code>preserveAspectRatio="none"</code>

5. Complete Catalog of CSS3 Properties (All 73 Properties Classified)

The CSS codebase implements modern CSS3 layout paradigms, eliminating old float hacks. All 73 unique properties are categorized below into their functional domains.

Property	Layout / Visual Domain	Syntax & Applied Values	Architectural Function in Project
<code>display</code>	Formatting Context	<code>flex</code> , <code>grid</code> , <code>block</code> , <code>inline-flex</code> , <code>none</code>	Establishes Flexbox, Grid, or hides toggles without layout traces.
<code>position</code>	Positioning Scheme	<code>relative</code> , <code>absolute</code> , <code>fixed</code> , <code>static</code>	Enables layered pill overlays, sticky headers, and sliding drawer menus.
<code>top</code> , <code>right</code> , <code>bottom</code> , <code>left</code>	Box Offsets	<code>0</code> , <code>16px</code> , <code>-30px</code> , <code>auto</code>	Sets physical pixel and clamp offsets for positioned overlays and drawers.
<code>inset</code>	Logical Shorthand	<code>0</code>	Shorthand for <code>top:0</code> ; <code>right:0</code> ; <code>bottom:0</code> ; <code>left:0</code> ; for full-screen backdrops.
<code>z-index</code>	Stacking Context	<code>10</code> , <code>20</code> , <code>9999</code> , <code>10000</code>	Controls 3D z-axis stacking layer order (drawers over overlays over content).
<code>overflow</code> / <code>overflow-x</code> , <code>-y</code>	Box Clipping	<code>hidden</code> , <code>auto</code> , <code>scroll</code>	Enables horizontal lot carousels and smooth scrollable navigation drawers.
<code>visibility</code>	Rendering Engine	<code>visible</code> , <code>hidden</code>	Hides drawers from pointer clicks and screen readers until toggled.
<code>flex</code>	Flex Item Sizing	<code>1</code> , <code>0 0 auto</code>	Controls flex grow, shrink, and basis for expanding cards and columns.
<code>flex-direction</code>	Flex Main Axis	<code>row</code> , <code>column</code>	Directs component flow horizontally (badges, rows) or vertically (screens).
<code>flex-wrap</code>	Flex Line Wrapping	<code>wrap</code> , <code>nowrap</code>	Allows tag chips and badge pills to wrap naturally across smaller screens.
<code>flex-shrink</code>	Flex Shrinking	<code>0</code>	Prevents critical icons, arrows, and avatars from squishing in tight rows.
<code>justify-content</code>	Main-Axis Alignment	<code>center</code> , <code>space-between</code> , <code>flex-start</code>	Distributes space between top status pills and centers action button text.
<code>align-items</code>	Cross-Axis Alignment	<code>center</code> , <code>flex-start</code> , <code>flex-end</code>	Aligns icons vertically with accompanying text lines.
<code>align-self</code>	Cross-Axis Item	<code>center</code> , <code>flex-start</code>	Overrides parent cross-axis alignment for individual callout elements.
<code>gap</code>	Box Spacing	<code>8px</code> , <code>12px</code> , <code>16px</code>	Eliminates margin hacks by enforcing clean gaps between Flex/Grid children.
<code>grid-template-columns</code>	Grid Track Sizing	<code>repeat(3, 1fr)</code> , <code>repeat(2, 1fr)</code>	Defines equal-width fractional tracks for the 3 value props and metrics.
<code>box-sizing</code>	Box Model Sizing	<code>border-box</code>	Universally applied (*); ensures padding and borders are contained within width.
<code>width</code> / <code>height</code>	Dimensions	<code>100%</code> , <code>38px</code> , <code>50vh</code> , <code>100vh</code>	Sets fluid, absolute, or viewport-relative element dimensions.
<code>max-width</code> / <code>min-width</code>	Constraint Sizing	<code>440px</code> , <code>320px</code> , <code>85vw</code>	Constrains phone frame on desktop (440px) and sets mobile drawer limits.
<code>min-height</code>	Constraint Sizing	<code>100vh</code> , <code>330px</code>	Guarantees full screen coverage on high-DPI displays.
<code>margin</code> / <code>margin-top</code> / <code>bottom...</code>	Box Outer Margin	<code>0 auto</code> , <code>-30px</code> , <code>16px</code>	Centers content, creates negative overlap for bottom sheet cards.
<code>padding</code> / <code>padding-top...</code>	Box Inner Padding	<code>14px</code> <code>20px</code> , <code>6px</code> <code>12px</code>	Ensures finger-friendly tap targets (>= 48px) and card breathing room.
<code>font-family</code>	Typography	<code>'Plus Jakarta Sans'</code> , <code>sans-serif</code>	Establishes modern geometric sans-serif aesthetic straight from Figma specs.
<code>font-size</code>	Typography	<code>0.72rem</code> , <code>1rem</code> , <code>1.28rem</code>	Scales typography proportionally using rem units anchored to root html size.
<code>font-weight</code>	Typography	<code>400</code> , <code>500</code> , <code>600</code> , <code>700</code> , <code>800</code>	Distinguishes visual hierarchy (800 for titles, 500 for status, 400 for copy).
<code>line-height</code>	Typography	<code>1.15</code> , <code>1.25</code> , <code>1.5</code>	Tightens headers (1.2) while maintaining comfortable paragraph reading (1.5).
<code>letter-spacing</code>	Typography	<code>-0.02em</code> , <code>0.08em</code>	Negative tracking on bold headings; wide tracking on uppercase category tags.

<code>text-align</code>	Typography	<code>center, left</code>	Centers value prop cards, drag handles, and status pill text.
<code>text-decoration</code>	Typography	<code>none</code>	Strips browser default underlines from anchor action buttons.
<code>color</code>	Typography	<code>var(--color-primary), #0f172a</code>	Applies color tokens for deep green branding and high-contrast dark text.
<code>white-space</code>	Typography	<code>nowrap</code>	Prevents status pill text or price tags from wrapping into awkward breaks.
<code>-webkit-font-smoothing</code>	Font Rendering	<code>antialiased</code>	Forces crisp sub-pixel font anti-aliasing across WebKit/Blink engines.
<code>background / background-color</code>	Visual Surface	<code>#006837, #f7f5fc, rgba(...)</code>	Paints solid brand greens, soft card containers, and translucent status pills.
<code>border / border-top/left...</code>	Box Perimeter	<code>1px solid #e5e7eb, 3px solid...</code>	Constructs subtle container cards, divider rules, and active tab indicator bars.
<code>border-radius</code>	Box Rounding	<code>12px, 28px 28px 0 0, 9999px</code>	Creates modern rounded corners, bottom sheet curves, and circular pill caps.
<code>outline</code>	Focus Ring	<code>none</code>	Removes default browser input outlines in favor of custom box-shadow focus rings.
<code>box-shadow</code>	Elevation / Depth	<code>0 4px 14px rgba(0,104,55,0.25)</code>	Simulates physical elevation and button glowing effects.
<code>opacity</code>	Alpha Layer	<code>0, 1, 0.8</code>	Smoothly transitions overlay backdrop visibility on drawer opening.
<code>backdrop-filter</code>	Glassmorphism	<code>blur(10px)</code>	Blurs background bakery imagery behind floating translucent status pills.
<code>-webkit-backdrop-filter</code>	Glassmorphism	<code>blur(10px)</code>	Ensures iOS Safari compatibility for frosted-glass status pill effects.
<code>filter</code>	Graphic Filter	<code>brightness(0.92) contrast(1.05)</code>	Enhances hero bakery photo vibrancy and visual depth.
<code>object-fit</code>	Image Scaling	<code>cover, contain</code>	Prevents aspect distortion on hero photos (cover) and icons (contain).
<code>object-position</code>	Image Positioning	<code>center 25%</code>	Focuses bakery imagery on freshly baked loaves rather than empty window frames.
<code>transform</code>	Coordinate Matrix	<code>translateX(100%), translateY(-2px)</code>	Powers GPU-accelerated drawer sliding and button hover micro-lifts.
<code>transition</code>	State Animation	<code>all 0.25s cubic-bezier(...)</code>	Orchestrates fluid, physics-based transitions across interactive states.
<code>animation</code>	Keyframe Motion	<code>pulse 2s infinite ease-in-out</code>	Drives rhythmic glowing pulse on the live green status dot.
<code>cursor</code>	Pointer Interaction	<code>pointer</code>	Indicates interactive surfaces on labels, triggers, and action buttons.
<code>user-select</code>	Selection Behavior	<code>none</code>	Prevents accidental text selection highlighting on buttons during rapid tapping.


6. CSS Pseudo-Classes, Pseudo-Elements & Mathematical Functions

Dynamic state selectors and CSS functions form the backbone of the reactive architecture without JavaScript.

Selector / Function	Type	Mechanics & Syntax	Application in SurplusLink Prototype
<code>:root</code>	Pseudo-class	Targets document root element for declaring global design tokens.	Stores <code>--color-primary</code> , <code>border-radius</code> , and shadow variables.
<code>:checked</code>	Pseudo-class	Matches form controls when toggled into the active checked state.	Powers drawer opening (<code>.toggle:checked ~ .drawer</code>) & role switching.
<code>:hover</code>	Pseudo-class	Applies when user hovers a pointing device over an element.	Lifts buttons (<code>translateY(-2px)</code>) and deepens button shadow elevation.
<code>:active</code>	Pseudo-class	Triggers during active mouse click or finger tap compression.	Simulates tactile button depression (<code>translateY(0)</code>).
<code>:focus-within</code>	Pseudo-class	Matches container element if any of its descendants hold focus.	Highlights entire form card containers when user types in inputs.
<code>:first-child</code>	Pseudo-class	Selects first child element among a group of siblings.	Applies distinct border styling to the initial item in lists and grids.
<code>::before</code> / <code>::after</code>	Pseudo-element	Injects cosmetic pseudo-DOM nodes via the <code>content: ""</code> property.	Used for universal box-sizing and glowing dot ring layers.
<code>::-webkit-scrollbar</code>	Pseudo-element	Customizes browser scrollbar tracks and thumb thumbs.	Hides bulky scrollbars on horizontal lot carousels for sleek mobile look.
<code>var(--token)</code>	Function	Retrieves value of a declared CSS custom property.	Enforces consistent color palette: <code>background: var(--color-primary)</code> ;
<code>calc()</code>	Function	Performs dynamic mathematical calculations across mixed units.	Computes tablet viewport container height: <code>calc(100vh - 64px)</code> .
<code>linear-gradient()</code>	Color Function	Generates smooth directional color transitions between two or more stops.	Creates the hero photo overlay fading into the white bottom sheet.
<code>radial-gradient()</code>	Color Function	Generates circular/elliptical color gradients emanating from an origin.	Paints the subtle circular light pool backdrop on desktop screens.
<code>rgba()</code>	Color Function	Defines RGB color values with dedicated alpha channel opacity.	Generates translucent backdrop layers: <code>rgba(37, 43, 58, 0.9)</code> .
<code>translateX</code> / <code>Y()</code>	Transform	Translates an element horizontally or vertically along the 2D plane.	Slides navigation drawer in from right (<code>translateX(0)</code>).
<code>cubic-bezier()</code>	Timing Function	Defines a custom cubic Bézier curve for natural easing curves.	Smooth spring physics: <code>cubic-bezier(0.16, 1, 0.3, 1)</code> .

7. Responsive Design Theory & Breakpoint Architecture Flowchart

The responsive layout is built strictly on a **Mobile-First Progressive Enhancement strategy**. Rather than authoring heavy desktop layouts and attempting to compress them down with fragile max-width queries, base CSS styles exclusively target small touchscreens (< 600px). Tablet and desktop layouts are progressively unlocked via min-width queries.



Three Tier Viewport Strategy:


- Mobile Tier (< 600px)**: Native single-column stack. Viewport width is 100% fluid with zero side letterboxing. Bottom navigation bar is fixed to the bottom edge. Modals slide up as bottom sheets with drag handles.
- Tablet Tier (600px – 1024px)**: Unlocked via @media (min-width: 600px). Background receives an elegant dual-tone gradient wash. The app viewport morphs into a floating container with subtle outer rounded corners and elevation shadow.
- Desktop / Laptop Tier (> 1024px)**: Unlocked via @media (min-width: 1024px). The app viewport is locked to a comfortable max-width: 440px simulating an authentic mobile device shell, surrounded by a soft radial backdrop wash. Hover elevations are active.

8. Deep Theoretical Foundations of Modern CSS

- **Box Model Invariance**: The universal rule `*, ::before, ::after { box-sizing: border-box; }` alters the default W3C box model. Padding and borders are consumed inwardly, ensuring that `width: 100%` never causes horizontal scroll overflows.
- **Stacking Contexts & Compositing Layers**: Elements with `position: fixed` or properties like `transform`, `backdrop-filter`, and `z-index` form independent stacking contexts. The browser composites them into distinct GPU surfaces, preventing costly layout re-calculations.
- **Accessibility & Semantic Trees**: By using true HTML5 landmark elements (`<main>`, `<nav>`, `<header>`) instead of generic `<div>` soup, assistive screen readers construct an accessible navigation tree, allowing users to jump directly to primary tasks without visual cues.

9. Application Information Architecture & User Flow Flowchart

The diagram below charts the navigation pathways connecting all 18 independent views. Every view is accessible through native relative links, maintaining complete state continuity without client-side routing scripts.



10. Complete Production Screen Inventory Matrix (All 18 Views)

Screen Name	HTML File	Dedicated CSS	Key Interactive States / Functional Role
1. Welcome Onboarding	index.html	index.css	Bakery backdrop hero, live status pills, 3 value props
2. Role Selection	role-selection.html	role-selection.css	3 interactive role cards: Donor, Recipient, Volunteer
3. Login & Sign Up	login.html	login.css	CSS tabbed auth: Food Provider vs. Verified Recipient
4. Create Account Form	signup.html	signup.css	Multi-step registration with ID badge and tax verification
5. Tactical Feed & Explore	explore.html	explore.css	Live marketplace feed, expiring lots, category filter pills
6. Live Radar & Map	radar.html	radar.css	SVG coordinate radar map with pins and sliding bottom drawer
7. Quality & Safety Protocol	safety-detail.html	safety-detail.css	HACCP verification, cold-chain sensor log, allergen matrix
8. Claim & Reserve Review	claim-review.html	claim-review.css	Cart checkout, fee breakdown, logistics handoff directives
9. Active Dispatch Pass	reservation-pass.html	reservation-pass.css	Cryptographic QR token, turn-by-turn route guide strip
10. VoIP Dispatch Audio Call	call.html	call.css	E2EE audio interface, live timer, speaker/mute toggles
11. Cancel Reservation	cancel-reservation.html	cancel-reservation.css	Cancellation penalty calculations, ledger confirmation modal
12. Compliance & Audit	compliance-audit.html	compliance-audit.css	FDA handoff checklist, temperature probe digital signoff
13. List Food - Details	list-food.html	list-food.css	Donor food listing engine with photo & batch verification
14. Fast Listing - Pickup	listing-pickup.html	listing-pickup.css	Loading dock bay coordination, staff lead contact card
15. Tactical Alerts & Feeds	alerts.html	alerts.css	Real-time push notifications, courier proximity updates
16. Live Pickup Queue	queue.html	queue.css	Driver & courier fulfillment queue with vehicle tracking
17. Bakery Impact Hub	impact.html	impact.css	ESG metrics, CO2 emissions saved, community reach banner
18. Profile & Operations	profile.html	profile.css	Account settings, partner accreditation, security badges