

SIMATS ENGINEERING

ASSESSMENT TOOL 1

COURSE NAME: Computer Networks

COURSE CODE: CSA0716

COURSE OUTCOME COVERED

CO1: *Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)*

Assessment Tool Weightage: 40%

Annexure A

SHORT ANSWER TEST

Code of Conduct:

*I **SANTHOSH E(192511470)** (Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.
I understand that any violation of academic integrity rules will result in disciplinary action.*

Signature of the student: Santhosh. E

Annexure A

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.
2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.
3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.
4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5%** overhead to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7. An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests of **3 MB** each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8. A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9. A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead

transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10. A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

ANSWERS

1. File Transfer (Transport + Data Link Layer)

Formula:

- Segments = File Size / Segment Size
- Overhead = Frames $\times$ Header Size
- Time = Total Bits / Bandwidth

Answer:

- Segments = $150 \times 10^6 / 1500 = 100,000$
- Frames = **100,000**
- Overhead = $100,000 \times 40 = 4,000,000 \text{ bytes} = \mathbf{4 \text{ MB}}$
- Total data = **154 MB** $\rightarrow$ Transmission time = **24.64 s** (50 Mbps).
Transport ensures reliable delivery, while Data Link provides framing and error detection.

2. Sliding Window Protocol

Formula:

- Windows = Frames / Window Size
- Retransmissions = $1 \times$ Windows

Answer:

- Windows = $48 / 6 = 8$
- Retransmissions = **8**
- Flow control prevents receiver overflow and improves network efficiency.
- Sliding window allows multiple frames before acknowledgment.

3. IP Fragmentation

Formula:

- Fragments = Packet Size / (MTU – Header)
- Header Overhead = Fragments $\times$ Header Size

Answer:

- Data per fragment = $1500 - 20 = 1480 \text{ bytes}$
- Fragments = **9**
- Header overhead = $9 \times 20 = 180 \text{ bytes}$
- The Network Layer fragments packets and reassembles them at the destination.

4. Sliding Window Protocol

Formula:

- $\text{Windows} = \text{Frames} / \text{Window Size}$
- $\text{Retransmissions} = \text{Windows}$

Answer:

- $\text{Windows} = 8$
- $\text{Retransmissions} = 8$
- Flow control manages transmission speed and avoids congestion.
- It increases communication efficiency.

5. Session Layer Synchronization

Formula:

- $\text{Checkpoints} = \text{Data Transferred} / \text{Checkpoint Interval}$
- $\text{Retransmission} = \text{Failure Point} - \text{Last Checkpoint}$

Answer:

- $\text{Checkpoints before failure} = 360/60 = 6$
- $\text{Data to retransmit} = 390 - 360 = 30\text{MB}$
- Session Layer resumes from the last checkpoint.
- This reduces retransmission time.

6. Presentation Layer Compression

Formula:

- $\text{Compressed Size} = \text{Original} \times (1 - \text{Compression})$
- $\text{Encrypted Size} = \text{Compressed} \times 1.05$

Answer:

- $\text{Compressed size} = 540 \text{ MB}$
- $\text{Encrypted size} = 567 \text{ MB}$
- $\text{Total reduction} = (900 - 567)/900 \times 100 = 37\%$
- Presentation Layer provides compression, encryption, and format conversion.

7. FTP File Transfer

Formula:

- $\text{Requests} = \text{File Size} / \text{Request Size}$
- $\text{Time} = \text{Total Bits} / \text{Throughput}$

Answer:

- $\text{Requests} = 3072/3 = 1024$
- $\text{Time} = 3072 \times 8/120 = 204.8\text{s}$
- Application Layer manages file transfer and user services.
- It provides reliable communication using FTP.

8. End-to-End Delay

Formula:

- $\text{Total Delay} = \text{Processing} + \text{Transmission} + \text{Propagation}$

Answer:

- $\text{Processing delay} = 4 + 3 + 5 + 2 + 1 = 15\text{ms}$
- $\text{Total delay} = 15 + 12 + 18 = 45\text{ms}$
- Each OSI layer processes data before forwarding.
- Propagation and transmission contribute to total delay.

9. Frame Overhead**Formula:**

- $\text{Frames} = \text{Data} / \text{Payload}$
- $\text{Overhead} = \text{Frames} \times \text{Overhead per Frame}$
- $\text{Efficiency} = \text{Useful Data} / \text{Total Data} \times 100$

Answer:

- $\text{Frames} = 80,000,000 / 1600 = 50,000$
- $\text{Overhead} = 50,000 \times 80 = 4,000,000\text{bytes} = \mathbf{4\ MB}$
- $\text{Efficiency} = 1600 / (1600 + 80) \times 100 = 95.24\%$
- Protocol overhead reduces available bandwidth.

10. Medical Record Transfer**Formula:**

- $\text{Compressed Size} = \text{Original} \times (1 - \text{Compression})$
- $\text{Segments} = \text{Compressed Size} / \text{Segment Size}$
- $\text{Overhead} = \text{Segments} \times \text{Frame Overhead}$

Answer:

- $\text{Compressed size} = \mathbf{168\ MB}$
- $\text{Segments} = 168,000,000 / 1400 = 120,000$
- $\text{Overhead} = 120,000 \times 60 = 7.2\text{MB}$
- $\text{Final transmitted data} = \mathbf{175.2\ MB}$.
- Presentation compresses, Transport segments, Data Link adds framing, and Physical Layer transmits the data.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation
Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organization	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers

Accuracy	10%	Completely accurate and covers all required points	Mostly accurate with minor omissions	Partially correct with missing points	Incorrect answers with major gaps
Clarity	5%	Clear, neat, professional presentation	Understandable with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand