

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

CODE :

```
def print_board(state):
```

```
    n = len(state)
```

```
    for row in range(n):
```

```
        line = ""
```

```
        for col in range(n):
```

```
            if state[col] == row:
```

```
                line += "Q "
```

```
            else:
```

```
                line += ". "
```

```
        print(line)
```

```
    print()
```

```
def calculate_cost(state):
```

```
    cost = 0
```

```
    n = len(state)
```

```
    for i in range(n):
```

```
        for j in range(i + 1, n):
```

```
            if state[i] == state[j] or abs(state[i] - state[j]) == j - i:
```

```
                cost += 1
```

```
    return cost
```

```
def get_neighbors(state):
```

```
    neighbors = []
```

```
    n = len(state)
```

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .
. Q . .
. . . Q
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .
. . Q .
. . . Q
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .
Q . . .
. Q . .
```

```
for i in range(n):
    for j in range(i + 1, n):
        neighbor = list(state)
        neighbor[i], neighbor[j] = neighbor[j], neighbor[i]
        neighbors.append((neighbor, (i, j)))
return neighbors
```

```
def hill_climbing(initial_state):
    current_state = initial_state
    current_cost = calculate_cost(current_state)
    print("Start State:")
    print_board(current_state)
    print(f"Cost: {current_cost}\n")

    path = [(current_state, current_cost, None)]

    while True:
        neighbors = get_neighbors(current_state)
        neighbor_costs = [(tuple(neighbor), calculate_cost(neighbor), swap) for neighbor, swap in
neighbors]

        neighbor_costs.sort(key=lambda x: (x[1], x[2]))

        best_neighbor, best_cost, best_swap = neighbor_costs[0]

        print(f"Neighbors of {current_state} with costs:")
        for neighbor, cost, swap in neighbor_costs:
```

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

```
print(f"Swap columns {swap}:")
```

```
print_board(neighbor)
```

```
print(f"Cost: {cost}\n")
```

```
if best_cost < current_cost:
```

```
    print(f"Moving to better neighbor by swapping columns {best_swap}:")
```

```
    print_board(best_neighbor)
```

```
    print(f"Cost: {best_cost}\n")
```

```
    current_state, current_cost = best_neighbor, best_cost
```

```
    path.append((current_state, current_cost, best_swap))
```

```
else:
```

```
    print("/nReached goal state.")
```

```
    break
```

```
return path
```

```
def get_initial_state():
```

```
    print("Enter the initial positions of the 4 queens (row for each column, 0-indexed):")
```

```
    positions = []
```

```
    for col in range(4):
```

```
        while True:
```

```
            try:
```

```
                pos = int(input(f"Column {col}: "))
```

```
                if 0 <= pos < 4:
```

```
                    positions.append(pos)
```

```
                    break
```

```
            else:
```

HILL-CLIMBING SEARCH ALGORITHM

```
Neighbors of (1, 3, 0, 2) with costs:
```

```
Swap columns (0, 1):
```

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

```
Cost: 1
```

```
Swap columns (0, 2):
```

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

```
Cost: 1
```

```
Swap columns (1, 3):
```

```
. . Q .  
Q . . .  
. Q . .
```

```
        print("Invalid input. Enter a number between 0 and 3.")  
    except ValueError:  
        print("Invalid input. Please enter an integer.")  
    return tuple(positions)
```

```
initial_state = get_initial_state()  
path = hill_climbing(initial_state)
```

```
print("Final path:")  
for i, (state, cost, swap) in enumerate(path):  
    print(f"Step {i}:")  
    print_board(state)  
    print(f"Cost: {cost}")  
    if swap is not None:  
        print(f"Swap columns: {swap}")  
    print("-----")
```

OUTPUT :

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

===== RESTAI

Santhosh N (1BM23CS302)

Enter the initial positions of the 4 queens (row for each column, 0-indexed):

Column 0: 3

Column 1: 1

Column 2: 2

Column 3: 0

Start State:

```
. . . Q  
. Q . .  
. . Q .  
Q . . .
```

Cost: 2

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

Neighbors of (3, 1, 2, 0) with costs:

Swap columns (0, 1):

```
. . . Q  
Q . . .  
. . Q .  
. Q . .
```

Cost: 1

Swap columns (0, 2):

```
. . . Q  
. Q . .  
Q . . .  
. . Q .
```

Cost: 1

Swap columns (1, 3):

```
. Q . .  
. . . Q  
. . Q .  
Q . . .
```

Cost: 1

Swap columns (2, 3):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 3):

```
Q . . .  
. Q . .  
. . Q .  
. . . Q
```

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

Neighbors of (1, 3, 2, 0) with costs:

Swap columns (2, 3):

```
. . Q .  
Q . . .  
. . . Q  
. Q . .
```

Cost: 0

Swap columns (0, 1):

```
. . . Q  
. Q . .  
. . Q .  
Q . . .
```

Cost: 2

Swap columns (0, 2):

```
. . . Q  
. . Q .  
Q . . .  
. Q . .
```

Cost: 2

Swap columns (1, 3):

```
. Q . .  
Q . . .  
. . Q .  
. . . Q
```

Cost: 2

Swap columns (0, 3):

```
Q . . .  
. . . Q  
. . Q .  
. Q . .
```

HILL-CLIMBING SEARCH ALGORITHM

Neighbors of (1, 3, 0, 2) with costs:

Swap columns (0, 1):

```
. . Q .  
. Q . .  
. . . Q  
Q . . .
```

Cost: 1

Swap columns (0, 2):

```
Q . . .  
. . Q .  
. . . Q  
. Q . .
```

Cost: 1

Swap columns (1, 3):

```
. . Q .  
Q . . .  
. Q . .
```

/nReached goal state.

Final path:

Step 0:

```
. . . Q  
. Q . .  
. . Q .  
Q . . .
```

Cost: 2

Step 1:

```
. . . Q  
Q . . .  
. . Q .  
. Q . .
```

Cost: 1

Swap columns: (0, 1)

Step 2:

```
. . Q .  
Q . . .  
. . . Q  
. Q . .
```

Cost: 0

Swap columns: (2, 3)
