

BTP Trial API Collection — Prerequisites & Disclaimer

Companion to `btp-trial-api-playbook.md`. Read this **first**. It lists everything you need before running the playbook, and the ground rules for letting an AI coding assistant execute it.

PDF vs. Markdown — which copy to use: A PDF export of these documents is for **humans to read and share**. An AI coding assistant must work from the Markdown (`.md`) versions, never the PDF.

Reason: PDF text extraction reflows content — it rewraps long commands and URLs, collapses wide tables, and can drop or mangle exact whitespace and tokens like `{{process.env.*}}`. Those details are load-bearing (a reflowed URL or split token produces a wrong request), so only the Markdown preserves them faithfully. If you only have the PDF, convert it back to Markdown before running the playbook.

Disclaimer — Read Before You Start

Using an AI coding assistant to administer SAP BTP is powerful and convenient — and carries real risk. You remain fully responsible for everything it does in your account.

- **The AI can make mistakes.** It may misread a value, target the wrong subaccount, pick the wrong service plan, or run a command that does more than you intended. Treat every generated command and file as a *draft* until you have reviewed it.
- **Human in the loop is mandatory.** Before any operation that creates, changes, or deletes something (service instances, bindings, credentials, IAS applications), the assistant must show you the exact command or payload and wait for your explicit confirmation. Do not enable "auto-approve" / "yolo" modes for this workflow. If you don't understand what a step does, stop and ask before approving.
- **Never run this against a productive account.** This collection and playbook are for **trial and personal-development accounts only**. The credentials it creates carry broad, sometimes write-capable scopes. Using them against a production global account can disrupt real systems and real users.
- **You are responsible for secrets.** The setup produces real client IDs, client secrets, and access tokens. Keep them in the git-ignored `.env` file, never commit or paste them into shared channels, and rotate or delete the bindings when you are done (`btp delete services/binding` / `btp delete security/api-credential`).
- **Irreversible operations exist.** Deleting a subaccount, binding, or instance can be permanent and may not be recoverable. Read delete commands especially carefully.
- **Costs / quota.** Even in trial, creating instances consumes entitlement quota. Clean up what you don't need.
- **Verify, don't trust.** After the assistant reports success, check the result yourself (in the BTP Cockpit, via `btp` CLI, or by re-running the relevant request). "It said 200" is not the same as "it did the right thing."

By proceeding you accept that you — not the AI — own the outcome of every action taken in your account.

Prerequisites

1. An SAP BTP trial account

- A free **SAP BTP trial** global account. Sign up at <https://www.sap.com/products/technology-platform/trial.html>.

- At least one **subaccount** (the trial wizard creates a `trial` subaccount for you). Note its **region** (e.g. `ap21` , `us10`) — the playbook needs it.
- Your **SAP Universal ID** login (used for the `--sso` browser login).
- Entitlement to the services the playbook uses (`cis` , `uas` , `service-manager` , `xsuaa`). These are available by default in trial; the playbook creates instances/bindings for them.

2. An AI coding assistant

- An agentic AI coding assistant that can read the playbook, run shell commands, and write files — e.g. **Claude Code**. It must support a **human-in-the-loop confirmation** step for write operations (see Disclaimer).
- Optional: a **browser automation tool** (e.g. Chrome DevTools MCP, Playwright MCP) connected to the assistant. It can semi-automate the manual IAS Admin Console step (Step 3). You still log in yourself (SSO/2FA) and capture the one-time client secret; treat it as convenience, not full automation.

3. Command-line tools

Tool	Purpose	Verified version	Install
btp CLI	Create service instances, bindings, API credentials; discover account values	2.106.1	https://tools.hana.ondemand.com/#cloud
Bruno CLI (bru)	Run the collection from the terminal to verify requests	4.0.0	<code>npm i -g @usebruno/cli</code>
Bruno Desktop	GUI for the collection; required for the IAS OAuth2 browser flow	latest	https://www.usebruno.com/downloads
cf CLI (optional)	Only if you create service keys the CF-native way	8.18.4	https://github.com/cloudfoundry/cli
python3 (optional)	Pretty-printing/parsing JSON in shell one-liners	3.12	preinstalled on macOS/Linux

Login: `btp login --url https://cli.btp.cloud.sap --subdomain <GLOBAL_ACCOUNT> --sso`
— opens a browser for SSO; your password never touches the terminal.

4. Bruno specifics

- **Open-source Bruno allows max 2 workspaces.** Unlimited requires the Pro/Ulimate plan (<https://www.usebruno.com/pricing>). Plan your workspaces accordingly.
- For the IAS **Authorization Code** flow, set **Preferences → Use system browser for OAuth → OFF** in Bruno Desktop, so the embedded browser can intercept the `localhost:8686/callback` redirect.
- Secrets go in a git-ignored `.env` at the collection root; environment files reference them via `{{process.env.*}}` (see the playbook's Step 6).

5. IAS (only for the `trial-ias` environment)

- Access to the **IAS Admin Console** of the tenant trusted by your subaccount (`https://<IAS_HOST>/admin/` , trust origin `sap.custom`).

- Permission to create an OpenID Connect application and a client secret in that tenant. If you don't have IAS admin access, skip the `ias/` folder and the `trial-ias` environment — the rest of the collection works without it.

What the playbook will create in your account

So you know what you're approving:

Resource	Service / Plan	Purpose
cis-central instance + binding	cis / central	Global account, entitlements APIs
cis-local instance + binding	cis / local	Provisioning, events, subscriptions APIs
uas-reporting instance + binding	uas / reporting-ga-admin	Usage reporting APIs
sm-audit instance + binding	service-manager / subaccount-audit	Service Manager APIs
xsuaa-api-cred	XSUAA API credential	Users, roles, IdPs APIs
bruno-test IAS app + secret	IAS OpenID Connect app	OAuth2 browser-login flow

All are created in **your trial subaccount**. Delete them when finished to free quota and reduce credential exposure.

Next step

Once the above is in place, run the playbook:

```
run this playbook btp-trial-api-playbook.md
```