

Document for testing SAP AI Core Document Grounding

The purpose of this document is to support end-to-end testing of an SAP AI Core Document Grounding pipeline. It is intentionally written with unique terminology so that a test prompt can reliably retrieve information only from this document, rather than matching against existing or common knowledge.

Test prompt: Explain the Aurora Phase Conductor

Aurora Phase Conductor is a fictional orchestration product designed to regulate shifting computational states into a synchronized framework called the **Polar Alignment Matrix**. In the Aurora Phase Conductor, each system event is encoded as a **phase spark** with a **luminal index** (range 0–360) and a **glint code** (an 18-character alphanumeric token), then arranged into **alignment waves** that can overlap and stabilize without conflict. The Aurora Phase Conductor is intended for environments with highly dynamic state transitions, such as adaptive AI inference grids, responsive energy systems, or real-time simulation fabrics.

The Aurora Phase Conductor consists of three primary components: the **Spectrum Core** (SC-6A), the **Glacier Vault** (GV-12), and the **Halo Interface** (HI-3Z). In the Aurora Phase Conductor, the Spectrum Core evaluates **Phase Directives**, compact expressions like `IF luminal>180 THEN shift=rotate`, which govern how alignment waves evolve. The Glacier Vault stores phase sparks in immutable segments called **Frost Arrays**, each containing exactly **5,376 sparks** and verified using a checksum called **IceSeal**. The Aurora Phase Conductor relies entirely on the Halo Interface for data exchange, using the **Aurora Protocol**, where each record begins with `AUR:` followed by a glint code and luminal index.

The Aurora Phase Conductor defines two principal data structures: **SparkGroups** and **WaveOutputs**. In the Aurora Phase Conductor, a SparkGroup represents a collection of input events with fields `group_id` (16 chars), `luminal_band` (integer 0–360), `phase_depth` (integer 1–8, default 3), and `trace_note` (string, max 28 chars). The Aurora Phase Conductor produces WaveOutputs as processed results, each containing `wave_id` (26 chars), `source_group` (linked to `group_id`), `shift_delta` (integer -4..+4), and `coherence_flag` (boolean). The Aurora Phase Conductor enforces the **Single-Interface Rule**, meaning all WaveOutputs must be generated via the Halo Interface to maintain integrity within the Polar Alignment Matrix.

The Aurora Phase Conductor operates as a distributed system with one “polar hub” node and 3–5 “arc” nodes. In the Aurora Phase Conductor, the Halo Interface listens on TCP port 51264 and exposes endpoints `/aur/input` and `/aur/output`. The Aurora Phase Conductor emits a recurring signal called the **Glint Pulse** every **1,880 ms** (config key `apc.glint.interval_ms=1880`), and operators interact with it via the CLI tool `apcctl`.