



Configuration Guide - Medallia Customer Experience Integration with SAP Signavio Process Intelligence

April 2025

Table of contents

Prerequisites.....	3
Access to Medallia	3
Access to Signavio Process Intelligence.....	4
Access to SAP Cloud Integration	5
Integration Logic Description	6
Configuration steps on SAP Cloud Integration	8
Replicate Customer Experience Data from Medallia to Signavio Configuration.....	8
Configure Timer	8
Configure Receiver Adapter	8
Additional Parameters	9
Define Medallia Query Configuration.....	10
Configure Sender Adapter.....	10
Additional Parameters	10
Convert Medallia Data to CSV.....	11
Configure Sender Adapter.....	12
Additional Parameters	12
Import Medallia Data to SAP Signavio Process Intelligence	12
Configure Sender Adapter.....	12
Configure Receiver Adapter	12
Additional Parameters	13
Send Error Notification Emails (Medallia Error Handler).....	13
Configure Sender Adapter.....	13
Configure Receiver Adapter	14

Prerequisites

Prerequisites to establish the Integration between Medallia Customer Experience and Signavio Process Intelligence are:

Access to Medallia

1. Integration role for OAuth client

- Go to Admin Suite
- Go to Organization > Roles
- Click on New Role
- Fill the form as follows:
 - Role Name: SAP Signavio API
 - Role Type: Other
 - Role Group: Integrations
- Click on Save
- Click on Administrative Permissions
- Enable the View Data from Query API permission
- Click on Save

2. OAuth client for API access

- a. Go to Advanced Setup (Classic)
- b. Go to Integrations > OAuth
- c. Click on AppID Accounts tab
- d. Click on New
- e. Fill the form as follows:
 - a. Account Name: sap_signavio
 - b. Account Type: Custom
 - c. Enabled: must be checked
 - d. Role: Select SAP Signavio API
- f. Click on Save
- g. Click on Clients tab
- h. Click on New
- i. Fill the form as follows:
 - a. Client ID: sap_signavio_oauth
 - b. Confidential: must be checked
 - c. Grants: Client Credentials Grant (for backend services)
 - d. Client subject: sap_signavio
- j. Click on Save
- k. The Generate new client secret button will now be visible,
 - a. Check Confirm next to it
 - b. Click the Generate new client secret button


- l. Scroll down to the end of the page and you should see a green box saying "Your request was successful!"
- m. Copy the client_secret value (note that after navigating away from this screen the client_secret will no longer be visible, make sure to store it securely)
- n. Click on Configuration tab
- o. Copy the value for OAuth Token endpoint

3. API Hostname

- Go to Advanced Setup (Classic)
- Go to Integrations > Public APIs Setup
- Copy the value on Public APIs Hostname

Access to Signavio Process Intelligence

In order to bring the customer, experience free text data into Process Intelligence for further analysis, a license for SAP Signavio Process Intelligence is needed.



To create a connection to Medallia go to Process Intelligence, then navigate to Data Integration, click on Connections and then select Create


Choose the Name (Example Medallia CX). Set the Connection Type to Ingestion API and choose your Repository.

Create Connection

General

Name:*	Connection Type:*	Repository:*
New Connection X	Ingestion API	Connections


After the connection for Medallia is created, we will receive the API endpoint needed for configuring the receiver adapter in the iFlow "Import Medallia Data to SAP Signavio Process Intelligence" (see chapter: Configuration steps on SAP Cloud Integration) and we will receive the token for authentication, which must be stored as a secure parameter in the Security Material section (see chapter: Access to SAP Cloud Integration).




Access to SAP Cloud Integration

Before configuring the iFlows, you need to set up the credentials for authentication from SAP Cloud Integration to Medallia and Signavio.

Navigate to the "Manage Security" section within the Monitoring area and then click on Security Material.



After that, we first set up the OAuth credentials for Medallia, configure the Values and Deploy.



Parameter	Value
Name	Select an alias of your choice, e.g., <i>Medallia_OAuth_Token</i> .
Description	Choose a description of your preference, such as <i>Medallia – Signavio Integration</i>
Token Service URL	See Chapter Prerequisites → Access to Medallia
Client ID	See Chapter Prerequisites → Access to Medallia
Client Secret	See Chapter Prerequisites → Access to Medallia
Client Authentication	Send Body as Parameter
Content Type	application/x-www-form-urlencoded

After that, we create the secure parameter for Signavio Process Intelligence authentication and deploy it.

Parameter	Value
Name	Select an alias of your choice, e.g., <i>Medallia_Ingestion_Token</i> .
Description	Choose a description of your preference, such as <i>Medallia – Signavio Integration</i>
Secure Parameter	See Chapter Prerequisites → Access to Signavio Process Intelligence

Integration Logic Description

The package includes a total of 5 interfaces. The "Replicate Customer Experience Data from Medallia to Signavio" interface is the main interface, and all other iFlows are called synchronously via the Process Direct Adapter. The interfaces "Replicate Customer Experience Data from Medallia to Signavio," "Import Medallia Data to SAP Signavio Process Intelligence," and "Medallia Errorhandler" should not be edited.




Medallia Customer Experience Integration with SAP Signavio Process Intelligence

Header Overview **Artifacts (5)** Documents Comments Tags

<div><div>Add</div><div>Migrate</div><div>Delete</div><div>Actions</div><div>Filter Artifacts</div><div>Q</div></div>				
<input type="checkbox"/>	Name	Type	Version	Actions
<input type="checkbox"/>	Convert Medallia Data to CSV Convert Medallia Data to CSV via SAP Cloud Integration (Direct Process Adapter) Modified	Integration Flow	1.0.0	>
<input type="checkbox"/>	Define Medallia Query Define Medallia Query via SAP Cloud Integration (Direct Process Adapter) Modified	Integration Flow	1.0.0	>
<input type="checkbox"/>	Import Medallia Data to SAP Signavio Process Intelligence Import Medallia Data via SAP Cloud Integration (Direct Process Adapter) to SAP Signavio Process Intelligence (HTTP Adapter) Modified	Integration Flow	1.0.0	>
<input type="checkbox"/>	Replicate Customer Experience Data from Medallia to Signavio Main iFlow to replicate Customer Experience Data from Medallia (Scheduler) to SAP Signavio Process Intelligence. Created	Integration Flow	1.0.0	>
<input type="checkbox"/>	Send Error Notification Emails Send Error Notification Emails via SAP Cloud Integration (Direct Process Adapter) via Email (eMail Adapter) Modified	Integration Flow	1.0.0	>

The interfaces "Define Medallia Query" and "Convert Medallia Data to CSV" can be customized according to needs, use cases, and specific customization requirements. The package is designed such that the Process Direct endpoints are configurable, meaning custom iFlows can be developed and then called via Process Direct Adapter.



Data flow:

1. Prepare the Medallia query (GraphQL)
2. Send the query to Medallia
3. Convert the Medallia response into CSV
4. Send the CSV to the Signavio Handler iFlow

5. Looping logic (Required if the Medallia response has multiple pages based on the configuration)
6. Error handler

The "Replicate Customer Experience Data from Medallia to Signavio" interface is a so-called time scheduled full load interface, meaning it always retrieves data based on the configuration (filter & query) set in the "Define Medallia Query" interface. Essentially, a JSON response is returned (if multiple pages are present), all pages are fetched, converted to CSV, and then prepared for the upload to Signavio Process Intelligence in the "Import Medallia Data to SAP Signavio Process Intelligence" interface.

Configuration steps on SAP Cloud Integration

Replicate Customer Experience Data from Medallia to Signavio Configuration

This is the main iFlow; for more details, see "Integration Logic Description."

Configure Timer

During the initial run, you should trigger the iFlow for the first time upon deployment. Afterward, adjust the scheduler according to your needs.

Configure "Replicate Customer Experience Data from Medallia to Signavio"

Timer: Start Timer 1 [StartEvent_4] ▼

☒ Basic ☐ Advanced

Frequency

Enter As: Simple Schedule ▼

Repeat: None ▼

Schedule: On Deployment ▼

Configure Receiver Adapter

In the receiver section, there are a total of 5 receivers, but only Medallia needs to be configured.

The other Process Direct endpoints can be configured according to your use case if you want to experiment with your own logic.

Configure "Replicate Customer Experience Data from Medallia to Signavio"

Timer	Receiver	More
Connection		
Receiver:	Medallia	
Adapter Type:	HTTP	
Address:	{{host_name}}/data/v0/query	
host_name:	https://sapsignavio-sapsignavio.apis.medallia.com	
Proxy Type:	Internet	
Authentication:	OAuth2 Client Credentials	
Credential Name:	Medallia_OAuth_Token	
Timeout (in ms):	60000	
Request Headers:	Content-Type Accept{{Request Headers}}	
Request Headers:	Content-Type Accept	

The host_name parameter is the Medallia endpoint, which must be provided by the Medallia admin, and the Medallia credentials are the alias of the Medallia OAuth credentials that were stored in the chapter "Prerequisites Access to SAP Cloud Integration."

Configure "Get Medallia Data"

Timer	Receiver	More
Connection		
Receiver:	Medallia	
Adapter Type:	HTTP	
Address:	{{host_name}}/data/v0/query	
host_name:	https://-----pis.medallia.com	
Credential Name:	Medallia_OAuth_Token	

Additional Parameters

In the "More" section, you should configure only the parameters error_email_notification (email dispatch in case of failure) and error_log_attachment (logging in case of an error). Adjust these settings according to your needs.

Configure "Get Medallia Data"

Timer	Receiver	More
More		
Type:	All Parameters	
allowed_headers:	Content-Type Accept	
error_email_notification:	false	
error_log_attachments:	true	
iflow_name:	Get Medallia Data	

Define Medallia Query Configuration

The Query API is a powerful analytics API that harnesses GraphQL to give you access to Medallia Experience Cloud data through a single endpoint. Send a standard HTTP POST request to the server through a single endpoint, specify what data you need, and get back exactly that.

More Details: [Query API | Medallia Documentation](#)

Configure Sender Adapter

In the Sender section, everything remains as it is. The Process Direct endpoint can be changed if a different query is needed or if the existing one, along with all configurations, is insufficient.

Configure "Define Medallia Query"

Sender **More**

Connection

Sender:

Adapter Type:

Address:

Additional Parameters

In our case, we use the standard query *getSurveyDetails* for the record-level response extraction use case.

The exact values for the *filter* parameter will depend on the use case, but commonly filters include date ranges and program conditions to fetch desired data. By leaving the filters as null your query is extracting everything the OAuth client has access to.

With the parameter *node_structure*, you specify the fields that are relevant for the use case. The nodes are specific fields to pull for each record.

The parameter *number_per_page* specifies the number of records per page. The maximum number of records per request will vary depending on the data requested for each one. The more fields the query includes, the fewer records will fit in the response. The limitation that must be considered to define page size is the cost limit, which provides a measurement of how many resources are needed to serve the request. While there is no clear recommendation as it depends on the data volume, it would be advisable to test with up to **500 records per page** and monitor the cost measurement (ideally kept in the low hundreds) and response time to adjust accordingly for your use case and avoid timeouts.

More Details about limit can be find here: [Restrictions and limits | Medallia Documentation](#)

Configure "Define Medallia Query"

Sender [More](#)

Type: All Parameters

allowed_headers: endCursor

filter:

node_structure: nodes { id email: fieldData(fieldId: "q_bp_itr_scale") { values } name: fieldData(fieldId: "q_sap_sample_comment") { values } }

number_per_page: 50

For example, if you want to request a specific date range the filters could look something like the following:

```
{
  "variables": {
    "filter": {
      "and": [
        {
          "fieldIds": "e_responedate",
          "lt": "2025-01-01"
        },
        {
          "fieldIds": "e_responedate",
          "gte": "2024-10-01"
        }
      ]
    }
  }
}
```

You need to convert the JSON Representation into a single line "compact representation."

`{"and":[{"fieldIds":"e_responedate","lt":"2025-01-01"},{"fieldIds":"e_responedate","gte":"2024-10-01"}]}`

Configure "Define Medallia Query"

Sender [More](#)

Type: All Parameters

allowed_headers: endCursor

filter: [{"and":[{"fieldIds":"e_responedate","lt":"2025-01-01"},{"fieldIds":"e_responedate","gte":"2024-10-01"}]}

node_structure: nodes { id email: fieldData(fieldId: "q_bp_itr_scale") { values } name: fieldData(fieldId: "q_sap_sample_comment") { values } }

number_per_page: 50

Convert Medallia Data to CSV

As described in the chapter "Integration Logic Description," the Medallia JSON response is converted into CSV format. A Groovy script was used for this conversion. If there is a need for more complex conversions, you can implement your own JSON-to-CSV conversion, ensuring that the format of the CSV header adheres to specific guidelines.

Configure Sender Adapter

Configure "Convert Medallia Data to CSV"

Sender More

Connection

Sender: Cloud_Integration

Adapter Type: ProcessDirect

Address: /convert/medallia/data

Additional Parameters

More Information: <https://help.sap.com/docs/signavio-process-intelligence/api-guide/ingestion-api-data-upload?locale=en-US>

Configure "Convert Medallia Data to CSV"

Sender **More**

Type: All Parameters

csv_header: id,email_id,comment

Import Medallia Data to SAP Signavio Process Intelligence

After the Medallia JSON response has been converted into CSV, the final step is to upload the CSV payload to Signavio Process Intelligence using the Ingestion API.

Configure Sender Adapter

In the configuration for the sender adapter, nothing needs to be done.

Configure "Import Medallia Data to SAP Signavio Process Intelligence"

Sender Receiver More

Connection

Sender: Cloud_Integration

Adapter Type: ProcessDirect

Address: /medallia/signavio/pint

Configure Receiver Adapter

In the receiver adapter configuration, the Ingestion API endpoint must be added, which can be obtained from the chapter "Prerequisites - Access to Signavio Process Intelligence."

Configure "Import Medallia Data to SAP Signavio Process Intelligence"

Sender Receiver More

Receiver: Signavio

Adapter Type: HTTP

Connection

Address: https://api.eu.signavio.cloud.sap/spi/ingestions/v1/data

Additional Parameters

The *connection_token* parameter is the alias of the secure parameter (for Process Intelligence) that was created in the chapter "Prerequisites - Access to SAP Cloud Integration."

The *fileName* parameter is defined arbitrarily. It appears in the logs after the import.

Source Data / Medallia CX (SAP Integration Suite)

Medallia CX (SAP Integration Suite)

Repository: ☐ Source Data ☐ Access Role Manager

Tables Logs

Status	Table	Start Date (UTC)	End Date (UTC)	Files	Message	Execution ID
Completed	Feedback	2025-03-18 12:55:47	2025-03-18 13:00:16	MedalliaCX.csv		69793449-3abb-4643-81ed-60582e...
Completed	Feedback	2025-03-18 12:26:41	2025-03-18 12:30:16	MedalliaCX.csv		7131a501-3340-4c5e-b0c6-5af95b...

The *logger* parameter is used to log the request and response payloads to and from Signavio. The default value is false.

Regarding *primary_keys* and *schema*, please see the explanation in the documentation:

<https://help.sap.com/docs/signavio-process-intelligence/api-guide/sending-ingestion-request?locale=en-US>

Configure "Import Medallia Data to SAP Signavio Process Intelligence"

Sender Receiver More

Type: All Parameters

connection_token: Medallia_Ingestion_Token

fileName: MedalliaCX.csv

logger: true

primary_keys: id

schema: [{"type": "record", "name": "Feedback", "fields": [{"name": "id", "type": ["null", "string"]}, {"name": "email_id", "type": ["null", "string"]}, {"name": "..."}]}

Send Error Notification Emails (Medallia Error Handler)

This interface serves as a central point for email dispatch in case of an error. If emails are to be sent, the SMTP server must be configured for email delivery.

Configure Sender Adapter

Configure "Send Error Notification Emails"

Sender Receiver

Sender: Cloud_Integration

Adapter Type: ProcessDirect

Connection

Address: /medallia/signavio/errorhandler

Configure Receiver Adapter

Configure "Send Error Notification Emails"

Sender **Receiver**

Connection

Receiver: EMail_Receiver

Adapter Type: Mail

Address: TBD

Proxy Type: Internet

Timeout (in ms): 30000

Protection: STARTTLS Mandatory

Authentication: Encrypted User/Password

Credential Name: TBD

Processing

From: TBD@from.com

To: TBD@to.com

Cc:

Bcc:

Subject:

Body Mime-Type: Text/Plain

Body Encoding: UTF-8

Add Message Attachments: ☐

Content Transfer Encoding: Automatic

Security

Signature and Encryption Type: None